

CONTOUR	SQUARE FEET	ACRE FEET
4722	200	2.30
4726	50,000	11.53
4730	201,100	23.00
4734	300,000	34.19
4738	444,700	6.11
BORROW		77.13
TOTAL		

SUBMERGED AREAS

Sec. 32, NW $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$.09 Acres
 SW $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$.31
 SE $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$ 3.84
 Sec. 5, NE $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$ 4.50
 SE $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$ 1.47
 TOTAL 10.21 Acres

$\frac{1}{4}$ cor. Sec. 32, T. 32 S., R. 24 E.
 and Sec. 5, T. 33 S., R. 24 E.
 lies 859.34 feet north
 and 402.27 feet east
 of Sta. 2+25

UNITED STATES DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

SHERLOCK GULCH DAM AND RESERVOIR

DESIGNED <u>DAB</u>	RECOMMENDED _____
DRAWN <u>DAB</u>	RECOMMENDED _____
CHECKED _____	APPROVED _____

CHIEF, DIV. OF ENGINEERING

SCALE 1" = 100' CONTOUR INTERVAL 4'

DATE 4-3-74 SHEET 1 OF 2

DRAWING NO.

Spillway Elev. 4738.2

Sta. 2+23
 Elev. 4741.2

R 51807