

RECEIVED

MAR 13 1953  
STATE ENGINEER  
SALEM, OREGON

Registration Statement

REG. NO. GR-412  
CERTIFICATE NO. 398

OF CLAIMANT OF RIGHT TO APPROPRIATE GROUND WATER

(Under Chapter 708, Oregon Laws 1955.)

TO THE STATE ENGINEER OF OREGON;

I, E. E. Larned Rt. 1, Box 381  
of Corvallis County of Benton

State of Oregon, do hereby make application for a certificate of registration as evidence of a right to appropriate ground water.

- 1. Source from which water is withdrawn is Pump well  
(Flowing well, pump well, infiltration trench, or tunnel)
- 2. Location is: 7 miles North of Corvallis  
(Approximate distance and direction from nearest city or town)

and is more particularly described as follows:

(a) 864' South & 231' East of the projected quarter corner between  
(Give distance and bearing to corner of section or other legal subdivision)  
between secs. 6 & 7, the NW 1/4 of the NE 1/4 of Sec. 7, Twp. 11S, Rge. 4W.  
(Smallest legal subdivision) (N. or S.) (E. or W.)

or (b) within limits of recorded platted property, town or city:  
in Lot \_\_\_\_\_, Block \_\_\_\_\_ of \_\_\_\_\_  
(Name of plat or addition)  
County of Benton  
(If within city or town, give name)

3. Construction Work was begun on March 21, 1953; was completed on March 25, 1953  
(Date) (Date)  
and the ground water claimed was first used for the purposes set out below on June 1, 1953  
(Date)  
since which time the water has been used continuously  
(Continuously or intermittently)  
from June, 1953 to Oct. 31, 1956  
(Date) (Date)

4. Quantity of water claimed and used is 200 gallons per minute; \_\_\_\_\_ acre  
feet per year.

5. Purpose or Purposes for which water is used Irrigation

(Domestic, irrigation, municipal, manufacturing, industrial, etc.)

6. Description of Well: Depth 44 feet. Type drilled  
(Dug or drilled)  
diameter 10 inches. Elevation of ground at well site 218 feet, mean sea level.  
(As near as known)  
Depth to water table 28 feet.

7. Capacity of Well: 270 g.p.m. with 20 feet drawdown;  
\_\_\_\_\_ g.p.m. with \_\_\_\_\_ feet drawdown.

Date of test June 1, 1953

If Flowing Well: Measured discharge \_\_\_\_\_ g.p.m. on \_\_\_\_\_  
(Date)

Shut-in pressure at ground surface \_\_\_\_\_ lbs. per sq. in. on \_\_\_\_\_  
(Date)

Water is controlled by \_\_\_\_\_  
(Cap, valve, etc.)

8. Casing: (Give diameter, commercial specifications and depth below ground surface of each casing size.)

10 inch diameter 441 from ..... to ..... feet  
 ..... inch diameter ..... from ..... to ..... feet  
 ..... inch diameter ..... from ..... to ..... feet  
 ..... inch diameter ..... from ..... to ..... feet

Describe and show depth of shoe, plug, adapter, liner or other details: .....

XX

9. Perforated Casings or Screens:

Unknown; Driller fixed casing as he thought from ..... to .....  
(Number per foot and size of perforations, or describe screen)  
 best. Have no record. from ..... to .....  
 ..... from ..... to .....  
 ..... from ..... to .....

10. Log of Well: (Describe each stratum or formation clearly, indicate if water bearing, and give thickness and depth as indicated.)

MATERIAL	Thickness (Feet)	Depth to Bottom (Feet)
<i>unknown</i>		



