

RECEIVED  
MAY 6 1957  
STATE ENGINEER  
SALEM OREGON

REGISTRATION NO. GR-426  
CERTIFICATE NO. 458

# Registration Statement

## OF CLAIMANT OF RIGHT TO APPROPRIATE GROUND WATER

(Under Chapter 708, Oregon Laws 1955.)

TO THE STATE ENGINEER OF OREGON:

I, Bose Brothers

of Rt. 1, Box 260, Albany County of Linn

State of Oregon, do hereby make application for a certificate of registration as evidence of a right to appropriate ground water:

1. Source from which water is withdrawn is pump well  
(Flowing well, pump well, infiltration trench, or tunnel)

2. Location is: 8 miles East of Albany, Oregon  
(Approximate distance and direction from nearest city or town)

and is more particularly described as follows:

(a) N. 32° 20' W. 32.5 chains from the SE corner S. 5, T. 11 S., R. 2 W. W.M.  
(Give distance and bearing to corner of section or other legal subdivision)

being within NW 1/4 of SE 1/4 of Sec. 5, Twp. 11 S, Rge. 2 W.  
(Smallest legal subdivision) (N. or S.) (E. or W.)

or (b) within limits of recorded platted property, town or city:

in Lot \_\_\_\_\_, Block \_\_\_\_\_ of \_\_\_\_\_  
(Name of plat or addition)

County of Linn  
(If within city or town, give name)

3. Construction Work was begun on Oct. 10, 1953; was completed on Oct. 13, 1953  
(Date) (Date)

and the ground water claimed was first used for the purposes set out below on May 16, 1954  
(Date)

since which time the water has been used continuously  
(Continuously or intermittently)

from May 16, 1954 to present time  
(Date) (Date)

4. Quantity of water claimed and used is 480 gallons per minute; 167.5 acre feet per year.

5. Purpose or Purposes for which water is used Irrigation

(Domestic, irrigation, municipal, manufacturing, industrial, etc.)

6. Description of Well: Depth 30 feet. Type Drilled  
(Dug or drilled)

diameter 10 inches. Elevation of ground at well site 260 feet, mean sea level.  
(As near as known)

Depth to water table 15 feet.

7. Capacity of Well: 500 g.p.m. with 5 feet drawdown.

\_\_\_\_\_ g.p.m. with \_\_\_\_\_ feet drawdown.

Date of test Estimated

If Flowing Well: Measured discharge \_\_\_\_\_ g.p.m. on \_\_\_\_\_  
(Date)

Shut-in pressure at ground surface \_\_\_\_\_ lbs. per sq. in. on \_\_\_\_\_  
(Date)


Water is controlled by \_\_\_\_\_  
(Cap, valve, etc.)

8. Casing: (Give diameter, commercial specifications and depth below ground surface of each casing size.)

10 inch diameter Steal casing from 0 to 30 feet  
inch diameter from to feet  
inch diameter from to feet  
inch diameter from to feet

Describe and show depth of shoe, plug, adapter, liner or other details:

9. Perforated Casings or Screens:



Slot perforations from to 30  
(Number per foot and size of perforations, or describe screen)  
from to  
from to  
from to

10. Log of Well: (Describe each stratum or formation clearly, indicate if water bearing, and give thickness and depth as indicated.)

172-641 Joseph M. & Erica I. Copeland to Alfred & Harry Bose

Beginning at a point 11.75 chains North and 7 chains West of the Southeast corner of the D.L.C. of John A. Powell, Not. No. 1197, Claim No. 40 in T. 11 S., R. 2 W. of the Will. Mer. in Linn County, Oregon, said beginning point being 10 feet East of the center of a private gravel road, thence West 1.22 chains to the center of a county road; thence N.42°45'W. 13.40 chains; thence N.19°30'E. 24.65 chains to the center of a Creek; thence Northerly down the center of said Creek to the South line of a 25 acre tract of land sold to Joseph H. Copeland, by Deed recorded in Vol. 124, page 447, Deed Records of Linn County, Oregon; thence East 9 chains, more or less, to the Southeast corner of said 25 acre tract; thence North 7.46 chains to a point 32 links East of an interior corner of said Claim, thence East 17.12 chains; thence S.12°40'E. 11.64 chains; thence S.46°30'W. 22.00 chains, more or less, to the center of Mill Creek; thence Westerly along the center of Mill Creek to the East line of said Claim No. 40; thence South 15 chains to an iron stake; thence West 5 chains, more or less, to a point 10 feet East of the center of a private gravel road; thence Southwesterly parallel with the center of said private gravel road, 8 chains, more or less, to the place of beginning, containing 99 acres, more or less, all lying and being situated in the County of Linn, State of Oregon.

Beginning at an iron pipe which is East 32 links distant and South 7.46 chains distant from the Southwest corner of the D.L.C. of John Y. Streithoff, being Not No. 1190 and Claim No. 41, in T. 11 S., R. 2 W. of the Will. Mer. in Linn County, Oregon, thence N. 7.46 chains, thence W. 32 links to the Southwest corner of said Claim; thence N.15°45'E. along the West line of said Claim 7.59 chains; thence S.89°30'W. 2.80 chains; thence N.15°45'E. 2.80 chains; to the center of a county road; thence S.89°30'W. along the center of said road 10.63 chains, thence S.19°30'W. 21.35 chains to the center of a Creek; thence Northeasterly down the center of said creek to a point due West of the place of beginning; thence East 9.00 chains to the place of beginning, containing 25 acres, more or less, all lying and being in Linn County, State of Oregon.

Beginning at a point on the East line, and 19.25 chains North of the Southeast corner of the John A. Powell D.L.C. No. 40 in T. 11 S., R. 2 W. of the Will. Mer. in Linn County, Oregon, and running thence North along the East line of said Claim 13.00 chains to the center line of Mill Creek; thence up stream on the center line of said Creek to a point 2.70 chains East of said Claim line, thence S.9°45'W. 12.00 chains, thence W. 1.06 chains to the place of beginning, containing 2.3 acres, ally in Linn County, Oregon.

If log of well is not available, give name and address of driller. Raymond Gellatly, Philomath, Oregon

11. Infiltration Trench: Covered or open .....

Dimensions: Length ..... ft. Minimum depth ..... ft. Maximum depth ..... ft.

Bottom width ..... ft. Discharge ..... g.p.m. Date of test .....

12. Tunnel: Type of lining .....

Dimensions: .....  
(Length, course, and cross sectional size)

Position of water bearing stratum with reference to portal of tunnel .....

Log of tunnel: (Preceding table for log of well may be used, if desired. Give footage from portal and character of materials, as pertinent.)

13. Pumping Equipment:

(a) Pump 3" Fairbanks Morse Centrifugal Capacity 500 g.p.m.  
(Make, type and size)

(b) Motor 25 H.P. electric  
(Type and horsepower)

14. Location of area irrigated or to be irrigated, or place of use if for purposes other than irrigation.

Township North or South	Range E. or W. of Willamette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated	Date of Reclamation
11 S	2 W	5	SW $\frac{1}{4}$ of NE $\frac{1}{4}$	2.5	May 16, 1954
11 S	2 W	5	SE $\frac{1}{4}$ of NE $\frac{1}{4}$	3.5	May 16, 1954
11 S	2 W	5	NE $\frac{1}{4}$ of SE $\frac{1}{4}$	29.0	May 16, 1954
11 S	2 W	5	NW $\frac{1}{4}$ of SE $\frac{1}{4}$	27.0	May 16, 1954
11 S	2 W	5	SW $\frac{1}{4}$ of SE $\frac{1}{4}$	3.5	May 16, 1954
11 S	2 W	5	SE $\frac{1}{4}$ of SE $\frac{1}{4}$	1.0	May 16, 1954
11 S	2 W	5	NE $\frac{1}{4}$ of SW $\frac{1}{4}$	0.3	May 16, 1954
11 S	2 W	5	SE $\frac{1}{4}$ of SW $\frac{1}{4}$	0.2	May 16, 1954
				67.0	

229-263 Ex. Alfred & Harry Bose to Frank & Mae L. Folsom

Beginning in the center oline of Mill Creek S.19°30'W. 51.144 chains from a point on the North line of and N.71°15'W. 12.32 chains from the Northeast corner of the John A. Powell D.L.C. No. 40 in T. 11 S., R. 2 W. of the will. Mer. in Linn County, Oregon, and running thence N.19°30'E. 580.3 feet to the center line of Mill Creek; thence along the center line of Mill Creek as follows: S.74°30'E. 245 feet, S.53°30'E. 145 feet, S.11°55'W. 345 feet, N.75°00'W. 105 feet, S.57°45'W. 40 feet, N.70°10'W. 120 feet, S.52°30'W. 45 feet, S.10°03'E. 159.2 feet and S.86°45'W. 253.2 feet to the place of beginning and containing 4.76 acres, more or less.

229-264

Beginning at a 3/4" iron bar S.19°30'W. 55.458 chains from a point on the North line of and N.71°15'W. 12.32 chains from the Northeast corner of the John A. Powell D.L.C. No. 40 in T. 11 S., R. 2 W. of the will. Mer. in Linn County, Oregon, and running thence N.81°30'W. 275 feet to the center line of Mill Creek; thence along the center line of Mill Creek as follows: N.11°00'W. 210 feet, N.55°45'W. 120 feet, N. 6°45'E. 140 feet, N.73°45'E. 170 feet, S.82°00'E. 90 feet, S.52°30'E. 120 feet, S.31°10'E. 175 feet, N.86°45'E. 51.0 feet to a point N.19°30'E. of the place of beginning; thence leaving said Mill Creek and running S.19°30'W. 284.7 feet to the place of beginning and containing 3.77 acres, more or less.

