

Permit No. G-1115

APPLICATION FOR A PERMIT

To Appropriate the Ground Waters of the State of Oregon

No. The Fairview Water District, 403 Marolf Drive,

(Name of applicant)

of Tillamook, county of Tillamook

(Postoffice Address)

state of Oregon, do hereby make application for a permit to appropriate the following described ground waters of the state of Oregon, SUBJECT TO EXISTING RIGHTS:

If the applicant is a corporation, give date and place of incorporation

Incorporated August 11 1919, Tillamook, Oregon

1. Give name of nearest stream to which the well, tunnel or other source of water development is situated Wilson River about 2 mi. North and Trask River about 2 mi. South

(Name of stream)

2. The District expects a 10% increase in customers each year, so that it may be possible to need another Well in 5 years.

2. The amount of water which the applicant intends to apply to beneficial use is cubic feet per second or Well No.1 gallons per minute. Maximum capacity is 300 gal. Well No.2 " " " " Maximum Capacity is 650 gal.

3. The use to which the water is to be applied is Domestic, No Irrigation, Quasi municipal. There are some fire hydrants installed in different parts of the system.

4. The well or other source is located No.1 931.2 North 46.6 East No.2 732.2 North and 224.5 ft. East from the corner of S.W. Corner of J.S. Tripp D.L.C., Sec. 29 T.L South, Range 9 West, W.M. in Tillamook, Tillamook County, Oregon. Well No.1 in NE 1/4 of SE 1/4 Sec. 29 Well No.2 in NW 1/4 of SW 1/4 Sec. 29 Both wells are in the same above Sec. and are rather close together. See map.

being within the of Sec. 22, Twp. 1 South, R. 2 West, W. M., in the county of Tillamook, Oregon

5. The pipe Lines to be about 6 or 7 miles in length, terminating in the of Sec. , Twp. , R. , W. M., the proposed location being shown throughout on the accompanying map.

6. The name of the well or other works is Well No.1 and Well No.2 of Fairview Water District. Constructed 1947 1953

DESCRIPTION OF WORKS

7. If the flow to be utilized is artesian, the works to be used for the control and conservation of the supply when not in use must be described.

Not artesian

8. The development will consist of Well No. 1 Well No. 2 having a diameter of 10 inches and an estimated depth of 150 feet. It is estimated that all feet of the well will require have 1/2" steel casing. Depth to water table is estimated 24 feet. Pumping level, No.1 70 feet No.2 70 feet

CANAL SYSTEM OR PIPE LINE--

9. (a) Give dimensions at each point of canal where materially changed in size, stating miles from headgate. At headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet.

The District has several large maps of different sections of the Pipe lines; no map has been made of the entire District. Lateral lines are 4 inch and 2 inch and 1 inch. Some are mostly 4 inch and (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet.

(c) Length of pipe, ft.; size at intake, in.; in size at ft. from intake in.; size at place of use in.; difference in elevation between intake and place of use, ft. Is grade uniform? Estimated capacity, sec. ft.

10. If pumps are to be used, give size and type No.1 Pump, Centrifugal No.2 Pump, Centrifugal

Give horsepower and type of motor or engine to be used No.1 motor, 20 horsepower, Electric. No.2 motor, 50 horsepower, Electric.

11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development Over 1/4 mile.

12. Location of area to be irrigated, or place of use No. irrigation, domestic use only.

Township N. or S.	Range E. or W. of Willamette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated
South 1/2 of T 1 S	9 W	20, 21, 22, 26, 27, 28, 29, & E. part 31, 32, 33.	See map.	
		CHARACTER OF SOIL.	Township 1 South, Range 9 West	
	0-9	Top soil	Sec. 19	SE 1/4
	9-35	Cemented gravel	20	S 1/2 NE 1/4, SW 1/4 NW 1/4, S 1/2
	35-59	Clay	21	NE 1/4, E 1/2 NW 1/4, SW 1/4 NW 1/4, S 1/2
	59-63	Gravel perforated	22	SW 1/4 NE 1/4, NW 1/4, S 1/2
	63-72	Clay and gravel	23	S 1/2 SW 1/4, SW 1/4 SE 1/4
	72-84	Gravel perforated	26	W 1/2 NE 1/4, W 1/2, W 1/2 SE 1/4, NE 1/4 SE 1/4
	84-110	Cemented gravel	27	ALL
	110-132	Red clay	28	ALL
	132-142	Water strata perforated	29	N 1/2, E 1/2 SW 1/4, SW 1/4 SW 1/4, SE 1/4
	142-150	Blue shale	30	E 1/2 NE 1/4, S 1/2 SE 1/4, NW 1/4 SE 1/4
			31	NE 1/4
			32	N 1/2, NE 1/4 SW 1/4
			33	N 1/2

(If more space required, attach separate sheet)

Character of soil
Kind of crops raised

To supply the water Fairview Water District
Tillamook county, having a present population of about 1000
and an estimated population of about 1000 in 1958

ANSWER QUESTIONS 14, 15, 16, 17 AND 18 IN ALL CASES

- 14. Estimated cost of proposed works, \$ 24,284.00 Wells, pumps, buildings & equipment. \$ 116,929.00 all pipe lines to date.
- 15. Construction work will begin on or before Built from 1919 at various times to date.
- 16. Construction work will be completed on or before All completed.
- 17. The water will be completely applied to the proposed use on or before Various times.

18. If the ground water supply is supplemental to an existing water supply, identify any application for permit, permit, certificate or adjudicated right to appropriate water, made or held by the applicant.

Permit; Hughey Creek, Small Dam,
Permit; Donaldson Creek, Small Dam,
Permit; Tilison Creek, Small Dam.

(Signature of applicant)

Respect: Fairview Water District,
By Board of Commissioners; Walter Naegel Chairman,
Karl Zivethell Secretary,
Norman Buddick Treasurer.

Fairview Water District also holds the following lease, dated 9-11-1953
For 20 years.
To construct a well, when needed, From School District No. 2 Tillamook.

Beginning at a point which is 378.73 feet North and 2729.00 feet East of the quarter corner on the west side of Se.28, T. 1 South, Range 9 West, W.M. Tillamook County, Oregon; Thence North 15 feet; thence 17 feet West; thence North 2022' W. 166 feet to the Northerly line of the School District school grounds property; thence Southerly along the west line of school grounds property to a point which is 15 feet South and 37 feet West of the place of beginning; thence East 37 feet; thence North 15 feet to the place of beginning, being situated in the Southwest quarter of Northeast quarter Se. 28, T. 1 South, Range 9 West, W.M. Tillamook County, Oregon.

STATE OF OREGON, }
County of Marion, } ss.

This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for completion

In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before November 10, 19 58.

WITNESS my hand this 11th day of September, 19 58.

RECEIVED
OCT 6 1958
STATE ENGINEER
SALEM, OREGON

LEWIS A. STANLEY
STATE ENGINEER
By Trevor Jones, ASSISTANT

PERMIT

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use and shall not exceed 2.30 cubic feet per second measured at the point of diversion from the well or source of appropriation, or its equivalent in case of rotation with other water users, from 2 wells, being 0.85 a.f.s. from Well #1 and 1.45 a.f.s. from Well #2.

The use to which this water is to be applied is municipal (all of the purposes for which water could be used in a city under a right initiated for municipal use)

If for irrigation, this appropriation shall be limited to of one cubic foot per second or its equivalent for each acre irrigated and shall be further limited to a diversion of not to exceed acre feet per acre for each acre irrigated during the irrigation season of each year;

and shall be subject to such reasonable rotation system as may be ordered by the proper state officer.

The well shall be cased as necessary in accordance with good practice and if the flow is artesian the works shall include proper capping and control valve to prevent the waste of ground water.

The works constructed shall include an air line and pressure gauge or an access port for measuring line, adequate to determine water level elevation in the well at all times.

The permittee shall install and maintain a weir, meter, or other suitable measuring device, and shall keep a complete record of the amount of ground water withdrawn.

The priority date of this permit is August 27, 1958

Actual construction work shall begin on or before November 20, 1959 and shall thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 1960

Complete application of the water to the proposed use shall be made on or before October 1, 1961

WITNESS my hand this 20th day of November 1958

Lewis A. Stanley STATE ENGINEER

Application No. G- 1220
Permit No. G- 1115

PERMIT

TO APPROPRIATE THE GROUND WATERS OF THE STATE OF OREGON

This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 27 day of Aug 1958, at 10:50 o'clock A. M.

Returned to applicant:

Approved: November 20, 1958
Recorded in book No. 5 of 1115
Ground Water Permits on page

LEWIS A. STANLEY STATE ENGINEER

Drainage Basin No. A / page 25

State Printing

2400