Permit No. G- 113

## APPLICATION FOR A PERMIT

## To Appropriate the Ground Waters of the State of Oregon

1, Flyd N. M.	(Name of applicant)	<u></u>	
of At 2 Bay 79 Hills	Aloro	, county of Kasher	ytan
(Posternos Astrom)	do hereby mak	ce application for a permit to	appropriate the
If the applicant is a corporation,	, give date and place of in	corporation	
	· · · · · · · · · · · · · · · ·	,	
1. Give name of nearest stream			r development is
situated Justitum	Tenen (Name of str	eam)	
Pallamet	e fere	ibutary of Mills	nette
2. The amount of water which feet per second or 200 appropallor	h the applicant intends to		cubic
3. The use to which the water	is to be applied is	unigation of	Jann
expe		. /	
4. The well or other source is	located Findit.	and fit.	from the
corner of 1/ 12 esemb.	of Sec. 8	358°42'E /166.	54 ft
(If p:	referable, give distance and bearing.		
The Barbara and Albara	of the William of the described of NW14 NW14 S	The separate sheet if necessary  This T2 S	R 2 W
W. M. r. tree way or Was	hington		
S = T U S	Í	ta be	*n;();(:)
	Casal et patembe	of $Sec$ ,	. Trop
	oration la ma discouranter	accloset on the accompanyin	
n de la companya de l La companya de la co			
		ne en	
	DESCRIPTION OF		
A Section of the sect	eribed .	cased so the control and -	
The section of the second	id approp	really con	20 20
adain and it		<i>,</i>	
gan an a	in the site of	elelela Carana nyangan	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1
geografia Grand Grand Gr	d an estimated depth of	300 // 1000	er en en Frank
, 42	Teek camp	Death to ware tasks or a	maril Carlo

thousand feet.  (b) At miles from headgate: width on top (at water line)  feet; width on bottom feet; depth of water f  grade feet fall per one thousand feet.  (c) Length of pipe, ft.; size at intake, in.; in size at  from intake in.; size at place of use in: difference in elevation between that and place of use, ft. Is grade uniform? Estimated capa see. ft.  10. If pumps are to be used, give size and type  Anywhile from The Rep. Le 20  Gree horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a fire and the ground surface at the source of development work is less than one-fourth mile from a fire and the distance to the nearest point on each of such channel, the difference in cleration between the stream hed and the ground surface at the source of development work is less than one-fourth mile from a fire and the difference in cleration between the stream hed and the ground surface at the source of development work is less than one-fourth mile from a fire and the difference in cleration between the stream hed and the ground surface at the source of development work is less than one-fourth mile from a fire and the ground surface at the source of development work is less than one-fourth mile from a fire and type of the distance to the nearest point on each of such channel.  12. Location of area to be irrigated, or place of use  13. Location of area to be irrigated, or place of use  14. Location of area to be irrigated, or place of use  15. Location of area to be irrigated, or place of use	·		(at water line)			feet; width on botton
feet; width on bottom feet; depth of water line)  feet; width on bottom feet; depth of water  from sprace feet fall per one thousand feet.  (c) Length of pipe, fi.; size at intake, in; in size at  from intake in.; size at place of use in.; difference in elevation between that and place of use, ft. Is grade uniform?  Sec. ft.  10. If pumps are to be used, give size and type  Anywhere from TA Kip La 20  Gove horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one	howand fast	eet; depth of wate	<b>7</b>	feet; grade	•	feet fall per one
feet; width on bottom feet; depth of water  from intake feet fall per one thousand feet.  (c) Length of pipe, fi.; size at intake, in.; in size at  from intake in.; size at place of use in.; difference in elevation between that and place of use, ft. Is grade uniform? Estimated capacitate and place of use, ft.  10. If pumps are to be used, give size and type  Anywhile from TA Rep. Li 20  (i) to horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation in th	nousana jeet.	,				
frede feet fall per one thousand feet.  (c) Length of pipe, fi.; size at intake, in.; in size at from intake in.; size at place of use in.; difference in elevation between that and place of use, ft. Is grade uniform? Estimated capable sec. ft.  10. If pumps are to be used, give size and type anywhere from TA Rep. La 20  (i) to horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a stream or stream channel, give the distance to the nearest point on each of such channel, the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation of the well.	(b) At	mile	s from headgate:	width on top (a	t water line)	
(c) Length of pipe.  ft.; size at intake, in.; in size at rom intake in.; size at place of use in.; difference in elevation between take and place of use,  ft. Is grade uniform?  Sec. ft.  10. If pumps are to be used, give size and type  Anywhate from 7% Right Li 20  Goe horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the difference i		feet; width on be	ottom	feet; dept	h of water	feet
rom intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacities see. ft.  10. If pumps are to be used, give size and type  Anywhere from Na Rep. Li 20  (i. to horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation of such characters to the nearest point on each of such characters to the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from	rade	feet fall pe	er one thousand fe	et.		
sec. ft.  10. If pumps are to be used, give size and type  Anywhere from 14 Rep. Li 20  (i. we horsepower and type of motor or engine to be used)  11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in clevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is l	(c) Length	of pipe,	ft.; size o	it intake,	in.; in	size at
10. If pumps are to be used, give size and type  Anywhere from 7/2 Rep. Lo 20  Gre horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile freedward stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedward stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedward stream or stream channels, give the distance to the nearest point on each of such channels the difference in elevation of area to be irrigated, or place of use  12. Location of area to be irrigated, or place of use  Take the source of development work is less than one-fourth mile freedward.  13. Location of area to be irrigated, or place of use  14. Location of area to be irrigated, or place of use  15. Location of area to be irrigated.  16. Location of area to be irrigated, or place of use  17. Location of area to be irrigated, or place of use  18. Location of area to be irrigated.  19. Location of area to be irrigated.	rom intake	in.; si	ze at place of use		in.; differen	e in elevation betwee
10. If pumps are to be used, give size and type  Anywhere from The Rep. Li 20  (i. to horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency, stream or stream channel, give the distance to the nearest point on each of such chowel the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free	ntake and place of	fuse,	ft. Is gra	ide uniform?		. Estimated capacity
Ampaches from The Rep. Li 20  Goe horsepower and type of motor or engine to be used  11. If the location of the well, tunnel, or other development work is less than one-fourth mile freedomal stream or stream channel, give the distance to the nearest point on each of such chow elekte difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedom elevation of each of such chow elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedom elevation of each of such as a surface of the nearest point on each of such chow elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedom elevation of each of such chow elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedom elevation of each of such chow elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedom elevation of each of such chow elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedom elevation of each of such chow elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freedom elevation ele		sec. ft.	•			
11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency stream or stream channel, give the distance to the nearest point on each of such channel, the difference in elevation between the stream bed and the ground surface at the source of development work that same  12. Lecation of area to be irrigated, or place of use  Taken Range Range Range Range Rector Forthwest Tract Number Acres To Be irrigated  The Range						
11. If the location of the well, tunnel, or other development work is less than one-fourth mile fractional stream or stream channel, give the distance to the nearest point on each of such chew of the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractional stream or stream channel, give the distance to the nearest point on each of such of such as the source of development work is less than one-fourth mile fractional stream or stream or stream or stream or stream of such of such as the source of development work is less than one-fourth mile fractional stream or st	any	where f	rom 73	Kep ,	420	
11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the stream or stream channel, give the distance to the nearest point on each of such channel, he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the surface of the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the surface of the stream bed and the ground surface at the source of development with the surface at the source of developm	G ne horsep	oncer and type of	motor or engine t	o be used		
11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the stream or stream channel, give the distance to the nearest point on each of such channel, he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the action of each of such of such of such of such as a surface at the source of development work is less than one-fourth mile from the action of each of such of such as a surface at the source of development work is less than one-fourth mile from action of each of such of such of such of such of such as a surface at the source of development work is less than one-fourth mile from action of each of such						
Range Range William Forty-acre Tract  Number Acres To Be irrigated  Tag P  Range William ette Meridan  Number Acres To Be irrigated		, ,				
Taris Williametre Merulian  Forty-acre Tract  Williametre Merulian  Forty-acre Tract  To Be irrigated  Taris  NW/14 NW/19  25  ZW   B   NW/14 NW/19  36.79	kim	sed the	same			
25 2W 8 NW'19 36.79	, -			of use		
25 2W 8 NW'19 36.79	12. Locator	on of area to be in	rigated, or place o		act	
	12. Location	on of area to be in	rigated, or place o		act .	
NF 1/2 10 W/2 4 98	12. Location	on of area to be in	rigated, or place o		v. √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √	To Be irrigated
1-6 4 12 - 7 170	12. Lecative	Range Work Williametre Meridian	rigated, or place of		w√g √w√g	To Be irrigated
	12. Lecative	Range Work Williametre Meridian	rigated, or place of	Forty acre Tra	4W <sup>1</sup> 9	To Be irrigated
	12. Lecative	Range Work Williametre Meridian	rigated, or place of	Forty acre Tra	4W <sup>1</sup> 9	To Be irrugated  7.1  36.79
	12. Lecative	Range Work Williametre Meridian	rigated, or place of	Forty acre Tra	4W <sup>1</sup> 9	To Be irrugated  7.1  36.79
	12. Lecative	Range Work Williametre Meridian	rigated, or place of	Forty acre Tra	4W <sup>1</sup> 9	To Be irrugated  7.1  36.79
	12. Locator Taroban No. 27	Range Work Williametre Meridian	rigated, or place of	Forty acre Tra	4W <sup>1</sup> 9	To Be irrugated  7.1  36.79

more and Whilamethe Lagree

MUNICIPAL SUPPLY—
13. To supply the city of
in
and an estimated population of
14. Estimated cost of proposed works, \$. 65007
45. Construction work will begin on or before The 10, 17 The
16. Construction work will be completed on or before face log for
17. The water will be completely applied to the proposed use on or before 15, 1956
18. If the ground water supply is supplemental to an existing water supply, identify any application for permit, permit, certificate or adjudicated right to appropriate water, made or held by the
applicant.
Tlays (Signature of applicant)
Remarks:
gg (1997) and the state of the
and the second of the second o
and the second of the second o
en e
en e
$C(t,T) \in \mathcal{N} \cup \mathcal{N}$ (8.8) $C(t,T) \in \mathcal{N}$ (8.8)
, in the second of the Elementamined the foregoing applies that together with the wealth in the second of
The state of the s
•
the strong money that amplication most be returned to the State Engineer of the strong
2 174), 11 (1956).
the state of the latter of the day of the January

Thrus L. Mealer, a posterio

County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same,

SUBJECT TO EXISTING RIGHTS and the following limitations and conditions: The right herein granted is limited to the amount of water which can be applied to beneficial use and shall not exceed 0.h5 cubic feet per second measured at the point of diversion from the well or source of appropriation, or its equivalent in case of rotation with other water users, from . \* well irrigation. The use to which this water is to be applied is 1/80 If for irrigation, this appropriation shall be limited to of one cubic foot per second or its equivalent for each acre irrigated and shall be further limited to a diversion of not to exceed 23 acre feet per acre for each acre irrigated during the irrigation season of each year: and shall be still further limited to a diversion of not to exceed 0.45 c.f.s., and shall be subject to such reasonable rotation system as may be ordered by the proper state officer The well shall be cased as necessary in accordance with good practice and if the flow is artesian the works shall include proper capping and control value to prevent the waste of ground water. The works constructed shall include an air line and pressure gauge or an access port for measuring Are adequate to determine water level elevation in the well at all times. January 6, 1956 The priority date of this permit is February 15, 1957 in that construction work shall begin on or before and chall thereafter he prosecuted with reasonable diligence and be completed on or before October 1, 1957 The permittee shall install and maintain a weir, meter, or other suitable measuring newice, and shall keep a complete record of the amount of ground water withdrawn. The special confidence 15th day of PERM on a company of the English 12 12 6 15 day of Q 1056 or 8'00 action Returned to applicants