Parent No. G. 1238

APPLICATION FOR A PERMIT

To Appropriate the Ground Waters of the State of Oregon

	of								
	(Postetlige Address)	•	•						
	state of								
	If the applicant is a corporation, give	e date and place of incorpore	ition .						
	•								
	1. Give name of nearest stream to	which the well, tunnel or	other source of water de	velopment is					
	situated Seneschal Creek	(Name of stream)	······································						
	•	tributary	of Rudding Liver						
	2. The amount of water which the feet per second or450 gallons pe		to beneficial use is	cubic					
	3. The use to which the water is a	to be applied is	Sprinkler Irrig	ation					
and	South 13 deg. 20 4. The well or other source is loca 5.36 deg. 25 W. 378 ft. the XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	ted ft. and ence Southeasterly oit D.L.C. #67 in (Section or subdivision)	ft. from from	nthe c v.W. corner					
	(If preferal	ble, give distance and bearing to section c	orner)						
	If there is more than one	we'', each must be described. Use separa	te sheet if necessary)						
	being within the Tri_SE_	•	· · · ·						
		•	· · · ·	 R. 2 ₩2 .,					
	w. M., in the county of Larion 5. The	•	· · · ·						
	w. M., in the county of Larion 5. The	of Sec. 26	.Twp. 4 S	miles					
	being within the ITT_SE_ W. M., in the county of Larion 5. The in length, terminating in the	of Sec. 26	to be	miles					
	being within the ITT_SE_ W. M., in the county of Larion 5. The in length, terminating in the	of Sec. 26 or pipe line: (Smallest legal susdivision) ion being shown throughout	to be	miles					
	being within the ITI_SE_ W. M., in the county of Larion 5. The in length, terminating in the R W. M., the proposed location 6. The name of the well or other to	of Sec. 26 or pipe line: (Smallest legal susdivision) ion being shown throughout	to be of Sec. Twp on the accompanying ma	miles					
	being within the ITI_SE_ W. M., in the county of Larion 5. The in length, terminating in the R W. M., the proposed location 6. The name of the well or other to	of Sec. 26 Complete lines Complete legal sustivisions Complete lines Complet	to be of Sec. Twp on the accompanying ma	miles o. ip.					
	being within the ITI_SE_ W. M., in the county of Larion 5. The Canal in length, terminating in the R W. M., the proposed location 6. The name of the well or other in 7. If the flow to be utilized is arter	of Sec. 26 Complete lines Complete legal sustivisions Complete lines Complet	to be of Sec. Twp on the accompanying ma	miles o. ip.					
	being within the ITI_SE_ W. M., in the county of Larion 5. The Canal in length, terminating in the R W. M., the proposed location 6. The name of the well or other in 7. If the flow to be utilized is arter	of Sec. 26 (Smallest legal susdivision) ion being shown throughout works is DESCRIPTION OF WORKS sian, the works to be used for	to be of Sec. Twp on the accompanying ma	miles o. ip.					
	being within the ITI_SE_ W. M., in the county of Larion 5. The in length, terminating in the R W. M., the proposed locate 6. The name of the well or other of 7. If the flow to be utilized is arte supply when not in use must be described.	of Sec. 26 (Smallest legal susdivision) ion being shown throughout works is DESCRIPTION OF WORKS sian, the works to be used for	to be of Sec. Two on the accompanying ma	miles o. ip.					
	being within the ITI_SE_ W. M., in the county of Larion 5. The Canal in length, terminating in the R W. M., the proposed locate 6. The name of the well or other of 7. If the flow to be utilized is arte supply when not in use must be described.	of Sec. 26 Complete lines Complete legal susdivisions Complete legal susdivisions Complete legal susdivisions Complete lines Complete li	to be of Sec. Two on the accompanying ma	miles o. p. vation of the					
	being within the ITI_SE_ W. M., in the county of Larion 5. The in length, terminating in the R W. M., the proposed locate 6. The name of the well or other of 7. If the flow to be utilized is arte supply when not in use must be described.	of Sec. 26 Complete legal susdivisions ion being shown throughout works is DESCRIPTION OF WORKS is an, the works to be used for	to be of Sec. Two on the accompanying ma	miles p. vation of the					

(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water frade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at form intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacity sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electrical stream or stream channel, give the distance to the nearest point on each of such channels	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water frade feet; width on bottom feet; depth of water frade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ominitake in.; size at place of use in.; difference in elevation between the water and place of use, ft. Is grade uniform? Estimated capacitake and place of use, ft. Is grade uniform? Estimated capacitake and place of use, ft. 10. If pumps are to be used, give size and type 8th Lineshaft Turbine Gire horsepower and type of motor or engine to be used 30 HP 2 phase Electric alural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development in elevation of area to be irrigated, or place of use Township Reference in elevation between the stream bed and the ground surface at the source of development in elevation of area to be irrigated, or place of use Township Williamstra Meridian Esection Forty-acre Treet Number Acres to Be unquised. 4 S. 2 T. 36 NE_ST. 5.27 4 S. 2 T. 36 NE_ST. 5.27 4 S. 2 T. 36 NE_ST. 5E. 23.18	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water from headgate: width on top (at water line) feet; width on bottom feet; depth of water from heade feet. (c) Length of pipe, ft.; size at intake, in.; in size at om intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacities asc. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric atural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for atural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for atural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for atural stream or stream channels, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for a turb of the property of the following surface at the source of development work is less than one-fourth mile for a turb of the following surface at the source of development work is less than one-fourth mile for a turb of the following surface at the source of development work is less than one-fourth mile for a turb of the following surface at the source of development work is less than one-fourth mile for a turb of the following surface at the source of development work is less than one-fourth mile for a turb of the following s	Seet; width on bottom Seet; depth of water line	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water from headgate: width on top (at water line) feet; width on bottom feet; depth of water from head feet. (c) Length of pipe, ft.; size at intake, in.; in size at ominitake in.; size at place of use in.; difference in elevation betweet take and place of use, ft. Is grade uniform? Estimated capacitate and place of use, sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric altural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to the distance of the pearset point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to the distance of the pearset point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to the distance of the pearset point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to the distance of the pearset point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to the pearset point on each of such channels he distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to the pearset point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to the pearset point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to the pearset point of the p	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at in.; in size at in.; in size at in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capace sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric at	(b) At	mil	BT		
(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water from feet; width on bottom feet; depth of water from feet; depth of water from feet; depth of water from feet; depth of pipe, feet; size at intake, in.; in size at from intake from intake, into intake, int	(b) At	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water for the stream of the strea	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water for a feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at rom intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capace sec. ft. 10. If pumps are to be used, give size and type 8th Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric attracts at roam or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm to reach of a reaction between the stream bed and the ground surface at the source of developm to reach of a reaction between the stream bed and the ground surface at the source of developm to reach of a reaction between the stream bed and the ground surface at the source of developm to reach of a reaction between the stream bed and the ground surface at the source of developm to reach of a reaction between the stream bed and the ground surface at the source of developm to reach of a reaction between the stream bed and the ground surface at the source of developm to react of the reaction between the stream bed and the ground surface at the source of developm to react of the reaction between the stream bed and the ground surface at the source of developm to react of the reaction between the stream to react of the reaction to reaction to reaction to r	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet (c) Length of pipe, ft.; size at intake, in.; in size at om intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capace sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 EP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free attraction of area to be irrigated, or place of use Township Township Stream of the stream bed and the ground surface at the source of development work is less than one-fourth mile free attraction of area to be irrigated, or place of use Township Township Stream one-fourth mile free attraction of area to be irrigated, or place of use Township Township Stream one-fourth mile free attraction of area to be irrigated, or place of use Township Township Stream one-fourth mile free attraction of a stream of the stream o	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet (c) Length of pipe, ft.; size at intake, in.; in size at com intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capace sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Gire horsepower and type of motor or engine to be used 30 EP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of developm 12. Location of area to be irrigated, or place of use Township Nors Wulliamite Meridian 4 S. 2 " 36 NEL-S" 5.57 4 3. 2 " 36 NEL-S" 5.57 4 3. 2 " 36 NEL-S" 9.95 4 3. 2 " 36 NEL-S" 9.95 4 5. 1 26 NEL-ST 9.95 4 5. 2 3.16 3 1 1 1 1 - S 9.95 3 2 4 5 9.95				feet; grade	feet fall per
feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at rom intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacities see. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric at the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or ot	feet; width on bottom feet; depth of water for the feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ominitake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacities see. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric at the location of the well, tunnel, or other development work is less than one-fourth mile frequency in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the property of the well, tunnel, or other development work is less than one-fourth mile frequency in the property of the property in the prop	feet; width on bottom feet; depth of water feet; depth of water feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at om intake in.; size at place of use in.; difference in elevation between that and place of use, ft. Is grade uniform? Estimated capacities and place of use, sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electrical stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the stream of a such channels he difference in elevation between the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the ground	feet; width on bottom feet; depth of water feet; depth of water feet; depth of pipe, feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at in.; difference in elevation between intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capace sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric interval in the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development in the surface in elevation of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. Location of area to be irrigated, or place of use 14. S. 2 " . 36 NE . ST	feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at om intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacises. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Gire horsepower and type of motor or engine to be used 30 HP 2 phase Electrical attractions of the well, tunnel, or other development work is less than one-fourth mile from attraction of the well, tunnel, or other development work is less than one-fourth mile from attraction of the well, tunnel, or other development work is less than one-fourth mile from attraction of a stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a stream of the manufacture of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the first than the	feet; width on bottom feet; depth of water for the peet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at form intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacities sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electrical stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream bed and the ground surface at the source of developm the continuous of the stream the continuous of the stream to the stream the stream to the stream				•	
rade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at rom intake in.; size at place of use in.; difference in elevation between that a take and place of use, ft. Is grade uniform? Estimated capacitake and place of use, sec. ft. 10. If pumps are to be used, give size and type 8. Lineahaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electrical and the location of the well, tunnel, or other development work is less than one-fourth mile frequents stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development of a real to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. Location of area to be irrigated, or place of use 14. S. 2 . 36 NEL_SEL 23.18 4. S. 2 . 36 NEL_SEL 4.59 4. S. 2 . 36 SWL_SEL 4.59	feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at omining the file of use in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacities see. ft. 10. If pumps are to be used, give size and type 8n Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electrical stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development or so in elevation of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. Location of area to be irrigated, or place of use 14. S. 2 S. 36 NE-3S. 23.18 4. S. 2 S. 36 SW. 3E. 28. 4.59 4. S. 2 S. 36 SW. 3E. 3E. 4.59	get fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ominate in.; size at place of use in.; difference in elevation between that and place of use, ft. Is grade uniform? Estimated capacitate and place of use, sec. ft. 10. If pumps are to be used, give size and type 8nd Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric atural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the stream o	feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at intake in.; difference in elevation between thake and place of use, ft. Is grade uniform? Estimated capacitake and place of use, sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Gire horsepower and type of motor or engine to be used 30 HP 2 phase Electric interpretation of the well, tunnel, or other development work is less than one-fourth mile from atural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development in the stream of the stream bed and the ground surface at the source of development in the stream of the stream of the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the groun	feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ominitake in.; size at place of use in.; difference in elevation betwoen take and place of use, ft. Is grade uniform? Estimated capacitate and place of use, ft. 10. If pumps are to be used, give size and type 8th Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels are stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels are stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels are stream or stream channels. 12. Location of area to be irrigated, or place of use 13. Surface Truching and the ground surface at the source of development work is less than one-fourth mile from the fourth mile	feet fall per one thousand feet. (c) Length of pipe. (c) Length of pipe. (c) Length of pipe. (c) Length of pipe. (d) fix, size at place of use in.; size at intake, in.; in size at in.; difference in elevation between the kerdian sec. ft. 10. If pumps are to be used, give size and type 8			es from headgat	e: width on top (at water li	ne)
(c) Length of pipe, ft.; size at intake, in.; in size at from intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacitate and place of use, ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric and the location of the well, tunnel, or other development work is less than one-fourth mile from the internal stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development in the stream of the contraction of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. Location of area to be irrigated, or place of use 14. S. 2 S. 36 NEL-ST. 5.87 4. S. 2 S. 36 NEL-ST. 5.87 4. S. 2 S. 36 SWSE. 23.18 4. S. 2 S. 36 SWSE. 23.18	(c) Length of pipe, ft.; size at intake, in.; in size at ominate in.; size at place of use in.; difference in elevation between take and place of use. Sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric alural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development with the source of the	(c) Length of pipe, ft.; size at intake, in.; in size at om intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacities and place of use, sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric attraction of the well, tunnel, or other development work is less than one-fourth mile for attractive at stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for attractive in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for attractive in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for attractive in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for attractive in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for attractive in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for attractive in elevation between the distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the nearest point on each of such channels have distance to the ne	(c) Length of pipe, ft.; size at intake, in.; in size at rom intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capaca sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric along the well, tunnel, or other development work is less than one-fourth mile from aloral stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm was a grow of without the stream bed and the ground surface at the source of developm and the stream bed and the ground surface at the source of developm and the ground surface at the source of the ground surface at the source of the ground surface at the source of the ground surface at the ground	(c) Length of pipe, ft.; size at intake, in.; in size at min; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacises. ft. Is grade uniform? Estimated capacises. ft. In If pumps are to be used, give size and type 8 Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electrical phase electrical stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work in the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work in each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a cach of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a cach of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a cach of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a cach of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a cach of such channels the cache of the	(c) Length of pipe. ft.; size at intake, in.; in size at rom intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacity sec. ft. 10. If pumps are to be used, give size and type 8n Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric at the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development in or source of development work is less than one-fourth mile from a stream or stream channels give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a surface at the source of development work is less than one-fourth mile from a surface at the source of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a surface at the source of development work is less than one-fourth mile from a surface at the source of development work is less than one-fourth mile from a surface at the source of development work is less than one-fourth mile from a surface at the source of development work is less than one-fourth mile from a surface at the source of the surface at the sou		feet; width on b	ottom	feet; depth of wate	r f
in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacing sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electrical places of the location of the well, tunnel, or other development work is less than one-fourth mile from the stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work is less than one-fourth mile from the development work	om intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacing sec. ft. 10. If pumps are to be used, give size and type & Lineshaft Turbine Gire horsepower and type of motor or engine to be used 30 HP 2 phase Electrical phase always and the location of the well, tunnel, or other development work is less than one-fourth mile frequent always are always as the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as the source of development work is less than one-fourth mile frequent always are always as a section of the well, tunnel, or other development work is less than one-fourth mile frequent always are always as a section of the well, tunnel, or other development work is less than one-fourth mile frequent always are always as a section of the well, tunnel, or other development work is less than one-fourth mile frequent always are always as a section of the well, tunnel, or other development work is less than one-fourth always are always as a section of the well, tunnel, or othe	in.; size at place of use in.; difference in elevation between that and place of use. ft. Is grade uniform? Estimated capacing sec. ft. 10. If pumps are to be used, give size and type 8. Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development works are at the source of development works. 12. Location of area to be irrigated, or place of use 13. Location of area to be irrigated, or place of use 14. S. 2 1. 36 NE -51. 5.97 4. S. 2 1. 36 NE -51. 5.97 4. S. 2 1. 36 Sil -35. 4.59	in.; size at place of use in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capacing sec. ft. 10. If pumps are to be used, give size and type 8nd Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric and the location of the well, tunnel, or other development work is less than one-fourth mile from a large stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of developm and the ground sur	in.; size at place of use in.; size at place of use in.; difference in elevation betwoetake and place of use, ft. Is grade uniform? Estimated capacing sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electrical stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of developm are not always and the ground surface at the source of developm are not surface at the source of surface at the source	in.; size at place of use in.; difference in elevation betwoestake and place of use, ft. Is grade uniform? Estimated capacities sec. ft. 10. If pumps are to be used, give size and type 8. Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric actual stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of developm of Nors Nors Nors Nors 12. Location of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. 2 1. 36 NEL-ST. 5.57 4 3. 2 1. 36 NEL-ST. 5.57 4 3. 2 1. 36 NEL-ST. 5.57 4 3. 2 1. 36 NEL-ST. 9.00 4 5. 1. 26 NEL-ST. 9.00 5 20 SEL-ST. 9.00 5 21 31 Elevation of SEL ST. SEL	raae	feet fall p	er one thousand	feet.	
sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Gire horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency in a stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in each of the surface at the source of development work is less than one-fourth mile frequency in each of the surface at the source of the each of the surface at the source of the each of the surface at the source of the each of t	sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is a less than one-fourth mile freatural stream or stream channels give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channels, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channels, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each of such channels for the distance to the nearest point on each o	sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in elevation of such channels are a stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the location of such channels are a stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the location of such channels are a stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the location of such channels are a stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the location of such channels are a stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the location of the well, tunnel, or other development work is less than one-fourth mile frequency	sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a latural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a latural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a latural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a latural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a latural stream or stream channels. 12. Location of area to be irrigated, or place of use 13. 2 "" 36 NEL-S". 5.57 4 3. 2 "" 36 NEL-S". 5.57 4 3. 2 "" 36 NEL-S". 5.57 4 3. 2 " 36 NEL-S". 9.95 4 5. 1 " 36 NEL-S". 9.95 4 5. 2 " 4.59 4 5. 2 " 4.59 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Sec. ft. 10. If pumps are to be used, give size and type Bn Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channels, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream or stream channels, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or	Sec. ft. 10. If pumps are to be used, give size and type Bn Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels for the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream or stream channels for the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or strea	(c) Length of	f pipe,	ft.; size	e at intake,in	.; in size at
sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the distance of the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the source of the source of development with the source of development	sec. ft. 10. If pumps are to be used, give size and type 8. Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freature. 12. Location of area to be irrigated, or place of use 13. 2 *** 36 *** Number Acres Tract 14. 3. 2 *** 36 *** Number Acres Tract 15. 2 *** 36 *** Number Acres Tract 16. 2 *** 36 *** Number Acres Tract 17. 30 *** Number Acres Tract 18. 4 ** 3. 2 *** 36 *** Number Acres Tract 18. 5 *** Number Acres Tract 19. 5 *** Number A	sec. ft. 10. If pumps are to be used, give size and type 8. Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream channels give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile freatural stream or stream or stream channels for the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free at the source of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free at the source of development work is less than one-fourth mile free at the source of such channels her difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile free at the source of development work is less than one-fourth mile free at the source of development work is less than one-fourth mile free at the source of the surface at the source of development work is less than one-fourth mile free at the source of the surface at t	sec. ft. 10. If pumps are to be used, give size and type 8. Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream or stream or stream one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream or stream or stream one-fourth mile from the stream of the	Sec. ft. 10. If pumps are to be used, give size and type 8. Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a liveral stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a liveral stream or stream channels have difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a liveral stream or stream channels have difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a liveral stream or stream channels have difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a liveral stream or stream channels have difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a liveral stream or	sec. ft. 10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels have been difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream of the nearest point on each of such channels have been difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream of the nearest point on each of such channels have been difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from a tural stream of the nearest point on each of such channels have been development work is less than one-fourth mile from a tural stream of the nearest point on each of such channels have been development work in the such channels have been devel	rom intake	in.; s	ize at place of us	e in.; diffe	erence in elevation betu
10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile free satural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development works are the source of development works. 12. Location of area to be irrigated, or place of use Township Range Rose Willamette Meridian Section Forty-scre Treet Number Acres To Be irrigated 4 S. 2 W. 36 NE ST. 5.27 4 S. 2 W. 36 NE ST. 5.27 4 S. 2 W. 36 SW. SE. 28.18 4 S. 2 W. 36 SW. SE. 28.18 4 S. 2 W. 36 SW. SE. 38.18 4 S. 2 W. 36 NE SW. SE. 28.18 4 S. 2 W. 36 SW. SE. 38.18 4 S. 2 W. 36 NE SW. SE. 28.18	Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency at the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream of such channels have difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream of such channels have difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream of the stre	10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency at the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency at the source of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency at the source of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency at the source of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency at the source of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency at the source of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency at the surface at the source of development work is less than one-fourth mile frequency at the surface at the source of development work is less than one-fourth mile frequency at the surface at the source of the surface at the surface at the source of the surface at	10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. 2 ". 36 NE_S". 5.27 14. 3. 2 ". 36 NE_S". 5.27 15. 2 ". 36 NE_S". 5.27 16. 36 ST. SE. 23.18 17. 36 ST. SE. 23.18 28. 10. 26 SEL-32 9.95	10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from alural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of developm or as with a surface at the source of the surface at the surface at the source of the surface at the surface at the source	10. If pumps are to be used, give size and type 8" Lineshaft Turbine Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream channels, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream or stream channels for the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or stream or stream channels for the distance to the nearest point on each of such channels for the stream bed and the ground surface at the source of development work is less than one-fourth mile from a tural stream or	ntake and place of t	use,	ft. Is g	rrade uniform?	Estimated capa
Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency and stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the mannels of the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the surface at the source of the nearest point on each of such channels have a surface at the source of the nearest point on each of such channels have a surface at the source of the nearest point on each of such channels have a surface at the source of the nearest point on each of such chann	Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency at the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work of Nors Range with the stream bed and the ground surface at the source of development work of Nors Withmente Medical Rection Forty-acre Tract Tober Institute To Be Irrigated 4 S. 2 % 36 NE 5% 5% 587 4 S. 2 % 36 NE 5% 5% 582 4 S. 2 % 36 NE 5% 582 5 S. 5% 582 4 S. 2 % 36 NE 5% 582 5 S. 5 %	Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile freatural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the st	Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the individual stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of developm in the individual surface at the source of develo	Gire horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from atural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the source of the source of development of the source of	Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development was a surface at the source of development work is less than one-fourth mile from a tural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development was a su	· 	sec. ft.			
Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the	Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from airral stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from airral stream or stream channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from airral stream or stream of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from airral stream or stream or stream or stream of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from airral stream or	Gire horsepower and type of motor or engine to be used 30 EP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency at the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency at the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the source of development with the source of development with the surface at the source of development with the source of development with the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth m	Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the stream of the stream	Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from atural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of the nearest point on each of such channels are surface at the source of the nearest point on each of such channels are surface at the source of the nearest point on each of such channels are surface at the source of the nearest point on each of such channels are surface at the source of such channels are surface at the source of such channels are surface at the source of	Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the distraction of stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels to the nea	10. If pumps	are to be used, g	rive size and type	e 8º Lineshaft	Turbine
Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the source of development with the stream bed and the ground surface at the	Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from airral stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from airral stream or stream channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from airral stream or stream of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from airral stream or stream or stream or stream of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from airral stream or	Gire horsepower and type of motor or engine to be used 30 EP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency at the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency at the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the source of development with the source of development with the surface at the source of development with the source of development with the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth m	Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream of the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the stream of the stream	Give horsepower and type of motor or engine to be used 30 HP 3 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from atural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of development of the nearest point on each of such channels are surface at the source of the nearest point on each of such channels are surface at the source of the nearest point on each of such channels are surface at the source of the nearest point on each of such channels are surface at the source of the nearest point on each of such channels are surface at the source of such channels are surface at the source of such channels are surface at the source of	Give horsepower and type of motor or engine to be used 30 HP 2 phase Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the distraction of stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels to the nea					
11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency alternal stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency and the difference in elevation between the stream bed and the ground surface at the source of development with t	11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treat of such channels with the source of such channels. 12. Location of area to be irrigated, or place of use Township Range Ra	11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treat of the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treat point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treat point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treat point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treat point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treat point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than one-fourth mile from the surface at the source of development work is less than	11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the location of stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the location of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the location of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the location of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the location of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the location of such channels the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream bed and the ground surface at the source of development work is l	11. If the location of the well, tunnel, or other development work is less than one-fourth mile from atural stream or stream channels give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from atural stream or stream or each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from atural stream or each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from atural stream or each of such channels the surface at the source of development work is less than one-fourth mile from attraction to each of such channels the source of development work is less than one-fourth mile from attraction to each of such channels the source of development work is less than one-fourth mile from attraction to each of such channels the source of development work is less than one-fourth mile from attraction to each of such channels the source of development work is less than one-fourth mile from attraction to each of such channels the source of development work is less than one-fourth mile from attraction to each of such channels the such channels that the source of development work is less than one-fourth mile from attraction to each of such channels than one-fourth mile from attraction to each of such channels that the source of development work is less than one-fourth mile from attraction to each of such channels that the source of development work is less than one-fourth mile from attraction to each of such channels that the source of development work is less than one-fourth mile from attraction to each of such channels that the source of development work is less than one-fourth mile from attraction to each of such channels that the source of such channels that the source of such channel	11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a tural stream or stream channels give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a turn of the point of the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development with the source of					
Township N or S. Range 2 or W of Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated 4 S. 2 W. 36 NE = SW. 5.27 4 S. 2 W. 36 NV = SE. 23.18 4 S. 2 W. 36 SW. = SE. 4.59 4 S. 2 W. 36 NEQ = SE. 9.95	Township N or S Range 2 or W of willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated 4 S. 2 W. 36 NEL = SW. 5.27 4 S. 2 W. 36 NV. = SE. 23.18 4 S. 2 W. 36 SW. = SE. 4.59 4 S. 2 W. 36 NEL = SE. 9.95	Township Range Section Forty-acre Tract Number Acres To Be Lirigated	Township Range 2 or W of Section Forty-acre Tract Number Acres To Be irrigated	Township N or S. Range 2 or W. of Willamette Meridian Gection Forty-acre Tract Number Acres To Be Irrigated 4 S. 2 W. 36 NEL_SWL 5.27 4 S. 2 W. 36 NWL_SEL 23.18 4 S. 2 W. 36 SWL_SEL 4.59 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 36 NEL_SEL 2.45 4 S. 31 2 WSEL 2.45 4 S. 31 2 WSEL 2.24	Township N or S Range 2 or W of willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated 4 S. 2 W. 36 NEL_SWL 5.27 4 S. 2 W. 36 NWL_SEL 23.18 4 S. 2 W. 36 SWL_SEL 4.59 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 31 NEL_SEL 2.45 4 W. 31 NEL_SEL .24	• • • • • • • • • • • • • • • • • • • •	•			
Township N or S. Range 2 or W of Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated 4 S. 2 W. 36 NE = SW. 5.27 4 S. 2 W. 36 NV = SE. 23.18 4 S. 2 W. 36 SW. = SE. 4.59 4 S. 2 W. 36 NEQ = SE. 9.95	Township N or S Range 2 or W of willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated 4 S. 2 W. 36 NEL = SW. 5.27 4 S. 2 W. 36 NV. = SE. 23.18 4 S. 2 W. 36 SW. = SE. 4.59 4 S. 2 W. 36 NEL = SE. 9.95	Township Range Section Forty-acre Tract Number Acres To Be Lirigated	Township Range 2 or W of Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated	Township N or S. Range 2 or W. of Willamette Meridian Gection Forty-acre Tract Number Acres To Be Irrigated 4 S. 2 W. 36 NEL_SWL 5.27 4 S. 2 W. 36 NWL_SEL 23.18 4 S. 2 W. 36 SWL_SEL 4.59 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 36 NEL_SEL 2.45 4 S. 31 2 WSEL 2.45 4 S. 31 2 WSEL 2.24	Township N or S Range 2 or W of willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated 4 S. 2 W. 36 NEL_SWL 5.27 4 S. 2 W. 36 NWL_SEL 23.18 4 S. 2 W. 36 SWL_SEL 4.59 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 36 NEL_SEL 9.95 4 S. 2 W. 31 NEL_SEL 2.45 4 W. 31 NEL_SEL .24					
4 5. 2 7. 36 NY SE. 23.18 4 5. 2 7. 36 SW SE. 35.1 4 5. 7 7. 36 NE2-501 9.90	4 5. 2 W. 36 NY. SE. 23.18 4 3. 2 W. 36 SW. SE. 4.59 4 5. 7. 26 NE2-3E. 9.95	4 5. 2 W. 36 NUL-SEL 23.18 4 3. 2 W. 36 SWL-SEL 4.59 4 S. 7 / 26 NEL-SEL 9.95 5 3. 2 / 26 SEL-SEL 23.15	4 5. 2 W. 36 NY. SE. 23.18 4 3. 2 W. 36 SW. SE. 4.59 4 5. 7 7. 26 NE2-5D2 9.98 5 3. 27. 26 SE2-3D2 2.45	4 5. 2 W. 36 NYSE. 23.18 4 3. 2 W. 36 SWSE. 4.59 4 S. 7 / 26 NE2-3D. 9.95 5 3. 2 / 31 NYSE. 23.18	4 5. 2 W. 36 NY. SE. 23.18 4 3. 2 W. 36 SW. SE. 4.59 4 5. 7 /. 26 NE2-3E. 9.95 4 5. 2 /. 36 SE. 3E. 2.15 4 7. 31 NY. SE. 24	12. Location	of area to be ir	rigated, or place	of use	
4 5. 2 W. 36 NY. SE. 23.18 4 5. 2 W. 36 SW. SE. 4.59 4 5. 7. 26 NEL-301 9.90	4 5. 2 W. 36 NY. SE. 23.18 4 3. 2 W. 36 SW. SE. 4.59 4 5. 7 7. 26 NE2-3E. 9.95	4 5. 2 W. 36 NY. SE. 23.18 4 5. 2 W. 36 SW. SE. 4.59 4 5. 2 W. 36 NEQ-SE. 9.95 5 5. 2 W. 36 SEL-SE. 2.15	4 5. 2 W. 36 NY. SE. 23.18 4 3. 2 W. 36 SW. SE. 4.59 4 S. 7 /. 36 NE2-5E. 9.95 5 3. 3 /. 36 SE. 36 SE. 37.	4 5. 2 W. 36 NY. SE. 23.18 4 3. 2 W. 36 SW. SE. 4.59 4 5. 2 W. 36 NE2-SE. 9.95 5 3. 3 % 36 SE. 25 24 23.18	4 5. 2 W. 36 NY. SE. 23.18 4 3. 2 W. 36 SW. SE. 4.59 4 S. 7 / 26 NE2-SE. 9.95 5 3. 2 / 31 NY. SE. 23.18	Township	Range			
4 3. 2 7. 36 SWSE. 4.59 4 S. 9 7. 36 NEQ-SEL 9.95	4 3. 2 7. 36 SWSE. 4.59 4 S. 7 / 26 NE2-SE. 9.95	4 3. 2 7. 36 SWSE! 4.59 4 5. 7 7. 26 NEG-SE! 9.95	4 3. 2 7. 36 SWSE. 4.59 4 5. 7 7. 36 NEL-SE. 9.95 4 5. 37. 36 SEL-SE. 2.45	4 3. 2 7. 36 SW[-SE] 4.59 4 5. 2 7. 26 NEQ-SE] 9.95 4 5. 2 7. 26 SE]-SE] 2.15 4 7. 31 N7(-SE] .24	4 3. 2 7. 36 SW[-SE] 4.59 4 5. 2 7. 26 NEQ-SE] 9.95 5 3. 2 7. 26 SE]-SE] 2.15 6 4 7. 31 N/(-SE] .24	Township N or S.	Range Z or W. of Willamette Meridian	Gection	Forty-acre Tract	To Be Irrigated
		2.15 36 3EL-4EL 2.15	; 3. 3. 36 Spl-02 2.45	2.5. 2.6. 26 3E1-0E1 2.15 2.6. 17. 31 E7SE1 .24	2.5. 2.6. 26 3E1-0E1 2.15 2.6. 17. 31 E7SE1 .24	Township N or S	Range Z or W. of Willamette Meridian	Section 36	Forty-acre Tract NE 2 = 3"7.	To Be Irrigated
3. 3. 2. 26 SEL-UEL 2.45	; 3. 27. 26 3EL-UEL 2.15			2	31 17. 32 32.	Township N or S. 4 S.	Range Z or W. of Willamette Meridian	36 36	Forty-acre Tract NE _ S'' _ SE _	5.87 23.18
		2 7 7 21 27 24	4 1 31	2 2 22 22 22 23 40	2 2 22 22 22 23 40	Township N or 8. 4 S. 4 S.	Range Z or W. of Willamette Meridian	36 36 36	Forty-acre Tract NE _ S'' _ SE _	5.87 23.18 4.59
31 2757.	31 27/5124			31 371-371 11.42	31 37 <u>-37</u> 11.42	Township N or S 4 S. 4 S. 4 S.	Range Z or W. of Willamette Meridian	36 36 36 36	Forty-acre Tract NEQ-SVQ NVQ-SEQ NEQ-SUQ	70 Be irrigated 5 . 27 23 . 18 4 . 59 9 . 95
			. s. <u>1.42</u>			Township N or S 4 S. 4 S. 4 S.	Range Z or W. of Willamette Meridian	36 36 36 36 36	Forty-acre Tract NEQ-SVQ NVQ-SEQ NEQ-SUQ	70 Be irrigated 5.87 23.18 4.59 9.90
7. 67	31 371-371 11.42	. 0. 01 0				Township N or S 4 S. 4 S. 4 S.	Range Z or W. of Willamette Meridian	36 36 36 36 36 26 26	Forty-acre Tract NEQ-SVQ NVQ-SEQ NEQ-SUQ	70 Be irrigated 5 • \$7 23 • 18 4 • 59 9 • 95 2 • 45 • 24
7. 67 27. 77.	37. 31 37. 31.42	. 0, 11,12		A STATE OF THE PROPERTY OF THE		Township N or S. 4 S. 4 S. 4 S.	Range Z or W. of Willamette Meridian	36 36 36 36 36 26 26	Forty-acre Tract NEQ-SVQ NVQ-SEQ NEQ-SUQ	70 Be irrigated 5 • \$7 23 • 18 4 • 59 9 • 95 2 • 45 • 24
3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3			63.7C ac	63.7C Ac	63.70 ac	Township N or S. 4 S. 4 S. 4 S.	Range Z or W. of Willamette Meridian	36 36 36 36 36 26 26	Forty-acre Tract NEQ-SVQ NVQ-SEQ NEQ-SUQ	70 Be irrigated 5.27 23.18 4.59 9.90 2.45 .24 11.42
3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3. 3			63.7C Ac	63.7C ac	63.7C ac	Township N or S. 4 S. 4 S. 4 S.	Range Z or W. of Willamette Meridian	36 36 36 36 36 26 26	Forty-acre Tract NEQ-SVQ NVQ-SEQ NEQ-SUQ	70 Be irrigated 5.27 23.18 4.59 9.90 2.45 .24 11.42
4 S. 1. 36 NEQ-SEL 9.95	4 s. <u>9 /. 36 MEG-SEG</u> 9.95	4 S. 9 /. 36 NEQ-SEL 9.95	4 S. 9 /. 36 NEQ-SDQ 9.98	4 S. 9 /. 36 NEQ-SEL 9.95 4 S. 3 /. 36 SEL-SEL 2.15 4 4 . 31 N/L-SEL	4 S. 9 /. 36 NEQ-SEL 9.95 4 S. 3 /. 36 SEL-SEL 2.15 4 1 //. 31 N/L-SEL			• •		
31 \\\ \tau_{\chi_0} \\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	31 <u>1757.</u> -24			31 371-371 11.42	31 372-372 11.42	Township N or S 4 S. 4 S. 4 S.	Range Z or W. of Willamette Meridian	36 36 36 36	Forty-acre Tract NEQ-SVQ NVQ-SEQ NEQ-SUQ	70 Be irrigated 5 . 27 23 . 18 4 . 59 9 . 95

Kind of crops raised.

Vegetable Crops

33. To supply the city of	•
in county, bouing a pr	esent population of
and an estimated population of	. in 19
ANSWER QUESTIONS 14, 15,	14, 17 AND 18 IN ALL CASES
14. Estimated cost of proposed works, \$.150	0.00
15. Construction work will begin on or before	March 1,1959
16. Construction work will be completed on or	before
17. The water will be completely applied to the	he proposed use on or beforeJune30.,1960
18. If the ground water supply is supplement	ntal to an existing water supply, identify any appli- ed right to appropriate water, made or held by the
	ed right to appropriate water, made or held by the
applicant.	······································
	Fluir Gara
	(Signature of applicant)
Remarks:	•
•	
	•
•	<u></u>
·	
·	
•	<u> </u>
STATE OF OREGON,	
County of Marion,	
This is to certify that I have examined the	foregoing application, together with the accompanyin
maps and data, and return the same for	······································
· · · · · · · · · · · · · · · · · · ·	
In order to retain its priority, this application	on must be returned to the State Engineer, with correc
tions on or before	. 19
WITNESS my hand this day of	
	STATE ENGINEER
	By ASSISTANT

County of Merion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The	right herein grante	d is limited to the amo	unt of wate	r which can be ap	plied to beneficial	use and
shall not es	cceed 0,80	cubic feet per seco	nd measure	d at the point of	liversion from the	e well or
source of a	ppropriation, or its	equivalent in case of re	otation with	other water user	s, from a well	· · · · · · · · · · · · · · · · · · ·
The	use to which this t	vater is to be applied i	, irri	gation		· · · · · · · · · · · · · · · · · · ·
If fo	r irrigation, this ap	propriation shall be lin	nited to 1	/80 of	one cubic foot pe	r second
or its equi	valent for each acr	e irrigated and shall b	e further lir	nited to a diversio	n of not to exceed	2
acre feet p	er acte for each ac	ere irrigated during th	e irrigation	season of each ye	ear;	
				•		
***************************************			••••			******
			•		······································	*******
			••••			
****			······································			•• •••••
	·	•				•••••••••••••••••••••••••••••••••••••••
	•	reasonable rotation sys				
the works	shall include prop	er capping and control	valve to pr	event the waste	of ground water.	
line, adeq	uate to determine	l shall include an air l water level elevation	in the well	at all times.		
keep a con	permittee shall in nplete record of th	stall and maintain a w e amount of ground w	ater withdr	awn.	ieusuring device,	unu snatt
The	priority date of th	is permit isFob	mary 5.]	1959	•	
		ork shall begin on or b			0	and shall
		th reasonable diligenc				_
	•	of the water to the pro		•		
	INESS my hand th			rgh	19.59	•
				Klivis	J. Stan	ley
				•	STATE 1	ENG INTERES
: 1 : 1 : 1		the gon,			° 20	
	UND	ed in N. Ore			1238 1238	35
1362	E GROI	Salem Salem		,	≦	page 93.
	THE THE SON	first fer at			n pag	
Application No. G-Permit No. G-	PERMIT APPROPRIATE THE WATERS OF THE S	was fi Inginee of o'clock	nt:	1959	k No. nits on pa	isin No. Z
ation No. (PE OPRI ERS OF	trument w e State Eng A day of	plica	797	ded in boo Vater Pern LEVIS A.	Basin .
Application Permit No.	PPR WATI	natru the Si 5 H	l to ap	ed: bacoh 16,	ded i	age B
∡ v	PERMIT TO APPROPRIATE THE GROUND WATERS OF THE STATE OF OREGON	This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 5th day of Tehrwory 1957, at 10:00 o'clock A.M.	Returned to applicant:	Approved:	Recorded in book No. Ground Water Permits on page LENIS A. STANGET.	Drainage Basin No. 81412 Prin
!		on t	Ret	Apı	Gr.	
		·				