

Parati No G. 1496

APPLICATION FOR A PERKE

To Appropriate the Ground Waters of the State of Oregon

1, albert Dempsey
of Bt. / Box 25 Hulland, Dr. , county of Marion
state of, do hereby make application for a permit to appropriate the following described ground waters of the state of Oregon, SUBJECT TO EXISTING RIGHTS:
If the applicant is a corporation, give date and place of incorporation
1. Give name of nearest stream to which the well, tunnel or other source of water development is
situated Pudding River (Manne of stream)
tributary of
2. The amount of water which the applicant intends to apply to beneficial use is cubic feet per second or
3. The use to which the water is to be applied is grantien
4. The well or other source is located 1394 ft. 5 and 125 ft. & from the NE corner of CHAS, HUBBABD Donation Land Claim (Bection or subdivision)
(If preferable, give distance and bearing to section corner)
being within the NW 4 of NE4 of Sec. 34 Twp. 45, R. I.W.,
W. M., in the county of Marion
5. The Pipe line (Canal or pipe line) to be # miles
in length, terminating in the NE 4 of NE 4 of Sec. 34 , Twp. 45
R. / W. M., the proposed location being shown throughout on the accompanying map.
6. The name of the well or other works is
DESCRIPTION OF WORKS
7. If the flow to be utilized is artesian, the works to be used for the control and conservation of the supply when not in use must be described.
8. The development will consist of One Will (Give number of wells, tunnels, etc.)
diameter of
feet of the well will require Lteel casing. Depth to water table is estimated 33 (Kind)

(b) At miles from headgets: width on top (at water line) feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at 162 intake in.; size at place of use 3 in.; difference in elevation to e and place of use, 22 ft. Is grade uniform? It is grade uniform? The sec. ft. 10. If pumps are to be used, give size and type for minute. Give horsepower and type of motor or engine to be used 10 H.P. Electric The fact meeter. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile ral stream or stream channel, give the distance to the nearest point on each of such chanifiference in elevation between the stream bed and the ground surface at the source of development in the surface of the source of development in the surface at the surface at the source of development in the surface at the source of development in the surface at the surface at the source of development in the surface at the surface a	gate. At headgate: width on top (at water line) feet; depth of water feet; grade feet; width feet; width on top (at water line) feet; width on bottom feet; width on bottom feet; width on bottom feet; width on bottom feet; depth of water feet; width on bottom feet; depth of water feet; width on top (at water line) feet; depth of water line) feet; width on top (at water line) feet; depth of water line) feet; depth of water line) feet; width on top (at water line) feet; depth of water line) feet; width on top (at water line) feet; depth of water line)	. At headgate; width on t	*		
feet; depth of water feet; grade feet fall and feet. (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at 162 intake 4 in.; size at place of use 3 in.; difference in elevation of and place of use, 222 ft. 10. If pumps are to be used, give size and type 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	feet; depth of water feet; grade feet; (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at lintake in.; size at place of use in.; difference in elevative and place of use, 22 miles ft. Is grade uniform? Festimate 16. Cer. sec. ft. 10. If pumps are to be used, give size and type from what I will feet for the first fill fill feet for the fill for the fill for the fill feet for the fill feet for the fill feet for the fil		each point of cal	not where materially changed	in size, stating mil
the section of the well, tunnel, or other development work is less than one-fourth miliference in elevation between the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of deve the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and	the feet: (b) At		top (at water lin	e)	feet; width on
(b) At	(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at lintake 4 in.; size at place of use 3 in.; difference in elevative and place of use, 72 ft. Is grade uniform? 4 Estimate 36 CAT. sec. ft. 10. If pumps are to be used, give size and type for minute. Give horsepower and type of motor or engine to be used 10 H.P. Electric 1750 R.P.M. Cap. 130 gal. per minute. 11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of difference in elevation of area to be irrigated, or place of use Township 2 Parage 1 On 18 Porty-acre Tract Number 12 Location of area to be irrigated, or place of use Township 2 Range 2 On 18 Porty-acre Tract Number 18 Bection Porty-acre Tract Number 18	jeet; depth of w	ater	feet; grede	feet fall
feet; width on bottom feet fall per one thousand feet. (c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at 162 intake 4 in.; size at place of use in.; difference in elevation is e and place of use, 72 miles ft. Is grade uniform? Estimated co. 36. Cer. sec. ft. 10. If pumps are to be used, give size and type Line Maft Lucrhine (750 R.P.M. leg. 130 gal. fin minute.) Give horsepower and type of motor or engine to be used 10. Her. Electric Thue Parall Market. 11. If the location of the well, tunnel, or other development work is less than one-fourth miles tream or stream channel, give the distance to the nearest point on each of such channifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth miles of the elevation between the stream bed and the ground surface at the source of development work is less than one-fourth miles of the elevation between the stream bed and the ground surface at the source of development work is less than one-fourth miles of the elevation between the stream bed and the ground surface at the source of development work is less than one-fourth miles of the location of the well, tunnel, or other development work is less than one-fourth miles of the location of the well, tunnel, or other development work is less than one-fourth miles of the location of the well, tunnel, or other development work is less than one-fourth miles of the location of the well, tunnel, or other development work is less than one-fourth miles of the location of the well, tunnel, or other development work is less than one-fourth miles of the location of the well, tunnel, or other development work is less than one-fourth miles of the location of the well, tunnel, or other development work is less than one-fourth miles of the location of the well, tunnel, or other development work is less than one-fourth miles of the location of the well of the locatio	feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at 1 intake 4 in.; size at place of use 3 in.; difference in elevative and place of use, 22 min. ft. Is grade uniform? Fig. 18 grade uniform? Fig. 28 gr	l feet.	Mary Mary 1		
feet fall per one thousand feet. (c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at 162 intake 4 in.; size at place of use 3 in.; difference in elevation is and place of use, 2 true ft. Is grade uniform? Lestimated of 36 cer. sec. ft. 10. If pumps are to be used, give size and type Line Shaft Lumbered 130 gal. per minute. (Give horsepower and type of motor or engine to be used 10. H.P. Electric 131 fthe location of the well, tunnel, or other development work is less than one-fourth mile al stream or stream channel, give the distance to the nearest point on each of such chanifference in elevation between the stream bed and the ground surface at the source of deve 132 ft. 14	feet fall per one thousand feet. (c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at 1. intake 4 in.; size at place of use 3 in.; difference in elevative and place of use, 2000 ft. Is grade uniform? 4 Estimate 36 Cer. sec. ft. 10. If pumps are to be used, give size and type 4 Int. Shaft 1 10 for horsepower and type of motor or engine to be used 1.0 H.P. Electrice (750 R.P.M. Cep. 130 gal. per minute) (Give horsepower and type of motor or engine to be used 1.0 H.P. Electrice 11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of the nearest point of the nearest point of the nearest point of the nearest point) At 77	illes from headg	ate: width on top (at water liv	ve)
(c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at 162 intake 4 in.; size at place of use 3 in.; difference in elevation of e and place of use, 2000 ft. Is grade uniform? 400 Estimated of 36 Car. sec. ft. 10. If pumps are to be used, give size and type 4 ft. Is grade uniform? (750 R.P.M. leg. 130 gal. per minute) Give horsepower and type of motor or engine to be used 10 H.P. Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mil ral stream or stream channel, give the distance to the nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve 12. Location of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. If the location of the well, tunnel, or other development work is less than one-fourth mil ral stream or stream channel, give the distance to the nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mil ral stream or stream channel, give the distance to the nearest point on each of such channels are the source of development work is less than one-fourth mil ral stream or stream channel, give the distance to the nearest point on each of such channels. 12. Location of area to be irrigated, or place of use 13. If the location of the well, tunnel, or other development work is less than one-fourth mil ral stream or stream channels. 14. If the location of the well, tunnel, or other development work is less than one-fourth mil ral stream or stream channels. 15. If the location of the well, tunnel, or other development work is less than one-fourth mil ral stream or stream or stream channels. 16. If the location of the well, tunnel, or other development work is less than one-fourth mil to the location of the well, tunnel, or other development work is less than one-fourth mil to the location of the well, tunnel, or other develop	(c) Length of pipe, 1920 ft.; size at intake, 4 in.; in size at 1. intake 4 in.; size at place of use 3 in.; difference in elevative and place of use, 22 ft. Is grade uniform? 4 Estimate 36 Cer. sec. ft. 10. If pumps are to be used, give size and type 1 whaft 1 whire 1750 R.P.M. Ceg. 130 gal. per minute. Cive horsepower and type of motor or engine to be used 10. H.P. Electric 11. If the location of the well, tunnel, or other development work is less than one-fourtheal stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of difference in elevation of area to be irrigated, or place of use Township Range 1 are 15 getting 15 get	feet; width on	bottom	feet; depth of water	•
intake 4 in.; size at place of use in.; difference in elevation of a place of use, ?? It is grade uniform? Yes Estimated of 36 C47 sec. ft. 10. If pumps are to be used, give size and type In Maft Invited (750 R.P.M. left 130 gal. fin minute) Give horsepower and type of motor or engine to be used 10 H.P. Electric 11. If the location of the well, tunnel, or other development work is less than one-fourth mil ral stream or stream channel, give the distance to the nearest point on each of such chanifiference in elevation between the stream bed and the ground surface at the source of deve nor so a surface at the source of deve will nor so will be used 12. Location of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. If any surface is represented by the stream bed and the ground surface at the source of deve will nor so will be used 15. If we will not surface is represented by the surface of the surface is represented by the surface of the surface of the surface is represented by the surface of the surface o	intake				
e and place of use, ??	e and place of use, Real ft. Is grade uniform? The Estimate) Length of pipe,	20 ft.; si	ize at intake, 4 in.,	in size at 162
10. If pumps are to be used, give size and type Line Shaft Inviting 1750 R.P.M. log. 130 gal. per minute 18. If the location of the well, tunnel, or other development work is less than one-fourth military all stream or stream channel, give the distance to the nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve to such that the surface will be surface at the source of deve to such that the surface will be surface at the source of deve to surface at the surface to the nearest point on each of such channels are surface at the source of deve to surface at the	10. If pumps are to be used, give size and type Line shaft Inchine (750 R.P.M. lag. 130 gal. per minute Give horsepower and type of motor or engine to be used 10. H.P. Electric The Part motor 11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of difference in elevation of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. Location of area to be irrigated, or place of use 14. S	ake 4 in.;	; size at place of	use	rence in elevation b
10. If pumps are to be used, give size and type Line Shaft Lurbine 1750 R.P.M. Cep. 130 gal. for minute. Give horsepower and type of motor or engine to be used 10 H.P. Electric The Part Manuel. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile all stream or stream channel, give the distance to the nearest point on each of such chanifference in elevation between the stream bed and the ground surface at the source of deve 12. Location of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. If the location of the well, tunnel, or other development work is less than one-fourth mile all stream or stream channel, give the distance to the nearest point on each of such chanifference in elevation between the stream bed and the ground surface at the source of deve 12. Location of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use 13. If the location of area to be irrigated, or place of use 14. So I W 27 SW/4 SE/4 I SU/4 SU/4 SE/4 I SU/4 SU/4 SU/4 SU/4 I SU/4 SU/4 SU/4 SU/4 SU/4 SU/4 SU/4 I SU/4 SU/4 SU/4 SU/4 SU/4 SU/4 SU/4 SU/4	10. If pumps are to be used, give size and type Line Shaft Lurking 1750 R.P.M. leg. 130 gal. per minute Give horsepower and type of motor or engine to be used 10 H.P. Electric Three Plant motor 11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of difference in elevation of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use Township Range Range Section Forty-scre Tract Number of Deliric Williametre Moridian Section Forty-screen Tract Number of Deliric Williametre Section Forty-screen Tract Number of Deliric Williametre Section Forty-screen Tra	nd place of use,	4 ft. Is	grade uniform? Yes	Estimated c
Give horsepower and type of motor or engine to be used 10. H.P. Electric Thus - place motor. 11. If the location of the well, tunnel, or other development work is less than one-fourth mil ral stream or stream channel, give the distance to the nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream bed and the ground surface at the source of deve nearest point on each of such chan difference in elevation between the stream development with the surface at the source of the surface at the source of development with the surface at the source of the surface at the surface at the surface at the surface at	Give horsepower and type of motor or engine to be used 1.0. H.P. Electric Three place makes 11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of difference in elevation of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use Township Range S. or W. of S. Williamstie Meridian Section Forty-screen Tract Number of To Be Irrigated 4 S / W 27 SW/4 SE/4 / 5		••		,
Give horsepower and type of motor or engine to be used 10. H.P. Electric Thue - place market. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile of stream or stream channel, give the distance to the nearest point on each of such chancifference in elevation between the stream bed and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the g	Give horsepower and type of motor or engine to be used 10. H.P. Electric Thu - paal motor 11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of d 12. Location of area to be irrigated, or place of use Township Range Row Section Forty-acre Tract Number of the Number of the North Section Section Forty-acre Tract To Be Irrigated 4 S / W 27 SW/4 SE/4 / 5). If pumps are to be used	, give size and ty	pe Time shaft	Iurline
Give horsepower and type of motor or engine to be used 10. H.P. Electric Thue - place market. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile of stream or stream channel, give the distance to the nearest point on each of such chancifference in elevation between the stream bed and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the ground surface at the source of deve and the g	Give horsepower and type of motor or engine to be used 10. H.P. Electric Thu - paal motor 11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of d 12. Location of area to be irrigated, or place of use Township Range Row Section Forty-acre Tract Number of the Number of the North Section Section Forty-acre Tract To Be Irrigated 4 S / W 27 SW/4 SE/4 / 5	50 R.P.M. Cop	. 130 gal	per minute	
11. If the location of the well, tunnel, or other development work is less than one-fourth mil ral stream or stream channel, give the distance to the nearest point on each of such chancifference in elevation between the stream bed and the ground surface at the source of deve development work is less than one-fourth mil ral stream or stream or stream or such as the nearest point on each of such chancifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mil ral stream or stream or such as the nearest point on each of such chancifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mil ral stream or stream or stream or stream or such as the source of development work is less than one-fourth mil ral stream or stream or stream or such as the source of development work is less than one-fourth mil ral stream or stream or such as the source of development work is less than one-fourth mil ral stream or stream or such as the source of development work is less than one-fourth mil ral stream or such as the source of development work is less than one-fourth mil ral stream or such as the source of development work is less than one-fourth mil ral stream or such as the source of development work is less than one-fourth mil ral stream or such as the source of development work is less than one-fourth mil ral stream or such as the suc	11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation between the stream bed and the ground surface at the source of difference in elevation bed and the ground	ive horsepower and type	of motor or engis	ne to be used 10 H.P. E	lectric
11. If the location of the well, tunnel, or other development work is less than one-fourth mileral stream or stream channel, give the distance to the nearest point on each of such chancifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mileral stream or stream or such as the source of such that the ground surface at the source of development work is less than one-fourth mileral stream or stream or such as the source of such as the source of development work is less than one-fourth mileral stream or stream or such as the source of development work is less than one-fourth mileral stream or stream or such as the source of development work is less than one-fourth mileral stream or stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than or such as the source of development work is less than one-fourth mileral stream or such as the source of development work is less than or such as the source of development work is less than or such as the source of development work is less than or such as the source of development work is less than or such as the sou	11. If the location of the well, tunnel, or other development work is less than one-fourth ral stream or stream channel, give the distance to the nearest point on each of such chifference in elevation between the stream bed and the ground surface at the source of d 12. Location of area to be irrigated, or place of use Township N. or 5. Range E. or W. of Willamette Meridian Section Forty-scre Tract Number of De Irri 4 S / 4 S / 5 SW/4 SE/4 / 5				a tradition disclorate disclosing the scholar disclosing the scholar discrete.
Township N. or 5. Range E. or W. et Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated 4 S 1 W 27 SW/4 SE/4 15 34 NE/4 NE/4 12° NW/4 NE/4 155	Township Range E. or W. of Williamette Meridian Section Forty-scre Tract Number of To Be Irri		-		
N. or 8. Williamette Meridian 16 Be Irrigated 15 1 W 27 SW 1/4 SE 1/4 1 5 1 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Williamette Meridian 16 Be Irri 4 S / W 27 SW/4 SE/4 /5	wnship Range		and the same of th	Number Acres
34 NE'/4 NE'/4 12° NW'/4 NE'/4 155		. or 5. Willamette Meridian			To Be irrigated
NW 14 NE14 155	34 NE/M NE/M 12°	45 1 W			1 —
			34	ALE ILL ALE ILL	The same of the sa
			1		12°
	29 =				12° 15 <u>5</u>
					12° 15 <u>5</u>
					12° 15 <u>5</u>
					12° 15 <u>5</u>
					12° 15 <u>5</u>
					12° 15 <u>5</u>
	i i				12° 15 <u>5</u>

(If more space required, attach separate sheet)

Character of soil

Kind of crops raised Berries and Pasture

MUNICIPAL SUPPLY—	d		************	* 488 Už medo byna po na a z byodo žiri	18 4 pro 6 + 1 p. pro 6 pro 12 cm 20 + 20 cm 20 e 1
	county, having	s present popu	ilation of	4+ 0+ 4+ 4+ 4+ 4+ + + + + + + + + + + +	, a gáng e hade saliger + e replace saliga r
and an estimated population p		in 19			
has an annual hab arrents to	4				
ANSWI	ER QUESTIONS 14.		18 DF ALL	CASES	
14. Estimated cost of pr	roposed works, \$	4101-			
15. Construction work t	will begin on or be	fore	1.20	1959	,
16. Construction work s	will be completed o	n or before	Samme	K 1960	*****************
17. The water and?! be co	ompletely applied	to the propose	l use on or i	petore Isla	1 1960
II. If the ground wate	er supply is suppl	mental to an	existing so	ster supply, id	entifu anu app
cation for permit, permit, ce					
applicant	*************			••••••	•••••••
,	•				
	10000000000000000000000000000000000000	0	11.7	Dim	e seed .
			(Sig	nature of applicant	
Remarks:	•				•
	······································				
Ministration and the second of					This came is an amount into developed the Calculus and the company while held

	•••••••••••••••••••••••••••••••••••••••		••••••	•••••••••••	
	•••••••••••••••••••••••••••••••••••••••	•••••••		••••••	
		••••			•••••
······					
	•••••	•••••••			
					•••••••
					•••••
STATE OF OREGON,					
County of Marion,	•				
This is to certify that	I have examined	the foregoing o	application,	together with	the accompany
maps and data, and return th	e same for		•••••		
		•••••	***************************************	••••••	
In order to retain its p	oriority, this appli	cation must be	returned to	the State End	ineer with cor
				g	
tions on or before	• • • • • • • • • • • • • • • • • • • •	, 19			
•					
WITNESS my hand thi	is day c	of		······································	, 19
					ATATE ENCINE
		<u></u>	······································		STATE ENGINE

County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

shall not e	acceed 0.27	cubic feet per seco	nd measur	red at the point of diversion from the well or the other water users, from
-0.000.00.000.000.000.000.000.000.000.0	***************************************	, , , , , , , , , , , , , , , , , , ,		gation
••••••			<i></i>	
	•			1/80th of one cubic foot per second
				n season of each year;
acre jeet j	per acre jor each a	cre trrigated during we		s season of each year,
The state of the s	- Committee and a second secon	· · · · · · · · · · · · · · · · · · ·		
••••••			•	
	,		•••••••••	
and shall	he subject to such	reasonable votation sust	tem as ma	y be ordered by the proper state officer.
The	well shall be case	d as necessary in accor	dance wit	th good practice and if the flow is artesian
The	works constructed		ne and pr	essure gauge or an access port for measuring
The	permittee shall in		eir, meter,	or other suitable measuring device, and shall
,				November 21, 1959
				November 24, 1959 January 20, 1961 and shall
		ork shall begin on or be		completed on or before October 1, 19.61
				shall be made on or before October 1, 1962
	TNESS my hand th			January 1960
		•		Lavia a Lauley
1	l	1 2 £ 1	;	/
١	QN.	in tl Orego		
26	GROU	ceived alem, C 1 & C. L.		ge 149.
Application No. G- 16-26 Permit No. G- 14-94	PERMIT APPROPRIATE THE GROUND WATERS OF THE STATE OF OREGON	This instrument was first received in the ce of the State Engineer at Salem, Oregon, the LALAday of NOVEWDELL.		page st
G- 1	PERMIT PRIATE THE SS OF THE SF OREGON	tment was fi tate Enginee: Aay of .N.c. O.C o'clock	ıt:	book No. Permits on Stain No. Z
ation t No. (PER APPROPRIAT WATERS OF OF OR	tate E	oplica	proved: January 2C. 1960 Recorded in book No. nund Water Permits of LEVIS A. STALLEY Drainage Basin No.
Application Permit No.	APPR	instru the S	d to aj	proved: January Recorded i nund Water Drainage I
, 7	70	This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 24 thay of November	Returned to applicant	Approved: January 20. 1960 Recorded in book No. 6. Ground Water Permits on page IEVIS A. STALLEY Drainage Basin No. 2. page
	I		₹ :	: ₹ : 5 :