

APPLICATION FOR A PERMIT

To Appropriate the Ground Waters of the State of Oregon

	<i>I</i> ,	Charles F.	Thomas (Name of applican	•••	*****
of	River Rd	1., Gladstone (Postoffice Address		, county of Clackamas	· ···· · · · · · · · · · · · · · · · ·
state follou	ofOz	MgQD	, do hereby 1	make application for a permit to appr SUBJECT TO EXISTING RIGHTS	opriate the
	If the appl	licant is a corporati	ion, give date and place o	of incorporation	
************				tunnel or other source of water deve	elopment is
s ituat	edCl	ackamas river	(Name c		
				tributary of Willamotte Rive	er
feet p	2. The an	nount of water wh or 200 gal	tich the applicant intend lons per minute.	ds to apply to beneficial use is	cubic
	3. The us	e to which the wat	ter is to be applied is	Watering & golf course	
01 34455	4. The we	ell or other source in which is 106 quarter section	is located ft. feet north of a state corner between Sec	and 1149 ft. Ely from the 35.37 chains S. Egrw 7.88 ctions 19 and 20	the conter chains W. c
<	2865.		by 1479 ff	subdivision) West from E'4 (6/ ing to section corner)	Sec 19
being	within the	(If there is more t	than one we'', each must be described.	f Sec. 30., Twp. 2. S., R.	2. E. of
) The S		
	5. The				miles
in len	gth, termin	nating in the	(Canal or pipe line)	of Sec. Two	
R		. M., the proposed	(Smallest legal subdivision location being shown th	n) aroughout on the accompanying map.	
			other works is 🛦 🖈		
			DESCRIPTION OF		
suppl	7. If the f y when not	low to be utilized i in use must be de	is artesian, the works to	be used for the control and conserva	ition of the
····		***	· ······		
•••••					
			••••		
	8. The de	velopment will co	nsist of QDS WG	11 re number of wells, tunnels, etc.)	having a
diame	eter of t	gminches an		f 60 to 65 feet. It is estimated th	at 56
feet o	f the well 1	will require	steel casing.	. Depth to water table is estimated	34 feet

feet; depth of water feet; grade feet fall per musand feet. (b) At miles from headgate; width on top (at water line) feet; width on bottom feet; depth of water fall per mile feet; width on bottom feet; depth of water fall per one thousand feet. (c) Length of pipe. ft.; size at intake, in.; in size at intake in.; difference in elevation between the size at place of use in.; difference in elevation between the size and type 15 horse-power submersibleturbine Cive horsepower and type of motor or engine to be used 15 horse-power submersibleturbine Cive horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fritural stream or stream channel, give the distance to the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fritural stream or stream channel, give the distance to the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fritural stream or stream channel, give the distance to the nearest point on each of such channels at the source of development work is less than one-fourth mile fritural stream or stream channel, give the distance to the nearest point on each of such channels at the source of development work is less than one-fourth mile fritural stream or stream channel give the distance to the nearest point on each of such channels at the source of development work is less than one-fourth mile fritural stream or stream work is less than one-fourth mile fritural stream or stream o	uyute. At neat	ayatt. widin on to	p (at water time)		
feet; width on bottom feet; depth of water fine) feet; width on bottom feet; depth of water fine feet; width on bottom feet; depth of water fine feet; width on bottom feet; depth of water fine feet; width on bottom feet; depth of water fine feet; width on bottom feet; depth of water fine feet; width on bottom feet; depth of water fine feet; width on bottom feet; depth of water fine fine; in size at intake, in.; in size at in.; difference in elevation betwe ake and place of use, ft. Is grade uniform? Estimated capa sec. ft. 10. If pumps are to be used, give size and type 15 horse-power subwersible turbine Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequently stream or stream channel, give the distance to the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of developments from Cleckanes River with ground surface 801 shove stream bed. 7501 from Willemotte River with ground surface 801 shove stream bed. 12. Location of area to be irrigated, or place of use Township River with ground surface 801 shove stream bed. 13. 2 area of the section for the section		feet; depth of wate	er	feet; grade	feet fall per
feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at mintake in.; size at place of use in.; difference in elevation betw ake and place of use, ft. Is grade uniform? Estimated capa sec. ft. 10. If pumps are to be used, give size and type 15 horse-power submersibleturbine Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frectural stream or stream channel, give the distance to the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frectural stream or stream channel, give the distance to the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of development with ground surface at the source of development with ground surface 80° above stream bed. 750° from Clackeness River with ground surface 80° above stream bed. 12. Location of area to be irrigated, or place of use Township Range York-off Williamste Meridian Section Forty-sere Tract Number Arres To be Irragated 751 The Backeness Number Arres To be Irragated 752 Surfa Seriay 154 Surfa Seriay	usand feet.				
de feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at m intake in.; size at place of use in.; difference in elevation betu ake and place of use, ft. Is grade uniform? Estimated capa sec. ft. 10. If pumps are to be used, give size and type 15 horse-power submersibleturbine Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequent stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequent stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the distance in the stream bed and the ground su	(b) At	mil	es from headgate	e: width on top (at water liv	ne)
(c) Length of pipe, ft.; size at intake, in.; in size at m intake in.; size at place of use in.; difference in elevation betu ake and place of use, ft. Is grade uniform? Estimated capa sec. ft. 10. If pumps are to be used, give size and type 15 horse-power submersible turbine Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fractural stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of developments are in elevation between the stream bed and the ground surface at the source of developments. 750' from Clackanas River with ground surface 80' above stream bed. 12. Location of area to be irrigated, or place of use Township Range R		feet; width on b	oottom	feet; depth of water	r. J
m intake in.; size at place of use in.; difference in elevation betu ake and place of use, ft. Is grade uniform? Estimated capanasec. 10. If pumps are to be used, give size and type 15 horse-power submersible turbine Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequent stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequent in the stream of the meanest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at t	de	feet fall p	er one thousand	feet.	
sec. ft. 10. If pumps are to be used, give size and type 15 horse-power submersible turbine Give horsepower and type of motor or engine to be used 15 horse-power electric submersible notor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fractural stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream cannot be remarked and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream cannot be remarked and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream or stream one-fourth mile fractural stream	(c) Length	ı of pipe,	ft.; size	at intake, in in	; in size at
Sec. ft. 10. If pumps are to be used, give size and type 15 horse-power submersible turbine Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream channels are difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than o	m intake	in.; s	ize at place of us	e in.; diffe	rence in elevation betu
10. If pumps are to be used, give size and type 15 horse-power submersible turbine Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency in the stream channel, give the distance to the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream of the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of development work is less than one-fourth mile frequency in the stream bed and the ground surface at the source of developmen	ake and place	of use,	ft. Is g	rade uniform?	. Estimated capa
Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fractural stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channels, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream or stream or stream or such channels e difference in elevation between the stream bed and the ground surface 80' above stream bed. 750' from Willamotte River with ground surface 80' above stream bed. 12. Location of area to be irrigated, or place of use Township Nor S. Page 19 Stall SE'19 12 23. 25. 25. 25. 26. 26. 26. 26. 27. 27. 27. 27. 27. 27. 27. 27. 27. 27		sec. ft.			
Give horsepower and type of motor or engine to be used 15 horse-power electric submersible motor 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fractural stream or stream channel, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channels, give the distance to the nearest point on each of such channels e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream or stream or stream or such channels e difference in elevation between the stream bed and the ground surface 80' above stream bed. 750' from Willamotte River with ground surface 80' above stream bed. 12. Location of area to be irrigated, or place of use Township Nor S. Page 19 Stall SE'19 12 23. 25. 25. 25. 26. 26. 26. 26. 27. 27. 27. 27. 27. 27. 27. 27. 27. 27	10. If pum	ips are to be used, g	give size and type	15 horse-power sub	mersibleturbine
11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency stream or stream channel, give the distance to the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of development of the control of the stream bed and the ground surface at the source of development of the control					
11. If the location of the well, tunnel, or other development work is less than one-fourth mile from tural stream or stream channel, give the distance to the nearest point on each of such channels to difference in elevation between the stream bed and the ground surface at the source of development of the control of the source of development of the control of the c	Give horse	power and type of	motor or engine	to be used 15 horse-pow	er electric
11. If the location of the well, tunnel, or other development work is less than one-fourth mile frequency stream channel, give the distance to the nearest point on each of such channels edifference in elevation between the stream bed and the ground surface at the source of development of the source of					
Township Range Z or W. of Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated 2 S. 2 B. 1960 19 SE'14 TRACES A SUMP SE'14 TRACES A	tural stream of difference in 275° from C	or stream channel elevation between lackanas River	, give the distar the stream bed with ground	and the ground surface at	the source of develop
2 S. 2 B. 1944 /9 Swill Seine 22 acres	tural stream of difference in 275' from 0	or stream channel elevation between clackamas River fillametta River	, give the distart the stream bed with ground a	surfact 80' above str	the source of develops
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackanas River fillamette River ion of area to be in	, give the distart the stream bed with ground are with ground arrigated, or place	surfact 80' above streets of use	the source of develops eam bed. Number Acres
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place section	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place section	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place section	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place section	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place	of use	Number Acres To Be Irrigated
	tural stream of difference in 275° from 0.750° from 0.	or stream channel elevation between clackamas River fillamette River ion of area to be in Range Z or W. of Willamette Meridian	, give the distart the stream bed with ground are with ground are rigated, or place	of use	Number Acres To Be Irrigated

13. To supply the city of	
	present population of
and an estimated population of	in 19
ANSWER QUESTIONS 14, 1	US, 16, 17 AND 18 IN ALL CASES
14. Estimated cost of proposed works, \$	3500.
15. Construction work will begin on or befo	
	or before Work completed
17. The water will be completely applied to	o the proposed use on or before Immediately
18. If the ground water supply is supplemention for permit permit pertisions or adjudi-	mental to an existing water supply, identify any applicated right to appropriate water, made or held by the
applicant.	
	(Signature of applicant)
Remarks:	
STATE OF OREGON,	
County of Marion,	
This is to certify that I have examined t	the foregoing application, together with the accompanying
maps and data, and return the same for	
	tion must be noturned to the State Freinger with correct
	cation must be returned to the State Engineer, with correc
tions on or before	, 19
WITNESS my hand this day o	of, 19 .
	STATE ENGINEER
	By

County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same. SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

		i is limited to the an		which can be appl	ied to beneficial use	and
		cubic feet per se				
ource of ap	propriation, or its e	equivalent in case of	rotation with	other water users, j	rom a well	***
The v	ise to which this w	pater is to be applied	is	rrigation		
•••••						
		propriation shall be l e irrigated and shall				
		re irrigated during				
		reasonable rotation s				
The	mell shall be cased	d as necessary in ac	cordance with	good practice an	d if the flow is ar	
The	works constructed	er capping and contr I shall include an air water level elevatio	r line and pres	ssure gauge or an o	access port for mea	suring
The	permittee shall ins	water level elevalio stall and maintain a e amou nt of ground	weir, meter, c	r other suitable me	easuring device, and	i shall
neep a con		,,,				
		is permit is		May 16, 1961 August 11, 196		
		ork shall begin on or		•		i shall 62
		th reasonable dilige				67
	iplete application of the control of	of the water to the pais		August	19 61	
**11	NESS my hand in			Lewis a.	Stanley	
				• •	STATE ENG	INEER
	0	n the		70	29	<i>:</i>
27 76	OUN	ived i			186.	\
20%	E GRO	it Sale			· [a find
ප් `	PERMIT APPROPRIATE THE GROUND WATERS OF THE STATE OF OREGON	neer o		1961	ts on pag	· ±
Application No. Permit No. G-	PERMI PRIATE T RS OF TH OF OREG	nent was fi ate Enginee day of	icant:	п, ц	ermits A. S.	State Printing
Application Permit No.	PROP VTER	e State Eng	appli	ed: August 1	ater P	je nas st
Арр	l.	ins th		Approved:	Ground Water Permits on page LEATS A. STANLEY	Drainage Basin Ivo. Sue Prin
	OT	This office of on the	Retur	Appr	Grou	7