Permit No. G- 2171

APPLICATION FOR A PERMIT

To Appropriate the Ground Waters of the State of Oregon

1, - a x c/d 4 B - a co > c	
of AT3 Box 89 SCID county of AIN N	
state of, do hereby make application for a permit to appropr following described ground waters of the state of Oregon, SUBJECT TO EXISTING RIGHTS:	iate the
If the applicant is a corporation, give date and place of incorporation	,
1. Give name of nearest stream to which the well, tunnel or other source of water develop	ment is
situated Scath San Tian	
situated Seath San Time of stream) (Name of stream) tributary of Use 1/ans si	<i>.</i>
2. The amount of water which the applicant intends to apply to beneficial use is feet per second or 3.6.6. gallons per minute.	
3. The use to which the water is to be applied is	
aiscribec land	
4. The well or other source is located /156 ft. W. and 156 ft. 11 from the	EY
corner of & Co C+ 5= (./it) 33 (Section or subdivision)	
(If preferable, give distance and bearing to section corner)	
being within the SE /4 NE /4 of Sec. 33, Twp. 165, R.	у <i>н</i> ,
W. M., in the county of \mathcal{L} \mathcal{N} \mathcal{N}	
5. The (Canal or pipe line)	miles
in length, terminating in the	
R W. M., the proposed location being shown throughout on the accompanying map.	
6. The name of the well or other works is	
DESCRIPTION OF WORKS	
7. If the flow to be utilized is artesian, the works to be used for the control and conservation supply when not in use must be described.	on of the
. The second of	
and the second of the second o	
8. The development will consist of (Give number of wells, tunnels, etc.)	having (
diameter of inches and an estimated depth of 12 feet. It is estimated tha	t 17
feet of the well will require STEC casing. Depth to water table is estimated	3 (Feet)

headgate. At headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet. (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet. (c) Length of pipe, ft.; size at intake, in.; in size at ft from intake in.; difference in elevation between intake and place of use, ft. Is grade uniform? Estimated capacity sec. ft. 10. If pumps are to be used, give size and type Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels are	2171				
thousand feet. (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet: grade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ft. from intake in.; size at place of use in.; difference in elevation between intake and place of use, ft. Is grade uniform? Estimated capacity sec. ft. 10. If pumps are to be used, give size and type Generally for the horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels are the difference in elevation between the stream bed and the ground surface at the source of development in the difference in elevation between the stream bed and the ground surface at the source of development in the difference in elevation between the stream bed and the ground surface at the source of development in the difference in elevation between the stream bed and the ground surface at the source of development in the difference in elevation between the stream bed and the ground surface at the source of development in the difference in elevation between the stream bed and the ground surface at the source of development in the difference in elevation between the stream bed and the ground surface at the source of development in the difference in elevation between the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of the stream bed and the g	CANAL SYSTE	M OR PIPE LINE	-1000	\$	
feet; depth of water feet; grade feet fall per one thousand feet. (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ft. from intake in.; size at place of use in.; difference in elevation between intake and place of use, ft. Is grade uniform? Estimated capacity, sec. ft. 10. If pumps are to be used, give size and type Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development in the difference in elevation between the stream bed and the ground surface at the source of development in the stream of the difference in elevation between the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed and the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream bed in the ground surface at the source of development in the stream of the ground surface at the source of development in the stream of the ground surface at the source of the stream of the stream of the	9. (a) Giv	re dimensions at ea	ch point of c	c <mark>anal</mark> where materially changed	l in size, stating miles from
housand feet. (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ft. from intake in.; size at place of use in.; difference in elevation between intake and place of use, ft. Is grade uniform? Estimated capacity, sec. ft. 10. If pumps are to be used, give size and type FF N 1 1 GCA FF. Give horsepower and type of motor or engine to be used FF N 1 1 GCA FF. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a matural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development the difference in elevation between the stream bed and the ground surface at the source of development to be irrigated, or place of use Township Refer to the irrigated or place of use Township Refer to the irrigated or place of use Number Acres To be irrigated.	readgate. At hea	dgate: width on to	p (at water li	ine)	feet; width on bottom
(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ft. from intake in.; size at place of use in.; difference in elevation between intake and place of use, ft. Is grade uniform? Estimated capacity sec. ft. 10. If pumps are to be used, give size and type CP V Y 1 Sec. 1 Give horsepower and type of motor or engine to be used for a C fixed		feet; depth of wat	et	feet; grade	feet fall per one
feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at ft. from intake in.; size at place of use in.; difference in elevation between intake and place of use, ft. Is grade uniform? Estimated capacity sec. ft. 10. If pumps are to be used, give size and type SP VIII SECS Give horsepower and type of motor or engine to be used SP VIII SECS 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a matural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development to difference in elevation between the stream bed and the ground surface at the source of development to the contract of the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of development to the stream bed and the ground surface at the source of the stream bed and the ground surface at the source of the stream bed and the	housand feet.				
(c) Length of pipe, ft.; size at intake, in.; in size at ft. ft. rom intake in.; size at place of use in.; difference in elevation between ntake and place of use, ft. Is grade uniform? Estimated capacity, sec. ft. 10. If pumps are to be used, give size and type Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development 12. Location of area to be irrigated, or place of use Township Even of Be Irrigated Williamette Meridian Bection Forty-acre Treet Number Acres To Be Irrigated	(b) At	mil	es from head	lgate: width on top (at water li	ne)
(c) Length of pipe, ft.; size at intake, in.; in size at ft. rom intake in.; size at place of use in.; difference in elevation between ntake and place of use, ft. Is grade uniform? Estimated capacity, sec. ft. 10. If pumps are to be used, give size and type Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development 12. Location of area to be irrigated, or place of use Township Township Even C. Porty-acre Tract Number Acres To Be Irrigated		feet; width on b	oottom	feet; depth of wate	er feet;
in.; size at place of use in.; difference in elevation between ntake and place of use, ft. Is grade uniform? Estimated capacity. sec. ft. 10. If pumps are to be used, give size and type GP V 1 1 1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	rade	feet fall p	er one thouse	and feet.	
Sec. ft. 10. If pumps are to be used, give size and type Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a matural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development and the ground surface at the source of development and the ground surface at the source of development are ground surface at the sourc	(c) Lengtl	h of pipe,	ft.;	size at intake, in	; in size at ft.
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development less than one-fourth mile from a natural stream or stream or stream channels. 12. Location of area to be irrigated, or place of use	rom intake	in.; s	ize at place o	f use in.; diffe	erence in elevation between
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a matural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development surface at the source of development develo	ntake and place	of use,	ft.	Is grade uniform?	Estimated capacity.
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development development in the difference in elevation of area to be irrigated, or place of use 12. Location of area to be irrigated, or place of use Township Range 2. or W. of 8 getton Porty-acre Tract Number Acres To Be Irrigated					,
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development and the ground sur	10. If pun	nps are to be used.	rive size and	tupe GP N/ 11	ecal Lix
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a matural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development development is a surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source					
11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development developmen		••••			
11. If the location of the well, tunnel, or other development work is less than one-fourth mile from a natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development developmen	Give horse	power and type of	motor or eng	gine to be used L.C. 120	Com Chair Co
natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development at the ground surface at the ground surface at the source of development at the ground surface at the ground surface at the g			····		
natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development devel	11 If the	location of the wel	l tunnel or o	other development work is less	than one-fourth mile from o
12. Location of area to be irrigated, or place of use Township Range Section Forty-acre Tract Number Acres To Be Irrigated	natural stream	or stream channel	, give the di	stance to the nearest point on	each of such channels and
Township Range E. or W. of Willemette Meridian Section Forty-acre Tract Number Acres To Be Irrigated	the difference in	elevation between	the stream	bed and the ground surface at	the source of development
Township Range S. or W. of Willemette Meridian Section Forty-acre Tract Number Acres To Be Irrigated					
Township Range E. or W. of Bection Forty-acre Tract Number Acres To Be Irrigated		·····			
Township Range E. or W. of Bection Forty-acre Tract Number Acres To Be Irrigated					
Township E. or W. of Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated	12. Locat	ion of area to be ir	rigated, or pl	lace of use	
1. 5 2 W 33 SE14 NE1/4 21.1 total S. p. 12. 6 Prim. 2.5		Z. or W. of	Section	Forty-acre Tract	
S. p. 12. 6 P.im. 2. 5	, ,	3 10	33	SE /4 NEV	21.1 total
P.im. 2. 5					S. = 1) 16
	-				Pin 25
		1 .			

(If more space required, attach separate sheet)

Character of soil	
Kind of crops raised	

county, havin	
	ig a present population of
nd an estimated population of	in 19
ANSWER QUESTIONS 1	14, 15, 16, 17 AND 16 IN ALL CASES
14. Estimated cost of proposed works,	8
	before Gon Ple Ted
•	d on or before Con Plitted
19. The englan will be completely and	ed to the proposed use on or before CC 1,1963
18. If the ground water supply is sup ation for permit, permit, certificate or adj	oplemental to an existing water supply, identify any applitudicated right to appropriate water, made or held by the
pplicant 30 27/ a	pplication
30781	
Remarks:	Carolic (Signature of applicant)
L.D in 7:1/c 3	+ 871 30781
	(J
······································	
3	
STATE OF OREGON,	
County of Marion,	
This is to certify that I have examine	ed the foregoing application, together with the accompanying
maps and data, and return the same for	
In order to retain its priority, this are	plication must be returned to the State Engineer, with corre
tions on or before	, 19
WITNESS my hand this da	y of, 19,
	STATE ENGINEE
	Ву

County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

	0.26	ed is limited to the amo				
shall not es	xceed	equivalent in case of r			_	well
The	use to which this t	water is to be applied	_{is} irri e ti	on and suppl	emental i	rrigation
		opropriation shall be li	mited to 4	′80 <u>*</u>	f one cubic	foot per second
		re irrigated and shall b			•	
		cre irrigated during th				
		herein shall be 1				
supply o	of any prior rie	ght existing for t	he same la	nd and shall	not exce	sed the
limitati	on allowed here	ein,				
	•					
*** ** ** ** * * * *				······································	•••••••••••••••••••••••••••••••••••••••	

and shall	be subject to such	reasonable rotation sy	stem as may	be ordered by t	he proper s	tate officer.
the works The line, adeq	shall include prop works constructed uate to determine permittee shall in	ed as necessary in according and controller capping and controller and air water level elevation ustall and maintain a une amount of ground une	l valve to pro line and pres in the well o veir, meter, o	event the waste ssure gauge or a at all times. r other suitable	of ground in access po	water. ort for measuring
	priority date of th			11, 1962		
Act	ual construction w	oork shall begin on or	before	August 27, 19	963	and shal
thereafte	r be prosecuted w	ith reasonable diligen	ce and be co	ompleted on or	before Oct	
	•	of the water to the pro				
WI	TNESS my hand th	his $\frac{27^{2}}{}$ day of	Augus	·	, 19.6	2
			<i>C</i>	Krist	-she	STATE ENGINEER
Application No. G- 235/ Permit No. G- 2/7/	PERMIT TO APPROPRIATE THE GROUND WATERS OF THE STATE OF OREGON	This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 1/1 the day of the state of the state of the o'clock.	Returned to applicant:	Approved:	Recorded in book No. 8 of Ground Water Permits on page 2171	CHRIS I., WHELLER GTATE ENGINEER Drainage Basin No. 2. page 96.11