

Permit No. G- 2401

APPLICATION FOR A PERMIT

To Appropriate the Ground Waters of the State of Oregon

I, CLYDE W. FENIMORE (Name of applicant)	
of Route 6, Lakeview	•
state of Oregon , do hereby make ap	pplication for a permit to appropriate the
following described ground waters of the state of Oregon, SUBJE	
If the applicant is a corporation, give date and place of incorp	poration
· · · · · · · · · · · · · · · · · · ·	
1. Give name of nearest stream to which the well, tunnel	or other source of water development is
situated Drews Creek (Name of stream)	
tribut	
2. The amount of water which the applicant intends to applicate per second or 1500 gallons per minute.	ply to beneficial use is cubic
3. The use to which the water is to be applied isIrr	rigation
4. The well or other source is located 1438.3 ft. N or S.	and 105.3 ft. E from the N quarte
corner of Section 30, Township 40 South, Range 19 E	ast of the Willamette Meridian
(This well has had a previous filing - see remarks (If preferable, give distance and bearing to sect	
(If there is more than one we'll each must be described. Use so	eparate sheet if necessary)
being within the NW ₄ SE ₄ of Sec.	19 Twp . 40S R . 19E
W. M., in the county of Lake	•
5. The	to be 3 1/4 miles
in length, terminating in the NELNEL (Smallest legal subdivision)	of Sec. 19 . Twp 4CS .
R. 19E . W. M., the proposed location being shown through	out on the accompanying map.
6. The name of the well or other works is Well No. 2,	Clyde W. Fenimore
DESCRIPTION OF WOR	RKS
7. If the flow to be utilized is artesian, the works to be use supply when not in use must be described.	ed for the control and conservation of the
	· · · · · · · · · · · · · · · · · · ·
8. The development will consist of one well (alrea	idy filed on) having a per of wells, tunnels, etc.)
diameter of 10 inches and an estimated depth of 48	feet. It is estimated that 160
	th to water table is estimated
drawn down to 25†	(Feet)

feet; width on bottom feet; depth of water line) feet; width on bottom feet; depth of water ide feet fall per one thousand feet. (c) Length of pipe. ft.; size at intake. in.; in size at om intake in.; size at place of use in.: difference in elevation be ake and place of use. ft. Is grade uniform? Estimated ca sec. ft. 10. If pumps are to be used, give size and type 10. Lane & Bouler 3 stage boltes Give horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile tivual stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development in the source of the source
pusand feet. (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water ade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at om intake in.; size at place of use in.; difference in elevation but take and place of use, ft. Is grade uniform? Estimated va sec. ft. 10. If pumps are to be used, give size and type 10. Lane & Bouler 3 stage boltes Give horsepower and type of motor or engine to be used 30. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile actural stream or stream channel, give the distance to the nearest point on each of such channel actural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile actural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile actural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile actural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile actural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile actural stream or stream channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile actural stream or stream channel ediffe
feet; width on bottom feet; depth of water ade feet fall per one thousand feet. (c) Length of pipe. ft.; size at intake. in.; in size at om intake in.; size at place of use in.: difference in elevation be take and place of use. ft. Is grade uniform? Estimated ca sec. ft. 10. If pumps are to be used, give size and type 10. Lane & Bouler 3 stage boltes Give horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development in the stream of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile
feet; width on bottom feet; depth of water ide feet fall per one thousand feet. (c) Length of pipe. ft.; size at intake. in.; in size at om intake in.; size at place of use in.: difference in elevation be take and place of use. ft. Is grade uniform? Estimated va sec. ft. 10. If pumps are to be used, give size and type 10. Lane & Bouler 3 stage boltes Give horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile aivaral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development in the surface at the surface at the source of development in the surface at the surface a
feet fall per one thousand feet. (c) Length of pipe. ft.; size at intake. in.; in size at in.; difference in elevation be take and place of use. ft. Is grade uniform? Sec. ft. 10. If pumps are to be used, give size and type 3 stage boltes Give horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile airural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development 12. Location of area to be irrigated, or place of use
(c) Length of pipe. ft.; size at intake. in.; in size at minitake in.; size at place of use in.; difference in elevation be take and place of use. ft. Is grade uniform? Estimated ca sec. ft. 10. If pumps are to be used, give size and type 3 stage boltes Give horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel work is less than one-fourth mile airral stream or stream channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the di
om intake in.; size at place of use in.: difference in cleration be take and place of use. ft. Is grade uniform? Estimated ca sec. ft. 10. If pumps are to be used, give size and type 10. Lane & Bouler 3 stage boltes Give horsepower and type of motor or engine to be used 30. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile advance at stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile advance in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile advance in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile advanced in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development work is less than one-fourth mile advanced in elevation of the well, tunnel, or other development wo
sec. ft. 10. If pumps are to be used, give size and type 10. Lane & Bouler 3 stage boltes Give horsepower and type of motor or engine to be used 30. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel to the nearest point
sec. ft. 10. If pumps are to be used, give size and type 10. Lane & Bouler 3 stage boltes Give horsepower and type of motor or engine to be used 30. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel airral stream bed and the ground surface at the source of development work is less than one-fourth mile airral stream or stream channel, give the distance to the nearest point on each of such channel airral stream or stream channel give the distance to the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the nearest point on each of such channel give the distance of the n
10. If pumps are to be used, give size and type 10. Lane & Bouler 3 stage boltes Give horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile attend stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile attend to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile attend to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile attend to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile attend to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile attend to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile attend to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile attend to the nearest point of the surface at the source of development work is less than one-fourth mile attend to the nearest point of the surface at the source of the nearest point of the surface at the source of the nearest point of the surface at the source of the nearest point of the surface at the source of the nearest point of the surface at the source of the nearest point of the surface at the source of the nearest point of the surface at the source of the
Give horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile award stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile award stream or stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile award stream or stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile award stream or stream or stream channel, give the distance to the nearest point on each of such channel difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile award stream or str
Gire horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile thural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile thural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile thural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile thural stream or stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile thural stream or stre
Give horsepower and type of motor or engine to be used 30 11. If the location of the well, tunnel, or other development work is less than one-fourth mile tural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile stream or stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile stream or stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile stream or stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile stream or str
Township N. or S E. or W. of Section Forty-acre Tract To Be Irrigated
40 S 19 E 19 NELNEL 26.4
40 S 19 E 19 NW-NE- 2.2
40 S 19 E 20 NW1NW1 17.3
10 S 19 E 20 SW1NW1 3.4

(If more space required, attach separate sheet)

Character of soil	Loan			
Kind of crops raised	Hav	and	Grain	

ASSISTANT

MUNICIPAL SUPPLY—	
13. To supply the city of	
in county, l	having a present population of
and an estimated population of	in 19
ANSWEE QUESTIC	ONS 14, 15, 16, 17 AND 18 IN ALL CASES
14. Estimated cost of proposed wo	orks, \$ 600
15. Construction work will begin o	on or before September 1, 1963
16. Construction work will be com	pleted on or before October 1, 1963
17. The water will be completely	applied to the proposed use on or before October 1, 1964
18. If the ground water supply i cation for permit, permit, certificate o	s supplemental to an existing water supply, identify any appli- or adjudicated right to appropriate water, made or held by the
applicant. None - this	is a new filing
	(Senature of applicant)
Remarks: Applicant inter	nds to abandon supplemental right from said well
on 27.0 acres of land lo	cated in SW1SW1, Section 20, Township 40 South,
nge 19 Fast of the Willamett Meric	dian and to use water on this filing.
	<u></u>
	<u></u>
STATE OF OREGON, ss.	
County of Marion,	
•	amined the foregoing application, together with the accompanying
maps and data, and return the same for	7
	•
In order to retain its priority, th	his application must be returned to the State Engineer, with corre
tions on or before	, 19
	·
WITNESS my hand this	day of

County of Marion.

This is to certify that I have examined the foregoing application and do hereby grant the same,

SUBJECT TO EXISTING RIGHTS and the following limitations and conditions: The right herein granted is limited to the amount of water which can be applied to beneficial use and 0.62 cubic feet per second measured at the point of diversion from the well c shall not exceed source of appropriation, or its equivalent in case of rotation with other water users, from Penimore well No. 2 irrigation The use to which this water is to be applied is 1/802 If for irrigation, this appropriation shall be limited to ... of one cubic foot per second or its equivalent for each acre irrigated and shall be further limited to a diversion of not to exceed 3 acre feet per acre for each acre irrigated during the irrigation season of each year; and shall be subject to such reasonable rotation system as may be ordered by the proper state officer. The well shall be cased as necessary in accordance with good practice and if the flow is arresian the works shall include proper capping and control valve to prevent the waste of ground water. The works constructed shall include an air line and pressure gauge or an access port for measuring line, adequate to determine water level elevation in the well at all times. The permittee shall install and maintain a weir, meter, or other suitable measuring device, and shall keep a complete record of the amount of ground water withdrawn. April 10, 1963 The priority date of this permit is Actual construction work shall begin on or before June 24, 1964 and shall thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 19 64 Complete application of the water to the proposed use shall be made on or before October 1. 19 65 WITNESS my hand this ... day of in X Thinks. eceived in the Salem, Oregon office of the State Engineer at Son the 10th day of Afri Application No. G- 3 Permit No. G. 34 June 44, 196 TO APPROPRIATE THE WATERS OF THE S This instrument was first 1 19 6 3 at / 16 o'clock Recorded in book No. Ground Water Permits on page Drainage Basin No. 13 p. PERMIT Returned to applicant:

State Printing

Approved: