

Permit No. G. G 3348

APPLICATION FOR A PERMIT

CERTIFICATE NO. 39550

To Appropriate the Ground Waters of the State of Oregon

I, MARSHAL H. CAIN (Name of applicant)
(Name of applicant)
of Route 1, Box 213A, McMinnville, Ore , county of Yamhill (Postoffice Address)
state ofOregon, do hereby make application for a permit to appropriate the following described ground waters of the state of Oregon, SUBJECT TO EXISTING RIGHTS:
If the applicant is a corporation, give date and place of incorporation .
1. Give name of nearest stream to which the well, tunnel or other source of water development is
situatedSalt_Creek(Name of stream)
tributary of Yamhill River
2. The amount of water which the applicant intends to apply to beneficial use is .88/100. cubic feet per second or gallons per minute.
3. The use to which the water is to be applied isIrrigation
4. The well or other source is located
corner of(Section or subdivision)
South 57° East 1470 feet from the N.W. corner of Sec. 18, (If preferable, give distance and bearing to section corner)
T5S, R4W, W.M. (If there is more than one well, each must be described. Use separate sheet if necessary)
being within the NW1 of NW1 of NW1 of Sec. 18 Twp. 5S R. 4W
W. M., in the county of Yamhill
5. The to be miles
in length, terminating in the
R, W. M., the proposed location being shown throughout on the accompanying map.
6. The name of the well or other works is
DESCRIPTION OF WORKS
7. If the flow to be utilized is artesian, the works to be used for the control and conservation of the supply when not in use must be described.
8. The development will consist of
diameter of 10" inches and an estimated depth of 40 2 100 feet. It is estimated that All
feet of the well will require

9. (a) Give dimensions at each point of canal where materially changed in size, stating miles froe eadgate. At headgate: width on top (at water line)	CANAL SYSTEM		ah maina af amu		G 3348
feet; depth of water feet; grade feet; grade feet fall per on tousand feet. (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; width on bottom feet; depth of water feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake in.; in size at stake and place of use, ft. Is grade uniform? Estimated capacit see. It. 10. If pumps are to be used, give size and type Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channels and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channels and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channels and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channels and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channels and the ground surface	9. (a) Give	e dimensions at ea	ien point of cana	l where materially change	ed in size, stating miles fro
tousand feet. (b) At	eadgate. At head	dgate: width on to	p (at water line)		feet; width on botto
(b) At	······································	feet; depth of w	ater	feet; grade	feet fall per or
feet; width on bottom	nousand feet.				
radefeet fall per one thousand feet. (c) Length of pipe,ft.; size at intakein.; in size at	(b) At	mile	es from headgate	e: width on top (at water	line)
(c) Length of pipe,	••••••	feet; width on b	oottom	feet; depth of wa	ter fee
in.; size at place of use	rade	feet fall po	er one thousand	feet.	
take and place of use,	(c) Length	of pipe,	ft.; size	e at intakein	ı.; in size at j
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development with the	om intake	in.; siz	ze at place of use	? in.; diffe	rence in elevation betwee
10. If pumps are to be used, give size and type Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the natural stream or stream channel, give the distance to the nearest point on each of such channels are difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the nearest point on each of such channels are difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the nearest point on each of such channels are difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from natural stream or stream channels are difference in elevation between the stream bed and the ground surface at the source of development with the surface at the source of development work is less than one-fourth mile from natural stream of the surface at the source of development work is less than one-fourth mile from natural stream of the surface at the source of development work is less than one-fourth mile from natural stream of the surface at the source of development work is less than one-fourth mile from natural stream of the surface at the source of development work is less than one-fourth mile from natural stream	take and place (of use,	ft. Is g	rade uniform?	Estimated capacit
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the nearest point of such channels and the ground surface at the source of development of the nearest point of such channels and the ground surface at the source of development of the nearest point of such channels and the ground surface at the source of development of the nearest point of such channels and the ground surface at the source of development of the nearest point of such channels and the					
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the interval stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development in the interval of the interval	10. If pump	os are to be used, g	ive size and type		·
Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the action of stream channel, give the distance to the nearest point on each of such channels are difference in elevation between the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the strea	•				
11. If the location of the well, tunnel, or other development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development of the nearest point on each of such channels and the ground surface at the source of development of the source of the source of development of			·		
11. If the location of the well, tunnel, or other development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels and the difference in elevation between the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the source of developmen	•				
Township E. or W. of Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated	natural stream o e difference in e	or stream channel, elevation between	, give the distand the stream bed o	and the ground surface at	each of such channels an the source of developmen
SW-SW 8.3 18 NE-NW 9.2 NW-NW 33.0 SW-NW 16.5	natural stream one difference in e	or stream channel, elevation between	, give the distance the stream bed o	and the ground surface at	each of such channels an the source of developmen
18 NE-NW 9.2 NW-NW 33.0 SW-NW 16.5	natural stream of the difference in e	n of area to be irra	, give the distance the stream bed of the stream	f use	each of such channels an the source of developmen
NW-NW 33.0 SW-NW 16.5	natural stream of the difference in each of	n of area to be irre	give the distance the stream bed of the stream b	of use	Number Acres
SW-NW 16.5	natural stream of edifference in edi	n of area to be irre	give the distance the stream bed of the stream b	of use Forty-acre Tract SE-SW	Number Acres To Be Irrigated
	natural stream of edifference in edi	n of area to be irre	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW	Number Acres To Be Irrigated 3.0 8.3
TOTAL 70.0 acres	natural stream of the difference in each of	n of area to be irre	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW	Number Acres To Be Irrigated 3.0 8.3 9.2
	natural stream of the difference in each of	n of area to be irre	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW NW-NW	Number Acres To Be Irrigated 3.0 8.3 9.2 33.0
	natural stream of the difference in each of	n of area to be irre	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW NW-NW SW-NW	Number Acres To Be Irrigated 3.0 8.3 9.2 33.0 16.5
s s	natural stream of edifference in edi	n of area to be irre Range E. or W. of Willamette Meridian 4 W	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW NW-NW SW-NW	Number Acres To Be Irrigated 3.0 8.3 9.2 33.0 16.5
•	natural stream of the difference in each of	n of area to be irre Range E. or W. of Willamette Meridian 4 W	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW NW-NW SW-NW	Number Acres To Be Irrigated 3.0 8.3 9.2 33.0 16.5
	natural stream of the difference in each of	n of area to be irre Range E. or W. of Willamette Meridian 4 W	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW NW-NW SW-NW	Number Acres To Be Irrigated 3.0 8.3 9.2 33.0 16.5
	natural stream of the difference in each of	n of area to be irre Range E. or W. of Willamette Meridian 4 W	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW NW-NW SW-NW	Number Acres To Be Irrigated 3.0 8.3 9.2 33.0 16.5
	natural stream of the difference in each of	n of area to be irre Range E. or W. of Willamette Meridian 4 W	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW NW-NW SW-NW	Number Acres To Be Irrigated 3.0 8.3 9.2 33.0 16.5
(If more space required, attach separate sheet)	natural stream of the difference in each of	or stream channel, elevation between of area to be irrectly and the strength of willamette Meridian 4 W	give the distance the stream bed of the stream b	f use Forty-acre Tract SE-SW SW-SW NE-NW NW-NW TOTAL	Number Acres To Be Irrigated 3.0 8.3 9.2 33.0 16.5

CHRIS L. WHEELER

SISTANT

County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The 1	right herein granted	is limited to the amov	int of wate	r which can be applied to	beneficial use
				ed at the point of diversion with other water users, from	
The t	use to which this wat	er is to be applied is	irrigati	on	
If for	r irrigation, this appro	opriation shall be limi	ted to	1/80th of one cubic j	foot per second
or its equiv	valent for each acre ir	rigated and shall be f	urther limi	ted to a diversion of not to	exceed 2½
acre feet pe	er acre for each acre	irrigated during the i	rrigation se	eason of each year;	•••••••••
	•••••••••••••••••••••••••••••••••••••••	•••••••••••••••••••••••••••••••••••••••	•••••••••••		•••••••••••••••••••••••••••••••••••••••
	***************************************	······································			•••••
***************************************	•••••••••••••••••••••••••••••••••••••••	•			•••••••••••••••••••••••••••••••••••••••
***************************************	······································	••••••••••••••••			••••••••••
***************************************	•••••••••••••••••••••••••••••••••••••••	·	·	·	•••••••••••••••••••••••••••••••••••••••
and shall he	e subject to such reas	onable rotation suster	n. as man he	e ordered by the proper sta	te officer
the works s The r line, adeque The r	shall include proper c works constructed sh ate to determine wat permittee shall instal	apping and control va all include an air line er level elevation in	lve to prevent and pressue the well at the meter, or	r other suitable measurin	iter. for measuring
The 1	priority date of this p	permit is	••••••	April 6, 1967	
Actu	al construction work	shall begin on or befo	re	May 17, 1968	and shall
thereafter	be prosecuted with r	reasonable diligence a	nd be com	pleted on or before Octob	er 1, 19.68
Com	plete application of th	ne water to the propos	ed use shal	l be made on or before Oct	tober 1, 19.69
WIT	NESS my hand this	17th day of	Мау	,1967	••• •
1			<u>C</u>	La Della Landina	TATE ENGINEER
Application No. G-3675 Permit No. G-3348	PERMIT TO APPROPRIATE THE GROUND WATERS OF THE STATE OF OREGON	This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 6th day of April.	Returned to applicant:	Approved: May 17, 1967 Recorded in book No. Ground Water Permits on page, 35.1.8	CHRIS L. WHELLER STATE ENGINEER Drainage Basin No. 2. page 97H