

## Permit No. G- 563

## APPLICATION FOR A PERMIT

## To Appropriate the Ground Waters of the State of Oregon

1, Gustave Hoffman & Mary Hoffman (Wife Decease
of Rt 2 Bex 538 Hellsberg, Oregon, country of Washington
state of Congression, do hereby make application for a permit to appropriate the following described ground waters of the state of Oregon, SUBJECT TO EXISTING RIGHTS:
If the applicant is a corporation, give date and place of incorporation
1. Give name of nearest stream to which the well, tunnel or other source of water development is
situated Tualation Fiver (Name of streets)
tributary of
2. The amount of water which the applicant intends to apply to beneficial use is cubic feet per second or gallons per minute.
3. The use to which the water is to be applied is Irrigation of French Crops
4. The well or other source is located ZCC ft. N and 140 ft. E from the 3W
corner of SVY 4 Ct NW 4 Ct Santu N 2 (Bection or subdivision)
(If preferable, give distance and bearing to section corner)
being within the 24/4 st Nus/4 of Sec. 2
W. M., in the country of lulashirigton.
5. The to be mile
in length, terminating in the
R. W. M., the proposed location being shown throughout on the accompanying map.
6. The name of the well or other works is
DESCRIPTION OF WORKS
7. If the flow to be utilized is artesian, the works to be used for the control and conservation of th supply when not in use must be described.
8. The development will consist of CN2 1021/ having (Give number of wells, tunnels, etc.)
diameter of E inches and an estimated depth of A. feet. It is estimated that
feet of the well will require

(b) At miles from headgate: width on top (at water line)  feet; width on bottom feet; depth of water  ade feet fall per one thousand feet.  (c) Length of pipe, ft.; size at intake, in.; in size at  om intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capa  sec. ft.  10. If pumps are to be used, give size and type Je. Type  Give horsepower and type of motor or engine to be used 3 cc. 5 M 14 months  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fratural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the stream of a control of the stream bed and the ground surface at the source of development of the stream of the stream of the stream bed and the ground surface at the source of development of the stream of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream bed and the ground surface at the source of development of the stream of the stream of the stream bed and the ground surface at the source of development of the stream	NAL SYSTEM ( 9. (a) Give (	•	h point of co	mal where materially changed is	s size, stating milies jou
(b) At miles from headgate: width on top (at water line)  feet; width on bottom feet; depth of water feet; depth of water feet; depth of pipe feet; depth of pipe, ft.; size at intake, in.; in size at om intake in.; size at place of use in.; difference in elevation between the and place of use, ft. Is grade uniform? Estimated capa sec. ft.  10. If pumps are to be used, give size and type Is. Type  Give horsepower and type of motor or engine to be used 3 cc. 5 ft. 14: maches for the size of the interval stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development in the surface of the size	adgate. At headg	ate: width on top	(at water li	ne)	feet; width on botto
(b) At miles from headgate: width on top (at water line)  feet; width on bottom feet; depth of water  ade feet fall per one thousand feet.  (c) Length of pipe, ft.; size at intake, in.; in size at  om intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capa  sec. ft.  10. If pumps are to be used, give size and type le. ft. fype  Give horsepower and type of motor or engine to be used 3 cc. 5 ft. 14 maches  and the location of the well, tunnel, or other development work is less than one-fourth mile fraitural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fraitural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development works in the surface of the surface of the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the source of development works in the surface at the surface at the source of the surface at the source of the surface at the surface at the surface at the surface at the surface		et; depth of water	<b>7</b>	feet; grade	feet fall per or
feet; width on bottom  feet; depth of water  in.; in size at  feet; depth of water  in.; difference in elevation between the size and type  feet; depth of water  in.; difference in elevation between the size and type  Level and uniform?  Estimated capa  Seet In.  10. If pumps are to be used, give size and type  Jeet Ingeled  Give horsepower and type of motor or engine to be used  Jeet Ingeled  Give horsepower and type of motor or engine to be used  Jeet Ingeled  Give horsepower and type of motor or engine to be used  Jeet Ingeled  Give horsepower and type of motor or engine to be used  Jeet Ingeled  Give horsepower and type of motor or engine to be used  Jeet Ingeled  Type	ousand feet.				
(c) Length of pipe, ft.; size at intake, in.; in size at some intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capa sec. ft.  10. If pumps are to be used, give size and type Section Sect	(b) At	miles	s from head	gate: width on top (at water line	)
(c) Length of pipe, ft.; size at intake, in.; in size at omining in size at intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capa sec. ft.  10. If pumps are to be used, give size and type Let type  Give horsepower and type of motor or engine to be used 3 c 5 ft. 14 metrical section of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream of the difference in elevation between the stream of the difference in elevation between the stream of the difference in elevation between		feet; width on bo	ottom	feet; depth of water .	fee
om intake in.; size at place of use in.; difference in elevation between take and place of use, ft. Is grade uniform? Estimated capa sec. ft.  10. If pumps are to be used, give size and type Is. † type  Give horsepower and type of motor or engine to be used 3 cast from the second s	ade	feet fall per	r one thousa	nd feet.	
sec. ft.  10. If pumps are to be used, give size and type	(c) Length o	f pipe,	ft.;	size at intake, in.; i	n size at
Sec. ft.  10. If pumps are to be used, give size and type	om intake	in.; siz	e at place of	f use in.; differe	ence in elevation betwee
10. If pumps are to be used, give size and type  Give horsepower and type of motor or engine to be used  3 cc 5 P 14 mit to  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fractural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channel, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channels, give the distance to the nearest point on each of such channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channels he difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fractural stream or stream channels have been development work is less than one-fourth mile fractural stream or stream channels have been development work is less than one-fourth mile fractural stream or stream channels have been development work is less than one-fourth mile fractural stream or stream channels have been development work is less than one-fourth mile fractural stream or stream channels have been development work is less than one-fourth mile fractural stream or stream channels have been development work is less than one-fourth mile fractural stream or stream channels have been de	take and place of	use,	ft.	Is grade uniform?	Estimated capacit
Girc horsepower and type of motor or engine to be used 3 cc. 5 AP 14 mc/c.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fratural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or stream channels, give the distance to the nearest point on each of such channels that the source of development work is less than one-fourth mile fratural stream or stream channels, give the distance to the nearest point on each of such channels that the source of development work is less than one-fourth mile fratural stream or stream channels, give the distance to the nearest point on each of such channels that the source of development work is less than one-fourth mile fratural stream or stream channels, give the distance to the nearest point on each of such channels that the source of development work is less than one-fourth mile fratural stream or stream or stream channels at the source of development work is less than one-fourth mile fratural stream or strea				,	•
11. If the location of the well, tunnel, or other development work is less than one-fourth mile fratural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or stream or stream on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or stream or stream or such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or stream	10. If pumps	are to be used, gi	ve size and 1	type Jet type	
11. If the location of the well, tunnel, or other development work is less than one-fourth mile fratural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or stream or stream on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or stream or stream or such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or stream or stream or stream or such channels the following stream of the following stream of the stream bed and the ground surface at the source of development work is less than one-fourth mile fratural stream or strea		•			
11. If the location of the well, tunnel, or other development work is less than one-fourth mile fratural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation difference in elevat	Give horsepo	ower and type of n	motor or eng	rine to be used 3 cc 5/	P 14 meter
atural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development of the difference in elevation between the stream bed and the ground surface at the source of development of the source of	CAC Velts				
Township N or S  E or W of Williamette Meridian  Section Forty-acre Tract  Number Acres To Be Irrigated  SW/4 of NW/4  SE/4 of NE/4  13 Acres	atural stream or	stream channel,			
12. Th. 3 west 3 SE/4 of NE/4 13 Acre	atural stream or he difference in e	stream channel, levation between 1	the stream l	bed and the ground surface at the	
	atural stream or he difference in e	stream channel, levation between to be irri	the stream l	ace of use	Number Acres
	atural stream or the difference in e	stream channel, levation between to of area to be irrived and the street of willamette Meridian	igated, or pl	ace of use	Number Acres
	atural stream or he difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres
	atural stream or the difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated  13 Acres
	atural stream or the difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated  13 Acres
	atural stream or he difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated
	atural stream or he difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated
	atural stream or he difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated
	atural stream or he difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated
	atural stream or he difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated
	atural stream or he difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated
(If more space required, atlack separate sheet)	atural stream or he difference in e	stream channel, levation between to of area to be irrived E or W of Willamette Meridian	igated, or pl	ace of use  Forty-acre Tract  SW/4 of NW/4	Number Acres To Be Irrigated

STATE ENGINEER

county, having a	s present population of
i an estimated population of	
14. Estimated cost of proposed works, \$.,	1000
15. Construction work will begin on or be	fore June 157 1957
	on or before Aug 15-145-Z
17. The water will be completely applied	to the proposed use on or before Aug 13-19
18. If the ground water supply is supplition for permit, permit, certificate or adjud	emental to an existing water supply, identify any appli licated right to appropriate water, made or held by th
plicant. Nace	
	Gustave Hoffman
Remarks:	
,	
County of Marion (ss.	
County of Marion,	
This is to certify that I have examined t	the foregoing application, together with the accompanying
naps and data, and return the same for	
In order to retain its priority, this appli	ication must be returned to the State Engineer, with corre

County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use an	
shall not exceed0_13cubic feet per second measured at the point of diversion from the well of appropriation, or its equivalent in case of rotation with other water users, from _one_well	
The use to which this water is to be applied is irrigation	••
If for irrigation, this appropriation shall be limited to 1/80 of one cubic foot per second	nd
or its equivalent for each acre irrigated and shall be further limited to a diversion of not to exceed $2\frac{1}{2}$	
acre feet per acre for each acre irrigated during the irrigation season of each year;and shall ba	
still further limited to a diversion of not to exceed 0.13 c.f.s.	
•	
and shall be subject to such reasonable rotation system as may be ordered by the proper state officer.	
The well shall be cased as necessary in accordance with good practice and if the flow is artesi	ian
the works shall include proper capping and control valve to prevent the waste of ground water.  The works constructed shall include an air line and pressure gauge or an access port for measuring the works constructed shall include an air line and pressure gauge or an access port for measuring the well at all times.	ing
line, adequate to determine water level elevation in the well at all times.  The permittee shall install and maintain a weir, meter, or other suitable measuring device, and sh keep a complete record of the amount of ground water withdrawn.	all
keep a complete record of the amount of ground water annual and	
The priority date of this permit isMay 10, 1957	*****
Actual construction work shall begin on or beforeJuna. 20, 1958 and sh	ıall
thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 19.58.	
Complete application of the water to the proposed use shall be made on or before October 1, 19 59	<b>3</b>
WITNESS my hand this 20th day of June , 19.57	
STATE ENGINEE	ER.
OUND oed in the oed in the M.  M.  ENGLINEER PROJECTION OF SOLVER	
E GROUND STATE  received in received in M.  A.  M.  A.  A.  B.  A.  A.  B.  B.  B.  B.  B	
THE GROUNTHE GROUNT TAT TECEIVE AND	ş
PERMIT PRIATE THE SS OF OREGON  The Engineer at the Engineer	State Printing 90748
PERMI PERMI PERMI PERMI PERMI PPROPRIATE T ATERS OF TH OF OREGO OF OREGO OF OREGO A day of A	34 71
ROP ROP (CO.)	ŭ
e i i i i i i i i i i i i i i i i i i i	
Permit No. G- 56.  Permit No. G- 56.  PERMIT  TO APPROPRIATE THE GROUND WATERS OF THE STATE OF OREGON  This instrument was first received in the office of the State Engineer at Salem, Oregon, on the ICM day of 1. 124  19:57, at 6. Coclock A. M.  Returned to applicant:  June 20, 1952  Recorded in book No. 3. of  Ground Water Permits on page 563  LEATS. 1. STATEY  ETATE A. STATEY  STATE BIODIER	