Harvey Machine Co., Inc.	
of 19200 South Western Avenue, Torrance	<b>,</b>
of California described ground waters of the state of Oregon, SUBJECT TO EXISTING RIGHTS:	priate the
If the applicant is a corporation, give date and place of incorporation	
April 1942 - California	***************************************
1. Give name of nearest stream to which the well, tunnel or other source of water developmen	
situated Chenowith Creek & Columbia River in Wasco County, Oregon	*****
(Name of stream)	
2. The amount of water which the applicant intends to apply to beneficial use is feet per second or 2000 gallons per minute. Total (See Item #18.) 500 GPM this  3. The use to which the water is to be applied is Industrial Water Requirement	cubic app/.
Rectifier Cooling, Scrubber Spray, Casting Machine Cooling, Fire	
4. The well or other source is located 1350 ft. and 2235 ft. from t	hal/4 28
corner of See Enclosed Drawing Section 28, twp. 28, R 13E	<i>ne-1.4 33</i>
(Section or subdivision)	
(If preferable, give distance and bearing to section corner)	
being within the NNE QL SVE of Sec. 28, Twp. 2 N. R.	138
W. M., in the county of Wasco	• •
5, • The (Canal or pipe line)	miles
in length, terminating in the	
R	
6. The name of the well or other works is WELL#/	
DESCRIPTION OF WORKS	
7. If the flow to be utilized is artesian, the works to be used for the control and conserva supply when not in use must be described.	tion of the
······································	
<b></b>	•• •• • • • • • • • • • • • • • • • • •
· · · · · · · · · · · · · · · · · · ·	
8. The development will consist of One Well (Give number of wells, tunnels, etc.)	having a
diameter of 20 inches and an estimated depth of 310 feet. It is estimated th	
feet of the well will require steel casing. Depth to water table is estimated	200 (Feet)

feet; depth of water
(b) At miles from headgate: width on top (at water line)  feet; width on bottom feet; depth of water  de feet fall per one thousand feet.  8" and larger as required  (c) Length of pipe, ft.; size at intake, lines and insustrial use  m intake in.; size at place of use in.; difference in elevation bett  ake and place of use, BONE ft. Is grade uniform? Estimated cape  sec. ft.  10. If pumps are to be used, give size and type Vertical, Motor Driven and/or E  rive.  Give horsepower and type of motor or engine to be used Estimated 150 - 200 h.p.  required; 550 volt 3-phase electric motor and/or diesel engine we right angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel e difference in elevation between the stream bed and the ground surface at the source of develop  12. Location of area to be irrigated, or place of use  The without the stream of the s
feet; width on bottom
de
de
(c) Length of pipe,  ft.; size at intake,  m intake  in.; size at place of use  in.; difference in elevation better  ake and place of use,  sec. ft.  10. If pumps are to be used, give size and type Vertical, Motor Driven and/or E  ive.  Give horsepower and type of motor or engine to be used Estimated 150 - 200 h.p.  required; 550 volt. 3-phase electric motor and/or diesel engine weight angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile futural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is at the source of development work in the stream of such channel and the ground surface at the source of development work in the stream of such channel and the ground surface at the source of development work in the stream of such channel and the ground surface at the source of development work is less than one-fourth mile for the stream of stream channel, give the distance to the nearest point on each of such channel and the ground surface at the source of development work is less than one-fourth mile for the stream of stream or stream channel, give the distance to the nearest point on each of such channel and the ground surface at the source of development work is less than one-fourth mile for the stream or stream channel, give the distance to the nearest point on each of such channel and the ground surface at the source of development work is less than one-fourth mile for the stream of the str
mintake in.; size at place of use in.; difference in elevation between the and place of use, ft. Is grade uniform? Estimated capable sec. ft.  10. If pumps are to be used, give size and type Vertical, Motor Driven and/or Evive.  Give horsepower and type of motor or engine to be used Estimated 150 - 200 h.p. required; 550 volt 3-phase electric motor and/or diesel engine wight angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile futural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is a less than one-fourth mile for the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile for the work is less than one-fourth mile for the mile for the work is less than one-fourth mile for the work is less than one-four
sec. ft.  10. If pumps are to be used, give size and type Vertical, Motor Driven and/or Evive.  Give horsepower and type of motor or engine to be used Estimated 150 - 200 h.p. required; 550 volt 3-phase electric motor and/or diesel engine weight angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fit tural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fit tural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fit tural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fit tural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fit tural stream or stream channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the nearest point on each of such channel give the distance to the neare
10. If pumps are to be used, give size and type Vertical, Motor Driven and/or Evive.  Give horsepower and type of motor or engine to be used Estimated 150 - 200 h.p. required; 550 volt 3-phase electric motor and/or diesel engine weight angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fit the location of area to be irrigated, or place of use  12. Location of area to be irrigated, or place of use  13. Number Acres To Be Irrigated Williametic Meridian Bertion Party-acre Tract
10. If pumps are to be used, give size and type Vertical, Motor Driven and/or Evive.  Give horsepower and type of motor or engine to be used Estimated 150 - 200 h.p. required: 550 volt 3-phase electric motor and/or diesel engine weight angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel.  12. Location of area to be irrigated, or place of use  Township Rose and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel.  13. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel.  14. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel.
Give horsepower and type of motor or engine to be used Estimated 150 - 200 h.p.  required; 550 volt 3-phase electric motor and/ or diesel engine wright angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fit tural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fit tural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fit tural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fit tural stream or stream channel, give the distance to the nearest point on each of such channel.  12. Location of area to be irrigated, or place of use  13. Township Range Rang
Give horsepower and type of motor or engine to be used Estimated 150 - 200 h.p.  required: 550 volt 3-phase electric motor and/ or diesel engine weight angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile futural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile futural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile futural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile futural stream or stream channel, give the distance to the nearest point on each of such channel and the ground surface at the source of development work is less than one-fourth mile futural stream or
required; 550 volt 3-phase electric motor and/ or diesel engine with angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitured in the fiture of the stream or stre
required; 550 volt 3-phase electric motor and/ or diesel engine with angle drive.  11. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel e difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitured in the fiture of the stream or stre
11. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel edifference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fitural stream or
11. If the location of the well, tunnel, or other development work is less than one-fourth mile fitural stream or stream channel, give the distance to the nearest point on each of such channel e difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation between the stream bed and the ground surface at the source of development difference in elevation differ
tural stream or stream channel, give the distance to the nearest point on each of such channel e difference in elevation between the stream bed and the ground surface at the source of develop  12. Location of area to be irrigated, or place of use  Township  Range  B. or W. of  Williametic Meridian  Bection  Forty-serve Tract  Number Acress To Be Irrigated
12. Location of area to be irrigated, or place of use  Township  Range  B. or W. of Williamette Meridian  Section  Party-acre Tract  Number Acres To Be Irrigated
12. Location of area to be irrigated, or place of use  Township Range B. or W. of Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated
12. Location of area to be irrigated, or place of use  Township Range B. or W. of B. or W. of Willamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated
12. Location of area to be irrigated, or place of use
12. Location of area to be irrigated, or place of use
12. Location of area to be irrigated, or place of use
Township Range E. or W. of Section Furty-acre Tract Number Acres To Be Irrigated  Number Acres To Be Irrigated
Township Range E. or W. of Section Furty-acre Tract Number Acres To Be Irrigated  Number Acres To Be Irrigated
R. or S. Willamette Meridian Section Forty-acre Tract To Be Irrigated
#1-2 N 13 E 28
• •
i i i i i i i i i i i i i i i i i i i
(If more space required, attach separate sheet)

CANAL SYSTEM OR PIPE LINE.

23. To supply the city of	
is	ing a present population of
and an estimated population of	
14. Estimated cost of proposed works	S 14 15 M 17 AND 18 IN ALL CASES
15. Construction work will begin on a	r before Hayaniter 1, 1956
16. Construction work will be comple	ted on or before
	lied to the proposed use on or beforeAugust29,1957
	applemental to an existing water supply, identify any appli-
cation for permit; permit, certificate or a	djudicated right to appropriate water, made or held by the
applicant. Increase GPM from 15	<u> </u>
Previ Permit #6 338	HARVEY MACHINE CO., INC.
	Claude C. Coop
n	Resident Remiger"
Remarks:	
STATE OF OREGON,	
County of Marion,	
This is to certify that I have examin	ned the foregoing application, together with the accompanying
maps and data, and return the same for	completion
In order to retain its priority, this a	application must be returned to the State Engineer, with correc-
tions on or beforeOctober 30	
, , , , , , , , , , , , , , , , , , , ,	
WIMNEGO I III 20Ah	1 / Angust
WIINESS my hand this 3940 o	lay of August , 19 57
•	
	LEVIS A. STANLEY
	STATE ENGINEER
	James W. Carver, Jr. ASSISTANT
	James W. Carver, Jr.

MUNICIPAL SUPPLY-

County of Merion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The subject to such reasonable rotation system as may be ordered by the proper state office well shall be cased as necessary in accordance with good practice and if the flow is a shall include proper capping and control valve to prevent the waste of ground water. works constructed shall include an air line and pressure gauge or an access port for meaning to determine water level elevation in the well at all times.  permittee shall install and maintain a weir, meter, or other suitable measuring device, an applete record of the amount of ground water withdrawn.  priority date of this permit is	e well shall be cased as necessary in ac shall include proper capping and contine works constructed shall include an ai quate to determine water level elevation expermittee shall install and maintain a complete record of the amount of ground the priority date of this permit is stual construction work shall begin on oner be prosecuted with reasonable diligated to the property of the water to the priority date of
--	--

State A ...