

Permit No. G- 809

APPLICATION FOR A PERMIT

To Appropriate the Ground Waters of the State of Oregon

I, Louis of applicant)
of 101 171 , county of,
state of Grand normal n
If the applicant is a corporation, give date and place of incorporation
1. Give name of nearest stream to which the well, tunnel or other source of water development is
situated
(Name of stream) tributary of
2. The amount of water which the applicant intends to apply to beneficial use is cubic feet per second or gallons per minute.
3. The use to which the water is to be applied is
4. The well or other source is located ft. and ft. from the
corner of
(Section or subdivision) (If preferable, give distance and bearing to section corner)
(If there is more than one we beach must be described. Use separate sheet if necessary)
being within the
W. M., in the county of
5. The to be miles
5. The to be miles
5. The to be miles in length, terminating in the
5. The to be miles in length, terminating in the (Smallest legal subdivision)
5. The Canal or pipe line to be miles in length, terminating in the Canal or pipe line of Sec. Twp. (Smallest legal subdivision) R
5. The to be miles in length, terminating in the (Smallest legal sundivision) R W. M., the proposed location being shown throughout on the accompanying map. 6. The name of the well or other works is
5. The to be miles in length, terminating in the (Smallest legal subdivision) R
5. The to be miles in length, terminating in the (Smallest legal subdivision) R
5. The to be miles in length, terminating in the (Smallest legal subdivision) R
5. The to be miles in length, terminating in the (Smallest legal subdivision) R
5. The to be miles in length, terminating in the smallest legal su advision: R W. M., the proposed location being shown throughout on the accompanying map. 6. The name of the well or other works is DESCRIPTION OF WOFKS 7. If the flow to be utilized is artesian, the works to be used for the control and conservation of the supply when not in use must be described.

CANAL	SYSTEM	OR	PIPE	LINE_
CANAL	GIGIEM	UR	FIFE	LIPP

thousand feet. Ditches to be the size of t	headgate. At head	gate: width on to	op (at water lin	epolout four (;); -: feet; 1	vidth on bottor
thousand feet. Ditches to be the core tire. (b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water grade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at from intake in.; size at place of use in.: difference in elevation between that and place of use, ft. Is grade uniform? Estimated capa 10. If pumps are to be used, give size and type . 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of the stream bed and the ground surface at the	cout two (2) for	eet; depth of wa	ter about (1)) feet; prade al.		feet fall per on
feet; width on bottom feet; depth of water grade feet fall per one thousand feet. (c) Length of pipe, ft.; size at intake, in.; in size at from intake in.; size at place of use in.: difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treatment of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from a treatment or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of the difference in elevation between the stream bed a				•		
grade	(b) At	· • • • • • • • • • • • • • • • • • • •	i les from headg	ste: width on top (at	water line)	<u>.</u>
from intake in.; size at place of use in.: difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from its less than one fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work is less than one-fourth mile from the difference in elevation of the well, tunnel, or other development work		feet; width on	bottom	feet; depth	of water	feet
in.; size at place of use in.; difference in elevation between the large of use in.; difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from all ference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from all ference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation of such charmels the difference in elevation of such charmels. 12. Location of area to be irrigated, or place of use 13. Location of area to be irrigated, or place of use 14. Location of area to be irrigated, or place of use 15. Location of area to be irrigated, or place of use	grade	feet fall 1	per one thousan	d feet.		
ft. Is grade uniform? Estimated capa 10. If pumps are to be used, give size and type Give horsepower and type of motor or engine to be used 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fr natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the following the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the following the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the following the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the following the difference in elevation between the following the following the following the follo	(c) Length	of pipe,	ft.; si	ze at intake,	in.; in size at	f
Give horsepower and type of motor or engine to be used. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation of the well, the difference in elevation of the well, the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation of the well at the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development	from intake	in.;	size at place of 1	use	in.; difference in el	eration betwee
Give horsepower and type of motor or engine to be used. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fr natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fr natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in each of such channels. 12. Location of area to be irrigated, or place of use 13. If the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in each of such channels. 14. If the location of the well, tunnel, or other development work is less than one-fourth mile from the difference in each of such channels. 15. Location of area to be irrigated, or place of use 16. Location of area to be irrigated, or place of use 17. Location of area to be irrigated, or place of use 18. Location of area to be irrigated. 19. Section Forty-acre Tract Number Acres To Be Irrigated.	intake and place of	use,	ft. Is	grade uniform?	Est	imated capacity
Give horsepower and type of motor or engine to be used. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fr natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fr natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fr natural stream or stream		-sec. ft		<u>.</u>		
Give horsepower and type of motor or engine to be used. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile fr natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fr natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile fr natural stream or stream	10. If pump	s are to be used,	give size and ty	pe •		
Give horsepower and type of motor or engine to be used. 11. If the location of the well, tunnel, or other development work is less than one-fourth mile from natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the following than the following the following the following that the stream bed and the ground surface at the source of development work is less than one-fourth mile from the following than the following that the following the following that the following that the following the following that the following that the following the following that the following t						
11. If the location of the well, tunnel, or other development work is less than one-fourth mile from the stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream or stream or stream or such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream or stream or such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile from the stream or strea	Cina horsen			,		
11. If the location of the well, tunnel, or other development work is less than one-fourth mile frantural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frantural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frantural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of development work is less than one-fourth mile frantural stream or	-				• •	
natural stream or stream channel, give the distance to the nearest point on each of such channels the difference in elevation between the stream bed and the ground surface at the source of develops. 12. Location of area to be irrigated, or place of use Township Range Forty-acre Tract Number Acres To Be Irrigated	11 C					
Township Range Sor W of Williamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated	11. If the lo natural stream or	cation of the wel	ll, tunnel, or oth l, give the dista	er development work ince to the nearest p	c is less than one-fo- point on each of suc	ch channels an
Township Range E or W of Williamette Meridian Section Forty-acre Tract Number Acres To Be Irrigated	11. If the lo natural stream or	cation of the wel	ll, tunnel, or oth l, give the dista	er development work ince to the nearest p	c is less than one-fo- point on each of suc	ch channels an
N or S Willamette Meridian Bection Forty-acre Fract To Be Irrigated	11. If the lo natural stream or the difference in e	cation of the wel	ll, tunnel, or oth l, give the disto n the stream be	er development work ince to the nearest p d and the ground sur	c is less than one-fo- point on each of suc	ch channels an
37.7	11. If the lo natural stream or the difference in e	cation of the well stream channel levation between n of area to be in	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lo natural stream or the difference in e 12. Location Township	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formation each of surface at the source	ch channels an of developmen
	11. If the lonatural stream or the difference in e	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lo natural stream or the difference in e	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lonatural stream or the difference in e	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lo natural stream or the difference in e	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lo natural stream or the difference in e 12. Location Township	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lo natural stream or the difference in e 12. Location Township	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lo natural stream or the difference in e	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lo natural stream or the difference in e 12. Location Township	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
	11. If the lo natural stream or the difference in e 12. Location Township	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen
,	11. If the lo natural stream or the difference in e 12. Location Township	cation of the well stream channel levation between the of area to be in Range of well as a strength of the control of the cont	ll, tunnel, or oth l, give the distont the stream be rigated, or place	er development work ince to the nearest p d and the ground sur	c is less than one-formit on each of surface at the source	ch chanvels an of developmen

(If more space required, attach separate sheet

Character of soil *

Kind of crops raised .

13. To supply the city of	
in	
-and the collected population of	
14. Estimated cost of proposed works, \$, L.(
18. Construction work will begin on or before	Charles and the
16. Construction work will be completed on or beforeiunel., 1	
17. The water will be completely applied to the proposed use on or	•
	•
18. If the ground water supply is supplemental to an existing we cation for permit, permit, certificate or adjudicated right to approprie	ster supply, identify any appli- ite water, made or held by the
applicant. Victor is to our ofrom 12. 2. 2	,
Dried , 1301.	
Lisensel	majure of applicant)
Remarks: Miliant 11 12 12 12 13 15 15 15 15 15 15 15 15 15 15 15 15 15	mediate of applicant)
to term a destine process	
The total and the second secon	
	L. G. Biller
	•
······································	
· · · · · · · · · · · · · · · · · · ·	
••••••••••••••••••••••••••••••••••••••	
······································	
STATE OF OREGON.	
County of Marion, ss.	
This is to certify that I have examined the foregoing application,	together with the accompanying
maps and data, and return the same for	
	·
In order to retain its priority, this application must be returned to	the State Engineer, with correc-
tions on or before, 19	
WITNESS my hand this day of	

County of Merion.

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use and 10 00 source of appropriation, or its equivalent in case of rotation with other water users, from a well (Ritter's well No. 1) The use to which this water is to be applied is 1771gation..... If for irrigation, this appropriation shall be limited to 1/80 of one cubic foot per second or its equivalent for each acre irrigated and shall be further limited to a diversion of not to exceed acre feet per acre for each acre irrigated during the irrigation season of each year; and shall be subject to such reasonable rotation system as may be ordered by the proper state officer. The well shall be cased as necessary in accordance with good practice and if the flow is artesian the works shall include proper capping and control valve to prevent the waste of ground water. The works constructed shall include an air line and pressure gauge or an access port for measuring line, adequate to determine water level elevation in the well at all times. The priority date of this permit is April 10, 1958 Actual construction work shall begin on or before April 25, 1959 and shall thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 19 59 Complete application of the water to the proposed use shall be made on or before October 1. 19 60 The permittee shall install and maintain a weir, meter, or other suitable measuring device, and shall keep a complete record of the amount of ground water withdrawn. WITNESS my hand this 25th . 19. 58. STATE ENGINEER first received in the Ö at Salem, Oregon THE GROUND Σ THE STATE 0 EGON 00 Application No. PER OF OR Permit No. G-TO APPROPRIAT WATERS OF This instrument we office of the State Engi on the 10 th day of. 19 58, at 8:00. o'cl Returned to applicant: Recorded in book N Ground Water Permits LEVIS A. STANLEY - 41 April 25, 1958

Approved:

9 State Prints