## Bearing Permit No. 1563

## Fermit to Construct a Reservoir and to Lonelicial Use the Unappropriated Waters of the State of Oregon

AND THE RESERVE

(Stame of Applicant)	
Mailing Address)	***************************************
(Mailing Address)	,
State of ORMION , do hereby make applica	tion for a permit to construct the
following described reservoir and to store the unappropriated waters of	f the State of Oregon, subject to
existing rights.	
If the applicant is a corporation, give date and place of incorporation	tion
1. The name of the proposed reservoir is	······································
2. The name of the stream from which the reservoir is to be filled	
Lo. Land Mo. Carron Commen	militar sample approx
tributary of	
3. The amount of water to be stored is	,
4. The use to be made of the impounded water is	toon, nower dignests sanna ites
5. The location of the proposed reservoir will be in Sec.	
Tp. 27. S, R. 1, W. M., in the county of	
(a) State whether situated in channel of running stream and give	ve character of material at outlet
	•
(b) If not in channel of running stream, state how it is to be fill	ed. If through a food conal aire
name and dimensions	ea. If thirdayie a feed canal, give
· ·	
6. The dam will be located in	, Sec.
Tp, R, W. M. The maximum height will be	feet above stream bed or ground
surface on center line of dam. The length on top will be	fect; length on
bottom feet; width on top	feet; slope of front
or water side ; ! ; ; slope on back ; [Feet horizontal to 1 vertical]	; height of dam above water line
when full feet.	
* A different form of application should be used for the appropriation of stored water to without charge, together with instructions, by addressing the State Engineer, Salem. Oregon	beneficial use that forms on he secured

4	
ر چوپ	
* /4¥	The construction of dam, the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of which it is to be built, and method of protection with the material of the material of which it is to be built, and method of protection with the material of the
	Fregent des is of rolled earth fill construction,
44	from Storage basine largely stor. Contains about 10,000
-pe	sposed to number arcavete the basin using the material to alle
	isting dam, providing & ft. freebbard. See plans. Small size of
¥e	getation on face precludes any necessity for wave protection.  8. The location of wasteway with dimensions are as follows:
<b>~</b> }	(State whether over or around the
21	dem Natural ground is compacted sandy clay and dictorrel route. 'C
P)	noted roo wmer states no troub a has been experimed a second copese to improve spillway with concrete about of a second concrete about the concret
****	······································
	9. The location of outlet from the proposed reservoir, with character of construction and dim
ar	e as follows: Prosect and the Soli and the provided with an outlet conduit, of such capacity and location
i:	ron nipe with swinging alban sun anisa. Live, and anisa
e.	ete sion end. No charge contemplates especial en el 22 en en el 22 en
	•
	10. The area submerged by the proposed reservoir, when full, will be
wi	
	ith a maximum depth of water of 12 feet; and approximate mean depth
	ith a maximum depth of water of 12 feet; and approximate mean depth 3.5 feet.
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ 2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ feet.  12. Construction work will begin on or before feet.  13. Construction work will be completed on or before
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ feet.  12. Construction work will begin on or before feet.  13. Construction work will be completed on or before
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ 2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ feet.  12. Construction work will begin on or before feet.  13. Construction work will be completed on or before
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ feet.  12. Construction work will begin on or before feet.  13. Construction work will be completed on or before
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ feet.  12. Construction work will begin on or before feet.  13. Construction work will be completed on or before
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$  12. Construction work will begin on or before  13. Construction work will be completed on or before  Carl William Yar 2
	ith a maximum depth of water of 12 feet; and approximate mean depth 3.5 feet.  11. The estimated cost of the proposed work is \$ 12. Construction work will begin on or before for feet.  13. Construction work will be completed on or before for feet; and approximate mean depth 3.5 feet; and approximate mean depth 4.5 feet; and approximate mean d
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$  12. Construction work will begin on or before  13. Construction work will be completed on or before  Carl Willy your 1  STATE OF OREGON, Ss.  County of Marion, Ss.
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ 12. Construction work will begin on or before  13. Construction work will be completed on or before  Carl William Lawrence and the foregoing application, together with the according to the construction work of the proposed work is \$ 12. Construction work will be completed on or before  TATE OF OREGON,   Ss. County of Marion,   Ss. County of Marion,   Ss. County of that I have examined the foregoing application, together with the according to the construction work is \$ 12. Construction work will be completed on or before   Carl William Lawrence   Carl William Lawrence
	ith a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$  12. Construction work will begin on or before  13. Construction work will be completed on or before  Carl Willyarul  TATE OF OREGON,   ss.
	the a maximum depth of water of 12 feet; and approximate mean depth  3.5 feet.  11. The estimated cost of the proposed work is \$ 12. Construction work will begin on or before  13. Construction work will be completed on or before  Carl William You I  TATE OF OREGON, { ss.  County of Marion, { ss.  This is to certify that I have examined the foregoing application, together with the access

STATE ENGINEER

	it is proposed to deepen basin and role on
	is proposed to deepen basin and released
	indicates no reason, structurally, why
	at it should be done to some call this
	balos den is a wide meadow and there are no he
	it is promotive would be involved in case of a follure . It was not the second of the
3	Spillway has been designed to permit lake bevel to be
be	s more than adequate capacity ( see data on plans).
man untering angles.	***************************************
	*
*****	***************************************
end to see to select a security see	***************************************
Pno north 8000 4 4 4 4 4 4 4	***************************************
***************************************	
*************	
***************************************	
•••••	
•	
*****	
	OF OREGON, } ss.
	y of Marion,
Th	is is to certify that I have examined the foregoing application and do hereby grant the same,
subject to	o the following limitations and conditions: The right herein granted is limited to the construc-
tion of N	veren Reservoir and the storage of water from No. 1 and No. 2 unnamed draws
	appropriated under Application No. 28866, Permit No. 22628 for supplemental
irri gai	
	e right hereunder shall be limited to the storage of 23.0 acre feet.
Th	e priority date of this permit is October 15, 1953
Ac	tual construction work shall begin on or before January 22, 1955 and
shall ther	reafter be prosecuted with reasonable diligence and be completed on or before October 1, 1955
	TNESS my hand this 22nd day of January 1951
	10000-00
	Char Stullin

CK

Application No. R-20065 Reservoir Permit No. A. 1543...

## PERMIT

To construct a reservoir and store for bena-ficial use the unappropriated waters of the State of Oregon.

This instrument was first received in the office of the State Engineer at Salem, Oregon, on the LSth day of October 19.53, at 11.00 velock P. M.

Returned to applicant:

Approved:

January 22, 1954

Recorded in Book No. 5 Reservoirs, on Page ..... 1563

STATE ENGINEER CHAS. E. STRICKLIN

Drainage Basin No. .../5 page 32-8

Jua part # 15.00