## • Reservoir Permit No. 2214

## Application for a Permit to Construct a Reservoir and to Store for Beneficial Use the Unappropriated Waters of the State of Oregon

I,
of Route = 2. Box 552. Gresham. Oregon (Mailing Address)
State of Oregon , do hereby make application for a permit to construct the
following described reservoir and to store the unappropriated waters of the State of Oregon, subject to
existing rights.
If the applicant is a corporation, give date and place of incorporation
1. The name of the proposed reservoir is Sester Reservoir No. 3
2. The name of the stream from which the reservoir is to be filled and the appropriation made is
Beaver Creek
tributary of Sandy River
3. The amount of water to be stored is Approximately twoacre feet.
4. The use to be made of the impounded water is . Irrigation (trugation, power, domestic supply, etc.)
5. The location of the proposed reservoir will be in Sec. 16  (Give sections or townships to be submerped)
Tp. 1 S , R. 4 E , W. M., in the county of Multnomah
(a) State whether situated in channel of running stream and give character of material at outlet
In channel of stream. Outlet clay.
(b) If not in channel of running stream, state how it is to be filled. If through a feed canal, give
name and dimensions
and the commence of the commen
6. The dam will be located in S.W. 1/4 of thes.E. 1/4 of Sec. 16
Tp. 1 S , R. 4 B . W. M. The maximum height will be 7 feet above stream bed or ground
surface on center line of dam. The length on top will be
bottom feet; width on top feet; slope of front
or water side; slope on back; height of dam above water line (Feet horizontal to 1 vertical)
when full feet.

\*A different form of application should be used for the appropriation of stored water to beneficial use. Such forms can be secured without charge, together with instructions, by addressing the State Engineer, Salem. Oregon.

The construction of dam, the material of which it is to be built, and material of protection from waves are as follows:  Cet and Carryall were used to fill; Clay was used with a crass sod.  Native with top soil; and banks are well protected with a crass sod.  Native with the property with dimensions are as follows: Around and of dam.  Has coment lined spillway 48 inches wide and 6 ft deep with grooves for tongue and grooved hoards to raise pond level after freehet season and prior to June 1 when storage season is over.  Native y  The location of damla from the proposed reservoir, with character of construction and dimensions, are as follows: around opposite end of dam from outlet; constructed out of earth. 16 foot bottom with 31d03 of 3:1 slope, and a gra 3 sod.  Note of a particular, I alloyd as I slope, and a gra 3 sod.  Note of a particular, I alloyd as I slope, and a gra 3 sod.  Note the areas submerged by the proposed reservoir, when full, will be 1 acres, with a maximum depth of water of geet; and approximate mean depth of water 2 feet.  The estimated cost of the proposed work is \$ 300.00  12. Construction work will begin on or before as constructed in 1937  13. Construction work will be completed on or before alterations will be concept by 1959 or Bov. 1960.  STATE OF OREGON.  County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion.  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9 1959.  WITNESS my hand this 8th day of Pecember 1959.  WITNESS my hand this 8th day of Pecember 1959.  STATE FOOREEN.  STATE FOOREEN.	
nired with top soil; and banks are well protected with a rais sod.  Outlet  8. The location of of the proposed with dimensions are as follows: Around and of dom.  Has coment lined spillway 48 inches wide and 6 ft deep with grooves for tongue and grooved boards to raise pond level after frechet season and prior to June 1 when storage season is over.  9. The location of called from the proposed reservoir, with character of construction and dimensions, are as follows: around opposite end of dan from outlet; constructed out of earth. 16 foot bottom with sides of 3:1 slope and a grain sod.  All of a pletting if the proposed reservoir, when full, will be 1 acres, with a maximum depth of water 2 feet; and approximate mean depth of water 2 feet.  11. The estimated cost of the proposed work is 300.00  12. Construction work will begin on or before as constructed in 1937  13. Construction work will begin on or before alterations will be lone by 1959 or Nov. 1960.  STATE OF OREGON.  County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9 1959.  WITNESS my hand this 8th day of December 1958.	7. The construction of dam, the material of which it is to be built, and method of protection from
8. The location of of the proposed preservoir, when full, will be 1 arcs.  11. The arcs submerged by the proposed reservoir, when full, will be 1 arcs.  12. feet.  13. Construction work will be completed on or before as constructed in 1937  13. Construction work will be completed on or before as follows:  STATE OF OREGON.  County of Marion.  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before Peturary 9  WINNESS my hand this 8th day of December 1959.  8th location of office and open or peture of the submerse of the proposed work is a policy of the proposed work is so constructed in 1937  10. The arcs submerged by the proposed work is so constructed in 1937  11. The estimated cost of the proposed work is so constructed in 1937  12. Construction work will be completed on or before as constructed in 1937  13. Construction work will be completed on or before as constructed in 1937  14. The estimated cost of the proposed work is so constructed in 1937  15. Construction work will be completed on or before as constructed in 1937  16. Construction work will be completed on or before as constructed in 1937  17. The structure of the proposed work is so constructed in 1937  18. Construction work will be completed on or before as constructed in 1937  1959.  WITNESS my hand this 8th day of December 1959.  WITNESS my hand this 8th day of December 1959.	waves are as follows: Cat and Carryall were used to fill; Clay was us d
8. The location of the location of the location of demonstrated and the least state and the least state and the least state and the least season and prior to June 1 when storage season is over.  Nasteways  9. The location of addition from the proposed reservoir, with character of construction and dimensions, are as follows:  Around opposite end of dam from outlet; constructed out of earth. 16 foot bottom with sides of 3:1 slope and a gra 3 sod.  Addit of a picklineary of large and state Dath Large and a gra 3 sod.  Addit of a picklineary of large and approximate mean depth of water feet; and approximate mean depth of water a feet;	mixed with top soil; and banks are well protected with a grass sod.
8. The location of the location of the location of demonstrated and the least state and the least state and the least state and the least season and prior to June 1 when storage season is over.  Nasteways  9. The location of addition from the proposed reservoir, with character of construction and dimensions, are as follows:  Around opposite end of dam from outlet; constructed out of earth. 16 foot bottom with sides of 3:1 slope and a gra 3 sod.  Addit of a picklineary of large and state Dath Large and a gra 3 sod.  Addit of a picklineary of large and approximate mean depth of water feet; and approximate mean depth of water a feet;	· · · · · · · · · · · · · · · · · · ·
8. The location of the location of the location of demonstrated and the least state and the least state and the least state and the least season and prior to June 1 when storage season is over.  Nasteways  9. The location of addition from the proposed reservoir, with character of construction and dimensions, are as follows:  Around opposite end of dam from outlet; constructed out of earth. 16 foot bottom with sides of 3:1 slope and a gra 3 sod.  Addit of a picklineary of large and state Dath Large and a gra 3 sod.  Addit of a picklineary of large and approximate mean depth of water feet; and approximate mean depth of water a feet;	ontlat
for tongue and grooved boards to raise pond level after freshet  season and prior to June 1 when storage season is over.  9. The location of suita from the proposed reservoir, with character of construction and dimensions, are as follows: around opposite end of dam from outlet; constructed out clear whether through or around the proposed dam of earth. 16 foot bottom with sides of 3:1 slope, and a grassod.  Willief of a pilling of the proposed reservoir, when full, will be acres.  10. The area submerged by the proposed reservoir, when full, will be feet; and approximate mean depth of water of feet; and approximate mean depth of water.  2. feet.  11. The estimated cost of the proposed work is \$ 300.00.  12. Construction work will begin on or before as constructed in 1937.  13. Construction work will be completed on or before alterations will be fonce.  by 1959 or Nov. 1960.  STATE OF OREGON, St.  County of Marion.  STATE OF OREGON, St.  County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9, 1959.  WITNESS my hand this 6th day of December 1959.	8. The location of with dimensions are as follows: Around and of dam. (Stite whether over or around the dame)
Season and prior to June 1 when storage season is over.  9. The location of the proposed reservoir, with character of construction and dimensions, are as follows:  Around opposite end of dam from outlet; constructed out of earth. 16 foot bottom with sides of 3:1 slope, and a grain sod.  Next of apalinary is always and a grain sod.  10. The area submerged by the proposed reservoir, when full, will be 1 acres.  11. The estimated cost of the proposed work is \$ 300.00  12. Construction work will begin on or before as constructed in 1937  13. Construction work will be completed on or before alterations will be some by 1959 or Nov. 1960.  STATE OF OREGON, Season of the proposed work is \$ 300.00  STATE OF OREGON, Season of the proposed work is \$ 300.00  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows:  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9 ,1959.  WITNESS my hand this 8th day of December ,1958.	Has cement lined spillway 48 inches wide and 6 ft deep with grooves
9. The location of called from the proposed reservoir, with character of construction and dimensions.  are as follows: Around opposite end of dam from outlet; constructed out of earth. 16 foot bottom with sides of 3:1 slope, and a grassod.  Alule of Apalelia of the proposed reservoir, when full, will be 1 acres.  10. The area submerged by the proposed reservoir, when full, will be 1 acres.  with a maximum depth of water of feet; and approximate mean depth of water 2 feet.  11. The estimated cost of the proposed work is \$ 300.50  12. Construction work will begin on or before alterations will be 3000 by 1959 or Nov. 1960.  STATE OF OREGON, county of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9 1959.  WITNESS my hand this 8th day of December 1958.	for tongue and grooved boards to raise pond level after freshet
are as follows: Around opposite end of dam from outlet; constructed out of earth. 16 foot bottom with sides of 3:1 slope, and a grass sod.  **Alleget of Apallicant of Alleget Colors of State Engineer with corrections, on or before  10. The area submerged by the proposed reservoir, when full, will be a cores.  11. The estimated cost of the proposed work is \$ 300.00  12. Construction work will begin on or before as constructed in 1937  13. Construction work will be completed on or before alterations will be completed by 1959 or Nov. 1966.  **STATE OF OREGON.**  **County of Marion.**  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9 ,1959.  WITNESS my hand this 8th day of December ,1958.	
of earth. 16 foot bottom with sides of 3:1 slope, and a grain sod.  **Nuclear April 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Rasteway 9. The location of cullet from the proposed reservoir, with character of construction and dimensions,
10. The area submerged by the proposed reservoir, when full, will be acres.  with a maximum depth of water of feet; and approximate mean depth of water  2. feet.  11. The estimated cost of the proposed work is \$ 300.00  12. Construction work will begin on or before as constructed in 1937  13. Construction work will be completed on or before alterations will be one by 1959 or Nov. 1960.  STATE OF OREGON, County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9, 1959.  WITNESS my hand this 8th day of December ,1958.	
10. The area submerged by the proposed reservoir, when full, will be acres.  with a maximum depth of water of feet; and approximate mean depth of water  2. feet.  11. The estimated cost of the proposed work is \$ 300.00  12. Construction work will begin on or before as constructed in 1937  13. Construction work will be completed on or before alterations will be one by 1959 or Nov. 1960.  STATE OF OREGON, County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9, 1959.  WITNESS my hand this 8th day of December ,1958.	With of and bury 3 it high on a lo Duit to it:
in order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [15] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [16] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [17] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [18] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [18] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [18] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [18] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [18] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [18] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [18] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before  [18] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before [19] In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before [19] In order to retain its priority, this application must be returned to the State Engineer.	
2feet.  11. The estimated cost of the proposed work is \$ 300.60  12. Construction work will begin on or beforeas constructed in 1937  13. Construction work will be completed on or beforealterations will be done by 1959 or Nov. 1960.  STATE OF OREGON,	
11. The estimated cost of the proposed work is \$ 300.00  12. Construction work will begin on or before as constructed in 1937  13. Construction work will be completed on or before alterations will be lone by 1959 or Nov. 1960.  STATE OF OREGON, S.S. County of Marion,  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9 ,1959.  WITNESS my hand this 8th day of December ,1958.	
13. Construction work will be completed on or before alterations will be lone by 1959 or Nov. 1960.  STATE OF OREGON, County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before  February 9 1959.  WITNESS my hand this 8th day of December 1958.	mawork to of cline.
STATE OF OREGON,  County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows:  for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before  February 9, 1959.  WITNESS my hand this 8th day of December, 1958.	12. Construction work will begin on or before as constructed in 1937
STATE OF OREGON, County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9, 1959.  WITNESS my hand this 8th day of December ,1958.	13. Construction work will be completed on or before alterations will be some
County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows: for completion  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9 , 1959.  WITNESS my hand this 8th day of December , 1958.	by 1959 or Nov. 1960.
County of Marion.  This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows:  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before  February 9, 1959.  WITNESS my hand this 8th day of December 1958.	· · · · · · · · · · · · · · · · · · ·
This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction or completion as follows:  In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before  February 9, 1959.  WITNESS my hand this 8th day of December, 1958.	ss.
In order to retain its priority, this application must be returned to the State Engineer. with corrections, on or before	County of Marion,
In order to retain its priority, this application must be returned to the State Engineer, with corrections, on or before February 9 , 1959  WITNESS my hand this 8th day of December , 1958	
rections, on or before February 9 , 1959  WITNESS my hand this 8th day of December , 1958	maps and data, and return the same for correction or completion as follows: for completion
rections, on or before February 9 , 1959  WITNESS my hand this 8th day of December , 1958	
rections, on or before February 9 , 1959  WITNESS my hand this 8th day of December , 1958	
rections, on or before February 9 , 1959  WITNESS my hand this 8th day of December , 1958	
WITNESS my hand this 8th day of December ,1958	In order to retain its priority, this application must be returned to the State Engineer. with cor-
•	rections, on or before February 9 , 1959.
By Games M. Camer J. James W. Carver, Jr. Assistant	WITNESS my hand this 8th day of December ,1958
By Camer James W. Carver, Jr. Assistant	
James W. Carver, Jr. Assistant	STATE ENGINEER
James W. Carver, Jr. Assistant	De Come War
<del></del>	James W. Carver, Jr., Assistant

						_			•	
			ed repair			s life	e snd	'n в		
.carrie	all the	water in	the spi	llwuy.	• • • • •					
Xo	will con	atruot a	Wasteway	accor	ling	to the	a abec	ifica	tions	•
here	n specif	ded.whiol	the dam	has n	t ha	<b>d</b> •				. •
***************************************	······································		••••••				•			
	······································						• · · ·			
									• •	
	-		••••••				•			
••••••			••••••					* * *		
*************************	***************************************	• • • • • • • • • • • • • • • • • • • •	· · · · · · · · · · · · · · · · · · ·							
	•									
					. ••		, ,			
	•	***************************************	************		••••					
••••••		••••••••	,			•				• •
		• • • • • • • • • • • • • • • • • • • •						•		••
***************************************		••••••••••••								
•••••••••••••••••••••••••••••••••••••••		······································				**				
			********		••••••	•••				
					•••••	•••				
•••••••••••••••••••••••••••••••••••••••	·····	••••••••••	•••••••		••••				••	
		•••••••••••••••••••••••••••••••••••••••	••••••		· · · · · · · · · · · · · · · · · · ·	••••				
					•					
ATE OF OF  County of M	> ee									
		4 7 7	• • • •					_	•	
			mined the fo							
•			conditions: Th							
			#3 and the							
appropria	ted under	Application	n No. 32875	Permi	t No.	25965	for s	uppleme	ntal i	rri
The righ	: hereunder s	shall be limit	ed to the store	age of	2.0	•••••••			acre f	eet.
The prio	ity date of th	hi <b>s permit is</b> .	August	15, 19	58				••••	
Actual co	nstruction u	vork shall beg	gin on or befo	re Mar	ch 16	1960	· • · · · · • • • · · · · · · · · · · ·	••••		<b>.</b>
d shall there	ifter be pros	ecuted with r	easonable dili	gence an	d be co	mplete <b>d</b>	on or be	fore <b>Oc</b> 1	ober 1	,1
		•••••••								
WITNES	S my hand t	his 16th	day o	fY	arch .	••••		19 59.		
			<del>-</del> '						•	
	•	•			t	1	_			

Reservoir Permit No. R. 2221 Application No. 62 5227

## PERMIT

To construct a reservoir and store for beneficial use the unappropriated waters of the State of Oregon.

on the 12th day of Highert office of the State Engineer at Salem, Oregon, This instrument was first received in the 19.56, at £'40. o'clock A. M.

Approved:

Merch 16, 1959

Recorded in Book No. 8
Reservoirs, on Page 221.4

LESTIS A. STAILLY STATE ENGINEER

Drainage Basin No. 3 page 12 C

Fees Paid.

) State Printing Dept. 31271