SEP 15 1965 OCT 7 1965

STATE ENGINEERSTATE ENGINEERS Proir Permit No. 4608 CERTIFICATE NO. 2885
SALEM. OREGON SALEM OFFICIN

Application for a Permit to Construct a Reservoir and to Store for Beneficial Use the Unappropriated Waters of the State of Oregon

I, Charles S. Moore
(Name of Applicant)
of Tall Timber Ranch, P.O. Box 398, Selma, (Mailing Address)
State ofOregon, do hereby make application for a permit to construct the
following described reservoir and to store the unappropriated waters of the State of Oregon, subject to
existing rights.
If the applicant is a corporation, give date and place of incorporation
1. The name of the proposed reservoir isTallTimberLake
2. The name of the stream from which the reservoir is to be filled and the appropriation made is
Salt Gulch Creek
tributary of Deer Creek
3. The amount of water to be stored is # Cossested To - # 20.33 acre feet.
4. The use to be made of the impounded water is <u>Irrigation</u> (Irrigation, power, domestic supply, etc.)
5. The location of the proposed reservoir will be in Sec
Tp. 38 S , R. 7 W, W.M., in the county ofIosephine
(a) State whether situated in channel of running stream and give character of material at outlet
In channel of running stream- Earth fill dam with underwater outlet
(b) If not in channel of running stream, state how it is to be filled. If through a feed canal, give
name and dimensions
6. The dam will be located in NW SN SN SN Sec
Tp. 38.5., R. 7. W.M. The maximum height will be 28.5 feet above stream bed or ground
surface on center line of dam. The length on top will be272 feet; length on
bottom75
or water side 3:1 ; slope on back 2:1 ; height of dam above water line (Feet horizontal to 1 vertical)
when full 4
* A different form of application should be used for the appropriation of stored water to beneficial use. Such forms can be secured

Some are as follows: Comparated earth fill of clay and fine graval, with constituenth and core ambankment of impermenble material. **Maxa protection: Seed upstroam dam face and develop: sod layer. **8. The location of wasteway with dimensions are as follows: 36 inch dism. Computation (class whether we exceed the day) **8. The location of wasteway with dimensions are as follows: 36 inch dism. Computation metal pine (under dam) with drop inlet; also an emergency spillway **West of wasterly end of dam, with minimum waterway of hu aquare feet. **9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: A. 12 inch dism. Stock plus bottom drain, valved at inlets. Alacharacing into the above 36 inch pine. **10. The area submerged by the proposed reservoir, when full, will be \$2.99 acres with a maximum depth of water of \$2.50 inch pine. **10. The area submerged by the proposed work is \$18,000 **12. Construction work will begin on or before As soon in 1965 as plans are appropriated by State Engineer. **13. Construction work will be completed on or before Dag 31, 1965. **STATE OF OREGON, State Oregins application, together with the accompanyin maps and data, and return the same for	7. The construction of dam, the material of	f which it is to be built, and meth	od of protection from
8. The location of wasteway with dimensions are as follows: 36 inch.diam. corrugate. 8. The location of wasteway with dimensions are as follows: 36 inch.diam. corrugate. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: A 12 inch.diam. steel pipe bottom drain, valved at contains a second contains and second contain	aves are as follows: .Compacted earthf:	ill of clay and fine gr	avel, with
8. The location of wasteway with dimensions are as follows: 36 inch diam. Corrugate 19tal pipe (under dam) with drop inlet; also an emargency spillway 19tal of westerly end of dam, with minimum waterway of 40 square feet. 9. The location of outlet from the proposed reservoir, with character of construction and dimen ons, are as follows: A 12 inch diam. steel pipe hostom drain. Walked at 19th discharging into the above 36 inch pipe. 10. The area submerged by the proposed reservoir, when full, will be 29 acres with a maximum depth of water of 15 feet. 11. The estimated cost of the proposed work is \$18,000. 12. Construction work will begin on or before As soon in 1965 as plans are approby State Engineer. 13. Construction work will be completed on or before Dac 31, 1965. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin maps and data, and return the same for In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before, 19	ore trench and core embankment	of impermeable material	•
8. The location of wasteway with dimensions are as follows: 36 inch dism. corrusgate (State washer over or around the dim) netal pipe (under dam) with drop inlet; also an emergency spillway (seek of westerly end of dam, with minimum waterway of 40 square feet. 9. The location of outlet from the proposed reservoir, with character of construction and dimen ons, are as follows: A 12 inch diam, steed pipe bottom drain, valvad at (Ald dams screen satural steems channels must be proposed with an outlet conduit of such especially and location to pease the inlett. dischanging into the above 36 inch pipe. 10. The area submerged by the proposed reservoir, when full, will be 299 acress with a maximum depth of water of 200 feet. 11. The estimated cost of the proposed work is \$18,000. 12. Construction work will begin on or before As soon in 1965 as plans are appropriate by State Engineer. 13. Construction work will be completed on or before Dag 31, 1965. STATE OF OREGON, SS. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin maps and data, and return the same for	Wave protection: Seed upstream de		
9. The location of outlet from the proposed reservoir, with character of construction and dimen ions, are as follows: A. 1.2. indicate them channels must be provided with a mottle conduit, of such capacity and location to pass the inlett, discharging into the above 36 inch pipe. 10. The area submerged by the proposed reservoir, when full, will be 299 acres with a maximum depth of water of feet; and approximate mean depth of water of feet. 11. The estimated cost of the proposed work is \$18,000. 12. Construction work will begin on or before As. Soon in 1965, as plans we approve by State Engineer. 13. Construction work will be completed on or before Day 31, 1965. STATE OF OREGON, Ss. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin maps and data, and return the same for		ons are as follows:36 inchd.	iam. Corrugated over or around the dam)
in let. discharging into the above 36 inch pipe. The area submerged by the proposed reservoir, when full, will be 2.94 acres with a maximum depth of water of feet. 10. The area submerged by the proposed reservoir, when full, will be acres with a maximum depth of water of feet. 11. The estimated cost of the proposed work is \$.18,000. 12. Construction work will begin on or before As. soon in 1965, as plans are appropriate to the struction work will be completed on or before Dear 1, 1965. STATE OF OREGON, This is to certify that I have examined the foregoing application, together with the accompanyin maps and data, and return the same for In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before, 19	,		·
with a maximum depth of water of	ions, are as follows: A.l.2inchdiamst (All dams across natural stream channels mu	eelpipebottomdrain st be provided with an outlet conduit, of such ca	valved at pacity and location to pass the
11. The estimated cost of the proposed work is \$.18,000		•	
11. The estimated cost of the proposed work is \$18,000		feet; and approximate	mean depth of water
12. Construction work will begin on or before AsSoon in 1965asplansareappro by State Engineer. 13. Construction work will be completed on or before Dec31, 1965	₩ 7. ² feet.		· · · · · · · · · · · · · · · · · · ·
by State Engineer. 13. Construction work will be completed on or before Dac. 31, 1965. STATE OF OREGON, Ss. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin maps and data, and return the same for In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before	11. The estimated cost of the proposed wor	k is \$.18,000	
STATE OF OREGON, ss. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin maps and data, and return the same for		by State Engineer.	lans are approve
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin naps and data, and return the same for		(Signature of appl	icant)
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin naps and data, and return the same for			
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin naps and data, and return the same for			
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanyin naps and data, and return the same for	STATE OF OREGON,		•
naps and data, and return the same for			• ·
In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before, 19	This is to certify that I have examined th	e foregoing application, together u	with the accompanying
ions on or before, 19, 19	naps and data, and return the same for	••••••	
ions on or before, 19, 19			
	In order to retain its priority, this applica	ation must be returned to the State	Engineer, with correc-
WITNESS my hand this day of, 19, 19	ions on or before, 19.	······································	
WITNESS my hand this day of, 19, 19		•	······································
STATE ENGINEER	WITNESS my hand this day of		19
STATE ENGINEER			
A . A . 3 C B			STATE ENGINEER
		Por Control of the Co	Win to a fine

Remarks:Detailedplanswillbesubmitted	as soon as possible
This application concerns improvement and e	nlargement of reservoir
covered by Reservoir Permit No. R-1084, and	also construction of a
new and higher dam. The area to be irrigate	d is already covered by
existing Water Right Certificate as recorded	in State Record of Water
Right Certificates, Volume 15, pages 21523 a	nd 21524 (Re: application.
numbers 21991 and 21995 and Permit No. 19908	.)
*	
•••••••••••••••••••••••••••••••••••••••	Aller •
	(£_
es de la companya de	\. \. \. \. \. \. \. \. \. \. \. \. \. \
2-85 CL	
	······································
·	*
	1 1 2
STATE OF OREGON,	suppl Irrig
County of Marion,	suppl Irrig
This is to certify that I have examined the foregoing appli	cation and do hereby grant the same,
subject to the following limitations and conditions: The right herei	n granted is limited to the construction
of Tall Timber Reservoir and storage of water from Sal	lt Gulch Creek to be appropriated
under application No. 41382, permit No. 30623 for	supplemental irrigation.
······································	
······································	₂₀ .3
The right hereunder shall be limited to the storage of	20.33 acre feet.
The priority date of this permit is	October 7, 1965 Oct
Actual construction work shall begin on or before	November 30, 1966 and
shall thereafter be prosecuted with reasonable diligence and be co	mpleted on or before October 1, 1967.
WITNESS my hand this30th day ofNovember	, 19. 65.
21	

Application No. R-41470

Reservoir Permit No. 4608

PERMIT

To construct a reservoir and store for bene-ficial use the unappropriated waters of the State of Oregon.

on the 7th day of October, office of the State Engineer at Salem, Oregon, 19.65, at 8.00 o'clock . A.M. This instrument was first received in the

Returned to applicant:

Approved:

November 30, 1965

Recorded in Book No. of

Reservoirs, on Page 4608.

CHRIS L. WHEELER

State Engineer

Drainage Basin No. 15 page 561

1500