

RECEIVED  
OCT 11 1966  
STATE ENGINEER  
SALEM, OREGON

\* Reservoir Permit No. **R 4795**

CERTIFICATE NO. **38565**

# Application for a Permit to Construct a Reservoir and to Store for Beneficial Use the Unappropriated Waters of the State of Oregon

I, Jim Snider  
(Name of Applicant)

of Rte #2, Box #17, Lakeview, 97630  
(Mailing Address)

State of Oregon, do hereby make application for a permit to construct the following described reservoir and to store the unappropriated waters of the State of Oregon, subject to existing rights.

If the applicant is a corporation, give date and place of incorporation

1. The name of the proposed reservoir is Hammersly Canyon Creek Reservoir

2. The name of the stream from which the reservoir is to be filled and the appropriation made is Hammersly Canyon Creek

tributary of tributary of Thomas Creek

3. The amount of water to be stored is 6.0 acre feet.

4. The use to be made of the impounded water is flood control, stock water and irrigation of approx. 2.0 acres - 5 acre ft. & 1 acre ft. stock  
(Irrigation, power, domestic supply, etc.)

5. The location of the proposed reservoir will be in Sec. 3  
(Give sections or townships to be submerged)

Tp. 39 S, R. 20 E, W.M., in the county of Lake

(a) State whether situated in channel of running stream and give character of material at outlet  
yes - intermittent stream

Material - gravelly loam

(b) If not in channel of running stream, state how it is to be filled. If through a feed canal, give name and dimensions

6. The dam will be located in NW $\frac{1}{4}$ SW $\frac{1}{4}$ , Sec. 3  
(Smallest legal subdivision)

Tp. 39 S, R. 20 E, W.M. The maximum height will be 10 feet above stream bed or ground

surface on center line of dam. The length on top will be 700 feet; length on

bottom 250 feet; width on top 15 feet; slope on front

or water side 3 to 1; slope on back 3 to 1; height of dam above water line  
(Feet horizontal to 1 vertical) (Feet horizontal to 1 vertical)

when full 2.5 feet.

\* A different form of application should be used for the appropriation of stored water to beneficial use. Such forms can be secured without charge, together with instructions, by addressing the State Engineer, Salem, Oregon 97310.

7. The construction of dam, the material of which it is to be built, and method of protection from waves are as follows: .....

Built by carryall of earth fill; riprap, if necessary

8. The location of wasteway with dimensions are as follows: in undisturbed  
(State whether over or around the dam)

earth at south end of dam

20.0 feet bottom width, 1 to 1 sideslope

9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: at center of dam in natural earth

(All dams across natural stream channels must be provided with an outlet conduit, of such capacity and location to pass the normal flow of the stream at any time)

asphalt dipped corrugated iron pipe 10" diameter x 80' long-

normal flow of the stream at any time)

5' vertical drop end to end

10. The area submerged by the proposed reservoir, when full, will be 1 acres, with a maximum depth of water of 8.0 feet; and approximate mean depth of water

3.2 6.0 feet.

11. The estimated cost of the proposed work is \$4,233

12. Construction work will begin on or before Nov. 1, 1966 (or receipt of permit.)

13. Construction work will be completed on or before Nov. 1, 1967

*Jim Snider*

(Signature of applicant)

STATE OF OREGON, }  
County of Marion, } ss.

This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for correction and completion correction

In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before December 26, 1966.  
January 3 67

WITNESS my hand this 25th day of October, 1966.  
3rd November 66

RECEIVED RECEIVED  
OCT 20 1966 NOV 1 1966  
STATE ENGINEER STATE ENGINEER  
STATE OF OREGON STATE OF OREGON

CHRIS L. WHEELER  
STATE ENGINEER

*Samuel D. Busch*  
ASSISTANT

Remarks: Plans and specifications prepared and construction to be supervised by Soil Conservation Service engineers. 10" pipe estimated by Soil Conservation Service engineers and by watermaster Glenn Tyler as adequate for by pass requirements of stream flow. Purposes of dam are primarily for minor flood control, a settling basin for coarse gravel and a stock watering pond, and secondarily for irrigation of yard, trees and small garden.

STATE OF OREGON, }  
 County of Marion, } ss.


This is to certify that I have examined the foregoing application and do hereby grant the same, subject to the following limitations and conditions: The right herein granted is limited to the construction of Hammersly Canyon Creek Reservoir and storage of water from Hammersly Canyon Creek to be appropriated under application No. 42900, permit No. 31591 for irrigation and stock being 5.0 af for irrigation and 1.0 af for stock

The right hereunder shall be limited to the storage of 6.0 acre feet.

The priority date of this permit is October 11, 1966

Actual construction work shall begin on or before February 7, 1968 and shall thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 1968.

WITNESS my hand this 7th day of February, 1967.

  
 STATE ENGINEER

PC

Application No. R-42879  
Reservoir Permit No. R 4795

**PERMIT**

To construct a reservoir and store for beneficial use the unappropriated waters of the State of Oregon.

This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 11th day of October, 1966, at 8:00 o'clock A. M.

Returned to applicant:

Approved:

February 7, 1967

Recorded in Book No. \_\_\_\_\_ of

Reservoirs, on Page R 4795

CHRIS L. WHEELER  
State Engineer

Drainage Basin No. 13 page 262

Fees 115.00