n mado

Application for a Permit to Construct a Reservoir and to Store for Beneficial Use the Unappropriated Waters of the State of Oregon

of801 N. I	Foothills Road,	Medford, Or	egon 97501	······································	
State of Oregon		, do hereby make	application for a	permit to constru	ct the
ollowing described res	ervoir and to store th	e unappropriated	vaters of the State	e of Oregon, subj	ect to
existing rights.					
If the applicant i	s a corporation, give o	late and place of i	acorporation		
1. The name of the	ie proposed reservoir i	sGarrett	Reservoir	•	***********
2. The name of t	he stream from which	the reservoir is to	be filled and the	appropriation m	ade is
	South Fork of U	-	· · · · · · · · · · · · · · · · · · ·		
ributary of Rogue I					• • •
3. The amount of	water to be stored is	8,1acre ft,	for A.T.C. pri	or to Aprilacr	e feet.
4. The use to be a	nade of the impounded	oir will be in Sec	(Irrigation, power, dom S.W. qtr of (Give sections or to	the N.E. qt.	tral Sec
4. The use to be a 5. The location of the control	nade of the impounded	oir will be in Sec. only ofJackso of running stream	(Irrigation, power, dom S.W. qtr of (Give sections or to	the N.E. QUI	itral c. Sec
4. The use to be a 5. The location of the second of the s	nade of the impounded f the proposed reserved Nest, W.M., in the court situated in channel	oir will be in Sec. onty ofJackson of running stream	(Irrigation, power, dom S.W. qtr of (Give sections or to	the N.E. QUI	itral r. Sec
4. The use to be a 5. The location of the second of the s	nade of the impounded f the proposed reserved Nest, W.M., in the court situated in channel	oir will be in Sec. onty ofJackson of running stream	(Irrigation, power, dom S.W. qtr of (Give sections or to	the N.E. QUI	outlet
4. The use to be a 5. The location of the control	nade of the impounded f the proposed reserved lest, W.M., in the court situated in channel and the court situated in channel of running stream	oir will be in Sec. of running stream of places are and the second are and the second are are and the second are	(Irrigation, power, dom S.W. qtr of (Give sections or to a and give character) of the filled. If three or the contraction is the filled.	the N.E. QUI	outlet
4. The use to be a 5. The location of the second of the s	nade of the impounded f the proposed reserved lest, W.M., in the court situated in channel and a stream of running stream	oir will be in Sec. onty ofJackson of running stream of particles of the stream on, state how it is t	(Irrigation, power, dom S.W. qtr of (Give sections or to a and give characters) be filled. If three	the N.E. QTI the N.E. QTI ownships to be submerge er of material at ough a feed cana	outlet
4. The use to be a 5. The location of the control o	nade of the impounded f the proposed reserved Nest, W.M., in the court situated in channel and a stream of running stream	oir will be in Sec. of running stream of purpose of the process	(Irrigation, power, dom S.W. qtr of (Give sections or to a and give character) o be filled. If three	the N.E. QUI waships to be submerge er of material at ough a feed cana	outlet
4. The use to be a 5. The location of Tp. 37 Sout R. 1) (a) State whether (b) If not in charantee and dimensions 6. The dam will	nade of the impounded f the proposed reserved lest, W.M., in the court situated in channel of running stream the located in	oir will be in Sec. of running stream of running stream of, state how it is t Salboye (Smallest legal subc	(Irrigation, power, dom S.W. qtr of (Give sections or to a and give character) of be filled. If three livision)	the N.E. QUI waships to be submerge er of material at ough a feed cana	outlet
4. The use to be a 5. The location of Tp. 37 South. 1 (a) State whether (b) If not in charantee and dimensions 6. The dam will Tp, R	nade of the impounded f the proposed reserve Nest, W.M., in the cou r situated in channel nnel of running stream be located in	oir will be in Sec. of running stream of running stream n, state how it is t Smallest legal subo mum height will b	(Irrigation, power, dom S.W. qtr of (Give sections or to a and give characters) be filled. If three livision)	estic supply, etc.) COI the N.E. QTI ownships to be submerge er of material at ough a feed cana ough a feed cana	outlet l, give
4. The use to be a 5. The location of the control	nade of the impounded f the proposed reserve Nest, W.M., in the cou r situated in channel nnel of running stream be located in	oir will be in Sec. of running stream of running stream n, state how it is t Shallest legal subcommum height will be	(Irrigation, power, dom S.W. qtr of (Give sections or to a and give characted) obe filled. If three (ivision) e. 8. feet above 25	estic supply, etc.) COI the N.E. Qt ownships to be submerge er of material at ough a feed cana ough a feed cana e stream bed or g feet; len	outlet l, give
4. The use to be a 5. The location of Tp. 37 South. 1 (a) State whether (b) If not in charantee and dimensions 6. The dam will Tp, R	nade of the impounded f the proposed reserve Nest, W.M., in the cou r situated in channel nnel of running stream be located in	oir will be in Sec. of running stream of running stream n, state how it is t Shallest legal subcommum height will be	(Irrigation, power, dom S.W. qtr of (Give sections or to a and give characted) obe filled. If three (ivision) e. 8. feet above 25	estic supply, etc.) COI the N.E. Qt ownships to be submerge er of material at ough a feed cana ough a feed cana e stream bed or g feet; len	outlet l, give
4. The use to be a 5. The location of the control	nade of the impounded f the proposed reserve Nest, W.M., in the countricated in channel nnel of running stream be located in	oir will be in Sec. of running stream of running stream of, state how it is t Shabove (Smallest legal subo mum height will b top will be5	(Irrigation, power, dom S.W. qtr of (Give sections or to a and give characters) be filled. If three livision) e. 8feet above 25	estic supply, etc.) COI the N.E. QTI ownships to be submerge er of material at ough a feed cana ough a feed cana e stream bed or g feet; len feet; slope or	outlet l, give round gth on front

otherwise construction of the dam itself, however, had been essentially completed and consequently the dam has sat and settled in place for more than two years and has a substantial cover of volunteer growth on top and both faces. Now that the need for this water is more definite it is proposed to obtain authorization for the dam so that water may be stored, and used. The dam so constructed of heavy clay soil which has spread and compacted by a rubber tired shatkethely undersumy with dimensions are as follows: The wasteway is around the South end of the dam on well sodded undisturbed ground. 3. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The Ottlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet may be stored to the stream at the proposed in the concrete box is protected with all others are at the first and expanded constanting stream for the dustriant stay flow is an expanded read to stream they flow atter. The opening of the concrete box is protected with an expanded metal screen to keep debris out. 11. The estimated cost of the proposed work is 9 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will begin on or before March 1, 1969 14. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for completed on or before March 1, 1969 15. Production work will begin on or before for the pump sump. 16. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for complete on or before for the pump sump. 17. County of Marion, The size English and the completed on or before for the pump sump. 18. County of Marion, 19. County of Marion, 19. County of Marion, 19. County o	Otherwise construction was stopped and all contemplated use was abandoned. Construction of the dam itself, however, had been essentially completed and consequently the dam has sat and settled in place for more than two years and has a substantial cover of volunteer growth on top and both faces. Now that the need for this water is more definite it is proposed to obtain authorization for the dam so that water may be stored and used. The dam was constructed of heavy clay soil which has spread and compacted by a rubber tired, farethelpol moretown with dimensions are as follows: The wasteway is around the South end of the dam on well souded undisturbed ground. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The Outlet is located in the old channel of the small astream at original grade lavel and consists of 12" bell and ring pipe. The inlet remains for all the same name are more more as a way from a south consult of some early and increase which was not consulted to the concrete box is protected by a 4' x 4' concrete hox with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with the opening of the concrete box is protected with an expanded metal screen to keep debris out. 12 1/2	7. The construction of dam, the material of which it is to be built, and method of protection from The proposed dam was started in the fall of 1966 under the	~
Construction of the dam latself, however, had been essentially completed and consequently the dam has sat and sotted in place for more than two years and has a substantial cover of volunteer growth on top and both faces, now that the need for this water is more definite it is proposed to obtain authorization for the dam so that water may be stored and used. The dam was constructed of heavy clay soil which has spread and compacted by a rubber tired emission are as follows: The wasteway is around the South end of the dam on well sodded undisturbed ground. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The outlet is located in the old channel of the sale is a constructed with a south conduct of the construction and dimensions, are as follows: The outlet is located in the old channel of the sale is a constructed with a content which is not the sale is a constructed with a content which is not the sale is a constructed with a content which is not the sale is a constructed with a content which is not the sale is a constructed by a 4. x. 4. concrete box with slots for cluice boards—to provide—for storing water. The opening of the concrete box is protected with an expanded metal screen to keep debris out. 2 1/2	Construction of the dam has sat and setted in place for more than two years and has a substantial cover of volunteer growth on top and both faces. Now that the need for this water is more definite it is proposed to obtain authorization for the dam so that water may be stored and used. The dam was constructed of heavy clay soil which has spread and compacted by a rubber tired first of water of first water may be stored. The wasteway with dimensiona are as follows: The wasteway is around the South and of the dam on well sodded undisturbed ground. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet is protected by a 4" x 4" concrete hox with severe commit of water well, while water and the stream at any times? An expanded metal screen to keep debris out. with a meaning depth of water of said water	waves are as follows: impression that approval was not required. Upon learning otherwise construction was stopped and all contemplated use was abandoned.	
years and has a substantial cover of volunteer growth on top and both faces, now that the need for this water is more definite it is proposed to obtain authorization for the dam so that water may be stored and used. The dam was constructed of heavy clay soil which has spread and compacted by a rubber tired grafted of heavy clay soil which has spread and compacted by a rubber tired grafted of heavy clay soil which has spread and compacted by a rubber tired grafted on the season of the dam on well sould undisturbed ground. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet season does not be season to be season as the season which we have does not be season as t	years and has a substantial cover of volunteer growth on top and both faces, now that the need for this water is more definite it is proposed to obtain authorization for the dam so that water may be stored and used. The dam was constructed of heavy clay soil which has spread and compacted by a rubber tired earlier of the dam was the stored and constructed by a rubber tired earlier of the same of the dam on well sould undisturbed ground. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The outlet is located in the old channel of the same lateral souls are as the control of the same lateral souls are as the control of the same lateral souls are as the control of the same lateral souls are as the control of the same lateral souls are as the control of the same lateral souls are as the control of the same lateral souls are as the control of the concrete box is protected by a d' x d' concrete box with slots for sluice boards to the provide-for storing water. The opening of the concrete box is protected with an expanded metal screen to keep debris out. 12. The assumed metal screen to keep debris out. 13. The simulated cost of the proposed work is \$770 was spent in 1966, another \$300 to the concrete box with be needed for the pump sump. 12. Construction work will be completed on or before March 1, 1969 13. Construction work will be completed on or before March 1, 1969 14. The simulated are as the complete on the concrete box is the completion. In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 1, 1969 14. The state of the proposed way of the concrete state and concrete souls. 15. The state is priority, this application must be returned to the State Engineer, with corrections on or before March 1, 1969 15. The EB 12 1969 16. The state of the proposed way of the concrete state of the state Engineer, with corrections on or before March 1, 1969 16. The state of the pro	Construction of the dam itself, however, had been essentially completed	
STATE OF OREGON, Country of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for semilestic mass of the same for semilestic se	STATE OF OREGON, Country of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Scampher State Engineer, with corrections on or before March 15, 1969 WITNESS my hand this 3145 met 1660 WITNESS my hand this 3145 met 1660 TEG EIVE PAGINEER FEB 1 1969 TEG EIVE PAGINEER FEB 1 1969 CORRESS MY hand this 3145 met 1660 CORRESS MY h	years and has a substantial cover of volunteer growth on top and hoth face	; .
The wasteway is around the South end of the dam on well sodded undisturbed ground. The wasteway is around the South end of the dam on well sodded undisturbed ground. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pape. The inlet is protected by a 4. x. 4. concrete box with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with an examided methal screen to keep debris out. An expanded metal screen to keep debris out. 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be medded for the pump sump. 12. Construction work will be needed for the pump sump. 13. Construction work will be more before March 1, 1969. 14. Construction work will be completed on or before March 1, 1969. 15. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for gamls by other screens and the state Engineer, with corrections on or before to retain its priority, this application must be returned to the State Engineer, with corrections on or before to retain its priority, this application must be returned to the State Engineer, with corrections on or before to retain its priority, this application must be returned to the State Engineer, with corrections on or before to retain its priority, this application must be returned to the State Engineer, with corrections on or before to retain its priority, this application must be returned to the State Engineer, with corrections on or before to retain its priority, this application must be returned to the State Engineer, with corrections on or before to retain its priority, this application for the state Engineer with the state of the proposed to the state Engineer with the state Engineer to the state Engineer to the state	Construction work will be completed on or before March 1, 1969. 11. Construction work will be completed on or before March 1, 1969. 12. Construction work will be completed on or before March 1, 1969. 13. Construction work will be completed on or before March 1, 1969. 14. Construction work will be completed on or before March 1, 1969. 15. Country of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for march 1, 1969. 16. Country of Marion, The stimus of the scand of the same for march 1, 1969. 17. Country of Marion, The stimus the march 1, 1969. 18. Construction work will be completed on or before March 1, 1969. 19. Construction work will be completed on or before March 1, 1969. 19. Construction work will be completed on or before March 1, 1969. 19. Construction work will be completed on or before March 1, 1969. 19. Construction work will be completed on or before March 1, 1969. 10. Construction work will be completed on or before March 1, 1969. 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969. 13. Construction work will be completed on or before March 1, 1969. 14. Construction work will be completed on or before March 1, 1969. 15. Country of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for march 1, 1969. 16. Country of Marion, The state Engineer, with corrections on or before March 1, 1969. 17. Country of Marion, 18. Construction work will be completed on or before March 1, 1969. 19. Construction work will be completed on or before March 1, 1969. 19. Construction work will be completed on or before March 1, 1969. 19. Construction work will be completed on or before March 1, 1969. 19. Construction work will be completed on the foregoing application, together with the acco	authorization for the dam so that water may be stored and usedThe dam was	;
The wasteway is around the South end of the dam on well sodded undisturbed ground. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe, The inlet is protected by a 4' x 4' concrete box with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with a standard-executive-gratepheto-phocomy-velocity-slowally in the 3 1/4 acres, an expanded metal screen to keep debris out. with a maximum depth of water of 2 feet. 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will be completed on or before March 1, 1969 13. Construction work will be completed on or before March 1, 1969 14. This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Gamplebion-and-Gampletion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 1, 1969 ECRIVE DECRIVE CHRIS L. MHERLER AND STANK ENGINEER FEB 12 1969 ECRIVE DECRIVE CHRIS L. MHERLER AND STANK ENGINEER FEB 12 1969 FEB 12 1969 FEB 12 1969 CHRIS L. MHERLER AND STANK ENGINEER FIRST	The wasteway is around the South end of the dam on well sodded undisturbed ground. 9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet is protected by a 4' x 4' concrete box with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with all expanded metal screen to keep debris out. All expanded metal screen to keep debris out. 11. The estimated cost of the proposed work is 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on before March 1, 1969. 13. Construction work will be completed on or before March 1, 1969. 14. Construction work will be completed on or before March 1, 1969. 15. County of Marion. This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for completion completion. In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before was a spent of the pump sump. April 6th February PECEIVE OHRIS L. MHERLER FEB 12 1969	constructed of heavy clay soll which was spread and compacted by a rubber	
9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The Outlet is located in the old channel of the construction and dimensions are as follows: The Outlet is located in the condition of the construction and at original grade level and consists of 12" bell and ring pipe. The inlet is protected by a 4' x 4' concrete box with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with an expanded metal screen to keep debris out. 11. The stimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will be completed on or before March 1, 1969. 13. Construction work will be completed on or before March 15, 1969. 14. Construction work will be completed on or before march 15, 1969. STATE OF OREGON, as construction work will be completed on or before march 15, 1969. This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for completed on the foregoing application together with the accompanying maps and data, and return the same for complete for the pump sump. In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before warch 3 is a point of the foregoing application. 11. PERSON my hand this complete the foregoing application of the State Engineer, with corrections on or before warch 3 is a point of the foregoing application. 12. Construction was a point of the proposed work is \$ 700 was spent in 1966, another \$300 with a point of the pump sump. 13. Construction work will be completed on or before march 15, 1969. 14. Construction work will be completed on or before warch 15, 1969. 15. Country of warch 15 is a point of the pump sump. 16. Construction work will be completed on or before warch 15 is a point of the pump sump. 17. Construction work will be completed on or before warch 15 is a point of	9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: The Outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet is protected by an authorized with a south conduct of the control of	M_{ullet} . The second of M_{ullet} is the second of M_{ullet} is the second of M_{ullet} in M_{ullet} in M_{ullet} is the second of M_{ullet} in M_{u	
sions, are as follows: The Outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet normal fow of the stream at any time) at original grade level and consists of 12" bell and ring pipe. The inlet normal fow of the stream at any time) is protected by a 4' x 4' concrete box with slots for sluce boards to provide for storing water. The opening of the concrete box is protected with an expansive development of the concrete box is protected with an expansive d	sions, are as follows: The Outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and tring pipe. The inlet normal dow of the stream at any three is any three is provided with an outlet conduct of much expectly add jection to push the normal dow of the stream at any three is provided. A stream that any three is provided for storing water. The opening of the concrete box is protected with all expending observed with slots for sluice boards to provided for storing water. The opening of the concrete box is protected with all expending observed with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with all expending observed with a maximum depth of water of the opening of the concrete box is protected with an expending observed with a storing with a maximum depth of water. The opening of the concrete box is protected with all expending observed with a storing with a stream of the opening of the concrete box is protected with all expending observed with a stream of the opening of the concrete box is protected with a cores. The opening of the concrete box is protected with a cores. The opening of the concrete box is protected with a cores. The opening of the concrete box is protected with a core. The opening of the concrete box is protected with a core of the opening of the concrete box is protected with a core of the proposed work is 770 was spent in 1966, another \$300 with be needed for the pump sump. STATE OF OREGON, STATE OF OREGON, STATE Engineer with the accompanying maps and data, and return the same for sample with the foregoing application, together with the accompanying maps and data, and return the same for sample with the complete of the state Engineer, with corrections on or before marked the foregoing application must be returned to the State Engineer, with corrections on or before marked with the complete of the concrete	sodded undisturbed ground.	
sions, are as follows: The Outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet normal fow of the stream at any time) at original grade level and consists of 12" bell and ring pipe. The inlet normal fow of the stream at any time) is protected by a 4' x 4' concrete box with slots for sluce boards to provide for storing water. The opening of the concrete box is protected with an expansive development of the concrete box is protected with an expansive d	sions, are as follows: The Outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and tring pipe. The inlet normal dow of the stream at any three is any three is provided with an outlet conduct of much expectly add jection to push the normal dow of the stream at any three is provided. A stream that any three is provided for storing water. The opening of the concrete box is protected with all expending observed with slots for sluice boards to provided for storing water. The opening of the concrete box is protected with all expending observed with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with all expending observed with a maximum depth of water of the opening of the concrete box is protected with an expending observed with a storing with a maximum depth of water. The opening of the concrete box is protected with all expending observed with a storing with a stream of the opening of the concrete box is protected with all expending observed with a stream of the opening of the concrete box is protected with a cores. The opening of the concrete box is protected with a cores. The opening of the concrete box is protected with a cores. The opening of the concrete box is protected with a core. The opening of the concrete box is protected with a core of the opening of the concrete box is protected with a core of the proposed work is 770 was spent in 1966, another \$300 with be needed for the pump sump. STATE OF OREGON, STATE OF OREGON, STATE Engineer with the accompanying maps and data, and return the same for sample with the foregoing application, together with the accompanying maps and data, and return the same for sample with the complete of the state Engineer, with corrections on or before marked the foregoing application must be returned to the State Engineer, with corrections on or before marked with the complete of the concrete	No. Maria and American Company of the Company of th	
sions, are as follows: The Outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet normal flow of the stream at any time) at original grade level and consists of 12" bell and ring pipe. The inlet normal flow of the stream at any time) is protected by a 4' x 4' concrete box with slots for sluce boards to provide for storing water. The opening of the concrete box is protected with an expansible described regardent deposite and provide for storing water. The opening of the concrete box is protected with an expansible described regardent deposite and provide for storing water of the proposed work is \$770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 14. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for	sions, are as follows: The outlet is located in the old channel of the small stream at original grade level and consists of 12" bell and ring pipe. The inlet normal dow of the stream at any three is not of the stream at any three is protected by a 4.4 x.4" concrete hox with slots for sluice boards to provide with a cutter to any three is protected by a 4.4 x.4" concrete hox with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with all expansion and expanded metal screen to keep debris out. 2. 1/2	J. 1987 348 247	
at original grade level and consists of 12" bell and ring pipe. The inlet bown of the second as well that is protected by a 4' x 4' concrete box with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with an expanded metal screen to keep debris out. area, an expanded metal screen to keep debris out. with a maximum depth of water of seet. 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will be completed on or before March 1, 1969. 13. Construction work will be completed on or before March 1, 1969. 14. This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for completed on the completion. In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 1 septembers. April 66 WITNESS my hand this septembers day of february	at original grade level and consists of 12" bell and ring pipe. The inlet more above the stream at an time. **More of the stream at an time.** is protected by a 4' x 4' concrete box with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with an expanded remetal-legative the decopiose provided solventil, will be a refer of a cres, an expanded metal screen to keep debris out, with a maximum depth of water of seet. 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 14. This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for sample thore and some section. Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 169 **WITNESS my hand this **31st** day of ** Christ I. where I. Arch 1969 **ECEIVE** CHRIS I. where I. Arch 1969 **STATE ENGINEER** FEB4 1969	9. The location of outlet from the proposed reservoir, with character of construction and dimen-	
is protected by a 4' x 4' concrete box with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with an expanded metal screen to keep debris out. 3 1/4 an expanded metal screen to keep debris out. 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 1, 1969 14. This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 1, 1969 WITNESS my hand this 21st day of February CHRIS L. NHEELER STATE ENGINEER ST	is protected by a 4' x 4' concrete box with slots for sluice boards to provide for storing water. The opening of the concrete box is protected with an expanded metal screen to keep debris out. an expanded metal screen to keep debris out. with a maximum depth of water of S. feet. II. The estimated cost of the proposed work is \$,770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 13. Construction work will be completed on or before March 15, 1969 14. This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Samplation and Convection Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 169 WITNESS my hand this 31st 1969 ECFIVE CHILE L. MHELLER 51at MILELER		١.
provide-for storing water. The opening of the concrete box is protected with an expanded metal screen to keep debris out. an expanded metal screen to keep debris out. beta maximum depth of water of seet, and approximate mean depth of water of seet, and approximate of seet, and a	provide for storing water. The opening of the concrete box is protected with an expanded metal screen to keep debris out. an expanded metal screen to keep debris out. with a maximum depth of water of S	at original grade level and consists of 12" bell and ring pipe. The inlet normal flow of the stream at any time)	
an expanded metal screen to keep debris out. ith a maximum depth of water of feet; feet. 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st Completion April 6th FEB 1 2 1969 FEG EIVE CHRIS L. MHELLER STATE ENGINEER STATE ENGI	an expanded metal screen to keep debris out. yith a maximum depth of water of seet; and approximate mean depth of water 2 1/2 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$500 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 1814 April 6th 69 WITNESS my hand this 31st day of February ECEIVE CHRIS L. WHERLER STATE ENGINEER FEB 4 1969	provide for storing water. The opening of the concrete har is protected with	h
2 1/2 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Samplation was be returned to the State Engineer, with corrections on or before March 31st — April 6th 69 WITNESS my hand this 1918 BECEIVE CHRIS L. WHEELER 1978 ENGINEER CHRIS L. WHEELER TATE ENGINEER	2 1/2 11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969. 13. Construction work will be completed on or before March 15, 1969. STATE OF OREGON, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st 1969. April 6th 69 WITNESS my hand this 31st day of February 69 ECEIVE CHRIS L. MHEILER 51ATE ENGINEER FEB 4 1969.	an expanded metal screen to keep debris out.	
11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Samplistic and Correction Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st and 1069 WITNESS my hand this 1916 day of February 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump. 12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Sempletion and Correction Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st April 6th 69 WITNESS my hand this 31st day of February 69 ECEIVE CHRIS L. MHEELER STATE ENGINEER FEB4 1969		
12. Construction work will be completed on or before March 15, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 21st and 1969 April 6th 69 WITNESS my hand this 231st day of February 69 ECEIVE CHRIS. L. NHEELER STATE ENGINEER	12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Samulation and Convection Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st 1 69 WITNESS my hand this 31st day of February 69 ECEIVE FEB 12 1969 ECEIVE CHRIS L. WHEELER STATE ENGINEER FEB 4 1969		
12. Construction work will be completed on or before March 15, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 21st and 1969 April 6th 69 WITNESS my hand this 231st day of February 69 ECEIVE CHRIS. L. NHEELER STATE ENGINEER	12. Construction work will begin on or before March 1, 1969 13. Construction work will be completed on or before March 15, 1969 STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Samulation and Convection Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st 1 69 WITNESS my hand this 31st day of February 69 ECEIVE FEB 12 1969 ECEIVE CHRIS L. WHEELER STATE ENGINEER FEB 4 1969	11. The estimated cost of the proposed work is \$ 770 was spent in 1966, another \$300 will be needed for the pump sump.	
STATE OF OREGON, Ss. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st — April 6th 69 WITNESS my hand this 31st — day of Lamberty 69 ECEIVE CHRIS. L. WHEFLER STATE ENGINEER	STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for	12. Construction work will begin on or before March 1, 1969	
STATE OF OREGON, Ss. County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st — April 6th 69 WITNESS my hand this 31st — day of Lamberty 69 ECEIVE CHRIS. L. WHEFLER STATE ENGINEER	STATE OF OREGON, County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for	13. Construction work will be completed on or before March 15, 1969	
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st (1969) April 6th 69 WITNESS my hand this 31st day of Lanuary 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for		
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st (1969) April 6th 69 WITNESS my hand this 31st day of Lanuary 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for	(Signature of applicant)	
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st (1969). April 6th 69 WITNESS my hand this 31st day of Lanuary 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for		
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st (1969) April 6th 69 WITNESS my hand this 21st day of Lanuary 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for	and the second of the second o	
County of Marion, This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st (1969) April 6th 69 WITNESS my hand this 21st day of Lanuary 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for	and the control of t The control of the control of	
This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for	This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for	STATE OF OREGON,	
maps and data, and return the same for Completion and Correction Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st 1969 April 6th 69 WITNESS my hand this 31st day of February 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	maps and data, and return the same for Completion and Convection Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before Narch 31st , 1959. April 6th 69 WITNESS my hand this 31st day of February 69 ECEIVE CHRIS L. WHEFIER STATE ENGINEER FEB 4 1969	County of Marion,	
maps and data, and return the same for Completion and Correction Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st 1969 April 6th 69 WITNESS my hand this 31st day of February 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	maps and data, and return the same for Completion and Correction Completion In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before Narch 31st , 1969 April 6th 69 WITNESS my hand this 31st day of February 69 ECEIVE CHRIS L. WHEFIER STATE ENGINEER STATE ENGINEER FEB 4 1969	This is to certify that I have examined the foregoing application, together with the accompanying	
In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before	In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before March 31st, 1969. April 6th 69 WITNESS my hand this 31st day of February 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER FEB 4 1969		
witness my hand this state day of Longry 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	witness my hand this 31st day of February 69 ECEIVE FEB 1 2 1969 FEB 4 1969 April 6th 69 CHRIS L. WHEELER STATE ENGINEER FEB 4 1969	Completion	
witness my hand this state day of Longry 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	witness my hand this 31st day of February 69 ECEIVE FEB 1 2 1969 FEB 4 1969 The state engineer feb 4 1969 FEB 1 2 1969 FEB 4 1969 FEB 1 2 1969 FEB 4 1969 FEB 4 1969		
WITNESS my hand this 31-st day of Lanuary 19-69-69 ECEIVE CHRIS L. WHEELER STATE ENGINEER	WITNESS my hand this 31st day of Lonuary 19-69-64 February 69 ECEIVE CHRIS L. WHEELER STATE ENGINEER FEB 4 1969		
ECEIVE CHRIS L. WHEELER STATE ENGINEER	February 69 DECEIVE CHRIS L. WHEELER STATE ENGINEER FEB4 1969		
ECEIVE CHRIS L. WHEELER STATE ENGINEER	February 69 DECEIVE CHRIS L. WHEELER STATE ENGINEER FEB4 1969	en e	
DECEIVE CHRIS L. WHEELER STATE ENGINEER	FEB121969 ECEIVE CHRIS. L. WHEELER STATE ENGINEER FEB4 1969		
STATE ENGINEER	STATE ENGINEER FEB4 1969		
STATE ENGINEER	STATE ENGINEER FEB4 1969	BECEIVEM	
STATE ENGINEER FER4 1960	STATE ENGINEER FEB4 1969		
1003		STATE ENGINEER FEB4 1969	
SALEM, OREGONSTATE ENGINEED BY WALL ASSISTANT	SALEM OREGONSTATE ENGINEER BY W. Jebousek		

•••••	100				•••••		******									******				,	
	4			* 1	J.		*****				A					••••		· .	*****		,
				• • • • •							: ,				**						
					V					******	*********	******		******			******				
••••					•••••	•••••		••••••		••••••	*******				• • • • • • • • • • • • • • • • • • • •		•••••			********	
		•••••	******		•••••			•••••		•••••			•••••					• • • • • • • • • • • • • • • • • • • •			
						*******		********					*****								
• • • • •		••••••	••••••	*******		•••,•••••		*********		*******	********	• • • • • • • • • • • • • • • • • • • •		*******	********			*******			
•••		••••					******			ţ. ••••••				••••••			•••••				
		*****								·					•••••		••••••• •				
	, .																				
		•			i Sky			: -t.				1		Zink in	· ·						Francisco Aprila
••••						13.15 14.15 14.15 14.15	:	- <u> </u>		******								4,			
••••• •		*****	• • • • • • • • • • • • • • • • • • • •			b				• • • • • • • • • • • • • • • • • • • •		:	·				******		•		
••••			- 5 mm 		•	· · · · · · · · · · · · · · · · · · ·			· · · · · · · · · · · · · · · · · · ·	•••••					••••••••••••••••••••••••••••••••••••••		•••••				
		•				en vad	150	(C)				;l	` . .>	ر, 		* 3	•••••				
					, T).								
	• • • • • • • • • • • • • • • • • • • •		्र [्]		:			;			Ď.				 !	;	į	1 "	,		
••••									<u></u>		# 				1.		•••••				;
	•••••	*****					**********		 	: • • • • • • • •		••••					•••••				
	*******	•••••			· .								····				•••••		•••••		
		•										*******									
									1,5 4												
••		******	••••••				*****									••••••			•••••		
											•										
A7	TE OI	7 O	REGO	ON,	}	_											•				
) }ss	3 . -											٠				
	ounty	of M	Iario i	n,)				mad 4	ha f	·	ina	anni	liaati	on am	. A A	o h	eraha	ı ara	nt th	a sam
Co	ounty This	of M	Iarion o cer	n, tify) that	: I ha								,							
Co oje	ounty This ect to t	of M is t the f	Iarion o cer follou	n, tify ving) that limi	: I ha tation	ıs an	ıd cor	rdition	ns: !	The r	ght	here	ein g	rante	d is	limi	ted t	o the	cons	tructio
Co Ga	This ect to t	of M is t the f	Iarion o cer follou leser	n, tify ving voi) that limi r ar	: I ha tation	is an	id cor	ndition	ns: '	The ri	ght So	here uth	ein g For	rante k Up	l is ton	limi Sl	ted t	o the	cons	tructio .ppr o-
Co Ga	This ect to t	of M is t the f	Iarion o cer follou leser	n, tify ving voi) that limi r ar	: I ha tation	is an	id cor	ndition	ns: '	The ri	ght So	here uth	ein g For	rante k Up	l is ton	limi Sl	ted t	o the	cons	tructio .ppr o-
Co Ga	This ect to t	of M is t the f	Iarion o cer follou leser	n, tify ving voi) that limi r ar	: I ha tation	is an	id cor	ndition	ns: '	The ri	ght So	here uth	ein g For	rante k Up	l is ton	limi Sl	ted t	o the	cons	tructio .ppr o-
Co Ga	This ect to t	of M is t the f	Iarion o cer follou leser	n, tify ving voi) that limi r ar	: I ha tation	is an	id cor	ndition	ns: '	The ri	ght So	here uth	ein g For	rante k Up	l is ton	limi Sl	ted t	o the	cons	tructio
Co Ge	This ect to tarret	of M is t the f it R	farion to cer follou deser er ap	tify ving voi	that limi r ar cat:	I ha	is an	nd cor	ndition of wa	ns: '	The ri	ght So	here	ein g For	ranted k Up fo	d is	limi Slo upp	ted tough	o the to	cons	tructio
Co Ge	This ect to the arretted with the The	of M is t the f tt R ande	farion to cer follou teser er ap	n, tify ving voi	that limi r ar cat:	I hattation and stand ion i	is an	id con	of wareled to t	ns: 'ter erm	The ri	ght So 3	here	ein g For	ranted k Up fo	d is	limi Sl upp	ted tough	o the to	cons	tructio ppro- igati cre fee
Co Ge	This ect to the arretted with the The	of M is t the f tt R ande	farion to cer follou teser er ap	n, tify ving voi ppli	that limi r ar cat: der of ti	tation nd station ion i	is an	d cor ge 0 4572 imite	ndition of wa 26, p	ns: 'ter erm	The ri	ght So	here uth 412	For	fo 8.1	d is ton	limi Slo upp	ted tough	o the to	cons be a irr	tructio ppro- rigati cre fee
Co Ge	This ect to the arretted with the The	of M is t the f tt R ande	farion to cer follou teser er ap	n, tify ving voi ppli	that limi r ar cat: der of ti	tation nd station ion i	is an	d cor ge 0 4572 imite	ndition of wa 26, p	ns: 'ter erm	The ri	ght So	here uth 412	For	fo 8.1	d is ton	limi Slo upp	ted tough	o the to	cons be a irr	tructio ppro- rigati cre fee
Co Ga iai	This ect to the arretted with the The Actre	is to the fact Runde	farion to cer follou leser er ap	n, tify ving voi opli reun date	that limi r ar cat: der of the	I hattation and stand ion	is an	imite	of wareless of the control of the co	ns: 'ter erm	The ri	ght So	here uth 412 Ja	For L nuar	fo fo 8.1 y 24	d is ton	969	ted tough	o the to	cons be s irr	tructio ppro- igati cre fee
Co Ga Lat	This ect to the arretted with the there	is to the fact Runde	farion to cer follou teser ar	n, tify ving voi ppli reun date ructi	that limi r ar cat: der of the	I ha tation nd st ion I shall his pe	be lith r	t is l begreeasor	ed to t	ns: 'ter erm the s	The ri	ght So 3	here uth 412 Ja A	For I nuar ugus	fo 8.1 24 leted	d is ton	Sloupp 969	ted tough	o the to ntal	cons be s irr	tructio ppro- rigati cre fee
Co Ga iai	This ect to the arretted with the there	is to the fact Runde	farion to cer follou teser ar	n, tify ving voi ppli reun date ructi	that limi r ar cat: der of the	I ha tation nd st ion I shall his pe	be lith r	t is l begreeasor	of wareless of the control of the co	ns: 'ter erm the s	The ri	ght So 3	here uth 412 Ja A	For I nuar ugus	fo 8.1 y 24	d is ton	Sloupp 969	ted tough	o the to ntal	cons be s irr	tructio ppro- igati cre fee

Application No. R-45225

Reservoir Permit No.R 5420

PERMIT

To construct a reservoir and store for beneficial use the unappropriated waters of the State of Oregon.

This instrument was first received in the

office of the State Engineer at Salem, Oregon,

on the 24th, day of Sanualy 19 69, at 8:00 o'clock A M.

Returned to applicant:

Approved:

August 19, 1969

Reservoirs, on Page R 5420 Recorded in Book No. ...

CHRIS L. WHEELER

Drainage Basin No. 15.

trus South Fork Upten Slov