

CERTIFICATE NO. 50712

R 6609

\* Reservoir Permit No. \_\_\_\_\_

WATER RESOURCES DEPT  
SALEM, OREGON

**Application for a Permit to Construct a Reservoir and to Store for Beneficial Use the Unappropriated Waters of the State of Oregon**

RECEIVED  
SEP - 1 1977  
WATER RESOURCES DEPT  
SALEM, OREGON

I, George W. Lind, Jr. and Josephine Sully Lind

(Name of Applicant)

of Route 1, Box 425 - Eagle Creek, Oregon 97022

(Mailing address)

(City)

State of \_\_\_\_\_, do hereby make application for a permit to construct the following described reservoir and to store the unappropriated waters of the State of Oregon, subject to existing rights.

(Zip Code)

If the applicant is a corporation, give date and place of incorporation \_\_\_\_\_

1. The name of the proposed reservoir is La Paloma Lake

2. The name of the stream from which the reservoir is to be filled and the appropriation made is un-named stream

tributary of Eagle Creek

3. The amount of water to be stored is 0.149 acre feet.

4. The use to be made of the impounded water is irrigation

(Irrigation, power, domestic supply, etc.)

5. The location of the proposed reservoir will be in Sec. 4

(Give sections or townships to be submerged)

Tp. 3 S, R. 4 E, W.M., in the county of Clackamas

(a) State whether situated in channel of running stream and give character of material at outlet in channel of stream. Outlet material cemented grave.

(b) If not in channel of running stream, state how it is to be filled. If through a feed canal, give name and dimensions \_\_\_\_\_

6. The dam will be located in SE 1/4 NW 1/4, Sec. 4

(Smallest legal subdivision)

Tp. 3S, R. 4E, W.M. The maximum height will be 5 feet above stream bed or ground

surface on center line of dam. The length on top will be 20 feet; length on

bottom 4 feet; width on top 15 feet; slope on front

or water side 3:1; slope on back 2:1; height of dam above water line

(Feet horizontal to 1 vertical)

(Feet horizontal to 1 vertical)

when full 2.5 feet.

\* A different form of application should be used for the appropriation of stored water to beneficial use. Such forms can be secured without charge, together with instructions, by addressing the State Engineer, Salem, Oregon 97310.

7. The construction of dam, the material of which it is to be built, and method of protection from waves are as follows: Compacted earth and gravel fill dam. Compaction was done with an International 175 Loader running over the fill material as it was placed in 6" lifts.

8. The location of wasteway with dimensions are as follows: see attached description.  
(State whether over or around the dam)

9. The location of outlet from the proposed reservoir, with character of construction and dimensions, are as follows: in addition to the 2-24" spillway pipes and the 12" overflow there is a 36" CMP at stream flow line, through the dam,  
(All dams across natural stream channels must be provided with an outlet conduit, of such capacity and location to pass the normal flow of the stream at any time)  
This has seepage collars on it. The flow thru is controlled by a timber and concrete gate works.

10. The area submerged by the proposed reservoir, when full, will be 0.05 acres, with a maximum depth of water of 4.5 feet; and approximate mean depth of water 3.25 feet.

11. The estimated cost of the proposed work is \$500.00

12. Construction work will begin on or before already completed

13. Construction work will be completed on or before already completed

George T. Lind, Jr.  
(Signature of applicant)  
Josephine Sully Lind

STATE OF OREGON, }  
County of Marion, } ss.

This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for completion

In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before October 31, 1977.

WITNESS my hand this 29th day of August, 19 77

Jim Saxon  
DIRECTOR  
By Larry M. Toll  
ASSISTANT

Remarks: .....

The spillway consists of 2 - 24" CMP in parallel around the south end of the dam with the flow lines 4 feet below the crest of the dam. There is a paved concrete spillway apron in front of them with the overflow elevation approximately 2 1/2 feet below the crest of the dam. The fall is about 1 1/2 feet from intake to discharge. These handle the run off after a heavy rain. In addition there is a 12" CMP with a flow line approximately 3 feet below the crest. This handles the normal overflow. There is an approximate fall of 3 feet from intake to discharge of this pipe.

Appl # P 5580

STATE OF OREGON, }  
County of Marion, } ss.

This is to certify that I have examined the foregoing application and do hereby grant the same, subject to the following limitations and conditions: The right herein granted is limited to the construction of La Paloma Lake reservoir and storage of water from unnamed stream to be appropriated under application No. 55808, permit No. 41783 for irrigation

The right hereunder shall be limited to the storage of 0.15 acre feet.

The priority date of this permit is May 3, 1977

Actual construction work shall begin on or before September 28, 1978 and shall thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 1979.

WITNESS my hand this 28th day of September, 1977

*James E. Larson*  
Water Resources Director

Application No. *R-55827*

Reservoir Permit No. **R 6609**

### PERMIT

To construct a reservoir and store for beneficial use the unappropriated waters of the State of Oregon.

This instrument was first received in the office of the State Engineer at Salem, Oregon, on the *23* day of *May*, 19 *27*, at *8* o'clock *A*. M.

Returned to applicant:

Approved:

Recorded in Book No. \_\_\_\_\_ of

Reservoirs, on Page \_\_\_\_\_

\_\_\_\_\_  
State Engineer

Drainage Basin No. \_\_\_\_\_ page \_\_\_\_\_

Fees *4 20 00*