Application for a Permit to Construct a Reservoir and to Store for Beneficial Use the Unappropriated Waters of the State of Oregon

	I, Tillamook City Water Commission (Name of Applicant)
ο £	Tilamook City , County of Tillamook
υ, .	(Postoffice)
Stat	e ofOregon , do hereby make application for a permit to construct the
folla	wing described reservoir and to store the unappropriated waters of the State of Oregon, subject to
exis	ting rights.
	If the applicant is a corporation, give date and place of incorporation
Feb	. 28, 1891
	1. The name of the proposed reservoir is Killam-Fawcett Reservoir
	2. The name of the stream from which the reservoir is to be filled and the appropriation made i
	Fawcett Creek
trib	utary of Tillamook River
	3. The amount of water to be stored is 200,000 gallons xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
	4. The use to be made of the impounded water is
	5. The location of the proposed reservoir will be in Sec. 22 T. 2 S., R. 9 W.M. (Give sections or townships to be submerged)
	(a) State whether situated in channel of running stream and give character of material at outle
	(b) If not in channel of running stream, state how it is to be filled. If through a feed canal, giv
nan	e and dimensions To be filled with 14" pipe
	diversion 6. The/dam will be located in SE_{4}^{1} NE_{2}^{1} (Smallest legal subdivision)
Tp.	(Smallest legal subdivision) 2 S , R. 9 W , W. M. It will be 9 ft. feet in height (No. N. or S.) (No. E. or W.)

^{*}A different form of application should be used for the appropriation of stored water to beneficial use. Such forms can be

The construction of dam, the material of which it is to be built, and method of protection of a greek are as follows: The dam is to be built of concrete. The bloye mentioned dam is the diversion dam from which the water is taken carried to the reservoir. The reservoir being 45 ft, square on botton and 1 with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows: Over dam. One dam is the diversion dam from which the water is taken carried to the reservoir. The reservoir being 45 ft, square on botton and 1 with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows: Over dam. Other da	i on top of42	feet; length on bottom42
7. The construction of dam, the material of which it is to be built, and method of protection aves are as follows: The dam is the diversion dam from which the water is takes carried to the reservoir. The reservoir being 43 ft. square on bottom and 1 with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows: Over dam. (State whether over or around the dam state of the proposed reservoir, with character of construction and dimensions. The outlet from the proposed reservoir, with character of construction and dimensions. The outlet from the reservoir is an 18" oice. (State whether over or around the proposed dam) 10. The area submerged by the proposed reservoir, when full, will be oit a maximum depth of water of feet. 11. The estimated cost of the proposed work is \$.535,000. 12. Construction work will begin on or before under construction. 13. Construction work will be completed on or before August 1, 1926. 14. Construction work will be completed on or before August 1, 1926. 15. Construction work will be application. 16. The state Water Board, accompany this application. 17. The derivation was as witnesses: 18. Signed in the presence of us as witnesses:	feet; width on top12fee	et slope of front or water sideverticle
7. The construction of dam, the material of which it is to be built, and method of protection was are as follows: The above mentioned dam is the diversion dam from which the water is taken carried to the reservoir. The reservoir being 43 ft. square on bottom and 1 with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows: 9. The location of outlet from the proposed reservoir, with character of construction and dimense as follows: 10. The area submerged by the proposed reservoir, when full, will be constituted in a maximum depth of water of 10 feet; and approximate mean depth of a feet. 11. The estimated cost of the proposed work is \$. £25,000. 12. Construction work will begin on or before and accompany this application. 13. Construction work will be completed on or before and accompany this application. TILLAMOOK CITY WATER COUNTSTON BY M. Hill, Pres.	1 to 1 (Feet horizontal to 1 vertical)	; height of dam above water line when full
The blogge mentioned dam is the diversion dam from which the water is taken carried to the reservoir. The reservoir being 45 ft. square on bottom and 1 with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows: (State whether ever or around the dam (State whether through or around the proposed dam) 9. The location of outlet from the proposed reservoir, with character of construction and dimense as follows: The outlet from the proposed reservoir is an 18" pipe. (State whether through or around the proposed dam) 10. The area submerged by the proposed reservoir, when full, will be 11. The estimated cost of the proposed work is \$.£35,000 12. Construction work will begin on or before		
The above mentioned dam is the diversion dam from which the water is taken carried to the reservoir. The reservoir being 45 ft. square on bottom and 1 with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows: 9. The location of outlet from the proposed reservoir, with character of construction and dimens as follows: 10. The outlet from the reservoir is an 18" pipe. 11. The area submerged by the proposed reservoir, when full, will be 10.1 12. Construction work will begin on or before 10. feet; and approximate mean depth of 12. Construction work will be completed on or before 13. Construction work will be completed on or before 14. August 1, 1926. 12. Construction work will be completed on or before 15. August 1, 1926. 13. Construction work will be completed on or before 2. August 1, 1926. 14. The Board, accompany this application. 15. Tillamook City water Commission Py M. Hill, Pres.	nstruction of dam, the material of whi	ch it is to be built, and method of protection from
The above mentioned dam is the diversion dam from which the water is taked carried to the reservoir. The reservoir being 45 ft. Square on bottom and I with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows:		
carried to the reservoir. The reservoir being 45 ft. square on bottom and 1 with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows:		
1 with 10 ft. verticle height. 8. The location of wasteway with dimensions are as follows: (State whether over or around the dan (State whether over or around the dan (State whether over or around the dan dan dimensions) 9. The location of outlet from the proposed reservoir, with character of construction and dimensions as follows: The outlet from the reservoir is an 18" pipe. (State whether through or around the proposed dam) 10. The area submerged by the proposed reservoir, when full, will be 11. The area submerged by the proposed work is \$ £25,000. 12. Construction work will begin on or before		
8. The location of wasteway with dimensions are as follows: 9. The location of outlet from the proposed reservoir, with character of construction and dimense as follows: The outlet from the reservoir is an 18" pipe. (State whether through or around the proposed dam) 10. The area submerged by the proposed reservoir, when full, will be	ed to the reservoir. The reservo	oir being 43 ft. square on bottom and slo
9. The location of outlet from the proposed reservoir, with character of construction and dimense as follows: The outlet from the reservoir is an 18" pipe. (State whether through or around the proposed dam) 10. The area submerged by the proposed reservoir, when full, will be	h 10 ft. verticle height.	
9. The location of outlet from the proposed reservoir, with character of construction and dimensive as follows: The outlet from the reservoir is an 18" pipe. (State whether through or around the proposed dam) 10. The area submerged by the proposed reservoir, when full, will be	cation of wasteway with dimensions are	e as follows: over dama (State whether over or around the dam)
the area submerged by the proposed reservoir, when full, will be		
th a maximum depth of water of		voir with character of construction and dimensions
10. The area submerged by the proposed reservoir, when full, will be		
10. The area submerged by the proposed reservoir, when full, will be	(State whether through	gh or around the proposed dam)
10. The area submerged by the proposed reservoir, when full, will be		
ith a maximum depth of water of		
ith a maximum depth of water of	area submerged by the proposed reservoi	ir, when full, will be
11. The estimated cost of the proposed work is \$.\$55,000. 12. Construction work will begin on or before	um depth of water of10	feet; and approximate mean depth of water
11. The estimated cost of the proposed work is \$.\$55,000. 12. Construction work will begin on or before		
12. Construction work will begin on or before	·	,
13. Construction work will be completed on or beforeAugust 1, 1926	estimated cost of the proposed work is \$	\$35,000
he State Water Board, accompany this application. TILLAMOOK CITY WATER COMMISSION (Name of applicant) By M. Hill, Pres.	truction work will begin on or before	under construction
uplicate maps of the proposed reservoir and storage works, prepared in accordance with the rune State Water Board, accompany this application. TILLAMOOK CITY WATER COMMISSION (Name of applicant) By M. Hill, Pres.	truction work will be completed on or bet	fore August 1, 1926
TILLAMOOK CITY WATER COMMISSION (Name of applicant) By M. Hill, Pres. igned in the presence of us as witnesses: 1) W. Elmderson		,
TILLAMOOK CITY WATER COMMISSION (Name of applicant) By M. Hill, Pres. Signed in the presence of us as witnesses: 1) W. Elmderson		b works, propurou in accordance service the times of
By M. Hill, Pres. igned in the presence of us as witnesses: W. Elmderson	er Board, accompany this application.	
Signed in the presence of us as witnesses: 1) W. Elmderson (Address of witness)		
igned in the presence of us as witnesses: 1) W. Elmderson (Address of witness)		
W. Elmderson , (Address of witness)		Dy me mility i i coe
1) W. Elmderson , (Address of witness)		
1) W. Elmderson , (Address of witness)	presence of us as witnesses:	······································
(Address of witness)	•	
	mderson ,	
(Name) (Address of witness)		(Address of witness)

Remarks: We have a permit to take water from the diversion dam of
Fawcett Creek \$6673 and are now applying for permit to construct a reservoir
to store water for beneficial use.
· · · · · · · · · · · · · · · · · · ·
STATE OF OREGON,
County of Marion,
This is to certify that I have examined the foregoing application, together with the accompanying
maps and data, and return the same for correction or completion as follows:
Completion
In order to retain its priority, this application must be returned to the State Engineer, with correc-
tions, on or before October 19, 1932 , 19
WITNESS my hand this 19th day of September , 19 32.
CHAS, E. STRICKLIN
EL State Engineer.
STATE OF OREGON,)
County of Marion, ss.
This is to certify that I have examined the foregoing application and do hereby grant the same, sub-
ject to the following limitations and conditions: The right herein granted is limited to the
construction of a reservoir for the storage of 200,000 gallons of water (2/3 acre-foot)
from Fawcett Creek, to be appropriated under Application No. 14810, Permit No. 10790.
The right hereunder shall be limited to the storage of 200000 gallons (2/3 acre feet.
The priority date of this permit isAugust 20, 1926.
Actual construction work shall begin on or beforeMarch 18, 1934
and shall thereafter be prosecuted with reasonable diligence and be completed on or before
Oct. 1, 1935 Extended to Oct. 1, 1936 WITNESS my hand this 18th day of March , 19 33.
CHAS. E. STRICKLIN
GRAS. E. STRICKLIN State Engineer.

Application No	11037
Reservoir Permit No	661

PERMIT

To construct a reservoir and store for beneficial use the unappropriated waters of the State of Oregon.

District No
This instrument was first received
in the office of the State Engineer at
Salem, Oregon, on the20 day
of, 19.26.,
at 8:30 o'clock A. M.
Returned to applicant for correction:
Corrected application received:
Approved:
March 18, 1933
Recorded in Book No3 of
Reservoirs, on Page 661
CHAS. E. STRICKLIN State Engineer.

Fees paid \$3.01