

* APPLICATION FOR PERMIT

CERTIFICATE NO. 15696

To appropriate the Public Waters of the State of Oregon

I, Glenn Hunter (Name of applicant) of Applegate Rural Route, Box 9 (Mailing address) State of Oregon, do hereby make application for a permit to appropriate the following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:

If the applicant is a corporation, give date and place of incorporation

1. The source of the proposed appropriation is Thompson Creek (Name of stream)

Big Applegate, a tributary of Rogue River

2. The amount of water which the applicant intends to apply to beneficial use is 0.04 cubic feet per second. (If water is to be used from more than one source, give quantity from each)

**3. The use to which the water is to be applied is logging pond, and fire protection (Irrigation, power, mining, manufacturing, domestic supplies, etc.)

4. The point of diversion is located 1160 ft. S. and 385 ft. W. from the SW corner of Section 28 (Section or subdivision)

Water pumped from ditch to pond at point 1186 feet West and 709 feet North from South quarter corner Section 28 applicant's ditch. (If preferable, give distance and bearing to section corner)

(If there is more than one point of diversion, each must be described. Use separate sheet if necessary)

being within the NE 1/4 NE 1/4 of Sec. 32, Tp. 38 S. (Give smallest legal subdivision) (N. or S.)

R. 14 W., W. M., in the county of Jackson

5. The pipe line to be 300 ft. total use in length, terminating in the SW 1/4 SW 1/4 of Sec. 28, Tp. 38 S. (Main ditch, canal or pipe line) (Miles or feet) (Smallest legal subdivision) (N. or S.)

R. 14 W., W. M., the proposed location being shown throughout on the accompanying map. (E. or W.)

DESCRIPTION OF WORKS

Diversion Works—

6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, timber crib, etc., wasteway over or around dam)

(b) Description of headgate (Timber, concrete, etc., number and size of openings)

(c) If water is to be pumped give general description 2" centrifugal (Size and type of pump)

20 H.P. Gas engine, 6 ft. total lift (Size and type of engine or motor to be used, total head water is to be lifted, etc.)

*A different form of application is provided where storage works are contemplated.

**Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the Hydroelectric Commission. Either of the above forms may be secured, without cost, together with instructions by addressing the State Engineer, Salem, Oregon.

Canal System or Pipe Line—

7. (a) Give dimensions at each point of canal where materially changed in size, stating miles from headgate. At headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet.

(b) At miles from headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet.

(c) Length of pipe, 300 ft.; size at intake, 2 in.; size at ft. from intake in.; size at place of use 2 in.; difference in elevation between intake and place of use, ft. Is grade uniform? Estimated capacity, sec. ft. 100 ft. 1 1/2" pipe used for fire sprinkler fire protection

8. Location of area to be irrigated, or place of use

Township	Range	Section	Forty-acre Tract	Number Acres To Be Irrigated
38 S.	4 W.	28	SW 1/4 SW 1/4	logging pond and fire protection
Jackson County Deed Records, Volume 256, Page 448, property belonging to Glenn and Grace R. Hunter as follows: The Southeast Quarter of the Southwest Quarter, excepting 10 acres, more or less, deeded to Warren D. Mee, and described in Volume 101 of Deeds, Page 565, records of Jackson County, Oregon), and the South Half of the Southwest Quarter of the Southwest Quarter of Section Twenty-eight; the South Half of the Southeast Quarter of the Southeast Quarter, and the South Half of the North Half of the Southeast Quarter of the Southeast Quarter of Section Twenty-nine; all in Township Thirty-eight South, Range Four West of the Willamette Meridian, and containing Eighty acres, more or less, together with all water rights, and rights in ditches, canals and laterals, and the rights of way therefor, appurtenant to said premises or used in connection therewith.				

(If more space required, attach separate sheet)

(a) Character of soil

(b) Kind of crops raised

Power or Mining Purposes—

9. (a) Total amount of power to be developed theoretical horsepower.

(b) Quantity of water to be used for power sec. ft.

(c) Total fall to be utilized feet.
(Head)

(d) The nature of the works by means of which the power is to be developed

(e) Such works to be located in of Sec.
(Legal Subdivision)

Tp., R., W. M.
(No. N. or S.) (No. E. or W.)

(f) Is water to be returned to any stream?
(Yes or No)

(g) If so, name stream and locate point of return

....., Sec., Tp., R., W. M.
(No. N. or S.) (No. E. or W.)

(h) The use to which power is to be applied is

(i) The nature of the mines to be served

Municipal or Domestic Supply—

10. (a) To supply the city of

..... County, having a present population of

(Name of)

and an estimated population of in 19.....

(b) If for domestic use state number of families to be supplied

(Answer questions 11, 12, 13, and 14 in all cases)

11. Estimated cost of proposed works, \$ 600.00

12. Construction work will begin on or before 1 yr. from date of priority

13. Construction work will be completed on or before 2 yrs. from date of priority

14. The water will be completely applied to the proposed use on or before 3 yrs. from date of priority

(Sgd) Glenn Hunter

(Signature of applicant)

Applegate Ore. Box 9
Rural Route

Remarks:

This logging pond is approximately 75 feet in diameter of circular form and was excavated by a dozer. The dirt was placed along the edges, forming a low broad dike which is not over 2 1/2 feet at any point and would average approximately 2 feet in height. The depth is sufficient to float logs and seems to be between 4 and 5 feet in most places.

STATE OF OREGON, }
County of Marion, } ss

This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for

In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before, 194.....

WITNESS my hand this day of, 194.....

STATE ENGINEER

Application No. 23165

Permit No. 18247

PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON

Division No. District No.

This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 4 day of May 1948 at 1:00 o'clock P. M.

Returned to applicant:

Corrected application received:

Approved:

July 30, 1948

Recorded in book No. 45 of Permits on page 18247

CHAS. E. STRICKLIN STATE ENGINEER

Drainage Basin No. 15 Page 16 D

Fees Paid \$20.00

PERMIT

STATE OF OREGON, } ss County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use and shall not exceed 0.04 cubic feet per second measured at the point of diversion from the stream, or its equivalent in case of rotation with other water users, from Thompson Creek

The use to which this water is to be applied is log pond and fire protection

If for irrigation, this appropriation shall be limited to - - - of one cubic foot per second

and shall be subject to such reasonable rotation system as may be ordered by the proper state officer.

The priority date of this permit is May 4, 1948

Actual construction work shall begin on or before July 30, 1949 and shall thereafter be prosecuted with reasonable diligence and be completed on or before

October 1, 1950

Complete application of the water to the proposed use shall be made on or before

October 1, 1951

WITNESS my hand this 30th day of July, 1948

CHAS. E. STRICKLIN STATE ENGINEER