fit in the property of the second of the

To Appropriate the Public Waters of the State of Oregon 10 10 mm 12 m 10 20 mm 中国的最高的

(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the South half of the South half of Soc. A, Tp. 145 (Citre smallest legal subdivision) R. 9 W, W. M., in the country of Locality 5. The (Main ditch, canal or pipe line) to be (Milles or feet) in length, terminating in the (Main ditch, canal or pipe line) of Sec. Tp. (N or 8) R. W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete massing) (b) Description of headgate (c) If water is to be pumped give general description 450 G.P.M. (Sine and type of pump)	, 	Tall and Wife The professor has bond and Nife
following described public vestions of the State of Oregon, SUBJECT TO EXISTING RIGHTS: If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is	of	
following described public vestions of the State of Oregon, SUBJECT TO EXISTING RIGHTS: If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is	State of	O rispan, do hereby make application for a permit to appropriate the
1. The source of the proposed appropriation is a tributary of 2. The amount of water which the applicant intends to apply to beneficial use is \$\textit{Office}\$. 2. The amount of water which the applicant intends to apply to beneficial use is \$\textit{Office}\$. 2. The amount of water which the applicant intends to apply to beneficial use is \$\textit{Office}\$. 2. The use to which the water is to be applied is \$\textit{Office}\$. 4. The point of diversion is located \$\textit{SYP}\$, \$\textit{IT}\$, \$\textit{A}\$ and \$\textit{LSP}\$, \$\textit{IT}\$ from the \$\textit{LY}\$ corner of \$\textit{SECA}\$. \$\textit{LY}\$, \$\te	following	
1. The source of the proposed appropriation is	If	
	1.	The source of the proposed appropriation is #1509 Triver
2. The amount of water which the applicant intends to apply to beneficial use is \$\textit{DLC}\$. cubic feet per second. (at water is to be and form more than one source, give quantity from each) ***3. The use to which the water is to be applied is \[\textit{ITIGATESTA}		
Cit waster to the sand from more than an source, give quality from such) **3. The use to which the water is to be applied is **Creation, server, mining, manufacturing, domestic napplies, etc.) 4. The point of diversion is located 340 ft. M. and 30 ft. W. from the 14 corner of 580 ft. A 4 9. In the 54 ft. Sally G. Sally	2.	
4. The point of diversion is located 240 ft. M. and 130 ft. W. from the 14 corner of Sections 449 in the Section of subdivision of Section of S	• .	Of water to to be used from more than one source, give quantity from each)
(If preferable, five distance and bearing to section corner) (If there is more than one point of diversion, each must be described. The separate sheet if necessary) being within the South (Italy attac South realf of Sec. A., Tp. 145 (It metallack legal subdivision) R. 9 W. M., in the country of Indianal or pipe line) 5. The (Main dich. canal or pipe line) in length, terminating in the (Main dich. canal or pipe line) (It or W.) W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose reck, concrete manure) rock and brush, timber crib, etc. westeway over or around dam) (b) Description of headgate (Timber, concrete etc., number and size of openings) (C) If water is to be pumped give general description (Siss and type of pump)	••3.	The use to which the water is to be applied is
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the South half of the South half of Soc. A, Tp. 145 (Citre smallest legal subdivision) R. 9 W, W. M., in the country of Locality 5. The (Main ditch, canal or pipe line) to be (Milles or feet) in length, terminating in the (Main ditch, canal or pipe line) of Sec. Tp. (N or 8) R. W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete massing) (b) Description of headgate (c) If water is to be pumped give general description 450 G.P.M. (Sine and type of pump)	4.	The point of diversion is located 340 ft. N and 130 ft. W from the 14
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the South Half of the South Half of Sec. A., Tp. 145 (Cive metallely legal subdivision) of Sec. A., Tp. 145 R. 9 W., W. M., in the county of Lately 5. The (Main ditch, canal or pipe line) to be (Miles or feet) in length, terminating in the (Smallest legal subdivision) of Sec. , Tp. R. W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete manners) rock and brush, timber crib. etc. westeway over or around dam) (b) Description of headgate (Timber, concrete etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	corner o	Sections 449. In the SELL Q SW/4 Sec 4. T. 145 TEG WWW.
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the South Half of the South Half of Sec. A., Tp. 145 (Cive metallely legal subdivision) of Sec. A., Tp. 145 R. 9 W., W. M., in the county of Lately 5. The (Main ditch, canal or pipe line) to be (Miles or feet) in length, terminating in the (Smallest legal subdivision) of Sec. , Tp. R. W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete manners) rock and brush, timber crib. etc. westeway over or around dam) (b) Description of headgate (Timber, concrete etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	***************************************	
being within the South Hall of the South Half of Sec. 7, Tp. 145 (Give smallest legal subdivision) of Sec. 7, Tp. 145 R. 9 W. M., in the county of	**	(If preferable, give distance and bearing to section corner)
5. The (Main ditch. canal or pipe line) to be (Miles or feet) in length, terminating in the (Smallest legal subdivision) of Sec. , Tp. (N or S) R. W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete manoning to the construction of headgate (Timber, concrete etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)		thin the South Half of the South naif of Sec. 4, Tp. 145 (Give smallest legal subdivision)
in length, terminating in the	R. 9.11	, W. M., in the county of
R	5.	Theto be
R	in length	t, terminating in the
6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete manuary rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)		
6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete masonry rock and brush, timber crib, etc. wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)		DESCRIPTION OF WORKS
feet; material to be used and character of construction (Loose rock, concrete masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate		
(b) Description of headgate	6.	•
(b) Description of headgate		feet; material to be used and character of construction (Loose rock, concrete masonry)
(c) If water is to be pumped give general description (Sue and type of pump)	rock and bru	
(c) If water is to be pumped give general description (Size and type of pump)	(b	;
15 40 Floor Motor	, (c) If water is to be pumped give general description 450 G.P.M.

^{*}A different form of application is provided where storage works are contemplated.

^{*}Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the Hydroelectric Commission. Either of the above forms may be secured, without cost, together with instructions by addressing the State Engineer. Salem Oregon. 3-52--4M

	gate: width on	top (at wate	r Nac)	jest; wath on bott
************	feet; depth of w	pater	feet; grede	feet fall per
and feet			hoodgate: width on top (at water	
•				
		•	foet; depth of we	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	feet fal			-
			; size at intake, 4"	
intake		; size at place	of use	erence in elevation betw
ce and place	of use,	pt.	Is grade uniform?	Estimated capac
	sec. ft.			
8. Location	n of area to be	irrigated, or	place of use	
Township North or South	Range S. er V. ef	Gootlen	Forty-acre Tract	Number Acres To Be Irrigated
14.5	9 w	4	54,461/2	40
			Lot 3 (SE SW)	19.0
			Lat 2 (3W SE)	14.9
			Lot 1 (SE SE)	2.7
				1 / 2 /
			1	
			. 17	
		<u> </u>	,	
			pace required, attach separate sheet)	
			dy Loam	
	-	sed Fall	rage 4 Permanent Past	ure and smys barden
	g Purposes—		developed	theoretical horsen
			or powerse	ec. ft.
(c) T	otal fall to be u	tilized	(Head)	
(d) T	he nature of the	e works by m	eans of which the power is to be	developed
				<u></u>
(e) S	uch works to be	e located in	(Legal subdivision)	of Sec
	, R			
			y stream?(Yes or No)	
(a) I	f so, name stree	am and locate	e point of return	
(9) 1			•	

STATE OF OREGON,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and canditions:

The i	light havels grants	GHTS and the following of is limited to the ame Cubic feet per use of rotation with other	unt of water which second measured a	can be applied to	ersion from the
*************		pater is to be applied is	gring = 0 = 0.00000 dagring - 0.00000 dagring = 0.00000 dagring = 0.00000 dagring = 0.00000 dagring = 0.0000000000000000000000000000000000	ba a a a a a a a a a a a a a a a a a a	
second or i	ts equivalent for e	opropriation shall be lin	shall be further	r_limited_to_a	diversion.of
		est per acre for a			TITIESTION
		reasonable rotation syst			state officer.
Act	ual construction w	nis permit isoork shall begin on or b th reasonable diligence	and be completed o	n or before Octobe	er 1, 19 5 5
	nplete application TNESS my hand th	of the water to the prop his 21st day o	oosed use shall be m		October 1, 19 56.
Application No. 28151. Permit No. 22143	PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON	This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 23rd day of Echwary. 1953, at 1:00 o'clock M.	Returned to applicant: Approved:	Recorded in book No. 56 of Permits on page 22143	CHAS. E. STRICKLIN STATE ENGINEER

State Printing #