

APPLICATION FOR PERMIT

To appropriate the Public Waters of the State of Oregon

I, Everett M. Crauch

of Tide water Yamhill Co. Oregon

State of Oregon, do hereby make application for a permit to appropriate the following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:

If the applicant is a corporation, give date and place of incorporation

1. The source of the proposed appropriation is Unnamed Spring, a tributary of Alsea River

2. The amount of water which the applicant intends to apply to beneficial use is X cubic feet per second. approx 1.6 gal per minute

3. The use to which the water is to be applied is Domestic

4. The point of diversion is located            ft.            and            ft. from the corner of            being within the N.W. 1/4 of the N.W. 1/4 of Sec. 33, Tp. 13 S R. R. 10 W, W. M., in the county of Lincoln            being S 74° 30' W - a distance of 936' from General Land Office Brass disc. which is a witness corner to the Meander corner, said disc being S 89° 55' E 1204.75' from N.W. corner of Sec 33 - T. 13 S - R. 10 W

5. The Pipe line to be 800' in length, terminating in the lots of Sec. 33, Tp. 13 S R. 10 W, W. M., the proposed location being shown throughout on the accompanying map.

DESCRIPTION OF WORKS

Diversion Works—

6. (a) Height of dam NONE feet, length on top            feet, length at bottom            feet; material to be used and character of construction           

(b) Description of headgate NONE

(c) If water is to be pumped give general description           

\*A different form of application is provided where storage works are contemplated. \*\*Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the Hydroelectric Commission. Either of the above forms may be secured, without cost, together with instructions by addressing the State Engineer, Salem, Oregon. 1-53-4M

28162

Canal System or Pipe Line

7. (a) Give dimensions at each point of canal where materially changed in size, stating miles from headgate. At headgate: width on top (at water line) ... feet; width on bottom ... feet; depth of water ... feet; grade ... feet fall per one thousand feet.

(b) At ... miles from headgate: width on top (at water line) ... feet; width on bottom ... feet; depth of water ... feet; grade ... feet fall per one thousand feet.

(c) Length of pipe, ... 800 ... ft.; size at intake, ... 1 1/2" ... in.; size at ... 150' ... ft. from intake ... 1" ... in.; size at place of use ... 3/4" ... in.; difference in elevation between intake and place of use, ... 50 ... ft. Is grade uniform? ... No ... Estimated capacity, ... 1 ... sec. ft.

8. Location of area to be irrigated, or place of use No Irrigation.

Table with 5 columns: Township North or South, Range E. or W. of Wisconsin Meridian, Section, Forty-acre Tract, Number Acres To Be Irrigated. Handwritten entries: 13-S, 10 W NH, 33, NW 1/4 of NW 1/4, Domestic.

(If more space required, attach separate sheet)

(a) Character of soil

(b) Kind of crops raised

Power or Mining Purposes

9. (a) Total amount of power to be developed ... theoretical horsepower.

(b) Quantity of water to be used for power ... sec. ft.

(c) Total fall to be utilized ... feet. (Head)

(d) The nature of the works by means of which the power is to be developed

(e) Such works to be located in ... of Sec. (Legal subdivision)

Tp. ... R. ... W. M. (No. N. or S.) (No. E. or W.)

(f) Is water to be returned to any stream? (Yes or No)

(g) If so, name stream and locate point of return

Sec. ... Tp. ... R. ... W. M. (No. N. or S.) (No. E. or W.)

(h) The use to which power is to be applied is

(i) The nature of the mines to be served

*Don Courcier and Catherine Courcier M & W.*

Beginning at a 5/8" iron rod set 454.75 feet South and 125.12 feet West of a General Land Office Disk set as a witness corner to the meander corner, and being South 89 d.-58' East 1204.75 feet from the northwest corner of Sec. 33, T 13 S, R 10 WWM, thence South 7 d.-42' West 240.24 feet; thence South 84 d.-48' East 100 feet more or less to the mean high water line of the Alsea River; thence North 7 d.-42' East along said mean high water line 240.42 feet more or less to a point that is South 84 d.-48' West 100 feet more or less, to the point of beginning. Bearings established from relocated Alsea Highway.

*Howard Herlin and Elizabeth Herlin M & W*

Beginning at a 5/8" iron rod set 692.82 feet South and 157.28 feet West of a General Land Office Disk set as a witness corner to the meander corner and being South 89 d.-58' East 1204.75 feet from the NW corner of Sec. 33, T 13 S, R 10 WWM; thence South 7 d.-42' West 80.08 feet; thence South 84 d.-48' East 100 feet more or less to the mean high water line of the Alsea River; thence North 7 d.-42' East along said meander high water line 80.08 feet more or less to a point that is South 84 d.-48' East from the point of beginning; thence North 84 d.-48' West 100 feet more or less to the point of beginning. Bearings established from the relocated Alsea Highway.

*Everett W. Couch*

Parcel 1: Beginning at the Southwest corner of the Herlin tract described in deed recorded as instrument No. B-10072, Deed Records of Lincoln County, Oregon, said point being a 5/8" iron rod set 772.18 feet South and 168.0 feet West of a General Land Office Disk set as a witness corner to the meander corner and being South 89 d.-58' East 1204.75 feet from the NW corner of Sec. 33, T 13 S, R 10 WWM; thence South 14 d.-42' West 40.56 feet; thence South 84 d.-48' East 100 feet more or less to the mean high water line of the Alsea River; thence North 14 d.-42' East along said high water line 40.56 feet more or less to a point that is South 84 d.-48' East from the point of beginning; thence North 84 d.-48' West 100 feet more or less to the point of beginning. Bearings established from the relocated Alsea Highway.

Parcel 2: Beginning at a 5/8" iron rod set 811.41 feet South and 178.29 feet West of a General Land Office Disk set as a witness corner to the meander corner and being South 89 d.-58' East 1204.75 feet from the NW corner of Sec. 33, T 13 S, Range 10 WWM; thence South 14 d.-42' West 40.56 feet thence South 84 d.-48' East 100 feet more or less to the mean high water line of the Alsea River; thence North 14 d.-42' East along said high water line 40.56 feet more or less to a point that is South 84 d.-48' East from a point of beginning; thence North 84 d.-48' West 100 feet more or less to the point of beginning. Bearings established from the relocated Alsea Highway.

Parcel 3: Beginning at a 5/8" iron rod set 850.64 feet South and 181.58 feet West of a General Land Office Disk set as a witness corner to the meander corner and being South 89 d.-58' East 1204.75 feet from the NW corner of Sec. 33, T 13 S, R 10 WWM; thence South 14 d.-42' West 40.56 feet; thence South 84 d.-48' East 100 feet more or less to the mean high water line of the Alsea River; thence North 14 d.-42' East along said high water line 40.56 feet more or less to a point that is South 84 d.-48' East from the point of beginning; thence North 84 d.-48' West 100 feet more or less to the point of beginning. Bearings established from the relocated Alsea Highway.

Parcel 4: Beginning at a 5/8" iron rod set 889.87 feet South and 194.87 feet West of a General Land Office Disk set as a witness corner to the meander corner and being 89 d.-58' East 1204.75 feet from the NW corner of Sec. 33, T 13 S, R 10 WWM; thence South 14 d.-42' West 40.56 feet to the NW corner of the Harwood tract, described in deed recorded as instrument No. B-9832 Deed Records of Lincoln County, Oregon; thence South 84 d.-48' East 100 feet more or less to the mean high water line of the Alsea River; thence North 14 d.-42' East along said high water line 40.56 feet more or less to a point that is South 84 d.-48' East from the point of beginning; thence North 84 d.-48' West 100 feet more or less to the point of beginning; ~~thence North~~ Bearings established from the relocated Alsea Highway.

That part of U.S. Lot 8, Sec. 33, T 13 S, R 10 WWM in Lincoln County, Oregon described as follows:

Beginning at a 5/8" iron rod set 929.10 feet South and 209.16 feet West of a General Land Office Disk set as a witness corner to the meander corner and being South 89 d.-58' East 1204.75 feet from the NW corner of Sec. 33, T 13 S, R 10 WWM; thence South 14 d.-42' West 50.7 feet thence South 84 d.-48' East 100 feet more or less to the mean high water line of the Alsea River; thence North 14 d.-42' East along said high water line 50.7 feet more or less to a point that is South 84 d.-48' East from the point of beginning; thence North 84 d.-48' West 100 feet more or less to the point of beginning.

Municipal or Domestic Supply

2. (a) To supply the city of \_\_\_\_\_

County, having a present population of \_\_\_\_\_

and an estimated population of \_\_\_\_\_ in 19\_\_\_\_

(b) If for domestic use state number of families to be supplied 48

11. Estimated cost of proposed works, \$ 1000.00

12. Construction work will begin on or before Oct 1 1953

13. Construction work will be completed on or before Oct 1 1954

14. The water will be completely applied to the proposed use on or before Oct 1 1954

Ernest W. Brouch

(Signature of applicant)

by Lloyd H. Brouch Attorney

Remarks: It is proposed to catch the water direct from the spring, diverting it to a settling barrel or tank, and thence to a small supply tank, probably 500 or 750 gal capacity.

STATE OF OREGON, }  
County of Marion, } ss.

This is to certify that I have examined the foregoing application, together with the accompanying maps and data, and return the same for completion

In order to retain its priority, this application must be returned to the State Engineer, with corrections on or before April 27, 1953.

WITNESS my hand this 25th day of March, 1953.

RECEIVED

STATE ENGINEER  
SALEM, OREGON

CHAS. E. STRICKLIN  
STATE ENGINEER

By Chris L. Wheeler  
Chris L. Wheeler, Assistant

PERMIT

STATE OF OREGON,

County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use and shall not exceed 0.925 cubic feet per second measured at the point of diversion from the stream, or its equivalent in case of rotation with other water users, from an unnamed spring

The use to which this water is to be applied is domestic

If for irrigation, this appropriation shall be limited to - - - of one cubic foot per second or its equivalent for each acre irrigated

and shall be subject to such reasonable rotation system as may be ordered by the proper state officer.

The priority date of this permit is March 2, 1953

Actual construction work shall begin on or before August 21, 1954 and shall thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 1955

Complete application of the water to the proposed use shall be made on or before October 1, 1956

WITNESS my hand this 21st day of August 1953

Chas. E. Stricklin

STATE ENGINEER

Application No. 28161

Permit No. 22162

PERMIT

TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON

This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 2nd day of March 1953, at 8:00 o'clock A. M.

Returned to applicant:

March 25, 1953

Approved:

August 21, 1953

Recorded in book No. 56 of

22162

Permits on page

CHAS. E. STRICKLIN

STATE ENGINEER