

Permit No. 22418

*APPLICATION FOR PERMIT

To Appropriate the Public Waters of the State of Oregon

I, Lorenzo Veryle Mumpower
(Name of applicant)
 of Rt 1 Clackamas, Oregon
(Mailing address)

State of Oregon, do hereby make application for a permit to appropriate the following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:

If the applicant is a corporation, give date and place of incorporation

1. The source of the proposed appropriation is Clackamas River

(Name of stream)

a tributary of Willamette River

2. The amount of water which the applicant intends to apply to beneficial use is ~~250~~ .338 cubic feet per second. (150 gal Minim)

(If water is to be used from more than one source, give quantity from each)

**3. The use to which the water is to be applied is Irrigation of grass and fruit trees

(Irrigation, power, mining, manufacturing, domestic supplies etc.)

4. The point of diversion is located ft. N or S and ft. E or W from the corner of

SW 1/4, SW 1/4, Twp. 12, Range 10, Clackamas Co., Oregon

Specify distance and bearing to nearest corner

Specify distance and bearing to nearest corner being within the boundaries of the proposed diversion

R. 12 Twp. 12 Range 10 Clackamas Co., Oregon

SW 1/4, SW 1/4, Twp. 12, Range 10, Clackamas Co., Oregon

in length ft. and ft. in width ft. and ft. Twp. 12 Range 10 Clackamas Co., Oregon

R. 12 Twp. 12 Range 10 Clackamas Co., Oregon

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

ft. N or S and ft. E or W

Specify distance and bearing to nearest corner

22448

Canal System or Pipe Line—

7. (a) Give dimensions at each point of canal where materially changed in size, stating miles from headgate. At headgate: width on top (at water line) feet; width on bottom feet; depth of water feet; grade feet fall per one thousand feet.

- (b) At miles from headgate: width on top (at water line)
..... feet; width on bottom feet; depth of water feet;
grade feet fall per one thousand feet.

- (c) Length of pipe, 2630 ft.; size at intake, $2\frac{1}{2}$ in.; size at uniform $2\frac{1}{2}$ in.; difference in elevation between intake and place of use, 15 ft. Is grade uniform? generally Estimated capacity, sec. ft.

- 8. Location of area to be irrigated, or place of use**

(If more space required, attach separate sheet)

- (a) Character of soil Sandy Loam

- (b) Kind of crops raised Grazing and cultivation; 100

Power or Mining Purposes--

9. (a) Total amount of power to be developed

- (b) Quantity of water to be used for paper

- (c) Total fall to be unseeded

- (d) The nature of the works as means of transmission.

- (e) Such works to be located on

Tp. , R. , W. M.
(No N or S) , No E or W

- (f) Is water to be returned to any stream?

- (g) If so, name stream and locate point of entry.

. 500.

1

三

- (h) The use to which power is to be applied.

- (i) The nature of the mines to be carried

Municipal or Domestic Supply—

ה'ג

10. (a) To supply the city of
..... County, having a present population of
(Name of) and an estimated population of in 19.....

(b) If for domestic use state number of families to be supplied

(Answer questions 11, 12, 13, and 14 in all cases.)

11. Estimated cost of proposed works, \$ 1380.00
 12. Construction work will begin on or before June 10, 1953
 13. Construction work will be completed on or before July 15, 1953
 14. The water will be completely applied to the proposed use on or before July 15, 1953

Remarks.

Part of the dust of "Lingering", U.S. - fragment of the

as follows:
First, I. S. R. R. E.
Then, thence easterly
along the easterly line of
Section 10, December 10,
1924, Clackamas
County, Oregon;
then easterly boundaries
of the corner of that
section, December 1, 1924 in back
of the first, thence east along the
easterly boundary line of the
tract in the Clackamas
County road
thereon, by lease/
or; thence south
to the Turnbow tract;
then west of that tract of
land, by lease
or; thence; thence
west to the
conveyed to Stephen
Turnbow; running thence
west a distance
of and conveyed
to him at page 386 said
tract to the
northeast corner of said
tract, including
thereby all land within

water and pipe **11**
etc. manpower, by deed

with the accompanying

Engineer, with correc-

PERMIT

STATE OF OREGON, **ss.**
County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same,
SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use
and shall not exceed ... 0.275 cubic feet per second measured at the point of diversion from the
stream, or its equivalent in case of rotation with other water users, from Clackamas River

The use to which this water is to be applied is irrigation

If for irrigation, this appropriation shall be limited to ... 1/80 of one cubic foot per
second or its equivalent for each acre irrigated and shall be further limited to a diversion of
not to exceed 2½ acre feet per acre for each acre irrigated during the irrigation
season of each year,

and shall be subject to such reasonable regulation as may be ordered by the State Engineer.

The priority date of this permit is April 1, 1952

Actual construction work shall begin on or before May 1, 1952
thereafter be prosecuted with reasonable diligence until completion.

Complete application of the water to the proposed uses.

WITNESS my hand this 1st day of April, 1952.

PERMIT

TO APPROPRIATE THE PUBLIC
WATERS OF THE STATE
OF OREGON

This instrument was first received in the
office of the State Engineer at Salem, Oregon
on the 1st day of April, 1952.

John C. Johnson
State Engineer

Application No. 28221

Permit No. 22447