

STATE ENGINEER SALEM, OREGON TO Appropriate the Public Waters of the State of Oregon

I, Annie Emma Pilkington and Mary Agnes Pilkington.					
ofHighway 20, Corvallis, B	enton County.				
State of Oregon , d	o hereby make application for a permit to appropriate the				
following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:					
If the applicant is a corporation, give date and place of incorporation					
1. The source of the proposed appropriati	on is Asbehr Lake (Name of stream)				
	(Name of stream) tributary of				
• •	is a second of the second of t				
	ant intends to apply to beneficial use is 1/60				
cubic feet per second. Per acre	o be used from more than one source, give quantity from each)				
**3. The use to which the water is to be app	plied isIrrigation of nursery (Brigation, power, mining, manufacturing, domestic supplies, etc.)				
	(arrigation, power, mining, manufacturing, dognestic supplies, etc.)				
4. The point of diversion is located	ftandftfrom the				
corner of portable pump within	n the southwest quarter of the northwest				
	(Mection or subdivision) quarter of the northeast quarter and the				
•	erter of Section 19, Twp. 11 S., h. 4 W.,				
•					
(If preferable, give di	pump travel being 30.163 chains North and				
48.297 East of the southwest corner of	the Jehiel S. Kendall DLC No. 48, T 11 S,, R 4				
	of Sec, Tp,				
R, W. M., in the county of Ber					
•					
	to be 1800 feet (Miles or feet)				
in length, terminating in the	of Sec. 19, Tp. 11 5, (N. or S.)				
R, W. M., the preposed locatio	ncbeing shown throughout on the accompanying map.				
Diversion Works—	PTION OF WORKS				
6. (a) Height of dam f	feet, length on top feet, length at bottom				
feet; material to be used and cl	haracter of construction				
feet; material to be used and cl	haracter of construction (Loose rock, concrete, masonry)				
rock and brush, timber crib, etc., wasteway over or around dam)	(Loose rock, concrete, masonry,				
rock and brush, timber crib, etc., wasteway over or around dam)	(Loose rock, concrete, masonry,				
rock and brush, timber crib, etc., wasteway over or around dam)	(Loose rock, concrete, masonry, (Timber, concrete, etc., number and size of openings)				
rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate	(Loose rock, concrete, majority,				
(c) If water is to be pumped give general	(Timber, concrete, etc., number and size of openings) I description 3" Gardner Denverting PA,				

igate. At hea	dgate: width on to	op (at water	r line)	feet; width on botto
	feet; depth of wa	ter	feet; grade	jeet fall per o
sand feet. (b) At		niles from I	readgate: width on top (at wo	ster line)
	feet; width on bo	ttom	feet; depth o	f water fee
	feet fall			
			.; size at intake,6	in ; size at 1800
_				difference in elevation betwe
	•			Estimated capaci
		је.	is grade unijorm:	Bstinuteu cupuc
0 gpm 8. Location	sec. ft. on of area to be ir	rigated, or	place of use	
Township	Range E. er W. ef	Section	Forty-acre Tract	Number Acres To Be Irrigated
North or South	Willemotte Meridian			6.6
<u> 11 S.</u>	4 ₩•	19	SE4 of NE2	
			NEa of Ska	5.0
			Nwa of SEa	0.4
		20	SWa of NWa	1.4
•				•
•				
				`
······································		(If more #	pace required, attach separate sheet)	
` *	•			
		d Nurs	sery stock, holly or	chard
	ng Purposes—	orner to he	deneloned	theoretical horsepo
			or power	
` '	• • •	•	•	•
			(Head)	
(d)	The nature of the	_		o be developed
(e)	Such works to be	located in	(Legal subdivision)	of Sec
p(No. N.	or 5.) R. (No.	, T	W. M.	
(f)	Is water to be ret	urned to an	y stream?(Yes or No)	
	If so name stress	n and locate	e point of return	
(g)	1) so, nume streut		•	

The use to which this water is to be applied is	•
The use to which this water is to be applied is 1rrigat	
If for irrigation, this appropriation shall be limited to	1/80 of one cubic foot per
second or its equivalent for each acre irrigated and shall be	
of not to exceed 2 acre feet per acre for each acr	e irrigated during the irrigation
season of each year,	
and shall be subject to such reasonable rotation system as may be	
The priority date of this permit is	pril 8,1958
Actual construction work shall begin on or beforeM	ay 26, 1959 and shall
thereafter be prosecuted with reasonable diligence and be compl	eted on or before October 1, 19 60
Complete application of the water to the proposed use shall	be made on or before October 1, 19 61.
WITNESS my hand this26th day of	in the second se
· ·	Klima ! Maniey

PERMIT

This instrument was first received in the TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON

office of the State Engineer at Salem, Oregon, on the Life day of Africal 19.5 %, at . Z . C . O'clock . A ... M.

Returned to applicant:

Approved:

May 26, 1958

Recorded in book No. 68.

Permits on page 25437

STATE ENGINEER LEWIS A. STANLEY

page 76A18 Drainage Basin No.

Fees 15 00

State Printing 16137