'APPLICATION FOR PERMIT

To Appropriate the Public Waters of the State of Oregon

2. The amount of water which the applicant intends to apply to beneficial use is		(Hanne of applicant) Result a. 2. Boy 7h. Toolsoon and 3.3.
Comparison of the state of Oregon, SUBJECT TO EXISTING RIGHTS: If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is . Storage. In . Squam Lake Reservoir,	, i	· · · · · · · · · · · · · · · · · · ·
If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is Storage in Squar Lake Reservoir, Demand of water which the applicant intends to apply to beneficial use is 0.13 c.f.s. 2. The amount of water which the applicant intends to apply to beneficial use is 0.13 c.f.s. bic feet per second. (If water is to be applied is 1.1 r.f. gattlen memories, give quantity from each) **3. The use to which the water is to be applied is 1.1 r.f. gattlen memories, departs supplies, etc.) 4. The point of diversion is located 790 ft. N. and 1840 ft. E. from the N. (R. or N.) (If water is more than one point of diversion, each must be described. Use separate sheet if necessary) sing within the SEA NNA (R. or N.) (If water is more than one point of diversion) 5. The main distance and replace is a supplication of Sec. 5 7. in 1.2 Sec. (R. or N.) 5. The main distance and replace is a supplication of Sec. 5 7. in 1.2 Sec. (R. or N.) 4. W. M., in the country of Jackson of Sec. 5 7. in 1.2 Sec. (Sec. N.) 4. W. W. M. the proposed location being shown throughout on the accompanying map. C. or N.) DESCRIPTION OF WORKS 6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom in feet; material to be used and character of construction Erush, loose rock concrete managers of loose. (C.) If water is to be pumped give general description grayity 2. Storm (the each tope of pumps)	ste of	Oragon, do hereby make application for a permit to appropriate the
1. The source of the proposed appropriation is Storage in Squar Lake Reservoir, a. trib. of Squar Creek	llowing descri	bed public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:
1. The source of the proposed appropriation is Storage in Squar Lake Reservoir, a. trib. of Squar Creek	If the app	licant is a corporation, give date and place of incorporation
a tributory of Big Applegate River 2. The amount of water which the applicant intends to apply to beneficial use is 0.13. c.f.s. abic feet per second. (If water is no to water is to be applied is 1rrigation. **3. The use to which the water is to be applied is 1rrigation. (Irrestion. power mining. manufacturing. domestic supplies, etc.) 4. The point of diversion is located 790. ft. Ns. and 1840 ft. Es. from the 14. (E. or W.) (If there is more than one point of diversion. such must be described. Use suparsts sheet if necessary) (If there is more than one point of diversion. such must be described. Use suparsts sheet if necessary) (If there is more than one point of diversion. such must be described. Use suparsts sheet if necessary) (If there is more than one point of diversion. such must be described. Use suparsts sheet if necessary) (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If the is more than one point of diversion. (If there is more than one point of diversion. (If there is more than one point of diversion. (If the is the i		
a. trib. of Squaw Creek	· · · · · · · · · · · · · · · · · · ·	
2. The amount of water which the applicant intends to apply to beneficial use is	1. The so	urce of the proposed appropriation is Storagein Squaw Inka Reservoir
this feet per second. (If water is to be used from more than one source, give quantity from each) **3. The use to which the water is to be applied is (If registion, power, mining, manufacturing, domestic supplies, etc) 4. The point of diversion is located 790. ft. No. and 1840 ft. E. from the Ni. (E. or W.) (If preferable, give distance and besting to section corner) (If there is more than one point of diversion, each must be described. Use separate thest if necessary) sing within the SE2 NW of the country of Jackson (It over an in the country of Jackson 5. The Main ditch (Main ditch, canal or pipe line) slength, terminating in the SE2 SW1 (Mines or feet) Limit of Sec. 36. T. No. or S.) W. M. The proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS five sign within the proposed of character of construction Erush, loose rock, character making and dirt thrown across stream bed. chand character of construction Erush, loose rock, concrete making and dirt thrown across stream bed. chand broak inner civ. etc. waterway over or around dam) (b) Description of headgate 2.5 feet in height and type of pump)	trib. of	Squaw Creek , a tributary of Big Applegate River
**3. The use to which the water is to be applied is 1rrigation, power, mining, manufacturing, domestic supplies, etc.) 4. The point of diversion is located 790 ft. Na. and 1840 ft. E. from the N. (R. or W.) **The point of diversion is located 790 ft. Na. and 1840 ft. E. from the N. (R. or W.) **The point of diversion is located 790 ft. Na. and 1840 ft. E. from the N. (R. or W.) **The point of diversion is located 790 ft. Na. and 1840 ft. E. from the N. (R. or W.) **The point of diversion is located 790 ft. Na. and 1840 ft. E. from the N. (R. or W.) **The point of diversion is located 790 ft. Na. and 1840 ft. Section or subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section or subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section or subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section or subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section or subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section or subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section or subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section of 1840 ft. Section of subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section of 1840 ft. Section of 1840 ft. Section of subdivision) **The point of diversion is located 790 ft. Na. and 1840 ft. Section of	2. The an	nount of water which the applicant intends to apply to beneficial use is0.13c.f.s.
**3. The use to which the water is to be applied is 1rrigation, power, mining, manufacturing, domestic supplies, etc.) 4. The point of diversion is located 790 ft. Na. and 1840 ft. E. from the Na. (R. or W.) **Inner of Section 6. (Bection or subdivision) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) sing within the SEA NWA Of Sec. 6 T. 11 Sa. (Give small at legal subdivision) 5. The main dick. (R. or W.) 5. The main dick. (Can or M.) 6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at botton 1. feet; material to be used and character of construction 1. Suck main dick. (Can or W.) 6. (a) Height of dam 1.5 feet, length on top 2.0 (Can or W.) Character of construction 1. Suck main dick. (Conserved. (Loose rock. (Conserved. (Can or W.) (Can o	hic feet ner se	oond
4. The point of diversion is located 790 ft. No. and 1840 ft. Es from the Ni. (Nor. 1) (Nor.	ioto jees per de	(If water is to be used from more than one source, give quantity from each)
(If preferable, give distance and besting to section correct) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the SEANNA of Sec. 6 (Nors) (Cive small set legal subdivision) 5. The main ditch to be approximately a mile (Rice w.) 5. The main ditch to be approximately a mile (Rice w.) 5. The main ditch spal subdivision) 6. Length, terminating in the SEANNA of Sec. 36 (Nors) 1. L. W. W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS DESCRIPTION OF WORKS 10. Jeet; material to be used and character of construction Brush, loose rock, concrete masons and dirt thrown across stream bed. ck and brush, timber crib. etc., "masterny over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (c) If water is to be pumped give general description gravity system.	**3. The us	e to which the water is to be applied is
(If preferable, give distance and besting to section correct) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the SEANNA of Sec. 6 (Nors) (Cive small set legal subdivision) 5. The main ditch to be approximately a mile (Rice w.) 5. The main ditch to be approximately a mile (Rice w.) 5. The main ditch spal subdivision) 6. Length, terminating in the SEANNA of Sec. 36 (Nors) 1. L. W. W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS DESCRIPTION OF WORKS 10. Jeet; material to be used and character of construction Brush, loose rock, concrete masons and dirt thrown across stream bed. ck and brush, timber crib. etc., "masterny over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (c) If water is to be pumped give general description gravity system.	***************************************	•
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the SEANNA of Sec. 6 (Nors) (Recew), W. M., in the country of Mackson (Recew), W. M., in the country of Mackson tength, terminating in the SEANNA of Sec. 36. The Main ditch. canal or pipe line) tength, terminating in the SEANNA of Sec. 36. The Main ditch. canal or pipe line) tength, terminating in the SEANNA of Sec. 36. The Main ditch. Canal or pipe line) tength, terminating in the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS diversion Works— 6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom 10 feet; material to be used and character of construction Brush, loose rock, concrete masons, and dirt thrown across stream bed. ch and brush, limber crib, etc., wastermy over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (c) If water is to be pumped give general description gravity system.	4. The po	pint of diversion is located 790 ft. No. and 1840 ft. E. from the Wi
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) sing within the SE2 NW1 of Sec. 16 77: 41 Sec. 28 NW2 (Give small) et legal subdivision) 5. The main ditch to be approximately 2 mile (Miles of feet) 1 length, terminating in the SE2 SW1 (Nors.) 1 W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS iversion Works— 6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom 10 feet; material to be used and character of construction Erush, 100se rock, concrete. matomy and brush, lumber orb, etc. wasternay over or around dam) (b) Description of headgate 2.5 feet in height, and 1.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity Systems. (Size and type of pump)		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ting within the SE2 NW1 of Sec. 6 77: 11 Sec. 78: 11 Sec.		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ting within the SE2 NW2 of Sec. 6 72. 41 S. (Nors) 3. W. M., in the county of Jackson (E. ex. W) 5. The main ditch (Main ditch, canal or pipe line) (Italian or ret) (Italian ditch, canal or pipe line) (Italian ditch, canal or pipe line) (Italian ditch, canal or pipe line) (Italian or ret) (Italian ditch, canal or pipe line) (Italian ditch, canal or pipe line) (Italian ditch, canal or pipe line) (Italian or ret) (Italian ditch, canal or pipe line) (Italian ditch, canal or pipe lin		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the SE\$ NW\$ of Sec. 6 SP. 41 S. (Nors) 3. W. M., in the county of Jackson (E. ev W.) 5. The main ditch (Main ditch, canal or pipe line) (In or S.) Length, terminating in the SE\$ SW\$ of Sec. 30 TP. 40 Sa. (Smallest legal subdivision) DESCRIPTION OF WORKS iversion Works— 6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom 10 feet; material to be used and character of construction Erush, loose rock, concrete maions and dirt thrown across stream bed. 2.5 feet in height and 4.0 feet wide, construction (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) pring within the SE2 NW2 of Sec. 6 (Nors) SE2 NW2 (Nors) M. M., in the county of Jackson SE2 SW1 (Nors) 5. The main ditch (Miles or feet) slength, terminating in the SE2 SW1 (Nors) Length, terminating in the special subdivision (Miles or feet) slength, terminating in the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS siversion Works— 6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom 10 feet; material to be used and character of construction Brush, loose rock, (Loose rock, concrete, material dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity, system. (c) If water is to be pumped give general description gravity, system. (d) Special Sward	.,,,,,,,,,	•
cing within the SE NW (Give small steps) subdivision of Sec. 6 (Nors) W. M., in the county of Jackson S. The main ditch (Main ditch, canal or pipe line) to be approximately. 2 mile (Miles or feet) Length, terminating in the SE SW (Semallest legal subdivision) of Sec. 36 (Tp. 40 Sa. (Semallest legal subdivision) DESCRIPTION OF WORKS Siversion Works— 6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom DESCRIPTION of Sruch, (Loose rock, concrete, masonry and dirt thrown across stream bed. ck and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)	2	(If preferable, give distance and besting to section correr)
5. The main ditch (Malles or feet) 1. In the country of Leckeon (Malles or feet) 1. In the main ditch (Malles or feet) 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being shown throughout on the accompanying map. 1. In the proposed location being s		
(Alles or feet) 5. The main ditch (Main dick, canal or pipe line) 1. length, terminating in the SE (Semallest legal subdivision) 1. W. W. W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom 10 feet; material to be used and character of construction Brush, loose rock, concrete, masons and dirt thrown across stream bed. (b) Description of headgate 2.5 feet in height and 1.0 feet wide, construction logs. (c) If water is to be pumped give general description gravity System. (Size and type of pump)	ring within the	(Give small st legal subdivision) of Sec. 9 ,7p: 44 Se , (N or S)
length, terminating in the SET SWT of Sec. 3.6. Tp. 40 Sa (Secallest legal subdivision) DESCRIPTION OF WORKS iversion Works— 6. (a) Height of dam 1.5. feet, length on top 2.0 feet, length at bottom 10. feet; material to be used and character of construction Brush, loose rock, concrete masonry and dirt thrown across stream bed. ck and brush, limber crib. etc., wasteway over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logsa. (c) If water is to be pumped give general description gravity. Systema. (Size and type of pump)	3 Wa	W. M., in the county of
length, terminating in the SET SWT of Sec. 3.6. Tp. 40 Sa (Secallest legal subdivision) DESCRIPTION OF WORKS iversion Works— 6. (a) Height of dam 1.5. feet, length on top 2.0 feet, length at bottom 10. feet; material to be used and character of construction Brush, loose rock, concrete masonry and dirt thrown across stream bed. ck and brush, limber crib. etc., wasteway over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logsa. (c) If water is to be pumped give general description gravity. Systema. (Size and type of pump)		main ditch to be approximately z miles
DESCRIPTION OF WORKS iversion Works— 6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom 10 feet; material to be used and character of construction Brush, loose rock, concrete masons and dirt thrown across stream bed. ct and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)	•	
DESCRIPTION OF WORKS iversion Works— 6. (a) Height of dam l. 5. feet, length on top 2.0 feet, length at bottom 10. feet; material to be used and character of construction Brush, loose rock, concrete masons and dirt thrown across stream bed. ck and brush, limber crib. etc., wasteway over or around dam) (b) Description of headgate 2.5 feet in height and 1.0 feet wide, construction (Timber, concrete, etc., number and size of openings) of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)	1	
6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom 10 feet; material to be used and character of construction Brush, loose rock, concrete masons and dirt thrown across stream bed. ct and brush timber crib. etc., wasteway over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction (Timber, concrete, etc., number and size of openings) of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)	(E. or W.)	, W. M., the proposed location being shown throughout on the accompanying map.
6. (a) Height of dam 1.5 feet, length on top 2.0 feet, length at bottom la feet; material to be used and character of construction Brush, loose rock, concrete masons and dirt thrown across stream bed. ck and brush, timber crib. etc., wasteway over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction (Timber, concrete, etc., number and size of openings) of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)		DESCRIPTION OF WORKS
la feet; material to be used and character of construction Brush, loose rock, concrete, masonry and dirt thrown across stream bed. (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)		:5—
and dirt thrown across stream bed. (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)		
and dirt thrown across stream bed. ct and brush timber crib. etc., wasteway over or around dam) (b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)	16	feet; material to be used and character of construction Brush, loose rock,
(b) Description of headgate 2.5 feet in height and 4.0 feet wide, construction of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)		
of logs. (c) If water is to be pumped give general description gravity system. (Size and type of pump)	ck and brush, timber	r crib. etc., wasteway over or around dam)
(c) If water is to be pumped give general description gravity system. (Size and type of pump)	(b) Desc	(Timber, concrete, etc., number and size of openings)
	of logs.	
	(c) If we	iter is to be pumped give general description gravity system.
		(Size and type of pump)

^{*}A different form of application is provided where storage works are contemplated.

[&]quot;Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the flydroelectric Commission. Either of the above forms may be secured, without cost, together with instructions by addressing the State Engineer. Salem Oregon.

25879				
anal System or F				4
7. (a) Give	dimensions et	each point of	canal where materially cha	nged in size, stating miles from
eadgate. At head	lgute: width on	top (at water	line) 4.0	feet; width on bottom
	feet; depth of w	ater	2.0 feet; grade2.	5 feet fall per one
iousand feet. (b) At9	me	miles from h	eadgate: width on top (at w	ater line)3.0
	feet; width on b	ottom	2.0	f water 2.0 feet;
rade2.5	•	•		
				in.; size at ft.
	• • •			
•		,		difference in elevation between
stake and place	of use	ft. I	s grade uniform?	Estimated capacity
	sec. ft.	rrigated or n	lace of use	······
	Range	rigarea, or p	1	
Township North or South	E. or W. of Williamette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated
40 S.	4 W.	36	SE SW	10.0 acres
· · · · · · · · · · · · · · · · · · ·				
		,		
•		. :		
•				-
			-	
				
			*	
(a) Ch	aracter of soil		required, attach separate sheet)	
			* * * * * * * * * * * * * * * * * * * *	
Power or Mining	_	a	rain,pasture,ano	hay.
-	- -	ower to be de	veloped	theoretical horsepowe
(b) Qu	uantity of water	to be used for	power	sec. ft.
		•	•	•
			(Head)	1 . 1
(a) In	e nuiure of the		•	be developed
• • • • • • • • • • • • • • • • • • • •	#			
(e) Su	ich works to be l	ocated in	(Legal subdivision)	of Sec.
Tp(No. N. or 8	, R. (No.	£. or W.)	M. ,	
(f) Is	water to be retu	irned to any s	tream?(Yes or No)	
(g) If	so, name strean	and locate p	oint of return	
***************************************		., Sec	, Tp	, R, W. 1

(h) The use to which power is to be applied is

(i) The nature of the mines to be served

Company of	runty, having a pro		*	* 3	
d an estimated population of				٠	
(b) If for domestic	use state number	of families to b	e supplied	0	
	(Answer question	11, 42, 12, and 14 in all a			
11. Estimated cost of pro	posed works, \$l.,	,000_00_			
12. Construction work u	vill begin on or be	forel.year.	from date	of priority	7.a
13. Construction work u	vill be completed (m or before 2;	years from	date of pri	lority.
14. The water will be co	mpletely applied t	o the proposed u	se on or before	3 years 1	
***************************************		·		······································	pri
•		a.E.C	ollings		
			(Manyature o	(applicant)	
Remarks: Water	will be let	down chann	el of Squar	v Creek Tron	n Squat
ake Reservoir and			•		
	•	4			CY.TKW.
f. 10.0 acres					************
	•••••	•••••••	•		
		······································	•		
		· · · · · · · · · · · · · · · · · · ·		D-	•

			***********		·····
***************************************		s j	0		••••
o		•			•••••••••••••••••••••••••••••••••••••••
······································	/		***************************************		
			••••••		
					··
		••••••••••••			·····
······································		• • • • • • • • • • • • • • • • • • • •	•		·•••
•					
·······					•••••
TATE OF OPECON					
TATE OF OREGON, County of Marion,					:
	7 %	ta damanda a			
COLD IN TO COMPARE THAT	I have examined t				
	_				
aps and data, and return the					

25879

STATE ENGINEE

of ty.

STATE OF OREGON,

County of Marian.

This is to certify that I have exemined the foregoing application and do hereby grant the same SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

	neasured at the point of diversion from the
ream, or its equivalent in case of rotation with other water	users, from Squam Lake Reservoir as
rovided under application No. R-28239, permit N	6. R- 2205
<u> </u>	
The use to which this water is to be applied isirrig	
<u> </u>	
	diversion of 12 acre feet
If for irrigation, this appropriation shall be limited to	
med existence that for each acre irrigated during the	
. •	
	2 7
	i sag
	,
·	
	<i>e</i>
nd shall be subject to such reasonable rotation system as ma	•
The priority date of this permit is	
Actual construction work shall begin on or before	
nereafter be prosecuted with reasonable diligence and be co	ompleted on or before October 1, 19
Complete application of the water to the proposed use	shall be made on or before October 1, 19 C
WITNESS my hand this 13th day of	· ·
TILITADO DE NAME DE DE LA CONTRACTOR DE	STATE ENGINEER

Permit No. 25879

Application No. 7. 1. 2.

This instrument was first received in the office of the State Engineer at Salem, Oregon,

TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON

PERMIT

on the 2 2 day of Lechelled

Recorded in book No. 70

Permits on page 27.5.7.9.

Approved:

Drainage Basin No.

page 💎

STATE ENGINEER

LEWIS A. STANLEY ...

Fees

State Printing 96137