NECEIVE DECEIVED

STATE ENGINEERATE ENGINEERSCATION FOR PRIMITE SALEM, GREGON SALEM, CREGON TO Appropriate the Public Waters of the State of Oregon

DI'	ookings,
State of Oregon	, do hereby make application for a permit to appropriate t
following described public waters of the Stat	te of Oregon, SUBJECT TO EXISTING RIGHTS:
If the applicant is a corporation, give d	late and place of incorporation
1. The source of the proposed appropri	ation is Springs at head of unnamed creek
raion pond, & OCV reservoir,	a tributary of Harris Creek
2. The amount of water which the appl	licant intends to apply to beneficial use is0., 25
cubic feet per second. (It water	to be used from more than one source, give quantity from each)
3. The use to which the water is to be a	applied Manufacturing and fire protection brigation, p. war, mining, manufacturing, domestic supplies, etc.)
4. The point of diversion is located 11	94.3 ft. N. and 578.6 ft. E. from the St.
corner of Section 25, T40S, R14W	(E. or W.)
	(Section or subdivision)

(If preferable, give	distance and bearing to section corner)
(If there is more than one sold of discount	distance end bearing to section corner)
(If there is more than one point of diversion being within the SW - SE -	
being within the SW1 - SE1	of Sec
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Guri	of Sec. 25 , Tp. 40S (N. or S.)
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Guri	of Sec. 25 , Tp. 40S (N. or S.)
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Gurn (E. or W.) 5. The 8n steel pipe 1i (Main ditch, canal or ply	ine to be 749.5 foot
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Gurr (E or W.) , W. M. in the county of Gurr 5. The Sn steel pipe li (Main dich, canal or ph in length, terminating in the SE1 - SW1 (Smallest leg	ine to be 749.5 foot (Nors) to be 749.5 foot (Miles or feet) to be 25 , Tp. 405 (Nors)
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Gurr (E or W.) , W. M. in the county of Gurr 5. The Sn steel pipe li (Main dich, canal or ph in length, terminating in the SE1 - SW1 (Smallest leg	ine to be 749.5 foot
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Gurr 5. The 8 ⁿ steel pipe 1; (Main ditch, canal or pig in length, terminating in the SE1 - SW1 (Smallest leg R. 14W , W. M., the proposed locat	ine to be 749.5 foot (Nors)
being within the SW1 - SE1 (Give smallest legal sub R. 1/W , W. M., in the county of Gurr 5. The 8" steel pipe li (Main ditch, earnal or pig in length, terminating in the SE1 - SW1 (Smallest leg R. 1/4W , W. M., the proposed locat DESCE	of Sec. 25 , Tp. 40S (N. or S.) Ty. ine to be 749.5 foot (Miles or feet) be intended by the second of Sec. 25 , Tp. 405 (N. or S.) tion being shown throughout on the accompanying map. RIPTION OF WORKS
being within the SW1 - SE1 (Give smallest legal sub R. 1/W , W. M., in the county of Gurr 5. The 8" steel pipe li (Main ditch, earnal or pig in length, terminating in the SE1 - SW1 (Smallest leg R. 1/4W , W. M., the proposed locat DESCE	of Sec. 25 , Tp. 40S (N. or S.) Ty. ine to be 749.5 foot (Miles or feet) be intended by the second of Sec. 25 , Tp. 405 (N. or S.) tion being shown throughout on the accompanying map. RIPTION OF WORKS
being within the SWL - SEL (Give smallest legal sub R. 11W , W. M., in the county of Gurr 5. The 8" steel pipe li (Main ditch, canal or pig in length, terminating in the SEL - SWL (Smallest leg R. 14W , W. M., the proposed locat (E. or W.) DESCE Diversion Works— 6. (a) Height of dam 9.0	ine to be 749.5 foot (Nors) ine to be 749.5 foot (Miles or feet) indivision) of Sec. 25 , Tp. 400 (Nors) tion being shown throughout on the accompanying map. RIPTION OF WORKS feet, length on top 60.0 feet, length at botto
being within the SWL - SEL (Give smallest legal sub R. 11W , W. M., in the county of Gurr 5. The 8" steel pipe li (Main ditch, canal or pig in length, terminating in the SEL - SWL (Smallest leg R. 14W , W. M., the proposed locat (E. or W.) DESCR Diversion Works— 6. (a) Height of dam 9.0 10,5 feet; material to be used and	ine to be 749.5 foot (N. or S.) ine to be 749.5 foot (Miles or feet) in of Sec. 25 , Tp. 400 (N. or S.) tion being shown throughout on the accompanying map. RIPTION OF WORKS feet, length on top 60.0 feet, length at botto character of construction steel reinforced concilioser rock concrete manning to the second concilioser rock concilioser roc
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Gurr 5. The 8" steel pipe 1: (Main dick, earnal or pig in length, terminating in the SE1 - SW2 (Smallest leg R. 14W , W. M., the proposed locat (E. or W.) DESCF Diversion Works— 6. (a) Height of dam 9.0 10,5 feet; material to be used and Wasteway is over top of da rock and brush, tumber crib, etc., wasteway over or around dam)	ine to be 749.5 foot (Nors) ine to be 749.5 foot (Miles or feet) and subdivision) from the management of Sec. 25 foot (Nors) in of Sec. 25 foot (Nors)
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Gurr 5. The 8" steel pipe 1: (Main dick, earnal or pig in length, terminating in the SE1 - SW2 (Smallest leg R. 14W , W. M., the proposed locat (E. or W.) DESCF Diversion Works— 6. (a) Height of dam 9.0 10,5 feet; material to be used and Wasteway is over top of da rock and brush, tumber crib, etc., wasteway over or around dam)	ine to be 749.5 foot (Nors) ine to be 749.5 foot (Miles or feet) be inne to be 749.5 foot (Miles or feet) construction being shown throughout on the accompanying map. RIPTION OF WORKS feet, length on top 60.0 feet, length at botto character of construction steel reinforced concummn tee, 81 above stream bed, 11 deep, 61 will (Climber, concrete, etc., number and size of openings)
being within the SW1 - SE1 (Give smallest legal sub R. 14W , W. M., in the county of Gurr 5. The 8 ⁿ steel pipe 1; (Main ditch, earnal or pig in length, terminating in the SE1 - SW1 (Smallest leg R. 14W , W. M., the proposed locat (S. or W.) DESCF Diversion Works— 6. (a) Height of dam 9.0 10,5 feet; material to be used and Wasteway is over top of da rock and brush, tumber crib, etc., wasteway over or around dam) (b) Description of headgate Concre	ine to be 749.5 foot (N. or S.) ine to be 749.5 foot (Miles or feet) in of Sec. 25 , Tp. 400 (N. or S.) tion being shown throughout on the accompanying map. RIPTION OF WORKS feet, length on top 60.0 feet, length at botto character of construction steel reinforced concilioser rock concrete manning to the second concilioser rock concilioser roc

. 26276

gate, At Ireadgate: width on top (at water line)			feet; width on botto	
	eet; depth of w	ater	feet; grade	feet fall per on
md feet. (b) At		miles from he	adgate: width on top (at w	ater line)
<u>.</u>	leet; width on b	ottom	fert; depth o	f waterfee
***************************************	feet fall	per one thou	and feet.	
(c) Length	of pipe,749	.5 ft.;	size at intake,	in.; size at7495
intake	8 in ;	size at place o	f use in.;	difference in elevation between
	•		•	Estimated capacit
: · · · · ·	sec. ft.			
8. Location	of area to be i	rrig ated , or pl	ace of use See atta	ched sheet
Township forth or South	Range S. or W. of Willernotto Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated
10 0	14 west	25	SWŁ SŁŁ	Demostic and Fire
40 Souti	14 WEST		ONE OFF	
				
		-		
				
			1	
				×
			- h y.,	
	<u> </u>	(If more space	required, attach separate sheet)	
(a) Ch	aracter of soil			
	•	:d		· · · · · · · · · · · · · · · · · · ·
	Purposes-			* · · · · · · · · · · · · · · · · · · ·
			•	theoretical horsepou
(b) Qı	antity of water	to be used for	power	sec. ft.
(c) To	tal fall to be uti	lized	(Head) feet,	
(d) Th	e nature of the	works by meai	ns of which the power is to	be developed
•••••		•		
(e) Su	ch works to be	located in	(Legal subdivision)	of Sec.
	, R			•
			ream?(Yes or No)	
(g) If			oint of return	, R

LEWIS A. STANLEY

STATE ENGINEER

James W. Carver, Jr.

ASSISTANT

The end shall stream, o	T 10 EXISTING right herein gra not exceed0.1 or its equivalent in	RIGHTS and the follow nted is limited to the a Dcubic feet p case of rotation with	wing limit mount of ser second other wat	g application and do hereby grant the lations and conditions: water which can be applied to benefic measured at the point of diversion from unnamed stream and No. R-33203, permit No. R- 2262	rial use
Th	e use to which this	s water is to be applied	is manuf	facturing and fire protection	
	for irrigation, this		limited to	of one cubic for	_
		· · · · · · · · · · · · · · · · · · ·	······································		
			·····		
***************************************	······································	· · · · · · · · · · · · · · · · · · ·	*****	uy be ordered by the proper state office	······································
		his permit is		1··1- 2 1000	
Act	tual construction 1	vork shall begin on or	before	September 22, 1960 and	d shall
thereafter	r be prosecuted wi	th reasonable diligence	and be c	completed on or before October 1, 1961	
			posed use	e shall be made on or before October 1,	19 62
WI	TNESS my hand t	his 22nd day	of	Serptember 1959	
			••	STATE ENG	INEER
				•	
Application No. 332.0 4 Permit No. 26276	PERMIT TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON	This instrument was first received in the office of the State Engineer at Salem, Oregon, on the 3 day of INY	Returned to applicant:	er 22, 1959 e.No. 71 200273	Drainage Basin No. 13 page KG. Fees

Fees