

APPLICATION FOR PERMIT

To Appropriate the Public Waters of the State of Oregon

continue debenom See of ORCANA , do hereby make application for a permit to appropriate the libraries of CREANA , do hereby make application for a permit to appropriate the libraries of described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS: If the epplicant is a corporation, give date and place of incorporation No. 1. The source of the proposed appropriation is SPING (Them of drawn) — a tributary of CIRCANAS 2. The amount of water which the applicant intends to apply to beneficial use is bit of feet per second. (Denestric 12 to be applied is CONSTRUCTOR AND STRUCTOR AND	1. Clyde H. Rice, Charles J. Smith, John A Johnson, Jack Forsy
see of	
1. The source of the proposed appropriation is SPINCS. 1. The source of the proposed appropriation is SPINCS. 2. The amount of water which the applicant intends to apply to beneficial use is bie feet per second. Comestive 2.5%. Lang. 2. The amount of water which the applicant intends to apply to beneficial use is bie feet per second. Comestive 2.5%. Lang. 3. The use to which the water is to be applied is Since 2.5%. Lang. 4. The point of diversion is located 2200. ft. M. and 1460 ft. E. from the 5 N. core is 1. The source of diversion is located 2200. ft. M. and 1460 ft. E. from the 5 N. core is 1. The point of diversion is located 2200. ft. M. and 1460 ft. E. from the 5 N. core is 1. The point of diversion is located 2200. ft. M. and 1460 ft. E. from the 5 N. core is 1. The point of diversion is located 2200. ft. M. and 1460 ft. E. from the 5 N. core is 1. The point of diversion is located 2200. ft. M. and 1460 ft. E. from the 5 N. core is 1. The point of diversion is located 2200. ft. M. and 1460 ft. E. from the 5 N. core is 1. The point of diversion is located 2200. ft. M. and 1460 ft. E. from the 5 N. core is 1. The from the 6 N. core is 1. The from	(Midding address)
1. The source of the proposed appropriation is \$\int_{\text{Const.}} \text{Const.} \te	
1. The source of the proposed appropriation is	
2. The amount of water which the applicant intends to apply to beneficial use is ble feet per second. (Demestra 258 for 17 for water in be used from now plant one source, give quantity from each) **3. The use to which the water is to be applied is Creation of plants, give with the water is to be applied is Creation of manufacturing demests supplies, etc.) 4. The point of diversion is located 2300 ft. Notice and plants and plants and plants and plants are subdivision. (If performing the source are point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be asserted to section corner) (If there is no new and per point of diversion, and must be used and character of construction (If the is not type of pump) (If the is not type of pump) (If the is not type of pump)	if the applicant is a corporation, give date and place of incorporation AYO
2. The amount of water which the applicant intends to apply to beneficial use is ble feet per second. (Demestic 255 for 17 for water in be used from now plad one source, give quantity from each) **2. The use to which the water is to be applied is **3. The use to which the water is to be applied is **4. The point of diversion is located 2300 ft. No. and // Locate from the SN (Rectan of which the water is to be applied is **5. The point of diversion is located 2300 ft. No. and // Locate for the SN (Rectan of which the water is to be applied in the state of the water is to be substituted to section corner) **1. The point of diversion is located 2300 ft. No. and proposed the state of the section corner) **(If been is man and proposed to diversion, and must be asserted to section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the state of the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is man and proposed in the section corner) **(If been is m	
2. The amount of water which the applicant intends to apply to beneficial use is ble feet per second. (It mestly 2.5% Fant 1.1 TCSC/L. II) 6. Which was a point of diversion is located 2.200 ft. M. and 1400 ft. (It or w) 6. The point of diversion is located 2.200 ft. M. and 1400 ft. (It or w) 6. The point of diversion is located 2.200 ft. M. and 1400 ft. (It or w) 6. The point of diversion is located 2.200 ft. M. and 1400 ft. (It or w) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bearing to section corner) 6. (If preferable, give distance and bear	1. The source of the proposed appropriation is 59101C. (Name of stream)
the feet per second. A messive 258 found The Second Construction and the second	, a tributary of Clackanas
4. The point of diversion is located \$20.0 ft. No. and \$40.0 ft. E. from the \$N. (R. or W.) 4. The point of diversion is located \$20.0 ft. No. and \$40.0 ft. E. from the \$N. (R. or W.) (If preferable, give distance and bearing to section corner) (If there is more than par point of diversion, each must be executed. Vie supports these if necessary) ing within the No. (Cive sumships least induction) (If there is more than par point of diversion, each must be executed. Vie supports these if necessary) ing within the No. (Cive sumships least induction) 3. E. (W. M., in the county of Co. (A.)) 5. The PHO. (Island dick. capas or pure thing). 4. In the proposed dick. capas or pure thing). 4. (Island dick. capas or pure thing). 5. The PHO. (Island dick. capas or pure thing).	2. The amount of water which the applicant intends to apply to beneficial use is
4. The point of diversion is located \$20.0 ft. Now and \$40.0 ft. E. from the \$5.0 mer of \$26.18 T25 R3 E (Bection or subdivision) (If preferable, give divines and bearing to section corner) (If there is more than per point of diversion, each must be described. Use supports these it necessary) ing within the \$10.0 ft. \$2.0 ft. \$3.0 ft. \$4.0 ft. \$5.0 ft. \$7.0	bic feet per second. Idomestic USE Front 1 pine in reservoir
4. The point of diversion is located \$20.0 ft. N. and \$70.0 ft. E. from the S.N. (Recent) The point of diversion is located \$20.0 ft. N. and \$70.0 ft. E. from the S.N. (Recent) The preferable, give distance and bearing to section content) (If preferable, give distance and bearing to section content) (If preferable, give distance and bearing to section content) (If there is more than pres point of diversion, each must by described. Use separate sheet if necessary) ing within the S.N. (Old smallest legal subdivision) 3. E. (N. or 8.) 5. The P.P. (Main stick, capat or pipe ling) (Is or w.) 5. The P.P. (Main stick, capat or pipe ling) (Is on the country of Sec. S. The S. (N. or 8.) 3. E. (N. or 8.) 3. E. (N. or 8.) 3. E. (N. or 8.) DESCRIPTION OF WORKS Version Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonity, the and broad tumber crib, ste. wasteway over or around dam) (b) Description of headgate (C) If water is to be pumped give general description (Stire and type of pump)	
(If preferable, give distance and bearing to section corner) (If there is more than pos point of diversion, such must be described. Use separate sheet if necessary) ing within the	(frigation, power, mining, manufacturing, domestic supplies, etc.)
(If preferable, give distance and bearing to section corner) (If there is more than pne point of diversion, such must be described. Use separate sheet if necessary) ing within the	
(If preferable, give distance and bearing to section corner) (If there is more than pre-point of diversion, each must be described. Use sepayate sheet if necessary) ing within the	4. The point of diversion is located 2200 ft. N and 460 ft. E from the 5 N
(If preferable, give distance and bearing to section corner) (If there is more than pre-point of diversion, each must be described. Use sepayate sheet if necessary) ing within the	mer of Sec 18 725 R3 E
(If there is more than pose point of diversion, each must be described. Use separate sheet if necessary) ing within the	
(If there is more than pose point of diversion, each must be described. Use separate sheet if necessary) ing within the	
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the	
3 E (Miles or test) 5. The	(If preferable, give distance and bearing to section corner)
3 E (Miles or test) 5. The	(If there is more than one point of diversion, each must be described. Use separate sheet if necessary)
5. The (Main dich, canal or pipe line) length, terminating in the (Smallestlegal subdivision) 3. F. (N. or S.) DESCRIPTION OF WORKS iversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, the and brush, timber crib, etc., wasteway ever or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	ing within the NE ft 1 th W 4 of Sec. 13 Tp. 7 (N. or 8.)
5. The (Main dich, canal or pipe line) length, terminating in the (Smallestlegal subdivision) 3. F. (N. or S.) (B. or W.) DESCRIPTION OF WORKS (version Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, the and brush timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	3 E , W. M., in the county of Clock (2000)
DESCRIPTION OF WORKS version Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry). k and brush timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	5. The pipe to be 14 32 44
DESCRIPTION OF WORKS version Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry). k and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	length, terminating in the NE 421 SW 4 of Sec. 18 To 2
DESCRIPTION OF WORKS (version Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, k and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	(Smallenflegal subdivision) (N. or S.)
6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, k and brush timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	(E. ar W.)
6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, which and brush timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc. number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	the control that are the control to
feet; material to be used and character of construction (Loose rock, concrete, masonry, k and brush timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	
(Loose rock, concrete, masonry, the and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate	
(b) Description of headgate	feet; material to be used and character of construction (Loose rock, concrete, masonry,
(c) If water is to be pumped give general description (Size and type of pump)	ck and brush, timber crib, etc., wasteway over or around dam)
(c) If water is to be pumped give general description (Size and type of pump)	(b) Description of headgate
(Size and type of pump)	(number, concrete, etc., number and size of openings)
(Size and type of pump)	(a) If support is to be supposed since constall description
(Size and type of engine or motor to be used, total head, water is to be lifted, etc.)	(c) 1) water is to be pumped give general description. (Size and type of pump)
	(Size and type of engine or motor to be used, total head, water is to be lifted, etc.)

[&]quot;A different form of application is provided where storage works are contemplated.

"Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the Hydroelectric Commission. Either of the above forms may be secured, without ous, together with instructions by addressing the State Engineer, Salem Directors.

	System		

26634 nal System of P	ipe Lint—			
" 1. (a) Give	dimensions at	each point of can	al where materially changed	in size, stating miles from
The state of the s		The second of the second)	•
	eet; depth of w	ater	feet; grade	feet fall per one
rusand feet. (b) At		miles from heads	pate: width on top (at water	line)
	eet; width on bo	ottom	feet; depth of wo	ıt er feet;
ide .	feet fall	per one thousan	å feet.	
(c) Length	of pipe,	50 ft.; siz	e at intake,	in.; size atft.
	•			erence in elevation between
take and place	of use. 10	-/2. ft. le o	rade uniform? 9	Estimated capacity,
2921	er mener	- summ	ea.	
8 Location	of area to be in	rrigated, or place	of use NOT	Applicante
Township North or South	Range E. or W. of Witinmette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated
25	3 E	18	1E 14 SK 14	Domedic 3
			NW14 SE14	Domestic 1
				
,			•	
	·			
			-	
		, , , , ,		·
·				
		(If more space rec	uired, attach separate sheet)	· ·
	-		: 	
(b) Ki	nd of crops raise	ed		
Power or Mining	-		9	
. •				theoretical horsepowe
. (b) Q	uantity of water	to be used for po	wetse	c. ft.
(c) To	tal fall to be ut	ilized	(Head)	
(d) T	ne nature of the	works by means	of which the power is to be	developed
	yi	•		0
(e) St	ich works to be	located in	(Legal subdivision)	of Sec
		, W. M.		
		•	am?(Yes or No)	
(g) If	so, name streat	m and locate poi	nt of return	
		:		
		, Sec	, Tp	, R , W.

LEWIS A. STANLEY

March

WITNESS my hand this

9th

day of

STATE ENGINEER

, 1940 .

ANNISTANT

	0.01 cubic	feet per second	measured at t	he point of d	liversion from th
cam, or its equivalent in	case of rotation	with other wat	er users, from	a_spri	ng

**************************************		*			
The use to which this	water is to be a	pplied is dome	stic use of	four famil	ies
		*			
If for irrigation, this a				of	one cubic foot s
	1 .				
ond or its equivalent for e		•			
2					
······································	. 0				
<u></u>					***************************************
		*			
			·		• • • • • • • • • • • • • • • • • • • •

		••••••	•••••		
1			c		***************************************
l shall be subject to such	reasonable rotai	tion sustem as n	au be ordered	by the prope	τ state officer.
The priority date of t				• .	
Actual construction i					and el
ereafter be prosecuted w					
Complete application					
	this 13 th	day of	AXENOGI. 7	.y , 19	72.
WITNESS my hand t	•		ΔHMz	18 1	Miles
					STATE ENGINEE
	· · · · · · · · · · · · · · · · · · ·			•	STATE ENGINEE
	l 2 2° ;			d	STATE ENGINEE
WITNESS my hand t	in the regon,			of	STATE ENGINE
WITNESS my hand t	ved in the m, Oregon, h	M.		0	ENGINEER COM.
WITNESS my hand t	received in the Salem, Oregon,	M.			STATE ENGINEER Page / 0 M.
WITNESS my hand t	irst received in the er at Salem, Oregon, VAFO h.	× ×		.3.1	
WITNESS my hand t	tos first received in the gineer at Salem, Oregon,	slock . R . M.		3, 1960 No. 72 26634	STANLET 2
WITNESS my hand t	ent was first received in the Engineer at Salem, Oregon, lay of March	o'clock R. M.		3, 1960 No. 72 26634	STANLEY 2
	This instrument was first received in the tree of the State Engineer at Salem, Oregon, a the AM and of March	(elurned to applicant:			STANLET 2

Permit No. 26634 Application No. 33693