*APPLICATION FOR PERMIT

To Appropriate the Public Waters of the State of Oregon

5. The Pipe /in.e. (Main ditch, canal or pipe line) to be (Miles or feet) in length, terminating in the SE/A of the SU/A of Sec. /, Tp. 6.5 (N. or 8.) R	1, Loc W Crowe + Mary wice (200
All points of diversion is located \$ 5.5 1.	of Rt 1 Box 12 Sheridan
If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is Crown tes 42 and Crosses of Streen (It may be seen to be used from the seed f	State of Ofe the do hereby make application for a permit to appropriate the
If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is Cross test 2 g to Consume of Street Managery	
1. The source of the proposed appropriation is Cross tes 42 gad and answer & street and a tribulary of Street tes 42 gad and a tribulary of Street tes 42 gad and tribulary of tes 42 gad and tribulary of Street tes 42 gad and tribulary of tes 42 gad and t	
a tribulary of Stankil titet. 2. The amount of water which the applicant intends to apply to beneficial use is subject feet per second. 8.5 acts. ft. from 5/1/49.8 acts. from 1/1/25 from 1/1/24 fr	If the applicant is a corporation, give date and place of incorporation
2. The amount of water which the applicant intends to apply to beneficial use is multic feet per second. 8.5 accept from 51/2 age 21/0.225 from Jirch flow (If water in to be used from more than one borroe, ever quantity from each) **3. The use to which the water is to be applied is // (trigation, power, mining, manufacturing, dements supplies, etc.) 4. The point of diversion is located 8.5 ft. S. and 2.150 ft. W. from the NE corner of Win. J. Flydran. DLC (Bection or subdivision) (If preferable, give distance and basering to section corner) (If there is more than one point of diversion, each must be described. The separate sheet If secessary) being within the NE/4 of the Ne/4 of the New Manual basering to section corner) (If there is more than one point of diversion, each must be described. The separate sheet If secessary) being within the Ne/4 of the New Manual basering to section corner) (If there is more than one point of diversion, each must be described. The separate sheet If secessary) being within the Ne/4 of the New Manual basering to section corner) (If there is more than one point of diversion, each must be described. The separate sheet If secessary) (If there is more than one point of diversion, each must be described. The section corner) (If there is more than one point of diversion, each must be described. The section corner) (If there is more than one point of diversion was been described. The section corner) (If there is no more than one point of diversion on the described. The section corner) (If there is no more than one point of diversion on the section corner) (If there is no more than one point of diversion on the section corner) (If there is no more than one point of diversion was been if the section corner) (If there is no more than one point of diversion on the section corner) (If there is no more than one point of diversion on the section corner) (If there is no more than one point of diversion on the section corner) (If there is no more than one point of diversion	1. The source of the proposed appropriation is Crowc 105 #2 04 d Unhamed Stream
ubic feet per second. 8.5 defect ff from 5 large gal 0.225 from direct flow (If water is to be used from more than one source, five quantity from each) ***3. The use to which the water is to be applied is (If preferable, give distance and bearing to section corner) (If there is now than one source distance and bearing to section corner) (If there is now than one sould of direction, each must be described. The separate sheet if necessary) being within the Nully of the Nully of Sec. 19. Tp. 6.5 (Reserve) 5. The Preferable, give distance and bearing to section corner) (If there is now than one sould of direction, each must be described. The separate sheet if necessary) being within the Nully of the Nully of Sec. 19. Tp. 6.5 (Reserve) 5. The Preferable, give distance and bearing to section corner) (If there is now than one sould of direction, each must be described. The separate sheet if necessary) being within the Nully of the Nully of Sec. 19. Tp. 6.5 (Reserve) 5. The Preferable, give distance and bearing to section corner) (If there is now then one sould of direction, each must be described. The security of Sec. 19. Tp. 6.5 (Reserve) (Reser	, a tributary of Standill titlet
ubic feet per second. 8.5 defect ff from 5 large gal 0.225 from direct flow (If water is to be used from more than one source, five quantity from each) ***3. The use to which the water is to be applied is (If preferable, give distance and bearing to section corner) (If there is now than one source distance and bearing to section corner) (If there is now than one sould of direction, each must be described. The separate sheet if necessary) being within the Nully of the Nully of Sec. 19. Tp. 6.5 (Reserve) 5. The Preferable, give distance and bearing to section corner) (If there is now than one sould of direction, each must be described. The separate sheet if necessary) being within the Nully of the Nully of Sec. 19. Tp. 6.5 (Reserve) 5. The Preferable, give distance and bearing to section corner) (If there is now than one sould of direction, each must be described. The separate sheet if necessary) being within the Nully of the Nully of Sec. 19. Tp. 6.5 (Reserve) 5. The Preferable, give distance and bearing to section corner) (If there is now then one sould of direction, each must be described. The security of Sec. 19. Tp. 6.5 (Reserve) (Reser	2. The amount of water which the applicant intends to apply to beneficial use is
4. The point of diversion is located \$85 ft. S. and 2180 ft. W. from the NE corner of Wm. J. Hadden. D.C. (Bection or middristens) (If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. The separate sheet if necessary) being within the NW./ for the New (Corner of Corner) (If there is more than one point of diversion, each must be described. The separate sheet if necessary) being within the NW./ for the New (Corner of Corner of Cor	
4. The point of diversion is located \$85 ft. S. and 2980 ft. W. from the NE CROWN of SCREENING. (If preferable, give distance and bearing to section conner) (If there is more than one point of diversion, each must be described. Use separate sheet if security) being within the NW/4 of the NW/4 of the NW/4. R. W. M., in the country of Pa/A. 5. The PRE/INT. (Realist dick, canal or pipes lines) (Realist team subdivision) (R. or W.) W. M., the proposed location being shown throughout on the accompanying map. (R. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (b) Description of headgate (c) If water is to be pumped give general description (Elies and type of pump)	
(If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NW/7 of the NW/8 of Sec. /7 , Tp. 65 (Give smallest legal subdivision) 7. Tp. 65 8. W. M., the proposed location being shown throughout on the accompanying map. 7. Tp. 65 8. (R. or W.) 8. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings)	(firrigation, power, mining, manufacturing, domestic supplies, etc.)
(If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NW/7 of the NW/8 of Sec. /7 , Tp. 65 (Give smallest legal subdivision) 7. Tp. 65 8. W. M., the proposed location being shown throughout on the accompanying map. 7. Tp. 65 8. (R. or W.) 8. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings)	4. The point of diversion is located 895 ft. 5 and 2980 ft. W from the NE
(If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NW/4 Ft. NW/5 of Sec. /4 , Tp. 6.5 (N. or 5.) R. W. M., in the county of Pe/A (Si or W) 5. The Pies / in. r. (Main ditch, canal or pips line) (In length, terminating in the SE/4 Ste/4 of Sec. // , Tp. 6.5 (N. or 5.) R. W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings)	corner of Wa J Andrew DLC
(If there is more than one point of diversion, each must be described. Use separate silved if secessary) being within the NW/4 of the NW/4 of the MW/4	
(If there is more than one point of diversion, each must be described. The separate sheet if necessary) being within the NW/F the NW/S of Sec. / P. Tp. 6.5. R. 6W., W. M., in the county of Ps/A. (Blue or feet) (Balan ditch, canal or pipe line) (Balan ditch, canal or pipe lin	
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NW/9 of this N.W. A. of Sec. /9. ,Tp. 6.5. (N. or S.) R. W. M., in the county of Pol/A. 5. The Pips //n. to be SOO (Miles or feet) in length, terminating in the SE of the SW/2 of Sec. /, Tp. 6.5. (N. or S.) R. W. M., the proposed location being shown throughout on the accompanying map. (R. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose reck, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings)	
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NW/9 of this N.W. A. of Sec. /9. ,Tp. 6.5. (N. or S.) R. W. M., in the county of Pol/A. 5. The Pips //n. to be SOO (Miles or feet) in length, terminating in the SE of the SW/2 of Sec. /, Tp. 6.5. (N. or S.) R. W. M., the proposed location being shown throughout on the accompanying map. (R. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose reck, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings)	
being within the NW/4 of Sec. // The NW/4	(If preserving, give distance and bearing to section corner)
R	
5. The Pior in the Self of the State of Sec. (Miles or feet) in length, terminating in the Self of the State of Sec. (N. or 8.) R	being within the NW/4 OF The NW/4 of Sec. / Tp. 6 S (Give smallest legal subdivision) (N or 5.)
in length, terminating in the SE SULP of Sec	R. (s. or W.), W. M., in the county of Polk
in length, terminating in the SE SULP of Sec	5. The <i>Pipe line</i> to be 1500
DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry) rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	
DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	
Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	R
Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	DESCRIPTION OF WORKS
feet; material to be used and character of construction (Loose rock, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump)	Diversion Works—
(Loose rock, concrete, masonry rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate	6. (a) Height of dam feet, length on top feet, length at bott
(b) Description of headgate	feet; material to be used and character of construction (Loose rock, concrete, mass
(c) If water is to be pumped give general description (Size and type of pump)	
(Size and type of pump)	(b) Description of headgate(Timber, concrete, etc., number and size of openings)
(Size and type of engine or motor to be used, total head water is to be lifted, etc.)	(c) If water is to be pumped give general description (Sine and type of pump)
	(Size and type of engine or motor to be used, total head water is to be lifted, etc.)

[&]quot;A different form of application is provided where storage works are contemplated.

"Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the selectric Commission. Either of the above forms may be secured, without cost, together with instructions by addressing the State Engineer, Salem

lgate. At head	gate: width on	top (at water	· line)	feet; width on bottom
			feet; grade	
eand foot				
			readgate: width on top (at water	
	feet; width on b	ottom	feet; depth of w	ater feet;
ia.	feet fal	l per one tho	usand feet.	
			A Company of the Comp	in coins at
			.; size at intake,	
n intake	in.,	size at place	of use in.; dif	ference in elevation betweer
ike and place	of use,	ft.	Is grade uniform?	Estimated capacity
		·	•	
8. Locatio	sec. jt. n of area to be	irrigated, or j	place of use	
	Range 2. or W. of		Forty-scre Tract	Number Acres To Be Irrigated
Township North or South	E. or W. of Willemette Moridian	Section	Futy-set fish	
65	64	//	Sw/4 of the SE/9	9./
65	6 4	14	NW' of the NE /4	17.3
85				
				And the second s
and a street of the street of			pace required, attach separate sheet)	
(a) C	hamastan of mail		pace required, attach separate aneet) O a ha	
		•	ries	
	-	sed 600	+/84	
Power or Mini	•		11	theoretical horseness
			developed	
(b) (Quantity of wate	er to be used	for power	sec. ft.
(c) 1	Total fall to be 1	ıtilized	(Heed)	
			neans of which the power is to l	e developed
(4)				
				•
(e)	Such works to b	e located in	(Legal subdivision)	of Sec.
	, R			
•				
			y stream?(Yes or No)	
(g)	If so, name stre	am and locat	te point of return	
				, R, W

funicipal or Domestic Supply—	30185
10. (a) To supply the city of	
	ılation of
d an estimated population ofin	19
(b) If for domestic use state number of famili	ies to be supplied
(Answer questions 11, 42, 12, and	4 14 in all onsee)
11. Estimated cost of proposed works, \$	
12. Construction work will begin on or before	
13. Construction work will be completed on or before	•
14. The water will be completely applied to the project	
14. The water will be completely applied to the pro-	posed use on or before
	(Bignetium of applicant)
Remarks: + wefer will be pomped +	
to Basetvoir # 1 whose it will be	
14 Hom B. with will be lifted 150'	
, .	······
STATE OF OREGON, }	
County of Marion,	
This is to certify that I have examined the foreg	
maps and data, and return the same for	······································
In order to retain its priority, this application m	ust be returned to the State Engineer, with corre
tions on or before, 19	
WITNESS my hand this day of	, 19
	STATE ENGINEES
. By	

PERMIT

STATE OF OREGON,

County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use stream, or its equivalent in case of rotation with other water users, from unnamed stream tributary. of South Yambill River and reservoir to be constructed under application No. R-40526 permit No. R- 4528 The use to which this water is to be applied is irrigation If for irrigation, this appropriation shall be limited to 1/80 th of one cubic foot per second or its equivalent for each acre irrigated from direct flow and shall be further limited to a diversion of not to exceed 2 acre feet per acre for each acre irrigated during the irrigation assaon of each year from direct flow and storage from reservoir to be constructed under permit No. R-4528 and shall be subject to such reasonable rotation system as may be ordered by the proper state officer. The priority date of this permit isJanuary 15, 1965 Actual construction work shall begin on or before March 12, 1966...... and shall thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 19.66... Complete application of the water to the proposed use shall be made on or before October 1, 19.67... WITNESS my hand this _____l2th ____ day of _____March

2 This instrument was first received in the office of the State Engineer at Salem, Oregon L. WHEELER STATE ENGINEER APPROPRIATE THE PUBLIC WATERS OF THE STATE Application No. 40521 OF OREGON 1.15 o'clock Recorded in book No. Returned to applicant: Drainage Basin No. Permit No. Permits on page Ħ ဥ