*APPLICATION FOR PERMIT

To Appropriate the Public Waters of the State of Oregon

I, Tillamook Water Commission, C	ity of Tillamook
of City Hall, Tillamook, (Mailing address)	
State of Oregon, do here	
following described public waters of the State of Ore	egon, SUBJECT TO EXISTING RIGHTS:
If the applicant is a corporation, give date and	place of incorporation Tillamook, Oregon
28 February 1891	
1. The source of the proposed appropriation is	Skookum Lake Reservoir
constructed on Fawcett Creek , a tribut	(Italie of param)
2. The amount of water which the applicant int	tends to apply to beneficial use is 700 acre-feet.
costogestpersecond (Maximum rate of use wi	11 be approx. 6.0 cfs initially and 12.0 cfs ult
	s municipal, domestic, and industrial
water supply.	(Hitgation, power, mining, mandiacturing, domesac supplies, e.e.,
4. The point of diversion is located 2113.46	ft. N. and 2300. 6ft. W. from the S. E.
corner of Section 19, Tp 2S, R8W, W.M.	Where the water is discharged from
(Sect	eriods of low natural flow downstream, the
water will be diverted from Fawcett Creek	at the existing diversion structure which
s described in previous permits. The ou	itlet from the reservoir
(If preferable, give distance a	nd bearing to section corner)
(If there is more than one point of diversion, each m	
being within the NW 1/4 of SE 1/4 (Give smallest legal subdivision)	
R. 8W, W. M., in the county of Tillamoo	
5. The outlet pipe (Main ditch, canal or pipe line)	to be 210 feet (Miles or feet)
in length, terminating in the NW 1/4 of SE 1/4 (Smallest legal subdivise	of Sec. 19 , Tp. 25 , (N. or S.)
R. $\frac{8W}{(\mathbf{z}. \text{ or } \mathbf{w}.)}$, W. M., the proposed location bei	ng shown throughout on the accompanying map.
DESCRIPTIO	N OF WORKS
Diversion Works—	and an tan 600 fact lands at bottom
	ength on top 600 feet, length at bottom
	ter of construction homogeneous earth dam of (Loose rock, concrete, masonry,
sandy clay silt, the spillway will be arou rock and brush, timber crib, etc., wasteway over or around dam)	
(b) Description of headgate One 30-inch of	liameter slide gate mounted in a concrete (Timber, concrete, etc., number and size of openings)
intake structure will regulate the flow thro	ough the dam outlet
(c) If water is to be pumped give general desc	ription (Size and type of pump)
	sed, total head water is to be lifted, etc.)

^{*}A different form of application is provided where storage works are contemplated.

^{**}Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the Hydroelectric Commission. Either of the above forms may be secured, without cost, together with instructions by addressing the State Engineer, Salem, Oregon.

Canal System or 7. (a) Giv	•			inged in size, stating miles from
headgate. At hea	dgate: width on	top (at water li	ne)	feet; width on bottom
thousand feet.				ater line)
	feet; width on l	bottom	feet; depth o	of water feet;
grade	feet fa	ll per one thousa	nd feet.	
(c) Lengt	h of pipe,	ft.; si	ze at intake,	in.; size at ft.
from intake	in.	; size at place of	use in.;	difference in elevation between
intake and place	of use,	ft. Is !	grade uniform?	Estimated capacity,
8. Locatio	sec. ft. on of area to be	irrigated, or plac	e of use Tillamook ar areas of possible fo	nd suburban districts includi
Township North or South	Range E. or W. of Williamette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated
1 South	9W_	19, 29, 30 31, 32, 33		
1 South	10 W_	24, 25, 26 34, 35, 36		
2 South	10_W_	3, 13, 24		
2 South	9W	4, 5, 6, 7, 8, 9, 10,		
		16, 17, 18, 20, 21, 28		
		29		
				<u> </u>
		_		
		(If more space re	quired, attach separate sheet)	
(a) Ch	naracter of soil .			
		ed		
Power or Mining 9. (a) To	-	ower to be devel	oped	theoretical horsepower.
(b) Q	uantity of water	to be used for po	wer	sec. ft.
(c) To	otal fall to be u t	ilized	feet.	
				be developed
(e) Si	ıch works to be	located in		of Sec. ,
		, W. M.		,
			am?(Yes or No)	
				, R, W. M.
				S.) (No. E. or W.)
(i) T	he nature of the	mines to be serv	ed	

Municipal or Domestic Supply	30192
10. (a) To supply the city of Tillamook and suburban dist	ricts
Tillamook County, having a present population of 5,	000
and an estimated population of 5,500 in 1985	
(b) If for domestic use state number of families to be supplie	d
(Answer questions 11, 12, 13, and 14 in all cases)	
11. Estimated cost of proposed works, \$ 115,000	
12. Construction work will begin on or before 1 July 1965	
13. Construction work will be completed on or before 15 Nove	mber 1965
14. The water will be completely applied to the proposed use on or b	pefore 1 July 1966
(Signature)	January of applicant)
President, Till	amook Water Commission
Remarks: The water from Skookum Lake Reservoir	will be released during the
summer and fall to supplement the normal creek flow. Th	ne water will flow down
the Fawcett Creek about 3.3 miles where it will be picked	up by the existing diversion
structure. A map of the existing distribution system and	the service area has been
previously filed.	
-	
STATE OF OREGON, County of Marion, ss.	
County of Marion,	
This is to certify that I have examined the foregoing application, t	ogether with the accompanying
maps and data, and return the same for	
In order to retain its priority this and its is	d. G
In order to retain its priority, this application must be returned to	the State Engineer, with correc-
tions on or before, 19	
WITNESS my hand this day of	, 19
	STATE ENGINEER
B y	
	ASSISTANT

STATE OF OREGON,
County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use 700.0 acre feet stored water only and shall not exceed rubin foot measured at the point of diversion from the stream, or its equivalent in case of rotation with other water users, from Skookum Lake Reservoir to be constructed under application No. R-40641, permit No. R-4532 municipal The use to which this water is to be applied is second or its equivalent for each acre irrigated and shall be subject to such reasonable rotation system as may be ordered by the proper state officer. February 25, 1965 The priority date of this permit is Actual construction work shall begin on or before April 16, 1966 thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 19.67.... Complete application of the water to the proposed use shall be made on or before October 1, 19.68... WITNESS my hand this र्ज

This instrument was first received in the

APPROPRIATE THE PUBLIC WATERS OF THE STATE

TO

II NEKG

OREGON

Application No. HOCH

Permit No.

office of the State Engineer at Salem, Oregon

at 2.00 o'clock

Returned to applicant:

Recorded in book No.

Permits on page

CHRIS

Basin No.

Drainage