

*APPLICATION FOR PERMIT

To Appropriate the Public Waters of the State of Oregon

Malheur Drive Ontario, Oregon Oregon do hereby make application for a permit to appropriate the plowing described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS: If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is Blanton Drain Other River 2. The amount of water which the applicant intends to apply to beneficial use is	I,D	ARRELL COCHRAN	and MATH C. SC			
Act of Oregon				1		
If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is Blanton Drain Others of the section of the proposed appropriation is 1. The source of the proposed appropriation is Blanton Drain Others of the proposed appropriation is Albert River 2. The amount of water which the applicant intends to apply to beneficial use is1.6. able feet per second.				,		,
1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed appropriation is Blanton Drain 1. The source of the proposed distance is applied is Carterial to the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The use to which the water is to be applied is Carterial Drain Blanton Drain 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner) 1. The source of the proposed distance and bearing to section corner. 1. The source of the proposed distance and bearing to section corner. 1. The source of the proposed distance and bearing to section corner. 1. The source of the proposed distance and bearing to section corner. 1. The source of the proposed distance and bearing to section section accused. 1. The source of the proposed distance and bearing to section accused. 1. The source of	ate of	Oregon	, do hereby mo	ake application for a p	ermit to approp	priate the
1. The source of the proposed appropriation is Blanton Drain (Common of fixens) (Com	llowing descri	bed public waters of	the State of Oregon, S	SUBJECT TO EXISTI	NG RIGHTS:	
	If the app	licant is a corporation	ı, give date and place	of incorporation		•••••
	•••••					***********
	1. The so	urce of the proposed a	ppropriation is	Blanton Dr	ain	,
**3. The use to which the water is to be used from more than one source, give quantity from each) **3. The use to which the water is to be applied is irrigation, power, mining, manufacturing, deposite supplies, etc.) (1) 422 N. 42 E SW 4. The point of diversion is located (2) 30 ft. S. and 35 ft. E from the W2 core of Section 6, Township 18 S., R. 47 E. W. M. (Geedlon or subdivision) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and deal profession corner) (If preferable, give distance and deal profession corner) (If preferable, give distance and deal profession corner) (If preferable, give distance and deal preferable description (If preferable, give distance and deal preferable description (If preferable, give distance and description (If give explained) (If preferable, give distance and bearing to section corner) (If preferable, give distance and description (If give explained) (If give explained) (If give explained)						
**3. The use to which the water is to be applied is	2. The an	rount of water which	the applicant intends t	to apply to beneficial	use is 1 <u>.6</u>	
**3. The use to which the water is to be applied is	bic feet per se	cond	, ,			
(I) 422 N. 42 E SW 4. The point of diversion is located (2) 30 ft. S. and 35 ft. E from the W2 cree s.) On or s. and section corner. On or s. and best set subdivision. On or s. and best set subdivision. On or s. and section corner. On or s. and best set subdivision. On or s. and section corner. On or s. and best set subdivision. On or s. and section corner. On or s. and secti						
(If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section described (It preferable describ	**3. The us	e to which the water i	is to be applied is	Irrigation, power, mining, manus	facturing, domestic sup	plies, etc.)
(If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner. (If preferable, give distance and bearing to section corner. (If preferable, give distance and bearing to section corner.	•••••		(T)	J 42	.	SW
orner of Section 6, Township 18 S. R. 47 E. W. M. (Bection or subdivision) (If preferable, give distance and bearing to section corner. (If preferable, give distance and bearing to section corner. (If preferable, give distance and bearing to section corner. (If preferable, give distance and bearing to section corner. (If preferable, give distance and bearing tof section. (If preferable, give distance and bearing to section.	4. The no	oint of diversion is loc	ated (2) 30 ft. S	35 ft.	E from the	, Wż
(Bection or subdivision) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section corner if necessary) (If preferable, give distance and bearing to section	2. 2.00 pc		(N.	or S.)	E. or W.)	
(If there is more, than one point of diversion, each must be described. Use separate sheet if necessary) eing within the (2) NWLSWL of Sec. 6 , Tp. 18 S., (N. or S.) 2. 47 E., W. M., in the county of Malheur (a. or W.) 5. The ditch (Malin ditch (eigh) or property SWL (Maline or feet) 1. 1250 5. The (Malin ditch (eigh) or property SWL (Maline or feet) 1. 1250 5. The (Malin ditch (eigh) or property SWL (Maline or feet) 1. 1250 5. The (Malin ditch (eigh) or property SWL (Maline or feet) 1. 1250 5. The (Malin ditch (eigh) or property SWL (Maline or feet) 1. 18 S., (N. or S.) 2. 18 S., (N. or S.) 3. 47 E., W. M., the proposed location being shown throughout on the accompanying map. 2. 27 E., W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, conscrete, masonary, Cooks and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Tumber, conscrete, etc., number and size of openings) (1) Parma Water lift 10" disc (1) 7½ H. P. (Size and type of pump) (2) 7½ H. P. Electric	orner ofS	ection 6, Towns	SN1D 18 S., K.	dbdivision)		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the(2) NW\frac{1}{2}\sum_{\text{Caffe}} \text{smallest legal subdivision}) \tag{Ar. or 8.} Ar. o						***************************************
(If there is more, than one point of diversion, each must be described. Use separate sheet if necessary) eing within the (2) NW1SW2 of Sec. 6 , Tp. 18 S., (N. or S.) 47 E., W. M., in the county of Malheur (a. or W.) 5. The ditch (Called ditch (eight) or provided W2 (2) 1350 1. (Alles or feet) 2. (Alles or feet) 3. (Alles or feet) 47 E., W. M., the proposed location being shown throughout on the accompanying map. 47 E., W. M., the proposed location being shown throughout on the accompanying map. 2. (Alles or feet) 3. (Alles or feet) 47 E., W. M., the proposed location being shown throughout on the accompanying map. 48 DESCRIPTION OF WORKS DIVERSION WORKS DIVERSION Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, conscrete, masoury, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Tumber, conscrete, etc., number and size of openings) (1) Parma Water lift 10" disc (1) 7½ H. P. (2) 7½ H. P. Electric						
(If there is more, than one point of diversion, each must be described. Use separate sheet if necessary) eing within the (2) NW1SW2 of Sec. 6 , Tp. 18 S., (N. or S.) 47 E., W. M., in the county of Malheur (a. or W.) 5. The ditch (Called ditch (eight) or provided W2 (2) 1350 1. (Alles or feet) 2. (Alles or feet) 3. (Alles or feet) 47 E., W. M., the proposed location being shown throughout on the accompanying map. 47 E., W. M., the proposed location being shown throughout on the accompanying map. 2. (Alles or feet) 3. (Alles or feet) 47 E., W. M., the proposed location being shown throughout on the accompanying map. 48 DESCRIPTION OF WORKS DIVERSION WORKS DIVERSION Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, conscrete, masoury, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Tumber, conscrete, etc., number and size of openings) (1) Parma Water lift 10" disc (1) 7½ H. P. (2) 7½ H. P. Electric						
(If there is more, than one point of diversion, each must be described. Use separate sheet if necessary) eing within the (2) NWLSWL of Sec. 6 , Tp. 18 S., (N. or S.) 1. 47 E., W. M., in the county of Malheur (a. or W.) 5. The ditch (Main ditch (appl or PSWLSWL) of Sec. 6 , Tp. 18 S., (N. or S.) 1. 47 E., W. M., in the county of Malheur (a. or W.) 5. The ditch (Main ditch (appl or PSWLSWL) of Sec. 6 , Tp. 18 S., (N. or S.) (amaliest legal subdivision) (a. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, conscrete, masoury, ock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Tumber, conscrete, etc., number and size of openings) (1) Parma Water lift 10" disc (1) 7 % H. P. Electric (Size and type of pump)						
eing within the (2) NW SW (1) (Core smallest legal subdivision) of Sec. 6 , Tp. 18 S., (N. or S.) 2. 47 E., W. M., in the county of Malheur (2. or W.) 5. The ditch (2) NW SW (2. or S.) (Mallest ditch (2. or S.) (2. or S.) (Mallest or feet) (Mallest legal subdivision) (R. or W.) (R. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, ock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (1) Parma Water lift 10" disc (1) 7 H. P. (Size and type of pumps)		(if pre	ferable, give distance and bearing	ig to section corner)	•	
eing within the (2) NWLSWL (Give smallest legal subdivision) 2. 47 E, W. M., in the county of Malheur (1) 1250 5. The ditch to be (2) 1350 (Miles or feet) (Main ditch (1/1) or rgwlyswl with the county of Sec. 6 (1) 18 S., (Miles or feet) (*****
(1) 1250 5. The ditch to be (2) 1350 (Maln ditch (crit) or PSW SW W W W (Miles or feet) n length, terminating in the (2) NW SW W of SW (Miles or feet) (Smallest legal subdivision) (E. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Leose rock, concrete, masonry, coat and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (1) Parma Water lift 10' disc (1) 7 2 H. P. Electric	eing within the	(2) W\{S\\\{\}	last lass) subdivision)	of Sec6	, Tp18	S.,
5. The	47 E	W M in the country	Malheur			1. 01 5.7
n length, terminating in the	(E. OF W.))]k 	(1)	1250	
DESCRIPTION OF WORKS Oiversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (1) Parma Water lift 10" disc (2) Parma Water lift 8" disc (1) 7½ H. P. (8ize and type of pump)	5. The	ditch		to be(2)	1350	••••••
DESCRIPTION OF WORKS Oiversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (1) Parma Water lift 10" disc (2) Parma Water lift 8" disc (1) 7½ H. P. (8ize and type of pump)	- 1	(Main diven	(1) or PSWZSWZ	of Son 6	To 1	8 S
DESCRIPTION OF WORKS 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description (Size and type of pump) (1) 7½ H. P (Size and type of pump)						
DESCRIPTION OF WORKS 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, ock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (1) Parma Water lift 10" disc (1) 72 H. P. (2) 72 H. P. (Size and type of pump)	47 E.	, W. M., the propo	sed location being sho	wn throughout on the	accompanying	map.
Oiversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, ock and brush, timber crib, etc., wasteway over or ground dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (1) Parma Water lift 10'' disc (1) 72 H. P. (Size and type of pump) (2) 73 H. P. Electric	(Æ. OF W.)					
6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (1) Parma Water lift 10" disc (1) 72 H. P. (Size and type of pump) (2) 73 H. P. Electric			DESCRIPTION OF	WORKS		· · ·
feet; material to be used and character of construction (Loose rock, concrete, masonry, (b) Description of headgate (Timber, concrete, etc., number and size of openings) (1) Parma Water lift 10'' disc (1) 7½ H. P. (3) 7½ H. P. (8) Electric						
(b) Description of headgate (Timber, concrete, etc., number and size of openings) (1) Parma Water lift 10" disc (2) If water is to be pumped give general description (2) Parma Water lift 8" disc (1) 7½ H. P. (Size and type of pump) (2) 7½ H. P. Electric	6. (a) He	gight of dam	feet, length	on top	feet, length	at bottom
(b) Description of headgate (Timber, concrete, etc., number and size of openings) (1) Parma Water lift 10" disc (2) If water is to be pumped give general description (2) Parma Water lift 8" disc (1) 7½ H. P. (Size and type of pump)		feet; material to be	used and character of	construction		
(b) Description of headgate					(Loose rock, cond	rete, masonry,
(1) Parma Water lift 10" disc (c) If water is to be pumped give general description (2) Parma Water lift 8" disc (1) 7½ H. P. (Size and type of pump) (2) 7½ H. P. Electric	ock and brush, timber	crib, etc., wasteway over or are	ound dam)		to	***************************************
(1) Parma Water lift 10" disc (c) If water is to be pumped give general description (2) Parma Water lift 8" disc (1) 7½ H. P. (Size and type of pump) (2) 7½ H. P. Electric						
(c) If water is to be pumped give general description (2) Parma Water lift 8" disc (1) 7½ H. P. (Size and type of pump) (2) 7½ H. P. Electric			(Timber,	concrete, etc., number and size	of openings)	
(c) If water is to be pumped give general description (2) Parma Water lift 8" disc (1) 7½ H. P. (Size and type of pump) (2) 7½ H. P. Electric				(1) Parma Wa	ter lift	10" disc
(2) 7½ H. P. Electric	(1)(c) If wa	ter is to be pumped g	ive general description	n (2) Parma Wa	ter lift	8" disc
(1) 11 lift (Size and type of engine or motor to be used, total head water is to be lifted, etc.)	(2) 7½ H.	P. Electr	ic			
	(1) 11 11	ift (Size and type of	engine or motor to be used, total	l head water is to be lifted, etc.))	

^{*}A different form of application is provided where storage works are contemplated.

lgate. At h ea c	lgate: width on	top (at water l	ine)	feet; width on botton
sand feet. •	•	•	feet; gradeadgate: width on top (at water	
	feet; width on l	oottom	feet; depth of wa	ter feet
		ll per one thous	*	
n intake ke and place	of use,in.	; size at place of	size at intake,if usein.; diffe	erence in elevation betwee
8. Locatio		irrigated, or pla	Forty-acre Tract	Number Acres To Be Irrigated
North or South	Willemette Meridian			33
18 S	47 E	6	NW\$SW\$	
			SW\2SW\2	31 11º 1/r 1 44º
\ <u>\</u>	,			44=
<u></u>				
				
			.>	
· -		, .		· · · ·
				······································
			required, attach separate sheet)	-
				•
wer or Mining	g Purposes— tal amount of p	oower to be deve	eloped	theoretical horsepowe
		,	oowersec	. ft.
			(Head)	
(d) T			s of which the power is to be o	ieveloped
(e) Si	ich works to be	located in	(Legal subdivision)	of Sec
(No. N. or	, R(No	, W. M.	4	•
(f) Is	water to be ret	urned to any str	ream?(Yes or No)	
	-	_	, Tp	
N.		Coo	The state of the s	

10 (a) To supply the situ of	31511
10. (a) To supply the city of	
d an estimated population of in 19 in 19	
(b) If for domestic use state number of families to be supplied	ed
(Answer questions 11, 12, 13, and 14 in all cases)	به بو دمود
	6 •
11. Estimated cost of proposed works, \$ 2000.00	K .
12. Construction work will begin on or beforeStarted	······
13. Construction work will be completed on or before	mpleted
14. The water will be completely applied to the proposed use on or	before June, 1966
Naine	Il Corkin
	ignature of applicant)
	yuu.
Remarks:	
j	
•	
	•••••••••••••••••••••••••••••••••••••••

	,
mama on onegov	
TATE OF OREGON, ss.	
County of Marion,) ·	
This is to certify that I have examined the foregoing application	, together with the accompany
naps and data, and return the same for	
In order to retain its priority, this application must be returned t	o the State Engineer with corr
	o the Blute Dilgineer, with corn
ions on or before, 19,	
	•
WITNESS my hand this day of	, 19
•	•

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

and shall not exceedl.l0 cubic fe	et per second	l measured at th	e point of diversi	ion from the
stream, or its equivalent in case of rotation w	ith other wa	ter users, from	Blanton Drain	
	***************************************	*******************************		
The use to which this water is to be app			, ;	

If for irrigation, this appropriation shall	be limited to	1/40th	of one c	ubic foot per
second or its equivalent for each acre irrigated	and shall	be further 1:	imited to a div	version of
not to exceed 3 acre feet per acre f	or each ac	re irrigated o	turing the irr	igation
season of each year,				
				,
				. 19
	***************************************	,		
and shall be subject to such reasonable rotation	n system as r	nay be ordered by	y the proper state	officer.
The priority date of this permit is	Ap	ril 25, 1966		·
Actual construction work shall begin or	n or before	January 18	3,1968	and shall
thereafter be prosecuted with reasonable dilig	ence and be	completed on or	before October 1,	1968
Complete application of the water to the	e proposed us	e shall be made o	on or before Octol	per 1, 19.69
WITNESS my hand this18th			-	
· · · · · · · · · · · · · · · · · · ·	day of	11.		
	***************************************	- Comments	STA	TE ENGINEER

Application No. 42135

Permit No.

PERMIT

TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON

This instrument was first received in the office of the State Engineer at Salem, Oregon,

on the 25th day of Apri 19 66, at 8:00 o'clock A

X.

Returned to applicant:

Approved:

January 18, 1967 Recorded in book No.

2

Permits on page

CHAIS L. CHALLER ENGINEER

State Printing 98137