CERTIFICATE NO. 38350

To Appropriate the Public Waters of the State of Oregon

Route 6, Box 600, Lakeview Oregon	Route 6, Box 600, Lakeview Commendation Oregon do hereby make application for a permit to appropriate the of Oregon do hereby make application for a permit to appropriate the official decided public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS: If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is	I,	Milo L. Cain
the of Oregon	And the of Oregon		Route 6, Box 600, Lakeview
lowing described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS: If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is	If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is		(Mailing address)
1. The source of the proposed appropriation is 2. The amount of water which the applicant intends to apply to beneficial use is 1. The source of the proposed appropriation in the source of the proposed applies ap	If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is way and unnamed reservoir located in the NEWNEY, Sec. 6, T 14 S, R 19 2. The amount of water which the applicant intends to apply to beneficial use is . 9.54 which feet per second. Three acre feet per acre for . 43. acres. Or . 129 acre for the proposed acres to be used more than one section more than one serves, see caustif wens such **3. The use to which the water is to be applied isirrigation. **4. The point of diversion is located .325 ft. S. and 80 ft. E. from the .NW cree for . 41 S, R 19 E.W.M. **4. The point of diversion is located .325 ft. S. and .80 ft. E. from the .NW cree for Also	tate of .	or egon do hereby make application for a permit to appropriate the
1. The source of the proposed appropriation is	1. The source of the proposed appropriation is	ollowing	described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:
2. The amount of water which the applicant intends to apply to beneficial use is . 0.54	2. The amount of water which the applicant intends to apply to beneficial use is . 0.54	If t	the applicant is a corporation, give date and place of incorporation
2. The amount of water which the applicant intends to apply to beneficial use is . 0.54	2. The amount of water which the applicant intends to apply to beneficial use is . 0.54		
**3. The use to which the water is to be applied is	ubic feet per second. Three acre feet per acre for 43 acres, or 129 acre f **3. The use to which the water is to be applied is irrigation. (trigation, power, mining, manufacturing, doorseld supplies, etc.) 4. The point of diversion is located 395 ft. S. and 80 ft. E. from the NW orner of NE 1/4 NE 1/4 of Section 6, T. 41 S, R. 19 E.W.M. (deciden or subdivision) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion, each must be described. Use separate sheet if necessary) (if there is more than one point of diversion is necessary. (if there is more than one point of diversion is necessary. (if there is more than one point of diversion is necessary. (if there is more than one point of diversion is necessary. (if there is more than one point of diversion is necessary. (if there is more than one point of diversion is necessary. (if there is no the necessary. (if there is no to	1. way	The source of the proposed appropriation is and unnamed drainage and unnamed reservoir located in the NE4NE4NE4, Sec. 6, T 14 S, R 19 aributary of
**3. The use to which the water is to be applied isirrigation_power, mining, manufacturing, domestic supplies, etc.) 4. The point of diversion is located .395	**3. The use to which the water is to be applied isirrigation_ (tragation_power, mining_manufacturing_domestic supplies, ste.) 4. The point of diversion is located 39.5	2.	The amount of water which the applicant intends to apply to beneficial use is 0.54
4. The point of diversion is located 3.9.5 ft. S. and 8.0 ft. E. Grow the NW C. C. or W.) There of NE 1/4 NE 1/4 of Section 6. T 41 S. R 19 E.W.M. (Rection or subdivision) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the NE 1/4 NE 1/4 of Section or subdivision of Sec. 6, Tp. 41 S. (Give smallest legal subdivision) 1.9 E. W.M., in the county of Lake (Section of Sec. 6, Tp. 41 S.) (C. or W.) 5. The main ditch. (Main ditch, canal or pipe line) (C. or W.) (Miles or feet) length, terminating in the SE 1/4 NE 1/2 of Sec. 6, Tp. 41 S. (C. or W.) (C. or W.) DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 1.5.0 feet; material to be used and character of construction KOCKY SO11 (Coose rock, concrete, masonry, Charlest, and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe. (C. or W.) (c) If water is to be pumped give general description POWER take—off drivenpump, (dise and type of pump))	4. The point of diversion is located 39.5 ft. S. and 80 ft. E. Gr. or W.) orner of NE 1/4 NE 1/4 Of Section 6. T 41 S. R 19 E.W.M. (Bection or subdivision) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) eing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S. (Cive smaller legal subdivision) 2. 19 E. W.M., in the country of Lake (Cov. or W.) 5. The main ditch (Cotain ditch, casal or plys line) (Miles or feet)	ubic feet	t per second. Three acre feet per acre for 43 acres, or 129 acre for (If water is to be used from more than one source, give quantity from each)
4. The point of diversion is located 3.9.5 ft. S. and 8.0 ft. E. Grow the NW C. C. or W.) There of NE 1/4 NE 1/4 of Section 6. T 41 S. R 19 E.W.M. (Rection or subdivision) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the NE 1/4 NE 1/4 of Section or subdivision of Sec. 6, Tp. 41 S. (Give smallest legal subdivision) 1.9 E. W.M., in the county of Lake (Section of Sec. 6, Tp. 41 S.) (C. or W.) 5. The main ditch. (Main ditch, canal or pipe line) (C. or W.) (Miles or feet) length, terminating in the SE 1/4 NE 1/2 of Sec. 6, Tp. 41 S. (C. or W.) (C. or W.) DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 1.5.0 feet; material to be used and character of construction KOCKY SO11 (Coose rock, concrete, masonry, Charlest, and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe. (C. or W.) (c) If water is to be pumped give general description POWER take—off drivenpump, (dise and type of pump))	4. The point of diversion is located 3.95 ft. S. and 80 ft. E. from the NW one of NE 1/4 NE 1/4 of Section 6, T 41 S, R 19 E, W.M. (Bection or subdivision) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate sibest if necessary) (If there is more than one point of diversion, each must be described. Use separate si	** 3.	The use to which the water is to be applied isirrigation
(If there is more than one point of diversion, each must be described. Use separate theet if necessary) (If there is more than one point of diversion, each must be described. Use separate theet if necessary) ing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (R. or W.) 19 E , W. M., in the county of Lake (E. or W.) 5. The main ditch. (Main ditch. canal or pipe line) (Miles or feet) length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (R. or W.) 19 E , W. M., the proposed location being shown throughout on the accompanying map. 19 E , W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction KOCKY Soil (Loces rock, concrete, masonry, Character, concrete, etc., number and size of openings) (b) Description of headgate 18 inch pipe. (Climber, concrete, etc., number and size of openings)	Orner of NE 1/4 NE 1/4 Of Section 6. T 41 S., R 19 E.W.M. (Bection or subdivision) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the NE 1/4 NE 1/4 of Sec. 6. Tp. 41 S. (Cive smallest legal subdivision) 2. 19 E., W. M., in the country of Lake (Ex. or W.) 5. The Main ditch (Main ditch, canal or pipe line) (Main ditch, canal or pipe line) (R. or W.) 7. Tp. 41 S. (R. or S.) 8. 19 E., W. M., the proposed location being shown throughout on the accompanying map. (Ex. or W.) DESCRIPTION OF WORKS Oversion Works— 6. (a) Height of dam 9. feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction (COCK or COCK of COC		(Mrigation, power, mining, manuacturing, domestic supplies, wat,
(If there is more than one point of diversion, each must be described. Use separate theet if necessary) (If there is more than one point of diversion, each must be described. Use separate theet if necessary) ing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (R. or W.) 19 E , W. M., in the county of Lake (E. or W.) 5. The main ditch. (Main ditch. canal or pipe line) (Miles or feet) length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (R. or W.) 19 E , W. M., the proposed location being shown throughout on the accompanying map. 19 E , W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction KOCKY Soil (Loces rock, concrete, masonry, Character, concrete, etc., number and size of openings) (b) Description of headgate 18 inch pipe. (Climber, concrete, etc., number and size of openings)	(If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the	4.	The point of diversion is located 395 ft. S and 80 ft. E from the NW
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the NE 1/4 NE 1/4 Of Sec. 6 , Tp. 41 S (Give smallest legal subdivision) 19 E , W. M., in the county of Lake (E. or W.) 5. The main ditch (Miles or feet)	(If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate abset if necessary) eing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (Give smallest legal subdivision) 2. 19 E , W. M., in the county of Lake (Rain ditch, canal or pipe line) to be 1960 feet (Miles or feet) In length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (Mines or feet) In length, terminating in the proposed location being shown throughout on the accompanying map. (Ex or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction KOCKY Soil (Loose rock, concrete, masonry, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take—off drivenpiump.		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (Give smallest legal subdivision) 19 E , W. M., in the county of Lake (E. or W.) 5. The main ditch (Main ditch, canal or pipe line) length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (More S.) 19 E , W. M., the proposed location being shown throughout on the accompanying map. (E. or W.) DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction rocky Soil (Cose rock, concrete, masonry, the and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	eing within the NE 1/4 NE 1/4 Of Sec. 6 Tp. 41 S (River shallest legal subdivision) 2. 19 E W. M., in the county of Lake (a. or w.) 5. The Main ditch canal or pipe line) 1. 19 E (Main etch, canal or pipe line) 1. 19 E (Miles or feet) 1. 19		(Section or subdivision)
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (Give smallest legal subdivision) 19 E , W. M., in the county of Lake (E. or W.) 5. The main ditch (Main ditch, canal or pipe line) length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (More S.) 19 E , W. M., the proposed location being shown throughout on the accompanying map. (E. or W.) DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction rocky Soil (Cose rock, concrete, masonry, the and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the NE 1/4 NE 1/4 Of Sec. 6 Tp. 41 S (Give smallest legal subdivision) 1. 19 E W. M., in the county of Lake (E. or W.) 5. The Main ditch (Main ditch, canal or pipe line) 1. 19 E (Miles or feet) 1. 1		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (Give smallest legal subdivision) 19 E , W. M., in the county of Lake (E. or W.) 5. The main ditch (Main ditch, canal or pipe line) length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (More S.) 19 E , W. M., the proposed location being shown throughout on the accompanying map. (E. or W.) DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction rocky Soil (Cose rock, concrete, masonry, the and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	eing within the NE 1/4 NE 1/4 Of Sec. 6 Tp. 41 S (N. or S.) 2. 19 E , W. M., in the county of Lake (E. or W.) 5. The Main ditch (Main ditch, canal or pipe line) (Miles or feet) n length, terminating in the SE 1/4 NE 1/2 of Sec. 6 Tp. 41 S (N. or S.) 2. 19 E , W. M., in the county of Lake (Miles or feet) n length, terminating in the SE 1/4 NE 1/2 of Sec. 6 Tp. 41 S (N. or S.) 2. 19 E , W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction FOCKY SOI1 (Loose rock, concrete, masonry, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) ing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (Give smallest legal subdivision) 19 E , W. M., in the county of Lake (E. or W.) 5. The main ditch (Main ditch, canal or pipe line) length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (More S.) 19 E , W. M., the proposed location being shown throughout on the accompanying map. (E. or W.) DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction rocky Soil (Cose rock, concrete, masonry, the and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	eing within the NE 1/4 NE 1/4 Of Sec. 6 Tp. 41 S (N. or S.) 2. 19 E , W. M., in the county of Lake (E. or W.) 5. The Main ditch (Main ditch, canal or pipe line) (Miles or feet) n length, terminating in the SE 1/4 NE 1/2 of Sec. 6 Tp. 41 S (N. or S.) 2. 19 E , W. M., in the county of Lake (Miles or feet) n length, terminating in the SE 1/4 NE 1/2 of Sec. 6 Tp. 41 S (N. or S.) 2. 19 E , W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction FOCKY SOI1 (Loose rock, concrete, masonry, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)		
ing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (Give smallest legal subdivision) (N. or S.) 19 E	(Give smallest legal subdivision) 19 E (N. or S.) 19 E (N. or W.) 5. The main ditch (Main ditch, canal or pipe line) (Miles or feet) (In length, terminating in the SE 1/4 NE 1/2 of Sec. 6, Tp. 41 S (N. or S.) 3. 19 E (Smallest legal subdivision) (E. or W.) (E. or W.) (DESCRIPTION OF WORKS DIVERSION WORKS DIVERSION WORKS Oct. and bright of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction KOCKY SOII (Loose rock, concrete, masonry, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Tumber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	•••••••	(If preferable, give distance and bearing to section corner)
ing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (Give smallest legal subdivision) (N. or S.) 19 E	eing within the NE 1/4 NE 1/4 of Sec. 6 , Tp. 41 S (Covers) 19 E , W. M., in the county of Lake (Ex or W.) 5. The main ditch (Main ditch, canal or pipe line) (Miles or feet) 10 length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (Smallest legal subdivision) (N. or S.) 11 E		(If there is more than one point of diversion, each must be described. Use separate sheet if necessary)
19 E , W. M., in the county of Lake (X. or W.) 5. The main ditch (Main ditch, canal or pipe line) to be 1960 feet (Main ditch, canal or pipe line) (Miles or feet) length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (Smallest legal subdivision) (N. or S.) 19 E , W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction rocky soil (Loose rock, concrete, masonry, canad brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	19 E	eina mit	
5. The	5. The		
length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (N. or S.) 19 E , W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction ROCKY Soil (Loose rock, concrete, masonry, Loose rock, concrete, masonry, concrete, etc., number and size of openings) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings)	n length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (Nors.) 1. 19 E , W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction Cocky Soil (Loose rock, concrete, masonry, Cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)) 19 (E. o	E , W. M., in the county of
length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (N. or S.) 19 E , W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction ROCKY Soil (Loose rock, concrete, masonry, Loose rock, concrete, masonry, concrete, etc., number and size of openings) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings)	n length, terminating in the SE 1/4 NE 1/2 of Sec. 6 , Tp. 41 S (Nors.) 1. 19 E , W. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction Cocky Soil (Loose rock, concrete, masonry, Cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	•	
DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction KOCKY SOIL (Loose rock, concrete, masonry, k and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction rocky soil (Loose rock, concrete, masonry, coke and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)		
DESCRIPTION OF WORKS version Works— 6. (a) Height of dam 9 feet, length on top 150 feet, length at bottom 150 feet; material to be used and character of construction KOCKY SOIL (Loose rock, concrete, masonry, k and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam9 feet, length on top150 feet, length at bottom 150 feet; material to be used and character of construction rocky soil (Loose rock, concrete, masonry, only soil and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18inchpipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power_take-off_drivenpump, (Size and type of pump)	ı length	terminating in the SE 1/4 NE 1/2 of Sec. 0, Tp. 41 5 (Smallest legal subdivision) (N. or S.)
6. (a) Height of dam feet, length on top feet, length at bottom	6. (a) Height of dam	219	E, W. M., the proposed location being shown throughout on the accompanying map.
6. (a) Height of dam feet, length on top feet, length at bottom	6. (a) Height of dam	O	E. or W.)
6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction	6. (a) Height of dam		
150 feet; material to be used and character of construction rocky soil (Loose rock, concrete, masonry, k and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	150 feet; material to be used and character of construction rocky soil (Loose rock, concrete, masonry, book and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 18 inch pipe (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)		
(b) Description of headgate	(b) Description of headgate		
(b) Description of headgate	(b) Description of headgate	150	feet; material to be used and character of construction
(b) Description of headgate	(b) Description of headgate		(Loose rock, concrete, masonry,
(c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	(c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	ock and bru	ısh, timber crib, etc., wasteway over or around dam)
(c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)	(c) If water is to be pumped give general description Power take-off drivenpump, (Size and type of pump)		
(Size and Gye of Pully)	(Size and type of pump)	, -	(Timber, concrete, etc., number and size of openings)
(Size and Gye of Pully)	(Size and type of pump)		
(Size and Gye of Pully)	(Size and Gye of yuniy)	(c) If water is to be pumped give general description Power take-off drivenpump.
b inch intake, 4 inch outlet, 32 norsepower			(Size and type of yamp)
(Size and type of engine or motor to be used, total head water is to be lifted, etc.)	(Size and type of engine or motor to be used, total head water is to be lifted, etc.)	b. i	nch intake, 4 inch outlet, 32 horsepower (Size and type of engine or motor to be used, total head water is to be lifted, etc.)

(g) If so, name stream and locate point of return

(h) The use to which power is to be applied is

(i) The nature of the mines to be served

, Sec., Tp., R., W. M. (No. N. or S.) (No. E. or W.)

10. (a) To supply the city of		3153
	oopulation of	
an estimated population of		
(b) If for domestic use state number of fa		
(Answer questions 11, 42,		. · ·
11. Estimated cost of proposed works, \$	(
12. Construction work will begin on or before.		•
13. Construction work will be completed on or		
· ·		
14. The water will be completely applied to the	proposed use on or before	n.n.t.\
	-)116 4. (asi	
•	(Signature of app	icant)
Remarks: Land to be sprinkler in	rigated. Moveable	hose to be u
		••••••
	4	·
***************************************		***************************************
		·
······································	·	,
		······································
	······································	
· · · · · · · · · · · · · · · · · · ·		••••••
	•••••••••••••••••••••••	***************************************
ATE OF OREGON,)		
County of Marion,		
This is to certify that I have examined the fo	regoing application, together	with the accompan
os and data, and return the same forCorrec	tion	•••••
In order to retain its priority, this application	must be returned to the State	Engineer. with co
is on or beforeJune 20th 1	0 -44	
August 22nd	66	I I 1966
October 18		
WITNESS my hand this20th day of	June	DREGON66
18th	August	
The same of the sa	CHRIS L. WHE	ELER
1 9 1966 F	/	STATE ENGIN

STATE OF OREGON, County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same,

SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:	
The right herein granted is limited to the amount of water which can be applied to beneficial us	e
and shall not exceed	e
stream, or its equivalent in case of rotation with other water users, from an unnamed drainage was	<i>I</i> .
and reservoir to be constructed under application No. R-42114, permit No. R-4787	
***************************************	••
The use to which this water is to be applied is irrigation	. .
If for irrigation, this appropriation shall be limited to1/80th of one cubic foot pe	
second or its equivalent for each acre irrigated from direct flow and shall be further limited	
to a diversion of not to exceed 22 acre feet per acre for each acre irrigated during	ıg
the irrigation season of each year from direct flow and storage from reservoir to	
be constructed under permit No. R- 4787	. .
	. -
	. .
	. .
and shall be subject to such reasonable rotation system as may be ordered by the proper state officer.	
The priority date of this permit is April 18, 1966 for 0.01 cfs, June 9, 1966 for 0.53	cfs
Actual construction work shall begin on or before February 7, 1968 and sha	L
thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 1968	,
Complete application of the water to the proposed use shall be made on or before October 1, 19.69.	. .
WITNESS my hand this 7th day of February, 1967.	
STATE ENGINEER	·•
	C
	. 1
PERMIT OPRIATE THE PUBLIC TRS OF THE STATE OF OREGON The Engineer at Salem, Oregon ay of April The Occock A M. The Occock A M. The Dook No. Book No. 31538 The Dook No. Book No. 31538 The Dook No. Book No. 31538 The Dook No. Book No. Book No. 31538	
TATE TATE TATE 1967 1967 1967 page 2 & page 2 &	
PERMIT PRIATE THE PUBI S OF THE STATE F OREGON The was first receive Soft of April The occor April The occup April The oc	
No. 400. STANIT IATE THE OF	•
PERMI PORIATE OF OREGA OF OF OREGA OF O	
PERMIT ROPRIATE THE PUBLIC ERS OF THE STATE OF OREGON ment was first received in the tate Engineer at Salem, Oregon, and of April Aday of April Aday of April Rebruary 7, 1967 February 7, 1967 This 1. Wheeler State engineer This 1. Wheeler This 1. T	

Application No. 42/15

Permit No.

PERMI

TO APPROPRIATE THE WATERS OF THE S

This instrument was first office of the State Engineer a

on the 18th, day of 1966, at . R. a.D. o'clock

Returned to applicant:

Approved:

Recorded in book No.

Permits on page

CENTS L. WH

Drainage Basin No. 13