CERTIFICATE NO: 4/662__

*APPLICATION FOR PERMIT

To Appropriate the Public Waters of the State of Oregon

tate of Oregon	I, Emory Moore (Name of applicant)	
tate of	f Kings Valley	······································
If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is 1. The source of the proposed appropriation is the source of the source, give quantity from each interest in the source of the source, give quantity from each interest in the source of the source, give quantity from each interest interest in the source of the source, give quantity from each interest inte	(Mailing address)	
1. The source of the proposed appropriation is Price Creek The source of the proposed appropriation is Price Creek The source of the proposed appropriation is Cream of decision of the source of the proposed appropriation is 1. The source of the proposed appropriation is 1. The use of which the applicant intends to apply to beneficial use is 1. 1. 2. 2. The amount of water which the applicant intends to apply to beneficial use is 1. 2. 2. The use to which the water is to be applied is 1. Trigation 1. Triga		
1. The source of the proposed appropriation is	ollowing described public waters of the State of Oregon, SUBJECT TO EXISTING RIG	HTS:
#3. The use to which the water is to be used from more than one source, give quantity from each) #3. The use to which the water is to be applied is #3. The use to which the water is to be applied is ((Frigation, power, mining, manufacturing, demestic supplies, etc.) #4. The point of diversion is located (2, 4182 ft. S. and 3770 ft. E. from the corner of most southerly southwest corner of the Samuel Rice DLC No. 45, said ((Section or subdivision) corner identified by stone monument, ((If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the Cr. NW. NEL C. K. S. N. S. N. N. N. S. of Sec. 27 , Tp. 10S. ((Citerwi) S. The buried tile ((Citerwi) M. M., in the county of Benton S. The buried tile ((Citerwi) M. M. the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works—Dismountable flashboard dam 6. (a) Height of dam 5! maximum, feet, length on top 20 feet, length at bottom of must be described. The sealers of the sealer	If the applicant is a corporation, give date and place of incorporation	
2. The amount of water which the applicant intends to apply to beneficial use is 1.9 which feet per second. (If water is to be used from more than one source, give quantity from each) ixtigation (It is interested power, mining, manufacturing, dementic supplies, etc.) **3. The use to which the water is to be applied is (Res 3175 5 2410 F F 72-77-67 4. The point of diversion is located on 4822 ft. S. and 3770 ft. E. from the C. e. e. e. of the Samuel Rice DLC No. 45. said corner of most southerly southwest corner of the Samuel Rice DLC No. 45. said corner identified by stone monuments. (If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the C. NW N. in the county of Benton (Core mailest legs subdivision) (Core w.) 5. The buried tile (Core mailest legs subdivision) (Corner of the Samuel Rice DLC No. 45. Said (Corne	1. The source of the proposed appropriation is $\frac{\text{Price Creek}}{\text{(Name of stream)}}$	eve in #8
whice feet per second. **3. The use to which the water is to be applied is in the use to which the water is to be applied is intrigation. The point of diversion is located at 4182 ft. S. and 3770 ft. E. from the corner of most southerly southwest corner of the Samuel Rice DLC No. 45, said corner identified by stone monuments. **Gill there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the **C**. NW\$_1 NE\$_2 ft. Res. NE\$_2 NW\$_1 of Sec. 27. Tp. 10S. (No. 78.) **Gill there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the **C**. NW\$_2 NE\$_2 ft. Res. NE\$_2 NW\$_1 of Sec. 27. Tp. 10S. (No. 78.) **Gill there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the **C**. NW\$_2 NE\$_3 ft. Sec. 27. Tp. 10S. (No. 78.) **Gill there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the **C**. NW\$_3 NE\$_4 ft. Sec. 27. Tp. 10S. (No. 78.) **Gill there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the **C**. NW\$_3 NE\$_4 ft. Sec. 27. Tp. 10S. (No. 78.) **Gill there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the **C**. NW\$_4 NE\$_4 ft. Sec. 27. Tp. 10S. (No. 78.) **Gill the sec. 28. (Mills each sec. 28. (Mill	, a tributary of Luckiamute	
**3. The use to which the water is to be applied is irrigation (consequence applied is consequence applied in the point of diversion is located at 122 ft. S. and 3770. ft. E. from the corner of conner of conner identified by stone monuments corner of the Samuel Rice DLC No. 45, said corner identified by stone monuments. (If there is more than one point of diversion, each must be described. The separate sheet if necessary) eing within the C. NWA NEL RES. NELS NEW OF Sec. 27 Tp. 10S. (Che smallest legal subdivision) (the country of consequence approximately approximate	2. The amount of water which the applicant intends to apply to beneficial use is	1.9
**3. The use to which the water is to be applied is irrigation (trigation, power, mining, manufacturing, domestic supplies, etc.) **Res 3175	ubic feet per second	······································
4. The point of diversion is located on 4182 ft. S. and 3770 ft. E. from the corner of most southerly southwest corner of the Samuel Rice DLC No. 45, said corner identified by stone monument, (If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the Cr. NW4 NF4 Res. NE/2 NW/3 of Sec. 27, Tp. 10S (Give mullest ignal subdivision) for corw.) 5. The buried tile to be approximately 1 mile total (Main ditch, canal or pipe line) SW4 NW2 Sec. 22 (Mines or feet) n length, terminating in the NF4 NW3 Sec. 27. and (M. or s.) c. Give. N. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— Dismountable flashboard dam 6. (a) Height of dam 5! maximum, feet, length on top 20 feet, length at bottom Oin winter when boards are removed 20 feet; material to be used and character of construction Reinforced concrete. (Goose rock, concrete, masonry, cost and brush, tumber crib, etc. wateway over or around dam) (b) Description of headgate 10 the same and size of opening) flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description S F SH Rainmaster Centrifgul	**3. The use to which the water is to be applied isirrigation	
4. The point of diversion is located 4.4182 ft. S. and 3770 ft. E. from the corner of most southerly southwest corner of the Samuel Rice DLC No. 45, said (Section or subdivision) corner identified by stone monuments (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the C. NW4 NE4 ft. NE5 NE/4 NEW/10 f Sec. 27 , Tp. 10S (Citive smallest legal subdivision) 5. The buried tile. (Real dich. canal or pipe line) (Real dich. ca		-
corner of most southerly southwest corner of the Samuel Rice DIC No. 45, said (Bection or subdivision) corner identified by stone monument, (If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the C: NW-1 NF-1 Res NE/4 NW-1 of Sec. 27 Tp. 108 (Give smallest legal subdivision) 5. The buried tile (Main ditch, canal or pipe line) Main ditch, canal or pipe line) (Simallest legal subdivision) (R. or W.) (Simallest legal subdivision) (R. or W.) (R. or W.) DESCRIPTION OF WORKS Diversion Works— Dismountable flashboard dam 6. (a) Height of dam 5! maximum, feet, length on top 20 feet, length at bottom Oin winter when boards are removed 20 feet; material to be used and character of construction Reinforced.concrete, masonry Steel braces and timber used in removable section. (b) Description of headgate 10" tile opening installad in concrete headwall of (Timber, concrete, tec., number and size of openings) flashboard dam, Stiding gate valve installed on face of headwall.	Res 3175 S 2410 E	H- 2-17-67
(If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate about it necessary) eing within the Cr. NW No. No. (Give smallest legal subdivision) (If we mallest legal subdivision) (If we we mallest legal subdivision) (If we mallest legal subdivision (If we mallest legal subdivision) (If we mallest legal subdivision (If we mallest legal subdivision) (If we mallest legal subdivision	4. The point of diversion is located 6. 4182 ft. S and 3770 ft. E ft. (N. or s.)	om the
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) eing within the Cr. NW2 NE2 FRS NE/4 NW/2 of Sec. 27 Tp. 108 (Give maliest legal subdivision) //- 2-17-67 (Give maliest legal subdivision) //- 2-	(Section or subdivision)	
eing within the C. NW NE NE RES NES NES NES NES NES NES NES NES NES N	corner identified by stone monument,	
eing within the C. NW NE NE RES NES NES NES NES NES NES NES NES NES N		*
eing within the Cr. NW-1 NE-1 Kes NEW NW/1 of Sec. 27 Tp. 108 (Give smallest legal subdivision) 1.		•
eing within the Cr. NW1 NE1 to Res. NE1 NW1 of Sec. 27 Tp. 108 (Give smallest legal subdivision) // 2-17-67 (M. or 8.) 6	(If preferable, give distance and bearing to section corner)	•
Steel braces and timber used in removable section. (Korw) Steel braces and timber used in removable section. Steel braces and timber used in removable section. (Corw) Steel braces and timber crib, etc., wasteway over or around dam) (Corw) Steel braces and timber used in removable section. (Corw) Steel braces and timber used in removable section. Steel braces and timber used in removable section. (Corw) Steel braces and timber used in removable section. Steel braces and timber used in removable section. (Corw) Steel braces and timber used in removable section. (Corw) Steel braces and timber used in removable section. (Corw) (Corw) Steel braces and timber used in removable section. (Corw) (Corw) Steel braces and timber used in removable section. (Corw) (Corw) Steel braces and timber used in removable section. (Corw) (Corw) Steel braces and timber used in removable section. (Corw) (Corw) (Corw) Steel braces and timber used in removable section. (Corw) (Corw) (Corw) Steel braces and timber used in removable section. (Corw) (Corw) (Corw) (Corw) (Corw) Steel braces and timber used in removable section. (Corw)		
Some substituting in the country of section shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— Dismountable flashboard dam 6. (a) Height of dam 5! maximum. feet, length on top 20 feet; material to be used and character of construction seck and brush. timber crib, etc., wasteway over or around dam) (b) Description of headgate 10" tile opening installed in concrete headwall of concrete, stc., number and size of openings) flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description S F 5H Rainmaster Centrifgul (Size and type of pump)		10S (N. or S.)
DESCRIPTION OF WORKS Diversion Works— Dismountable flashboard dam 6. (a) Height of dam 5. maximum, feet, length on top 20 feet, length at bottom O in winter when boards are removed feet; material to be used and character of construction Reinforced concrete. Cloose rock, concrete, masonry. Steel braces and timber used in removable section. (b) Description of headgate 10" tile opening installed in concrete headwall of (Timber, concrete, etc., number and size of openings) flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description S F 5H Rainmaster Centrifgul (Size and type of pump)	, W. M., in the county ofBenton	
DESCRIPTION OF WORKS Diversion Works— Dismountable flashboard dam 6. (a) Height of dam 5. maximum, feet, length on top 20 feet, length at bottom O in winter when boards are removed feet; material to be used and character of construction Reinforced concrete. Cloose rock, concrete, masonry. Steel braces and timber used in removable section. (b) Description of headgate 10" tile opening installed in concrete headwall of (Timber, concrete, etc., number and size of openings) flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description S F 5H Rainmaster Centrifgul (Size and type of pump)	5. The buried tile to be approximately	l mile total
DESCRIPTION OF WORKS Diversion Works— Dismountable flashboard dam 6. (a) Height of dam 5 maximum, feet, length on top 20 feet, length at bottom 7 in winter when boards are removed 20 feet; material to be used and character of construction Reinforced concrete. Cloose rock, concrete, masonry. Steel braces and timber used in removable section. Steel braces and timber used in removable section. (b) Description of headgate 10" tile opening installed in concrete headwall of (Timber, concrete, etc., number and size of openings) flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description S F 5H Rainmaster Centrifgul (Size and type of pump)	(Main ditch, canal or pipe line) SW ¹ / ₄ NW ¹ / ₅ Sec. 22 Sec. 22 True length terminating in the NF ² / ₄ NW ¹ / ₄ Sec. 27 and of Sec. True	105
DESCRIPTION OF WORKS Diversion Works— Dismountable flashboard dam 6. (a) Height of dam 5. maximum, feet, length on top feet, length at bottom 75 feet; material to be used and character of construction Reinforced concrete, (Loose rock, concrete, masonry) Steel braces and timber used in removable section. (b) Description of headgate 10" tile opening installed in concrete headwall of (Timber, concrete, etc., number and size of openings) flashboard dam. Stiding gate valve installed on face of headwall. (c) If water is to be pumped give general description S F 5H Rainmaster Centrifgul (Size and type of pump)		
6. (a) Height of dam 5 maximum, feet, length on top 20 feet, length at bottom 0 in winter when boards are removed 20 feet; material to be used and character of construction Reinforced concrete. (Loose rock, concrete, masonry, Steel braces and timber used in removable section. (b) Description of headgate 10 tile opening installed in concrete headwall of (Timber, concrete, etc., number and size of openings) flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description S F 5H Rainmaster Centrifgul (Size and type of pump)	\mathbf{C}	nying map.
6. (a) Height of dam 5! maximum, feet, length on top 20 feet, length at bottom 0 in winter when boards are removed 20 feet; material to be used and character of construction Reinforced concrete. Steel braces and timber used in removable section. (Loose rock, concrete, masonry, cock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate 10" tile opening installed in concrete headwall of (Timber, concrete, etc., number and size of openings) flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description SF 5H Rainmaster Centrifgul (Size and type of pump)	DESCRIPTION OF WORKS	
feet; material to be used and character of construction Reinforced concrete. (Loose rock, concrete, masonry, Steel braces and timber used in removable section. (b) Description of headgate		•
Steel braces and timber used in removable section. (b) Description of headgate	6. (a) Height of dam 5. maximum, feet, length on top	ength at bottom
(b) Description of headgatelo" tile opening installed in concrete headwall of(Timber, concrete, etc., number and size of openings) flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description SF 5H Rainmaster Cenrtrifgul (Size and type of pump)	feet; material to be used and character of constructionReinforced	concrete, masonry
flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description SF 5H Rainmaster Cenrtrifgul		
(c) If water is to be pumped give general description S F 5H Rainmaster Cenrtrifgul	(b) Description of headgate 10" tile opening installed in concrete	headwall of
	(Timber, concrete, etc., number and size of openings)	usauna++
Q HP Ford Gaspline 1301		
	flashboard dam. Sliding gate valve installed on face of headwall. (c) If water is to be pumped give general description S F 5H Rainmaster (Size and type of pumped)	Cenrtrifgul

^{*}A different form of application is provided where storage works are contemplated.

adgate. At hea	dgate: width or	ı top (at water lin	e)	feet; width on bottom	
••••	feet; depth of water feet; grade			feet fall per one	
ousand feet. (b) At		. miles from head	gate: width on top (at wa	ter line)	
	feet; width on	bottom	feet; depth of	water feet;	
		ll per one thousan	d feet.	•	
	lay tile h of %% ,	4600 ft.; siz	e at intake, 10	in.; size at5000 ft.	
om intake	8 in	; size at place of u	ıse8 in.; c	lifference in elevation between	
take and place	of use,65	ft. Is g	rade uniform? yes, by	section Estimated capacity,	
	,		•	accumulation reservoirs.	
8. Location				<u>3</u>	
Township North or South	Range E. or W. of Willemette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated	
108	6N	21	SEA SEA	13.0	
108	6W	21	NE SE	17.0	
108	6W	22	SW ¹ / ₄ SW ¹ / ₄	3,0	
108	6W	22	NW SW SW	22.0	
105	6W	22	SW NW	8.0	
108	6W	22	SEZ NWZ	4.0	
105	6W	22 3,	NE & SW&	22.0	
105	6W	22	SE ² SW ²	27.0	
105	6W	22	SW ¹ SE ¹	20.0	
<u> 105</u>	6W	27	NW ² NW ²	1.0	
10S	6W	27	$NE_4^1 NW_4^1$	7.0	
105	6N	27	NW- NE-	8.0 Total 152.	
(a) Ch	naracter of soil .				
(b) K	ind of crops rais	ed <u>f</u> o	rage	6	
ower or Minin		,	-		
9. (a) To	otal amount of p	ower to be develo	ped	theoretical horsepower.	
(b) Q	uantity of water	to be used for por	ver	sec. ft.	
(c) To	otal fall to be ut	ilized	(Head)		
			•	oe developed	
			•		
(e) Si				of Sec.	
		, W. M.	(Legal subdivision)		
	•	.E. or W.) urned to any strea	im?	•	
			•		
				, R, W. M.	
			(No. N. or S.	.) (No. E. or W.)	
(h) T	he use to which	power is to be ann	olied is		

funicipal or Domestic Supply— 10. (a) To supply the city of	and the second s		31730
,	•		***************************************
(Name of)			
nd an estimated population of			•
(b) If for domestic use st	ate number of families to	be supplied	
	(Answer questions 11, 12, 13, and 14 in		
11. Estimated cost of proposed	works, \$	1	
12. Construction work will be	gin on or beforeAugus	t 1965	
13. Construction work will be	completed on or before	July 1966	
14. The water will be complete	ely applied to the proposed	use on or before Fall	1967
		<u> </u>	
	(Linus	(Signature of applicant)	<i>0</i>
	.,	(Signature of applicant)	
Remarks: The diversion	system and accumula	ion reservoirs are p	eart of an
integrated water control	and use system that a	also involves the fol	lowing:
Permit No. 12907; Permit	,		
for Maxfield Creek draina	· · ·		
	90 1110012 04 20 11100		,
application.			•
ine pumping	points for field dis	stribution by sprinkl	ers are
located at the reservoirs		***************************************	
,		***************************************	,
		· .	***************************************
•			
			· · · · · · · · · · · · · · · · · · ·

	······································		·
TATE OF OREGON,)	•	•	
County of Marion, ss.		•	
This is to certify that I have	e examined the foregoing	application, together with	the accompany
aps and data, and return the same	76		
apo ana adua, ana revario ine dani		,	
	a		
In order to retain its priority		**	nnee r , with corr
ions on or before	, 19	and the second second	
		i	•
WITNESS my hand this	•		, 19
		e de la companya de	
range r			
	<u></u>		STATE ENGINEE

STATE OF OREGON,

County of Marion,

ss.

This instrument was first received in the

TO APPROPRIATE THE PUBLIC WATERS OF THE STATE

PERMIT

OF OREGON

office of the State Engineer at Salem, Oregon,

on the 26 Th day of Muy

19 66 at 1.31 o'clock

Returned to applicant:

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use
and shall not exceed
stream, or its equivalent in case of rotation with other water users, from Price Creek and
reservoir to be constructed under application No. R-42258, permit No. R-4820
The use to which this water is to be applied is <u>irrigation</u>

If for irrigation, this appropriation shall be limited to
second or its equivalent for each acre irrigated from direct flow and shall be further limited
*
to a diversion of not to exceed 2 acre feet per acre for each acre irrigated during
the irrigation season of each year from direct flow and storage from reservoir to be
constructed under permit No. R-4820
and shall be subject to such reasonable rotation system as may be ordered by the proper state officer.
The priority date of this permit is May 26, 1966
Actual construction work shall begin on or before March 23, 1968 and shall
thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 19.68
Complete application of the water to the proposed use shall be made on or before October 1, 1969
WITNESS my hand this23rd day of
ekin Lordon
STATE ENGINEER

70

Application No. 42259

Permit No. 31730

State Printing 98137

CHRIS L. WHEELER.

March 23, 1967

Approved:

Recorded in book No.

Permits on page

page 184

Drainage Basin No.