

*APPLICATION FOR PERMIT

CERTIFICATE NO. 38558

To Appropriate the Public Waters of the State of Oregon

of Star Route, Box 439, Shady Cove. (Reliable address) State of ORSON 97539 , do hereby make application for a permit to appropriate the following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS: If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is			applicant)	
State of	of Star Route,	Box 439, Shady (Cove,	
following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS: If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is ROGIR RIVEX (Stems of tream) 2. The amount of water which the applicant intends to apply to beneficial use is Q.Q.L. cubic feet per second. (It water is to be used from more than one source, give quantity from such) **3. The use to which the water is to be applied is IXILERATION. (It water is to be applied is IXILERATION. 6. The point of diversion is located 35Q. ft. Se. and 47Q. ft. We. from the NX. corner of SeQULION. 15. (It there is more than one spinit of diversion, seed must be described. The separate sheet if necessary) (If there is more than one spinit of diversion, seed must be described. The separate sheet if necessary) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is more than one spinit elegal subdivision) (If there is to be pumped give general description 1½" Suction X 1" discharge (the not tree to pump)	• • • • • • • • • • • • • • • • • • • •	·	y make application	for a permit to appropriate
1. The source of the proposed appropriation is ROGUE RIVER Oftens of reason, a tributary of Pacific Ocean. 2. The amount of water which the applicant intends to apply to beneficial use is Q.Q.L. cubic feet per second. (It water is to be used from more than one source, give quantity from each) **3. The use to which the water is to be applied is ITTIGATION (Creation, power, mining, manufactures, despets supplies, etc.) 4. The point of diversion is located JSQ. ft. S. and HZQ. ft. W. from the NA C. or W.) from the NA C. or W.) (It preferable, give distance and bearing to metion corner) (It there is more than one point of diversion, sects must be described. Use separate abset it necessary) being within the NEW NWW Of Sec. 15, Tp. 34 S. OK. or S.) R. L. W. W. M., in the county of J.B.Q.K.S.Q.L. (It was a manufactures of the county of J.B.Q.K.S.Q.L. (It was a manufacture of the county of J.B.Q.K.S.Q.L. (It was a manufacture of the county of Sec. 15, Tp. 34 S. OK. or S.) (It can w.) (It manufacture of the county of Sec. 15, Tp. 34 S. OK. or S.) (It can w.) (It manufacture of the county of Sec. 15, Tp. 34 S. OK. or S.) (It can w.) (It manufacture of the county of Sec. 15, Tp. 34 S. OK. or S.) (It can w.) (It manufacture of the county of Sec. 15, Tp. 34 S. OK. or S.) (It can w.) (It manufacture of the county of Sec. 15, Tp. 34 S. OK. or S.) (It can w.) (It manufacture of the county of Sec. 15, Tp. 34 S. OK. or S.) (It can w.) (It was a triple of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose reck, concrete, manner, reck and brush, tumber or the ease and character of construction (Loose reck, concrete, manner, other of the sec.) (It was not trye of pump)				
1. The source of the proposed appropriation is ROGUS RIVER Common of stream a tributary of PROLICE OCCUM. 2. The amount of water which the applicant intends to apply to beneficial use is O.O. Cubic feet per second. (If water is to be used from more than one source, give quantity from each) **3. The use to which the water is to be applied is ITTIGATION (trigation, power mining, manufacturing, domestic supplies, six) 4. The point of diversion is located 350 ft. S. and 470 ft. W. from the NY CR or W.) (If there is more than one point of diversion, each must be described. Was separate sheet if mecassary) being within the NEW Of Sec. 15, Tp. 34, S. (Ch. or S.) (If there is more than one point of diversion, each must be described. Was separate sheet if mecassary) being within the NEW NEW Of Sec. 15, Tp. 34, S. (Ch. or S.) R. J. W. M., in the county of J.B.Q.K.S.O.R. S. The Octaon disk, cannot or post uses) (In length, terminating in the NEW NEW M.) (Chan disk, cannot or post uses) (Ch. or S.) Diversion Works— (Ch. or H.) DESCRIPTION OF WORKS Diversion Works— (Ch. or H.) (•		
(If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If there is more than one spoint of diversion, each must be described. The separate about it increasery) (If there is more than one spoint of diversion, each must be described. The separate about it increasery) being within the NEW NEW of Sec. 15., Tp. 34 S.s., (R. or s.). (R. or w.). From the NEW OKASONA. (E. or w.). Dipeline to be 250 feet (Selles or read-obstination) Dipeline to be 250 feet (Selles or read-obstination) DESCRIPTION OF WORKS Diversion Works— (a) Height of dam feet, cannot dam) (b) Description of headgate (Chainer and description 1½", Suction X 1" discharge (Site and type of pump) (C. or s.).	if the applicant is a corp	poration, give date and pi	асе ој тсогрогано	n
(If preferable, give distance and bearing to section corner) (If there is more than one source) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If preferable, give distance and bearing to section corner) (If there is more than one source) (If preferable, give distance and bearing to section corner) (If there is more than one source) (If there is more than one point of direction, each must be described. The september there is no the section corner) (If there is more than one point of direction, each must be described. The section corner) (If there is more than one point of direction, each must be described. The september there is necessary) being within the NEW NEW of Sec. 15 , Tp. 34 Se. (No c s.) (If year mallering landwister) 5. The Distance and the country of Jackson. (If year mallering in the Country of year of give of years of y	1. The source of the pro	posed appropriation is	Rogue	River
2. The amount of water which the applicant intends to apply to beneficial use isQ.Ql		a tributar		
cubic feet per second. (If water is to be used from more than one source, give quantity from each) **3. The use to which the water is to be applied is				
4. The point of diversion is located 350 ft S. and 470 ft M. from the NK corner of Section of substitution (Bection of substitution) (If preferable, give distance and bearing to section corner) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the (Give smallers legal subdivision) 7. The Diversion of Sec. 15 Tp. 34 S. (Cit. or s.) 5. The Diversion of MEK NWM of Sec. 15 Tp. 34 S. (Cit. or s.) 1. W. (Cit. or w.) 5. The (Galler legal subdivision) 6. (a) Height of dam (Galler legal subdivision) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Geometric, masonry, reck and brush, timber cith, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and sais of openings) (c) If water is to be pumped give general description 112 Suction x 1 discharges	·			
(If there is more than one point of diversion is located 350 ft. S. and 470 ft. M. from the NX (R. or W.) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NX (Give smallest legal subdivision) of Sec. 15 , Tp. 34 S , (R. or W.) 7. The pipeline to be 250 feet (Asia dich, canal or pipe line) in length, terminating in the NEX NW (S. or S.) (C. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose reck, concrete, masoner, rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 112 Suction x 1" discharge	cubic feet per second.	(If water is to be used fro	om more than one source, g	ive quantity from each)
Corner of Section 15 (Section or subdivision) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NEW NW of Sec. 15, Tp. 34 S. (S. or S.) R. 1 W. NW, in the country of Jackson. S. The Dipeline to be 250 feet (Main dich, canal or pipe line) (Main of Sec. 15, Tp. 34 S. (N. or S.)) In length, terminating in the NEW NW of Sec. 15, Tp. 34 S. (N. or S.) R. 1 W. NW, which is the proposed location being shown throughout on the accompanying map. C. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, tumber orb, etc., wasteway over or acound dam) (b) Description of headgate (Tumber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" Suction x 1" discharge (Size and type of pumps)	**3. The use to which the	water is to be applied is	îr) (Irrigation, power, min	rigation ing, manufacturing, domestic supplies, etc
Corner of Section 15 (Section or subdivision) (If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NEW NW of Sec. 15, Tp. 34 S. (Cive smallest legal subdivision) of Sec. 15, Tp. 34 S. (Cive s.) R. 1 W. NW, in the county of Jackson. 5. The Dipeline to be 250 feet (Male or feet) in length, terminating in the NEW NW of Sec. 15, Tp. 34 S. (N. or s.) R. 1 W. NW of Sec. 15, Tp. 34 S. (N. or s.) Dipeline to be 250 feet (Smallest legal subdivision) of Sec. 15, Tp. 34 S. (N. or s.) R. 1 W. NW of Sec. 15, Tp. 34 S. (N. or s.) R. 1 W. Sec. 15, Tp. 34 S. (N. or s.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, tumber orth, etc., wasteway over or around dam) (b) Description of headgate (Tumber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" Suction x 1" discharge (Size and type of pumps)	4. The point of diversion	m is located 350 ft.	S. and 470	ft We from the NY
(If there is more than one point of diversion, each must be described. Use separate abset if necessary) being within the				,
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the NEW NEW of Sec. 15, Tp. 34 Sec., (R. or 8.) R. 1 We, W. M., in the county of Jacksone (E. or W.) Dipeline to be 250 feet (Main ditch, canal or pipe line) to be 250 feet (Main er feet) in length, terminating in the NEW NEW of Sec. 15, Tp. 34 Sec., (R. or 8.) R. 1 We, W. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" Suction x 1 discharge (Size and type of pump)	corner of	Section 15 (Section	or subdivision)	
being within the NEW NWW of Sec. 15 , Tp. 34 S. (Give smallers legal subdivision) R. 1 W. M., in the county of JECKSOR. 5. The Dipeline to be 250 feet (Main ditch, canal or pipe line) in length, terminating in the NEW NWW of Sec. 15 , Tp. 34 S. (N. or 8.) R. 1 W. M. M., the proposed location being shown throughout on the accompanying map. DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonary.) rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" Suction X 1" discharge (Size and type of pump)		(If preferable, give distance and b	earing to section corner)	
R				
in length, terminating in the NE% NW% of Sec. 15, Tp. 34 S. (Smallest legal subdivision) of Sec. 15, Tp. 34 S. (N. or S.), R. 1 W. (K. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" Suction x 1" discharge (Size and type of pump)				
in length, terminating in the NE% NW% of Sec. 15, Tp. 34 S. (Smallest legal subdivision) of Sec. 15, Tp. 34 S. (N. or S.), R. 1 W. (K. or W.) DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" Suction x 1" discharge (Size and type of pump)	5. The	pipeline	to be	250 feet
R	in langth terminating in the	Main ditch, canal or pipe line) NF.14 NW14	of San	(Miles or feet)
DESCRIPTION OF WORKS Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" suction 1" discharge (Size and type of pump)			,	
Diversion Works— 6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" suction x 1" discharge (Size and type of pump)	R, W, W. M., th (E. or W.)	e proposed location being	shown throughout	on the accompanying map.
6. (a) Height of dam feet, length on top feet, length at bottom feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" suction x 1" discharge (Size and type of pump)		DESCRIPTION	or works	
feet; material to be used and character of construction (Loose rock, concrete, masonry, rock and brush, timber crib, etc., wasteway over or around dam) (b) Description of headgate (Timber, concrete, etc., number and size of openings) (c) If water is to be pumped give general description 1½" suction x 1" discharge (Size and type of pump)	*		_	
(b) Description of headgate		•	_	• • •
(b) Description of headgate	feet; materia	l to be used and character	of construction	(Loose rock, concrete, mas
(b) Description of headgate	make and house tenhan order ato Wrotaway	mer or amund dam)		
(c) If water is to be pumped give general description 1½" suction x 1" discharge (Size and type of pump)	(b) Description of head	laate		
(c) If water is to be pumped give general description 1½" suction x 1" discharge (Size and type of pump)	(0, 2, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3, 3,			
	(c) If water is to be pu			tion x 1" discharge
	centrifugal, 1% H.F	electric motor	e de la	Mad ata
Total lift + 20 feet.		,		

^{*}A different form of application is provided where storage works are contemplated.

^{**}Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the Hydroelectric Commission. Either of the above forms may be secured, without cost, together with instructions by addressing the Stete Engineer, Salem,

Canal System or P	ipe Line—			33546
•	-	each point of c	anal where materially cho	inged in size, stating miles from
eadgate. At head	gate: width on	top (at water l	ine)	feet; width on botton
f	eet; depth of w	ater	feet; grade	feet fall per on
housand feet.				ater line)
f	eet; width on b	ottom	feet; depth o	of water feet
rade	feet fall	per one thouse	and feet.	
(c) Length	of pipe,250) ft.; s	rize at intake,2"	in.; size at f
rom intake	in.;	size at place of	usein.;	difference in elevation betwee
ntake and place o	of use,	ft. Is	grade uniform?	No. Estimated capacity
0.01		to do Vicini	•	
o. Location	Range	rigatea, or pla	ce of use	
Township North or South	E. or W. of Willemette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated
34 S.	ı W.	15	NE¼ NW¼	0.6
		,	*	
			·	
· 			· 	
				1.2
4 > 4			equired, attach separate sheet)	
(b) Kin Power or Mining		i	Lawn and gard	en.
_	_	wer to be dev e	loped	theoretical horsepowe
(b) Qua	intity of water i	to be used for p	ower	sec. ft.
			feet.	·
			•	be developed
(-	.	-	
(e) Suc				of Sec
Tp(No. N. or S.)				
			eam?	
			(100 00 00)	
		-	-	
				, R, W, W

By

STATE OF OREGON, County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use and shall not exceed						
stream, or its equivalent in case of rotation with other w						
The use to which this water is to be applied is irr	•					
If for irrigation, this appropriation shall be limited second or its equivalent for each acre irrigated and shall	to1/80th of one cubic foot per					
not to exceed $4\frac{1}{2}$ acre feet per acre for each a	•					
season of each year,	·					
· · · · · · · · · · · · · · · · · · ·						
·						
and shall be subject to such reasonable rotation system as	may be ordered by the proper state officer.					
The priority date of this permit is	May 3, 1968					
Actual construction work shall begin on or before						
thereafter be prosecuted with reasonable diligence and b	e completed on or before October 1, 19.70					
Complete application of the water to the proposed u	use shall be made on or before October 1, 1971					
WITNESS my hand this20th day of	January , 19 69					
	CK - The STATE ENGINEER					

This instrument was first received in the

TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON

PERMIT

Permit No. 33546

Application No. 44

office of the State Engineer at Salem, Oregon,

1968, at 8:00 o'clock A

Returned to applicant:

on the 3rd day of Ma

.

State Printing 98137

CHRIS L. WHEELER STATE ENGINEER

Drainage Basin No. 15

January 20, 1969

Approved:

Recorded in book No. ...

Permits on page