

CERTIFICATE NO: 42632 \*APPLICATION FOR PERMIT ASSIGNED, See Misc. Rec., Vol. 5

## To Appropriate the Public Waters of the State of Oregon

1, NODER U. F. a. MILLIKAN AND WITE, MARSA. (Name o	ret E. Millikar fapplicant)	l	***********	*************************
of Box 100 Whistlers Lane Roseburg, Oregon	97470		***************************************	
State of Oregon, do hereb	y make applicatio	n for a per	mit to a	ppropriat <b>e th</b> e
following described public waters of the State of Oreg	on, SUBJECT TO	EXISTINO	RIGH:	TS:
If the applicant is a corporation, give date and p	lace of incorporati	ion		
				7
1. The source of the proposed appropriation is	North Umpqua F	(Name of stream	n)	·····
, a tributa	ry ofUmpqua.	River		***************************************
2. The amount of water which the applicant inte				0.03
cubic feet per second. (If water is to be used fi	rom more than one source,	give quantity fo	rom each)	••••••
**3. The use to which the water is to be applied is	Irrigation	1	*************	
	(Irrigation, power, mi	ning, manuracti	ring, domes	mc supplies, etc.)
4. The point of diversion is located800 ft.	S and70	OftW	fro1	m theNE
corner of Section 16 (Section	n or subdivision)	·····	<b></b>	······
	***************************************	•••••	•=======	•
(If preferable, give distance and  (If there is more than one point of diversion, each must being within theNE	be described. Use separate of Sec.	e sheet if necess		26 S,
(a. 02 17.)		•		
5. Thepipeline(Main ditch, canal or pipe line)			•	
in length, terminating in the $NE_{11}^{\perp}NE_{12}^{\perp}$ (Smallest legal subdivision)	of Sec	16	, Tp	
R. $\frac{4 \text{ W}}{\text{(E. or W.)}}$ , W. M., the proposed location being	shown throughou	t on the acc	ompany	ing map.
DESCRIPTION	i			
Diversion Works—				
6. (a) Height of dam feet, len	gth on top		feet, len	gth at bottom
feet; material to be used and character	of construction		(Loose rock	, concrete, masonry,
rock and brush, timber crib, etc., wasteway over or around dam)	····· <del>;······</del>	•••••	*******************************	•••••••••••••••••••••••••••••••••••••••
(b) Description of headgate	nber, concrete, etc., numbe	er and size of op	enings)	······
(c) If water is to be pumped give general descrip				
(Size and type of engine or motor to be used	ugal horizon total head water is to be	lifted, etc.)	estag	ebawb
			***********	•••••••••••••••••••••••••••••••••••••••

~ 1	<b>~</b> ,		<b>~</b> :	
('anai	System	Or.	Pine	l.ino
Cana	C A D CCTT	O.	1 100	T1111C

gate. At hea	dgate: width on t	op (at water li	ne)	feet; width on bo
sand feet.				feet fall per
(b) At	1	niles from head	lgate: width on top (at w	ater line)
•••••	feet; width on bo	ttom	feet; depth o	f water
e	feet fall	per one thousa	nd feet.	
(c) Lengt	h of pipe,	ft.; si	ze at intake,	in.; size at
intake	in :	size at place of	use in:	difference in elevation betu
		jt. 18 g	уғаае ингуотт:	Estimated capa
8. Location		rigated, or plac	e of use	
Township	Range			
North or South	Williamette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated
26 S	4 W	16	NE <sup>±</sup> NE <sup>±</sup>	2.5
				· · · · · · · · · · · · · · · · · · ·
		٠ [.	•	
		· ·		
	·			
	1	1		
		(If more space re-	quired, attach separate sheet)	
(a) Ch	naracter of soil	pulmice - 1	Loam	
(b) K	ind of crops raised	lawn and	i pasture	
	g Purposes—		!	:
9. (a) To	otal amount of por	wer to be devel	oped	theoretical horsepo
(Ъ) Q:	uantity of water t	o be used for po	wer	sec. ft.
			i i	,
			(Head)	
(d) T	he nature of the u	orks by means	of which the power is to	be developed
·	•••••••••••••••••••••••••••••••••••••••		·	
(e) Si	uch works to be lo	cated in		of Sec.
	, R			•
•				
			am?(Yes or No)	•
(g) If				
	,	Sec	, Tp	, R, No. M. or W.)

Municipal or Domestic Supply—	::// !
10. (a) To supply the city of	04003
	at population of
id an estimated population of 4	1
(b) If for domestic use state number of	families to be supplied
% % % % % % % % % % % % % % % % % % %	ત્ છ જ
•	12, 13, and 14 in all cases)
11. Estimated cost of proposed works, \$l. Qb	39.400
12. Construction work will begin on or before	started
13. Construction work will be completed on o	r beforeas law allows
14. The water will be completely applied to th	e proposed use on or beforeas.law.allows
Remarks: I, the applicat <del>ion</del> , have	Actest MilleRace' (Signature of applicant) Mugaset E. MilleRan) been informed of the State Water
	Umpqua River and its tributaries.
	······································
Enclosed: (1) map, copy L. D.*, applic	eation, \$20.00 check payable to the
State Engineer.	
	ich the # corner of Sec. 15 & 16. Two 26S.
8.4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to	North Umpqua River; thence N. 84 degrees ank of the said River, upstream, to a sold a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less,
R. 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51! W., 200 ft. to the point of begin	North Umpqua River; thence N. 84 degrees ank of the said River, upstream, to a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less,
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51! W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in	North Umpqua River; thence N. 84 degrees ank of the said River, upstream, to a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R 4W, WM bears, S. 28 degrees 13' E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in	North Umpqua River; thence N. 84 degrees ank of the said River, upstream, to a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R. 4W, WM bears, S. 28 degrees 13' E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in	North Umpqua River; thence N. 84 degrees ank of the said River, upstream, to a sold iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in	North Umpqua River; thence N. 84 degrees ank of the said River, upstream, to a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R 4W, WM bears, S. 28 degrees 13' E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in	North Umpqua River; thence N. 84 degrees ank of the said River, upstream, to a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,	North Umpqua River; thence N. 84 degrees ank of the said River, upstream, to a sold iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the	Jorth Umpqua River; thence N. 84 degrees and of the said River, upstream, to a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51! W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	Jorth Umpqua River; thence N. 84 degrees and of the said River, upstream, to a sold a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51! W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	North Umpqua River; thence N. 84 degrees and of the said River, upstream, to a a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.
R 4W, WM bears, S. 28 degrees 13' E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	North Umpqua River; thence N. 84 degrees and of the said River, upstream, to a a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.  foregoing application, together with the accompanying must be returned to the State Engineer, with correct on must be returned to the State Engineer, with correct on must be returned to the State Engineer, with correct on must be returned to the State Engineer, with correct on must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer.
R 4W, WM bears, S. 28 degrees 13' E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	North Umpqua River; thence N. 84 degrees and of the said River, upstream, to a so a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.  foregoing application, together with the accompanying application, together with the accompanying must be returned to the State Engineer, with correct on must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer.
R 4W, WM bears, S. 28 degrees 13' E., 5/8" iron rod on the S. bank of the N 14' 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51' W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	North Umpqua River; thence N. 84 degrees and of the said River, upstream, to a so a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.  foregoing application, together with the accompanying application, together with the accompanying must be returned to the State Engineer, with correct on must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer, with correct or must be returned to the State Engineer.
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51! W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	North Umpqua River; thence N. 84 degrees and of the said River, upstream, to a o a 5/8" iron rod; thence N. 89 degrees ming, containing 2.4 acres more or less, Douglas County, Oregon.  foregoing application, together with the accompanying application, together with the accompanying on must be returned to the State Engineer, with correct the state Engineer and the state Engineer
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51! W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	North Umpqua River; thence N. 84 degrees and of the said River, upstream, to a a 5/8" iron rod; thence N. 89 degrees aning, containing 2.4 acres more or less, Douglas County, Oregon.  foregoing application, together with the accompanying on must be returned to the State Engineer, with correct 19
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51! W 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	North Umpqua River; thence N. 84 degrees and of the said River, upstream, to a a 5/8" iron rod; thence N. 89 degrees aning, containing 2.4 acres more or less, Douglas County, Oregon.  foregoing application, together with the accompanying on must be returned to the State Engineer, with correct 19
R 4W, WM bears, S. 28 degrees 13! E., 5/8" iron rod on the S. bank of the N 14! 30" E., 201.0 ft. along the S. ba 5/8" iron rod; thence S. 539.8 ft. to 51! W., 200 ft. to the point of begin in Sec. 16, Twp 26 S., R 4W., WM, in County of Marion,  This is to certify that I have examined the maps and data, and return the same for	North Umpqua River; thence N. 84 degrees and of the said River, upstream, to a said siver, upstream, to a sa 5/8" iron rod; thence N. 89 degrees aning, containing 2.4 acres more or less, Douglas County, Oregon.  foregoing application, together with the accompanying must be returned to the State Engineer, with correct 19

STATE OF OREGON,
County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial us
and shall not exceedQ.Q3 cubic feet per second measured at the point of diversion from the
etream, or its equivalent in case of rotation with other water wers, from "Nazzb. Unpqua. Alvaz
The use to which this water is to be applied is _irrigation
If for irrigation, this appropriation shall be limited to
second or its equivalent for each acre irrigated and shall be further limited to a diversion of
not to exceed $2\frac{1}{2}$ acre feet per acre for each acre irrigated during the irrigation
season of each year,
and shall be subject to such reasonable rotation system as may be ordered by the proper state officer.
The priority date of this permit is
Actual construction work shall begin on or beforeFebruary 22, 1972 and shall
thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 19.72
Complete application of the water to the proposed use shall be made on or before October 1, 1973.
WITNESS my hand this 22nd day of February , 19.71
STATE ENGINEER

Application No. 16789

Z

Permit No.

PERMIT

TO APPROPRIATE THE PUBLIC
WATERS OF THE STATE
OF OREGON

This instrument was first received in the office of the State Engineer at Salem, Oregon,

on the 6 th day of March

19.70., at . 2:00. o'clock

Returned to applicant:

February 22, 1971

Approved:

Recorded in book No.

Permits on page 34989

CHRIS 1 WURETED

CHRIS L. WHEELER STATE ENGINEER

State Printing 98137