## \*APPLICATION FOR PERMIT

## To Appropriate the Public Waters of the State of Oregon

Of Children derivation of Oregon 97101, do hereby make application for a permit to appropriate the following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:  If the applicant is a corporation, give date and place of incorporation  1. The source of the proposed appropriation is Robison Reservoir, a tributary of Namilian River  2. The amount of water which the applicant intends to apply to beneficial use is 0.79		I, Ivan C. Robison (Name of applicant)
(desing address)  (content of Oregon 97101 , do hereby make application for a permit to appropriate the following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:  If the applicant is a corporation, give date and place of incorporation	nf	
following described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:  If the applicant is a corporation, give date and place of incorporation  1. The source of the proposed appropriation is Robison Reservoir, a tributary of Otens of Ash Swale  2. The amount of water which the applicant intends to apply to beneficial use is 0.79  cubic feet per second.  (If water is to be used from more than one source, give quantity from each)  **3. The use to which the water is to be applied is Supplemental irrigation (intention, power, mining, manufacturing, domestic supplies, sec.)  4. The point of diversion is located 3600. If, Sold 1130 ft, Work from the SW (ac et w). From the SW (ac et w).  (If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each dust be described. The separate thest if incommer?)  being within the SW SW (acre and one point of diversion, each dust be described. The separate thest if incommer?)  (If there is more than one point of diversion, each dust be described. The separate thest if incommer?)  (If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each dust be described. The separate thest if incommer?)  (If there is more than one point of diversion, each dust be described. The separate thest if incommer?)  (If there is more than one point of diversion, each dust be described. The separate thest if incommer?)  (If preferable, give distance and bearing to section corner.)  (If there is no the incommerce than one point of diversion of section corner.)  (If preferable, give distance and bearing to section corner.)  (If preferable, give distance and bearing to section corner.)  (If preferable, give distance and bearing to section corner.)  (If preferable, give distance and bearing to section corner.)  (If preferable, give distance and bearing to section corner.)  (If there is no bearing to section section corner.)  (If there is no bearing to section corner.)  (If preferable, give	•	(Mailing address)
1. The source of the proposed appropriation is Robison Reservoir, a tributary of (Manus of stream)  Ash Swale , a tributary of Yamhill River  2. The amount of water which the applicant intends to apply to beneficial use is 0.79  cubic feet per second. (If water is to be used from more than one source, sire quality from each)  **3. The use to which the water is to be applied is supplemental irrigation (trigation, power, mining, manufacturing, demosate supplies, etc.)  4. The point of diversion is located 3600 ft. S. and 1130 ft. W. from the SW ox. or 8.)  4. The point of diversion is located 3600 ft. S. and 1130 ft. W. from the SW ox. or 8.)  (If there is more than one point of diversion, each must be described. Use separate sheet if necessary)  being within the SW SW SW of Sec. 28 , Tp. 5 S. (Ct. or 8.)  7. The Oxida with, can or pipe line to be 3300 feet (Main with, can or pipe line) (Alie or feet)  in length, terminating in the Nik Nik SW (Commission should be described)  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction reinforced concrete (Loose rock, concrete, manual)  (b) Description of headgate (Tribber, occurrent, ster. number and size of spenings)	State	of
1. The source of the proposed appropriation is Robison Reservoir, a tributary of Ash Swale , a tributary of Yamhill River  2. The amount of water which the applicant intends to apply to beneficial use is 0.79  cubic feet per second	follou	ving described public waters of the State of Oregon, SUBJECT TO EXISTING RIGHTS:
Ash Swale		If the applicant is a corporation, give date and place of incorporation
Ash Swale	***	1. The source of the proposed appropriation is Robison Reservoir, a tributary of
2. The amount of water which the applicant intends to apply to beneficial use is 0.79  cubic feet per second.  (If water is to be used from more than one source, give quantity from each)  **3. The use to which the water is to be applied is Supplemental irrigation (Irrigation, power, mining, manufacturing, domestic supplies, etc.)  4. The point of diversion is located 3600 ft. S and 1130 ft. W from the SW (R. or W.)  (If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each must be described. Use separate sheet if necessary)  being within the SW (SW of SW Of Sec. 28 , Tp. 5 S.  (Give smallest legal subdivision)  R. 4 W. W. M., in the county of Yamhill  (S. or W.)  5. The pipe line to be 3300 feet  (Main ditch, canal or pipe line)  (Main ditch, canal or pipe line)  (Mines or feet)  in length, terminating in the (Simulters legal subdivision)  R. 4 W. W. M., the proposed location being shown throughout on the accompanying map.  (E. or W.)  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction reinforced concrete  abutments with 4" wooden flashboards  (Charles concrete, the number and site of spannings)  (Charles on concrete, the number and site of spannings)		(Name or stream)
Cubic feet per second.  (If water is to be used from more than one source, give quantity from each)  **3. The use to which the water is to be applied is supplemental irrigation (drigation, power, mining, manufacturing, domestic expolles, etc.)  4. The point of diversion is located 3600 ft. S and 1130 ft. W from the SN (N. or S.)  Corner of Burch D.L.C. 71  (Bection or subdivision)  (If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each must be described. Use separate sheet if necessary)  being within the SW SW of Sec. 28 , Tp. 5 S.  (Give smallest legal subdivision)  7. The pipe line to be 3300 feet  (Main ditch, canal or pips line)  (Main ditch, canal or pips line)  (Main subdivision)  Companying map.  (Main subdivision)  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at bottom 54.0 feet; material to be used and character of construction reinforced concrete.  (Corner on the subdivision of the concrete, macron abuttents with 4" wooden flashboards  (Corner on the concrete, etc., number and site of spannings)		
**3. The use to which the water is to be applied is Supplemental irrigation (trigation, power, mining, manufacturing, domestic supplies, etc.)  4. The point of diversion is located 3600 ft. S and 1130 ft. W from the SN (K. or W.)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each must be described. Use separate thet if necessary)  being within the SW SW SW of Sec. 28 , Tp. 5 S. (R. or W.)  R. 4 W. (W. or W.) (R. or W.)  (It preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each must be described. Use separate thet if necessary)  being within the SW SW SW (SW SW) (Sive subdivision)  R. 4 W. (W. or W.)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If preferable,		2. The amount of water which the applicant intends to apply to beneficial use is
**3. The use to which the water is to be applied is Supplemental irrigation (trigation, power, mining, manufacturing, domestic supplies, etc.)  4. The point of diversion is located 3600 ft. S and 1130 ft. W from the SN (K. or W.)  (If preferable, give distance and bearing to section corner)  (If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each must be described. Use separate thet if necessary)  being within the SW SW SW of Sec. 28 , Tp. 5 S.  (Cive smallest legal subdivision)  R. 4 W. W. M., in the county of Yamhill  5. The pipe line to be 3300 feet  (Males or feet)  in length, terminating in the NW NW NW of Sec. 28 , Tp. 5 S.  (Smallest legal subdivision)  R. 4 W. W. M., the proposed location being shown throughout on the accompanying map.  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction. reinforced concrete (Loose rock, concrete, masson; abuttments with 4" wooden flashboards  reck and brush, timber crib, etc., wasteway over or sround dam)  (b) Description of headgate	cubic	feet per second. (If water is to be used from more than one source, give quantity from each)
4. The point of diversion is located 3600 ft. S and 1130 ft. W from the SW corner of Burch D.L.C. 71  (Gestion or subdivision)  (If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each must be described. The separate sheet if necessary)  being within the SW SW SW of Sec. 28 , Tp. 5 S.  (Give smallest legal subdivision)  R. 4 W. W. M., in the county of Yamhill  (So or W.)  5. The pipe line to be 3300 feet  (Main dich, canal or pips line)  in length, terminating in the NW NW NW of Sec. 28 , Tp. 5 S.  (Smallest legal subdivision)  R. 4 W. W. M. the proposed location being shown throughout on the accompanying map.  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction reinforced concrete (Choose rock, concrete, massoary abutments with 4" wooden flashboards  rock and brush, tumber crib, etc., wrateway over or around dam)  (b) Description of headgate  (Chingles of concrete, etc., number and size of openings)		
(If preferable, give distance and bearing to section corner)  (If there is more than one point of diversion, each must be described. Use separate sheet if necessary)  being within the SWk SWk of Sec. 28 , Tp. 5 S.  (Give smallest legal subdivision)  R. 4 W. W. M., in the county of Yamhill  (K. or W.)  5. The pipe line to be 3300 feet  (Main citch. canal or pipe line)  (M. or S.)  R. 4 W. (Smallest legal subdivision)  (E. or W.)  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction reinforced concrete (Loose rock, concrete, mason; character of the concrete, etc., number and size of openings)  (Description of headgate (Timber, concrete, etc., number and size of openings)		(Irrigation, power, mining, manufacturing, domestic supplies, etc.)
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the SW\$ SW\$ of Sec. 28 , Tp. 5 S.  (Give smallest legal subdivision)  R. 4 W. W. M., in the county of Yamhill  5. The pipe line to be 3300 feet  (Main citch, canal or pipe line)  in length, terminating in the NW\$ NW\$ of Sec. 28 , Tp. 5 S.  (Smallest legal subdivision)  R. 4 W. W. M., which proposed location being shown throughout on the accompanying map.  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction reinforced concrete abutments with 4" wooden flashboards rock and brush, timber citb. etc. wasteway over or around dam)  (b) Description of headgate (Tunber, concrete, etc., number and size of openings)	corne	4. The point of diversion is located 3600 ft. S and 1130 ft. W from the SW (N. or S.)
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary) being within the SWk SWk of Sec. 28 , Tp. 5 S.  (Give smallest legal subdivision)  R. 4 W. , W. M., in the county of Yamhill  5. The pipe line to be 3300 feet  (Main ditch, canal or pipe line)  in length, terminating in the NWk NWk of Sec. 28 , Tp. 5 S.  (Smallest legal subdivision)  R. 4 W. , W. M., the proposed location being shown throughout on the accompanying map.  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction reinforced concrete (Loose rock, concrete, mason; abutments with 4" wooden flashboards rock and brush, tumber crib, etc., wasteway over or around dam)  (b) Description of headgate (Tumber, concrete, etc., number and size of openings)		(Section or subdivision)
being within the SW\2 SW\2 W\3 (Give smallest legal subdivision)  R. 4 W. W. M., in the county of Yamhill  5. The pipe line to be 3300 feet  (Main ditch. canal or pipe line) (Miles or feet)  in length, terminating in the NW\2 NW\2 (Smallest legal subdivision)  R. 4 W. W. M. M., in the proposed location being shown throughout on the accompanying map.  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction reinforced concrete (Loose rock, concrete, mason; abutments with 4" wooden flashboards  (E) Diversion of headgate (Timber, concrete, etc., number and size of openings)		
being within the SW\frac{1}{2}		
(If there is more than one point of diversion, each must be described. Use separate sheet if necessary)  being within the SW\( \frac{1}{2} \) SW\( \frac{1}{2} \) Of Sec. 28 , Tp. 5 S.  (Give smallest legal subdivision)  R. 4 W. , W. M., in the county of Yamhill  5. The pipe line to be 3300 feet  (Main ditch, canal or pipe line) (Miles or feet)  in length, terminating in the NW\( \frac{1}{2} \) NW\( \frac{1}{2} \) Of Sec. 28 , Tp. 5 S.  (Smallest legal subdivision)  R. 4 W. , W. M., the proposed location being shown throughout on the accompanying map.  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at botton 54.0 feet; material to be used and character of construction reinforced concrete (Loose rock, concrete, mason; abutments with 4" wooden flashboards  rock and brush, timber crib, etc., wasteway over or around dam)  (b) Description of headgate (Timber, concrete, etc., number and size of openings)	•	
being within the SW\ SW\ SW\ (Give smallest legal subdivision)  R. 4 W. , W. M., in the county of Yamhill  5. The pipe line (Main ditch, canal or pipe line)  (Miles or feet)  (		(If preferable, give distance and bearing to section corner)
being within the SW\ SW\ SW\ (Give smallest legal subdivision)  R. 4 W. , W. M., in the county of Yamhill  5. The pipe line (Main ditch, canal or pipe line)  (Miles or feet)  (		
R. 4 W. , W. M., in the county of Yamhill  5. The pipe line (Main ditch, canal or pipe line) (Mulee or feet)  in length, terminating in the NW½ NW½ of Sec. 28 , Tp. 5 S.  (Smallest legal subdivision) (N. or S.)  R. 4 W. , W. M., the proposed location being shown throughout on the accompanying map.  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at bottom 54.0 feet; material to be used and character of construction reinforced concrete (Loose rock, concrete, masonry abuttments with 4" wooden flashboards  rock and brush, timber crib, etc., wasteway over or around dam)  (b) Description of headgate (Timber, concrete, etc., number and size of openings)		•
(E. or W.)  5. The pipe line to be 3300 feet  (Main ditch, canal or pipe line) (Miles or feet)  in length, terminating in the NW NW NW Of Sec. 28 Tp. 5 S.  (Smallest legal subdivision)  R. 4 W. (N. or S.)  DESCRIPTION OF WORKS  Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at bottom 54.0 feet; material to be used and character of construction reinforced concrete  abutments with 4" wooden flashboards  rock and brush, timber crib, etc., wasteway over or around dam)  (b) Description of headgate (Timber, concrete, etc., number and size of openings)	being	within the
in length, terminating in the NW\(\frac{1}{2}\) NW\(\frac{1}\) NW\(\frac{1}\) NW\(\frac{1}\) NW\(\frac{1}\) NW\(\frac{1}	R	4 W. W. M., in the county of Yamhill
in length, terminating in the NW\(\frac{1}{2}\) NW\(\frac{1}\) NW\(\frac{1}\) NW\(\frac{1}\) NW\(\frac{1}\) NW\(\frac{1}		5. The pipe line to be 3300 feet
R	in ler	
Diversion Works—  6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at bottom  54.0 feet; material to be used and character of construction reinforced concrete  (Loose rock, concrete, mason;  abutments with 4" wooden flashboards  rock and brush, timber crib, etc., wasteway over or around dam)  (b) Description of headgate (Timber, concrete, etc., number and size of openings)		
6. (a) Height of dam 8.5 feet, length on top 54.0 feet, length at bottom  54.0 feet; material to be used and character of construction reinforced concrete  (Loose rock, concrete, mason;  abutments with 4" wooden flashboards  rock and brush, timber crib, etc., wasteway over or around dam)  (b) Description of headgate (Timber, concrete, etc., number and size of openings)		
54.0 feet; material to be used and character of construction reinforced concrete  (Loose rock, concrete, masonry abutments with 4" wooden flashboards rock and brush, timber crib, etc., wasteway over or around dam)  (b) Description of headgate	Dive	
abutments with 4" wooden flashboards rock and brush, timber crib, etc., wasteway over or around dam)  (b) Description of headgate		
(b) Description of headgate		54.0 feet; material to be used and character of constructionreinforced_concrete
	rock ar	d brush, timber crib, etc., wasteway over or around dam)
		(b) Description of headgate
20 hp Coperal Flootyde @ 3/90 ypm		(Timber, concrete, etc., number and size of openings)
(c) If water is to be pumped give general description 20 lip. General Electric 3470 lpm	•	(c) If water is to be pumped give general description 20 hp. General Electric @ 3490 rpm
(Size and Cha or hamp)		(Size and Cype of Panip)
Rain-O-Flow Mod. 2½ W 2C 2 3" x 2½" Direct Drive Cent.  (Size and type of engine or motor to be used, total head water is to be lifted, etc.)		(Size and type of engine or motor to be used, total head water is to be lifted, etc.)

<sup>\*</sup>A different form of application is provided where storage works are contemplated.

<sup>\*</sup>Application for permits to appropriate water for the generation of electricity, with the exception of municipalities, must be made to the Hydroelectric Commission. Either of the above forms may be secured, without cost, together with instructions by addressing the State Engineer, Salem, Oregon.

Canal System or I				25400
7. (a) Giv	e dimensions at	each point of co	inal where materially change	ed in size, stating m25.498
headgate. At head	lgate: width on	top (at wate <del>r</del> li	ne)	feet; width on bottom
thousand feet.	•			r line)
	feet; width on b	ottom	feet; depth of u	oater feet;
grade	feet fal	l per one thousa	ınd feet.	,
from intake	of use, 32.4	size at place of	use in.; dif	in.; size at3300 ft.  ference in elevation between  Estimated capacity,
	•	rrigated, or plac	ce of use	
Township North or South	Range \$. or W. of Willemette Meridian	Section	Forty-acre Tract	Number Acres To Be Irrigated
5 S.	4 W.	28	neż nwż	4.2
			NM F NM F	26.8
,			SWŁ NWŁ	15.5
			seł nwł	3.0
		29	neż neż	7.2
			set net	6.6
			TOTAL	63.3 acres
		All within	Williams DLC No. 45	
				1
				-
				, .
(a) Ch	aracter of soil	-	equired, attach separate sheet)	
(b) Ki	nd of crops raise	d Grain,	clover, row crops	
Power or Mining	-		<u>i</u>	
9. (a) To	tal amount of po	ower to be deve	loped	theoretical horsepower.
(b) Qu	antity of water	to be used for p	owerse	c. ft.
(c) To	tal fall to be uti	lized	(Head)	
(d) Th	e nature of the	works by means	s of which the power is to be	developed
(e) Su	ch works to be l	ocated in	4	of Sec,
Tp(No. N. or S			i '	
	•	•	eam?	
			(Yes or No)  nt of return	
	•	_		, R, W. M.
			(No. N. or S.)  plied is	
, , , , , , , , , , , , , , , , , , , ,	F			·

Municipal or Domestic Supply—	2510
10. (a) To supply the city of	
(Name of) County, having a pre	resent population of
nd an estimated population of	in 19
(b) If for domestic use state number	of families to be supplied
(Answer questions	ns 11, 42, 12, and 14 in all cases)
11. Estimated cost of proposed works, \$3	,500.00
12. Construction work will begin on or be	efore
13. Construction work will be completed of	on or before Completed
14. The water will be completely applied to	to the proposed use on or before October 1, 1970
Total irrigation system is complete	e and water applied from direct flow.
	x time l'Istresse
	(Signature of applicant)
Remarks. This land is already cov	vered with a right from the direct flow from
	rmit #29822. The intention of this filing is
	i .
	ame land from stored water from Robison
Reservoir which was constructed u	under Permit #R-1318.
,	·
	······································
	······································
· ·	
STATE OF OREGON, ss.	;
County of Marion, ss.	
This is to certify that I have examined t	the foregoing application, together with the accompanying
maps and data, and return the same for	
In and an actain its majority, this applic	eastion must be noturned to the State Engineer with correct
	cation must be returned to the State Engineer, with correc-
tions on or before	, 19
•	•
WITNESS my hand this day o	of, 19,
·	
	STATE ENGINEER

STATE OF OREGON, County of Marion,

This is to certify that I have examined the foregoing application and do hereby grant the same, SUBJECT TO EXISTING RIGHTS and the following limitations and conditions:

The right herein granted is limited to the amount of water which can be applied to beneficial use and shall not exceed ...9.2 acre feet of stored water entire feet per second eneasured at the point of diversion from the stream, or its equivalent in case of rotation with other water users, from reservoir constructed under permit No. R-1318 The use to which this water is to be applied is supplemental irrigation If for irrigation, this appropriation shall be limited to 1.1/20 of one cubic foot per second or its equivalent for each acre irrigated and shall be further limited to a diversion of not to exceed 22 acre feet per acre for each acre irrigated during the irrigation season of each year, provided further that the right allowed herein shall be limited to any deficiency in the available supply of any prior right existing for the same land and shall not exceed the limitation allowed herein, and shall be subject to such reasonable rotation system as may be ordered by the proper state officer. The priority date of this permit is .......June 8, 1970 Actual construction work shall begin on or before ......May 26, 1972..... and shall thereafter be prosecuted with reasonable diligence and be completed on or before October 1, 19.73.. Complete application of the water to the proposed use shall be made on or before October 1, 19...714. WITNESS my hand this .... 26th day of . STATE ENGINEER

Application No.47CCA No. Permit

APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON

office of the State Engineer at Salem, Oregon This instrument was first received in

Q o'clock 4:45 \$1 \$1 at 30

Returned to applicant:

Recorded in book No. Permits on page STATE ENGINEER

page Drainage Basin No. rees

Printing