APPLICATION FOR A PERMIT

To Appropriate the Public Waters of the State of Oregon

of 155 E. 2223 St., North Pertland County of Multhouse. State of State of Grandine County of Multhouse. State of State of Grandine County of Multhouse. John Money Make application for a permit to appropriate the following described public waters of the State of Oregon, subject to existing rights: If the applicant is a corporation, give date and place of incorporation. 1. The source of the proposed appropriation is Universal State of Oregon and Spring and Water (Name of stream) 1. The source of the proposed appropriation is Universal State of State o	I, C. D. Grant
State of	(Name of applicant) of 155 E. 22nd St. North Portland County of Multnoneh
following described public waters of the State of Oregon, subject to existing rights: If the applicant is a corporation, give date and place of incorporation	(Postoffice)
If the applicant is a corporation, give date and place of incorporation 1. The source of the proposed appropriation is Unismed Gulch and Spring and water stored under reservoir application, tributary of 2. The amount of water which the applicant intends to apply to beneficial use is	State of
1. The source of the proposed appropriation is Unismed Gulch and Spring and water stored under reservoir application, tributary of 2. The amount of water which the applicant intends to apply to beneficial use is negligible 0.19 cubic feet per second. 3. The use to which the water is to be applied is Irriltin of fitting acres. (Brigation, power, mining, manufacturing, domestic supplies, etc.) 4. The point of division is located Besin N3 corner DLO Baniel Hess thence E 31 28/100 rods N. 1256 feet N 31 28/100 rods N. 1256 feet to Blace of Palianing. 1. The water of division is located Besin N3 corner DLO Baniel Hess thence E 31 28/100 rods N. 1256 feet to Blace of Palianing. 2. The point of division is located Besin N3 corner DLO Baniel Hess thence E 31 28/100 rods N. 1256 feet to Blace of Palianing. 3. West (No. N. or S.) 4. The point of division is located Besin N3 corner DLO Baniel Hess thence E 31 28/100 rods N. 1256 feet to Blace of Palianing. 3. West (No. N. or S.) 5. The Besin N M. M., in the county of Yambill (No. N. or S.) 6. The mane of the ditch, canal or pipe line) 7. West (No. N. or S.) 6. The name of the ditch, canal or other works is Galch—spring Reservoir Unrawed 7. (a) Height of dam 2.10" below feet, length on top 30 feet, length at bottom 9. feet; material to be used and character of construction Shandral suproyed reinforced steel concrete will 7" bottom 5" top and also reenforced steel concrete triungle brace rock and break, timber crib, etc., waterway over or around dam) 7. X 7 X E - 5' Apprt behind well in ground 2.10" same as wall and also a 7 ft. widely sail dam on inside (D. Description of heddgate (Timber, concrete, etc., number and size of openings)	following described public waters of the State of Oregon, subject to existing rights:
stored under reservoir application, tributary of 2. The amount of water which the applicant intends to apply to beneficial use is negligible 0.19 cubic feet per second. 3. The use to which the water is to be applied isirrication.of.fifteen acres_ (Irrigation, power, mining, manufacturing, demostic supplies, etc.) 4. The point of division is locatedBegin NS corner DLCDaniel Hess thence E 31 28/100	If the applicant is a corporation, give date and place of incorporation
2. The amount of water which the applicant intends to apply to beneficial use is	,
negligible 0.19 cubic feet per second. 3. The use to which the water is to be applied isirritation_of_fifteen_acres	stored under reservoir application, tributary of
3. The use to which the water is to be applied isirrication_of_fifteen_acres	2. The amount of water which the applicant intends to apply to beneficial use is
3. The use to which the water is to be applied isirrication_of_fifteen_acres	negligible 0.19 cubic feet per second.
4. The point of division is locatedBegin NE corner DLC Daniel Hess thence E 31 28/100 rods S. 1266 feet W 31 28/100 rods N. 1266 feet to place of herinning	
rods S. 1266 feet W 31 28/100 rods N. 1266 feet to place of helimins being within the 15 agres of Sec. 26 , Tp. 3 South, (No. N. or S.) R. 3 West., W. M., in the county of Yambill 5. The 3 agres of Sec. 36 , Tp. 3 South, (No. N. or S.) 5. The 3 agres of Sec. 36 , Tp. 3 South, (No. N. or S.) 6. The proposed location being shown throughout on the accompanying map. 6. The name of the ditch, canal or other works is Galch-spring Reservoir Unreaded DESCRIPTION OF WORKS DIVERSION WORKS— 7' a ove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforged (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 5" -8' spart belind wall in fround 2'10" same as wall and also a 7 ft. widely sail dam on inside (Timber, concrete, etc., number and size of openings)	(Irrigation, power, mining, manufacturing, domestic supplies, etc.)
being within the 15 acres (Give smallest legal subdivision) of Sec. 36 , Tp. 3 South, (No. No. S.) R. 3 West W. M., in the county of Yamhill 5. The (Main ditch, canal or pipe line) to be located (Main ditch, canal or pipe line) miles in length, terminating in the 15 acres of Sec. 36 , Tp. 3 South, (No. No. S.) R. 3 West W. M., the proposed location being shown throughout on the accompanying map. 6. The name of the ditch, canal or other works is Gulch-spring Reservoir Unrespect DESCRIPTION OF WORKS DIVERSION WORKS— 7' a ove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masoury, steel concrete well 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 5" -8' appart behind well in ground 2'10" same as well and also a 7 ft. wide clay Sail dam on inside (Description of heddgate (Timber, concrete, etc., number and size of openings)	(dive distance and searing to section estate)
R. 3. West , W. M., in the county of Yamhill 5. The Reservoir to be located (Main ditch, canal or pipe line) miles in length, terminating in the 15 acres (Smallest legal subdivision) R. 3. West , W. M., the proposed location being shown throughout on the accompanying map. (No. E. or W.) 6. The name of the ditch, canal or other works is Gulch-spring Reservoir Unressed DESCRIPTION OF WORKS DIVERSION WORKS— 7' a ove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. widely sail dam on inside (D) Description of heddgate (Timber, concrete, etc., number and size of openings)	
(No. E. or W.) 5. The Reservoir to be located (Main ditch, canal or pipe line) miles in length, terminating in the 15 acres (Smallest legal subdivision) R. 3 West W. M., the proposed location being shown throughout on the accompanying map. (No. E. or W.) 6. The name of the ditch, canal or other works is Gulch-spring Reservoir Juneaged. DESCRIPTION OF WORKS DIVERSION WORKS— 7' a ove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete well 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind well in ground 2'10" same as well and also a 7 ft, wide clay sail dam on inside (Timber, concrete, etc., number and size of openings)	being within the 15 acres of Sec. 36 , Tp. 3 South, (Give smallest legal subdivision) (No. N. or S.)
5. The Reservoir (Main ditch, canal or pipe line) miles in length, terminating in the 15 acres (Smallest legal subdivision) R. 3 West W. M., the proposed location being shown throughout on the accompanying map. (No. E. or W.) 6. The name of the ditch, canal or other works is	R. 3. West, W. M., in the county of
miles in length, terminating in the 15 acres (Smallest legal subdivision) R. 3 West (No. M. or N.) 6. The name of the ditch, canal or other works is (Sulch-spring Reservoir Unraised) DESCRIPTION OF WORKS DIVERSION WORKS— 7' a ove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (Description of heddgate (Timber, concrete, etc., number and size of openings)	5. The Reservoir to be located
R. 3 West , W. M., the proposed location being shown throughout on the accompanying map. (No. E. or W.) 6. The name of the ditch, canal or other works is	
DESCRIPTION OF WORKS DIVERSION WORKS— 7' a ove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (Timber, concrete, etc., number and size of openings)	R. 3 West , W. M., the proposed location being shown throughout on the accompanying map.
DESCRIPTION OF WORKS 7' a ove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (Timber, concrete, etc., number and size of openings)	6. The name of the ditch, canal or other works is
DIVERSION WORKS— 7' a nove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (Discription of heddgate (Timber, concrete, etc., number and size of openings)	Gulch-spring Reservoir Unnsmed
DIVERSION WORKS— 7' a nove ground 7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (Discription of heddgate (Timber, concrete, etc., number and size of openings)	
7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom 90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (b) Description of headgate (Timber, concrete, etc., number and size of openings)	DESCRIPTION OF WORKS
90 feet; material to be used and character of construction Standard approved reinforced (Loose rock, concrete, masonry, steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (Description of heddgate (Timber, concrete, etc., number and size of openings)	•
steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'lo" same as wall and also a 7 ft. wide clay sail dam on inside (b) Description of heddgate (Timber, concrete, etc., number and size of openings)	7. (a) Height of dam 2'10" below feet, length on top 90 feet, length at bottom
steel concrete well 7" bottom 5" top and also reenforced steel concrete triangle brace rock and brush, timber crib, etc., wasteway over or around dam) 7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (b) Description of headgate (Timber, concrete, etc., number and size of openings)	90 feet; material to be used and character of construction Standard approved reinforc
7' x 7' x 6" -8' apart behind wall in ground 2'10" same as wall and also a 7 ft. wide clay sail dam on inside (b) Description of heddgate (Timber, concrete, etc., number and size of openings)	steel concrete wall 7" bottom 5" top and also reenforced steel concrete triangle bra
	7' x 7' x 6" -8' apart behind wall in ground 2'10" ' same as wall and also a 7 ft. w clay sail dam on inside;
Wasteway 10' x3"	
	Wasteway 10' x3"

^{*} A different form of application is provided where storage works are contemplated. These forms can be secured without charge, together with instructions, by addressing the State Engineer, Salem, Oregon.

CANAL SYSTEM-

from headgate. At headgate: Width on top (at water line	?)	feet; width on bottom
feet; depth of water f	eet; grade	feet fall per one
thousand feet.		
(b) At miles from headgate: Width	h on top (at water l	ine)
feet; width on bottom	feet; depth of wa	ter feet;
grade feet fall per one thousand feet.		
FILL IN THE FOLLOWING INFORMATION WE	HERE THE WATE	R IS USED FOR
Irrigation—		
9. The land to be irrigated has a total area of	Fifteen	acres, located in each
smallest legal subdivision, as follows: (Give area of land in ea Begin NE corner DLC Daniel Hess, then	ach smallest legal subdivisce East 31 28/10	ion which you intend to irrigate) O rods south 1266 ft.
West 31 28/100 rods North 1266 ft. to point of		The second secon
6 .3 ac. in NW4 NW4 Sec. 36	, T. 3 S. A 3W.	
8 7 " " SW N 1 " "		
	h separate sheet)	
(If more space required, attack	h separate sheet) URPOSES—	
(If more space required, attack Power, Mining, Manufacturing, or Transportation Power, Mining, Manufacturing, Or Manufac	h separate sheet)	
(If more space required, attack Power, Mining, Manufacturing, or Transportation Pt 10. (a) Total amount of power to be developed	h separate sheet) URPOSES—	theoretical horsepower
POWER, MINING, MANUFACTURING, OR TRANSPORTATION Pound (a) Total amount of power to be developed	h separate sheet) URPOSES— et. h the power is to be	theoretical horsepower
POWER, MINING, MANUFACTURING, OR TRANSPORTATION Power. 10. (a) Total amount of power to be developed (b) Total fall to be utilized	h separate sheet) URPOSES— et. h the power is to be	theoretical horsepower
POWER, MINING, MANUFACTURING, OR TRANSPORTATION POWER, MINING,	h separate sheet) URPOSES— et. h the power is to be Legal subdivision)	theoretical horsepower
POWER, MINING, MANUFACTURING, OR TRANSPORTATION Power to be developed (b) Total fall to be utilized	h separate sheet) URPOSES— et. h the power is to be Legal subdivision)	developed
(If more space required, attack POWER, MINING, MANUFACTURING, OR TRANSPORTATION PO 10. (a) Total amount of power to be developed	h separate sheet) URPOSES— et. h the power is to be Legal subdivision) (Yes or No) return	theoretical horsepower
(If more space required, attack POWER, MINING, MANUFACTURING, OR TRANSPORTATION Power to be developed	h separate sheet) URPOSES— et. h the power is to be Legal subdivision) (Yes or No) return , R.	theoretical horsepower developed

MÜNICIPAL SUPPLY—	
	population of,
and an estimated population of	
(Answer questions 12,	13, 14, and 15 in all cases)
12. Estimated cost of proposed works, \$	
13. Construction work will begin on or before	ore
14. Construction work will be completed on	or before
15. The water will be completely applied to	the proposed use on or before
Duplicate maps of the proposed ditch or other	er works, prepared in accordance with the rules of the
State Engineer, accompany this application.	
	C. D. Grant (Name of applicant)
Signed in the presence of us as witnesses:	
(1) J. W. Hilderbrand	, 920 Marguerite Ave. No. Fortland, Oregon (Address of Witness)
\=.	, 405 Clay St., Portland, Oregon (Address of witness)
	· · · · · · · · · · · · · · · · · · ·
	<u></u>
STATE OF OREGON,	
County of Marion, \rangle^{ss} .	
	foregoing application, together with the accompanying
	or completion, as follows:
	cation must be returned to the State Engineer, with
corrections, on or before	, 192
WITNESS my hand this do	ay of, 192
	STATE ENGINEER.

2	Amilication	No	11748

Permit No. 8165

PERMIT

TO APPROPRIATE THE PUBLIC WATERS OF THE STATE OF OREGON

	District	No		_ å	
	This instrume office of the State		received in the Salem, Oregon,		
	on the 12th	day ofS	ept.	•	,
	192.7 , at8:	.00 o'cloc	k .AM.		
	Returned to apple	icant for corr	rection:	•	
	Corrected applica		l:, .		
	Approved:				
	Sept281	.927		-	
	Recorded in E	Book No	27 of		
	Permits, on page	8165	•		
	R.H.E.A.	LUPES ST.	ATE ENGINEER.	-	
	l map	្ឌី9.50			
STATE OF OREGON,	<u></u>	*****			
88.	•				
County of Marion,)					•
This is to certify tha subject to the following limits	t I have examined itations and conditi	the foregoin ions: If for	g application a irrigation, this	nd do hereby appropriation	grant the same, shall be limited
to one-eightieth of one cubic to such reasonable rotation	foot per second, or system as may be o	· its equivaler ordered by th	nt, for each acre ne proper state o	e irrigated, an officer.	d shall be subject
The ri	ght herein græ	ited is lim	ited to the	a ppropriati	on of water
from an Urmamed Gulo	h and Spring an	id water st	ored under P	ermit No. F	598 for irri-
gation					
The amount of water					
ficial use and not to exceed .					
rotation. The priority date	of this permit is		Sept. 12, 19	27	
Actual construction	work shall begin on	or before	Sept. 28,	1928	and shall
thereafter be prosecuted wi	th reasonable dilig	ence and be	completed on or	· before	
			June 1.		
Complete application		e proposed u	se shall be made Extend		Extended to Oct. 1, 1932
WITNESS my hand				,	o 7
WIINEDD MY NUMA	M009				
			R_H_E_	. 8	TATE ENGINEER.
Permits for power develop	nent are subject to the	limitation of fra	nchise as provided	in Section 5728,	Oregon Laws, and the

Permits for power development are subject to the limitation of franchise as provided in Section 5728, Oregon Laws, and the payment of annual fees as provided in Section 5803, Oregon Laws.

This form approved by the State Water Board, March 11, 1909.