STATE OF OREGON CHECKIVED

67746 34W-4cd Will.

1132			
(1) OWNER: MAY NOTE RESOURCE OF WELL by legal description:			
Name Jack Parsons SALEM.	REGORD Clackama Antitude Longitude		
WATER HASOURCES DERE	Township Nor S. Range Eor W. WM.		
SACEM OREGON	Section 4 SE 4 SW 4		
(2) TYPE OF WORK:	Tax Lot Lot Block Subdivision		
New Well Deepen Recondition Abandon	Street Address of Weil (or nearest address) 25460 S.W. Baken Rd,		
(3) DRILL METHOD	Sherwood, UK 97/40		
🔼 Rotary Air 🔲 Rotary Mud 🔲 Cable	(10) STATIC WATER LEVEL:		
Other	ft. below land surface. Date 5/2/88		
(4) PROPOSED USE:	Artesian pressure [b. per square inch. Date		
□ Domestic □ Community □ Industrial   Irrigation	(11) WATER BEARING ZONES:		
☐ Thermal ☐ Injection ☐ Other			
BORE HOLE CONSTRUCTION:	Depth at which water was first found		
Special Construction approval Yes No Depth of Completed Well 175' ft.	From To Estimated Flow Rate SWL		
	50' 70 8 GM		
Explosives used			
HOLE SEAL Amount	120' 155' 30 GM		
Diameter From To Material From To sacks or pounds	· · ·		
121" 0' 78' Cement 0' 78' 32 sacks	(12) WELL LOG: Ground elevation		
8" 791 !791			
	Material From To SWL		
How was seal placed: Method	Top Soil         0         2           Clay         2         /2		
Other	Inner beds of Black Basalt &		
Backfill placed fromft. toft. Material	Clay 12 25		
Gravel placed fromft. toft. Size of gravel	Soft Brown Clay 25 50		
(6) CASING/LINER:	Soft Decomp. Brown Rock 50 70		
Diameter From To Gauge Steel Plastic Welded Threaded	Med. Hand Gr/Brwn. Basalt 70 75		
Casing 8"   +1'   80'   .02f PCK   PCK	Hand Gray Basalt 75 85		
	Hand Broken Gr/Basalt 85 90		
	Hand Gnay Basalt 90 120		
	Hand Gn/Brwn. Basalt 120 155		
Liner:	Hand Gnay Basalt 155-163		
	Hand Blk. & Brwn. Basalt 163-175		
location of shoe(s)			
PERFORATIONS/SCREENS:			
Perforations Method			
Screens Type Material			
Slot Tele/pipe			
m To size Number Diameter size Casing Liner			
	1/07/56		
	Date started 4/25/88 Completed5/2/88		
	(unbonded) Water Well Constructor Certification:		
(8) WELL TESTS: Minimum testing time is 1 hour	I certify that the work I performed on the construction, alteration, or		
□ Pump □ Bailer ※ Air □ Artesian	abandonment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to my best		
Yield gal/min Drawdown Drill stem at Time	knowledge and belief.		
30 GPM /50' 1 hr.	WWC Number		
, Aq	Signed Date		
(bonded) Water Well Constructor Certification:			
I accept responsibility for the construction, alteration, or abandonment			
Was a water analysis done? Yes By whom work performed on this well during the construction dates reported above. all work performed during this time is in compliance with Oregon well			
Did any strata contain water not suitable for intended use? Too little construction standards. This report is true to the best of my knowledge and			
Saity Muddy Odor Colored Other Formation needed belief. WWC Number 645			
Depth of strata: 50-70' casin i. to imperson Signed Date S/7 88			
WHITE COPIES - WATER RESOURCES DEPARTMENT YELLOW COPY - CONSTRUCTOR PINK COPY - CUSTOMER 9809C 10/86			
	30.0C 10/00		

WATER RESOURCES DEPARTMENTS ETATE OF SALEM, OREGON 87819	MAK J.DJO	
within 50 days from the date		
of well completion.	CALEM CHEGON	
(1) OWNER:	(10) LOCATION OF WELL: MAY 2	A 2012
Took Bargons	County Clackamas Driller's well number D-96-78	
Name Jack Parsons Address 25460 S.W.Baker	• .	
Sherwood, Oregon 97140	NE %SW & Section AVATER RESOURCE W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section of ALEMAN PEGON	
New Well  Deepening  Reconditioning  Abandon	Sherwood Area	
If abandonment, describe material and procedure in Item 13.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	
Rotary HX Driven	Soften as which was mos much	
Cable		
	Artesian pressure De. per equa	s mca. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below easing 8#	
8 Diam from +2 ft to 97 ft Gage •250	Depth drilled 155 ft. Depth of completed well 155 ft.	
Diam. from ft. Gage	Formation: Describe color, texture, grain size and structure of materials:	
Diam from ft. to ft. Gage	and show thickness and nature of each stratu with at least-one entry for each change of forms	
PERFORATIONS: Perforated  \( \text{\texts} \) Yes \( \text{\texts} \) No.	position of Static Water Level and indicate prin	
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Top Soil	0 2
perforations from ft. to ft.	Clay Brown Med	2 26
perforations from ft. to ft.		77.
perforations from 11. to 12.	Bldrs broken med layered	26 40
permanents from	Sandstone med frct	40 88
(7) SCREENS: Well screen installed? [] Yes X No	Basalt hard gray	88 143
Manufacturer's Name	Decomposed rock	143 154
Type Model No	Basalt gray hard	154 155
Diam. Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
•	DECEIVED	
Was a pump test made? X Yes   No If yes, by whom? Driller		<del>                                     </del>
ried: 60+ gal./min. with ft. drawdown after 1½ hrs.	MAY 1 7 2006	
Pir Rotary . Total		<del></del>
* * * * * * * * * * * * * * * * * * * *	WATER RESOURCES DEPT	
Baller test gal./min. with ft. drawdown after hrs.	SALEM, OREGON	
Artesian flow g.p.m.		
berature of water Depth artesian flow encounteredft_	Work started 2- 20 1978 Complete	ed 2 - 23 1978
	Date well drilling machine moved off of well	2 - 23 198
(9) CONSTRUCTION:		
Well seal-Material used Cement Grout	Drilling Machine Operator's Certification:	
Well scaled from land surface to	This well was constructed under no Materials used and impropation reported	above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief	n c 80
Biameter of well bore below sealin.	[Signed] Criting Machine Operator)	Date 3- 6, 1978
Number of sacks of cement used in well seat	Drilling Machine Operator's License No.	1038
How was cement grout placed?		
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	
Was a drive shoe used? ☐ Yes No Files Bize: location ft.	Name S & M Drilling & Supply, Inc.	
Did any strata contain unusable water   Yes   No	(Ferson, firm or corporation) (Type or print)	
Type of water? depth of strata	Address 399 S.E. Walnut/ Canby, Or 97013	
Method of sealing strata off	[Signed] Jaluana	
Was well gravel packed? [ Yes 7 No Size of gravel:	(Water Well Conta	actor)
Gravel placed fromft. toft.	Contractor's License No. 497 Date	<u>3- 6 10.78</u>
- (USE ADDITIONAL SE	ERTS IF NECESTARY)	SP*45656-113

NOTICE TO WATER WELL CONTRACTOR! The original and first copy of this report WATER WELL REPORT are to be filed with the STATE OF OREGON WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 (Please type or print) within 30 days from the date (Do not write above this line of well completion. (10) LOCATION OF WELL: (1) OWNER: Driller's MAYnu264 20137 County Clackamas Name Jacque E. Parsons T. 38 R. 1W 34 Section 4 Address 25460 S.W. Baker Rd. WATER BESOURCES DEPT Sherwood, Oregon 97140 Bearing and distance from section SALEM, OREGON (2) TYPE OF WORK (check): Abandon 🗆 Reconditioning [ New Well IX Deepening | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found ft. Driven [ Domestic 🔲 Industrial 🖂 Municipal 🗖 Static level 76 ft. below land surface. Date 10/21/80 Jetted \_ Test Well | Other Irrigation Bored | lbs. per square inch. Date Artesian pressure glued
Threaded Diameter of well below casing 6" to 244 (5) CASING INSTALLED: Welded 15 (12) WELL LOG: 8\_\_ f Diam from LOP \_\_\_\_ ft. to \_\_\_84\_\_ ft Gage , 250 ft. Depth of completed well Depth drilled PVC Diam. from top ft. to 82 n Gage 125PSI Formation: Describe color, texture, grain size and structure of materials; et Gage 160PSI AVC Diam. from XXX 82 ff. to \_140\_ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. (6) PERFORATIONS: Perforated? N Yes No. Skilsew Type of perforator used 1/8 8 0 tre of perforations Topsoil 72 4 16 4 Gray Silty Clay, surface water perforations from 16 60 Grav Clav et to ## perforations from Brown Broken Basalt 60 75 ... perforations from . ft. to 75 89 Black Basalt (7) SCREENS: Well screen installed! - Yes - No Brown Lava (20 gpm) 89 101 76 Manufacturer's Name .... 101 Black Basalt 163 Model No. . Brown Broken Rock (5 gpm) 163 168 76 Slot size . Set from ... Black Basalt 168 215 \_\_ Bet from \_\_\_\_\_ ft. to .\_\_\_\_ Diam. ..... Slot size ..... 215 227 Brown Visecular Basalt 227 236 Black Basalt Drawdown is amount water level is lowered below static level (8) WELL TESTS: 236 Black Broken Basalt, water 241 a pump test made? Tyes if No If yes, by whom? Black Basalt gal./min. with ft. drawdown after Yield: hrs. 40 GPM with rod at 120' for a period of 2 hrs. er test gal./min. with ft. drawdown after Arresian flow Depth artesian flow encountered . Completed 10/21/80 Temperature of water 19 Work started Date well drilling machine moved off of well (9) CONSTRUCTION: Cement Wall seal-Material used Portland EMMNN & 5% bentonite Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my Well sealed from land surface to . ....12 best knowledge and belief Diameter of well bore to bottom of stal .... [Signed] Dellat Diameter of well bore below seal 8" to 140ft. 6" to 244ft. 19 99 1 Date 10/21/8019 ..... Brilling Machine Operator's License No. ..... How was cement grout placed? pumped in thru conductor p Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

(USE ADDITIONAL SHEETS-IF NECESSARY)

[Signed] ...

Name Willamette Drilling Co.

Contractor's License No.561

7365 O'Neil Rd. N.E. Salem, Oregn

Date ....

Was a drive shoe used? Yes No Plug..... Size: location

depth of strata

Did any strata contain unusable water? Tyes 💆 No

Was well gravel packed? ☐ Yes [] No Size of gravel:

Type of water?

Method of sealing strata off

Gravel placed from .....

10/21/80

(Type or print)

97303

BP\*45656-119