NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

UMAT

WATER WELL REPORTE CEIVED

3N	/28	126
7		

STATE ENGINEER, SALEM, OREGON 97810 215
within 30 days from the date
of well completion

(Please type or print) (AND MAY 25 1976 Well No. (Do not write above this lip ATER RESOURCES DEPT No.

(1) OWNER:	County HMAIILLA Driller's well number 04-76
Name LIL FARMS INC.	
Address 807 W. IAMARICK HERMISTON OFFGOR	SW 14 SE 14 Section 26 T. 3N R. 28 E. W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon A	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 306 ft.
Rotary Driven Domestic Industrial Municipal	Static level 330 ft. below land surface. Date 4-20.7
Cable	Artesian pressure None lbs. per square inch. Date
	16" 6 457
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 10 " to 1,012
16 Diam from + ft. to -49 ft. Gage 250	Depth drilled / 0/2 ft. Depth of completed well / 0/2 ft.
	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Yes W.No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	SILT, SAND 0 14
perforations from ft. to ft.	GRAVEL CLAY 14 30
perforations from ft. to ft.	MED HARD BROWN BASALT 30 65
perforations from ft. to ft.	HARD GREY " 65 85
(7) SCREENS: Well screen installed? Yes No	SATTO LARRY II 85 37
Manufacturer's Name	SUFF CREY
Type Model No.	MARD GREY " 135 256
Diam. Slot size Set from ft. to ft.	HAPP GREY 11 281 306
Diam. Slot size Set from ft. to ft.	SOFT BROKEN SERMS" 306 331 WATE.
	HARD GREY 1 11 331 452
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BROKEN GREY W/SEAPSTONE 432 456 WINTER
Was a pump test made? Xes No If yes, by whom?	HAPD GREV BASALT 456 588
Mad: 2000 + gal./min. with ft. drawdown after hrs.	BROKEN WISEAMS 588 638 WATE
	HARO GREV " 638 888
AIR LIFT	BROKEN WSOAPSTONE 888 913 WATER
" " " " " " " " " " " " " " " " " " "	HARD GREY BASALT 913 973
Bailer test gal./min. with ft. drawdown after hrs.	BROKEN BASALT 973 988 WATER
Artesian flow g.p.m.	HARD GREY BASALT 788 1012-
Perature of water 66 Depth artesian flow encountered	Work started 2-26 1976 Completed 420 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-24 1976
Aleas Annews	Drilling Machine Operator's Certification:
1/0	This well was constructed under my direct supervision.
20	Materials used and information reported above are true to my
	Signed Coreff W. Charachate 5-13 1976
Diameter of well bore below sealin. Number of sacks of cement used in well seal	(Brilling Machine Overstor)
The state of the s	Drilling Machine Operator's License No
Number of sacks of bentonite used in well sealsacks Brand name of bentonite	
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:
of waterlbs./190 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Auress BOX 392 FENDLETON
	Levet A. In Mare
West well grown nesteds CI Van Way	[Mater Well Contractor)
Was well gravel packed? Yes No Size of gravel:	Comment Vision Vo 583 5-23 76
Gravel placed fromft to	Contractor's License No. 583 Date 5-23 19.75
CALEM ORE	GON TOTAL A 2

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPRECEIVED 6. State Well No.

State Permit No.

(Please type or print) (Do not write above this ATER RESOURCES DEPT.

	SALEM. OREGON
(1) OWNER: Name LL FARINS (UMAT)	(10) LOCATION OF WELL:
Name LAL FARINS (UNIT)	County LATILLA Driller's well number
Address P. I. Box KCHD, ORE.	NW 14 NW4 Section 23 T. 3N, R. 28 E, W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 40 ft.
Rotary Driven Domestic Industrial Municipal	Static level 5/ ft. below land surface. Date /2-18-76
Cable	Artesian pressure // lbs. per square inch. Date
	14" le 500
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 8 1 Licour
16 " Diam. from + 1 tt. to -60 ft. Gage , 250	Depth drilled 936 ft. Depth of completed well 936 ft.
ft. Gage ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
(S) DEDECODATIONS.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
(6) PERFORATIONS: Perforated? Yes No.	
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	SANDY SOLL 0 12
perforations from	SOFT BROWN BASALT 12 40 moles
perforations from ft. to ft.	HARD GREY BASALT 40 127
perforations from ft. to ft.	BRIKEN KED W/SOADSTONE 127 14C Walter
(7) SCREENS: Well screen installed? Yes Wo	GREY BASAST, 140 172
	BRIKEN KED W/SOADSTONE 172 140 WATER
Manufacturer's Name	VERY HARY GERY BASAGI 190 272
Diam. Slot size Set from ft. to ft.	GREV W/SCAPSTEAS 272 277
Diam. Slot size Set from ft. to ft.	MED. HARO GREY BASHIT 277 415
Siet size	VERY NAPU GREY " 415 478
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	SOFT GREY BASALT 478 489
	SOUT CLEY 11 488 645
Was a pump test made? ☐ Yes P No If yes, by whom?	
gal./min. with ft. drawdown after hrs.	BROKEN RED " 1.43 670 TOZ-WATER
EST-2,000 GIRNI AIR GAT "	HARD GREY " 102 814
<i>II</i>	BRENTE GREY " 814 842 Wally
Bailer test gal./min. with ft. drawdown after hrs.	HARO GREV " 842 912
sian flow g.p.m.	BRENEN GIZEN 11 912 936 WATER
Temperature of water Depth artesian flow encounteredft.	Work started 12-3 1976 Completed 12-18 1976
	10 21
(9) CONSTRUCTION:	Date well drilling machine moved off of well 12-18 19 16
Well seal-Material used A'EAT CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal	[Signed] Statuallie Date 117, 1977
Number of sacks of cement used in well seal 30 sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and bellef.
Was a drive shoe used? 🗆 Yes 📝 No Plugs Size: location 🚾 📭 🧸 🎮	ICO WALLACE WELL URLG. C.
Did any strata contain unusable water? Yes No	(Person firm or corporation) (Type or print)
Type of water? depth of strata	Address ENDIFTON, CRE.
Method of sealing strata off	
	[Signed] (Water Well Contractor)
WAIEH HEOUUN	CES DEPT CARTERIOR No. 523 Date
SALEM OM	#OO!"
(USE ADDITIONAL SE	IERTS IF NECESSARY) SP-45656-119
	1 \Q_1 \L_1 \C_2 \Z_2 \Z_3 \Z_3 \Z_3 \Z_3 \Z_3 \Z_3 \Z_3 \Z_3

RECEIVED

STATE OF OREGON WATER WELL REPORT

MAY 171993

UMAT 58/6

3N/28E/234

(as required by ORS 537.765) (START CARD) # WATER RESOURCES DEPT. SALEM, OREGON (9) LOCATION OF WELL by legal description: (1) OWNER: County Umatilla Latitude rarms Name Township 3N N or S. Range_ Address E or W. WM. NW 4 NW 4 Tax Lot 7/00 Lot_ (2) TYPE OF WORK: Block_ Street Address of Well (or nearest address) Echo, 0R 97826 Recondition ☐ New Well ☐ Deepen ■ Abandon (3) DRILL METHOD: (10) STATIC WATER LEVEL: Rotary Air Rotary Mud Cable 349 ft. below land surface. Other (4) PROPOSED USE: Ib. per square inch. Artesian pressure (II) WATER BEARING ZONES: Irrigation Community Industrial ☐ Domestic ☐ Injection Other ☐ Thermal Depth at which water was first found (5) BORE HOLE CONSTRUCTION: Special Construction approval Yes You Depth of Completed Well 1055 ft. SWL Explosives used Yes No Type_ Estimated Flow Rate From 300 978 HOLE Amount Material sacks or pounds 600 1059 (12) WELL LOG: Ground elevation How was seal placed: Method A □в SWL Material From Other _ Keconditioning Backfill placed from____ _ ft. to____ _ ft. Material rocedure: Deepenine Gravel placed from_ ft. to_ ft. Size of gravel (6) CASING/LINER: Fristing was: Steel Plastic Welded Threaded Gauge mm 0 to 500 deepened Final location of shoe(s) (7) PERFORATIONS/SCREENS: Perforations Method . Screens Material Type _ Tele/pipe Slot To Diameter Casing Liner From Number size \Box JUN 0 8 2012 WATER RESOURCES DEPT SALEM OREGON (8) WELL TESTS: Minimum testing time is 1 hour 12-22-93 Date started Completed Flowing ☐ Bailer Air (unbonded) Water Well Constructor Certification: ☐ Pump Artesian I certify that the work I performed on the construction, alteration, or abandon-Yield gal/min Drlll stem at Drawdown Time ment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to my best knowledge and belief. 1500+ 1 hr. WWC Number _ Signed_ (bonded) Water Well Constructor Certification: Temperature of Water _ Depth Artesian Flow Found I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed Was a water analysis done? Yes By whom_ during this time is in compliance with Oregon well construction standards. This report Did any strata contain water not suitable for intended use?

Too little is true to the best of my knowledge and belief. WWC Number 21 ☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other Depth of strata: Signed _ SECOND COPY - CONSTRUCTOR THIRD COPY - CUSTOMER ORIGINAL & FIRST COPY - WATER RESOURCES DEPARTMENT

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

WATER WELL REPORT CEIVED GAST STATE OF OREGON MAY 25 1976 State Well No. 3N/Z8F-26 (Please type or print)

STATE ENGINEER, SALEM, OREGON 97310 #1 within 30 days from the date of well completion.

(Do not write above the ATER RESOURCES LEEF Fermit No. SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:	The second secon
Name LAL FARMS INC.	County THATILLA Driller's well no	ımber 7-76
Address P. G. Box 611	NE 14 NW14 Section 26 T. 3N	
ECHO, ORE,	Bearing and distance from section or subdivisi	
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	327 ft.
Rotary Driven Domestic Industrial Municipal		surface. Date 5-7-76
Cable		
Dig Bored Infigation A fest well Other	Artesian pressure NONE lbs. per squar	e inch. Date
CASING INSTALLED: Threaded Welded A ft. to ft. Gage 1250	(12) WELL LOG: Diameter of well 1	pelow casing .g.u. To 450
"Diam. from ft. to ft. Gage	Depth drilled 9// ft. Depth of compl	eted well // ft.
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size	
2000	and show thickness and nature of each stratuments with at least one entry for each change of forma	
PERFORATIONS: Perforated?	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	SAND SILT	0 4
perforations from ft. to ft.	CLAY	4 12
perforations fromft. toft.	GRAVEL	12 38
perforations from ft. to ft.	BROWN BASALT	38 67
(E) CODERIO	HARD GREY BASALT	67 145
(7) SCREENS: Well screen installed? Yes No	BRIKEN KEO BASALT	145 165
Manufacturer's Name	HARD GREY HASALT	165 274
Type Model No.	BRIKEN GREY BASALT	274 295
Diam, Slot size Set from ft.	HARD GREY BASILIT	295 327
Diam,Slot sizeSet fromft. toft.	PRENEW/A/SOAP STONE	327 341 WATE
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	HARD GREY BASALT	1/25 1/25
. /	HAPD GEEN BASALT	1/25 1/35 WATER
Was a pump test made? Yes No. If yes, by whom?	57-11-11	135 501
Yield: /000 Tgal./min. with ft. drawdown after hrs.	HARE GREY BASAUT	608 615
AIR "LIFT"	BROWEN GREY BASALT	615 650
n " " " " " " " " " " " " " " " " " " "	MED, HARD GREV	650 870
Bailer test gal./min. with ft. drawdown after hrs.	BROKEN GREY BASALT	870 901 WATER
Artesian flow NONE g.p.m.	HARD GREY BASALT	901 911
erature of water 67 Depth artesian flow encountered MANE it.	Work started 4-26 1976 Complete	ed 5-7 1976
(9) CONSTRUCTION:	Date well drilling machine moved off of well	5-7 1976
Well seal-Material used NEAT CEMENT	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	
Diameter of well bore to bottom of seal	best knowledge and belief	1
Diameter of well bore below seal	[Signed] Lucrell H. Chillen	Date 5-23 1976
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	886
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons SCAL, WAFER	This well was drilled under my jurisd	iction and this report is
of water lbs./100 gals.	true to the pest of my knowledge and bel	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name WALLACE WELL	LELG CO.
Did any strata contain unusable water? Yes I No	(Person, firm or corporation)	OLETAN (D)
Type of water? depth of strata	Address DOX	Major, OR.
Method of sealing strata off	[Signed] Werell H.	unlland
Was well gravel packed? Yes No Size of gravel 1 0 8 2312	(Water Well Conti	ractor)
Gravel placed from ft. to ft.	Contractor's License No. 593. Date	19/6
WATER DESCRIBES A	HETS IF NECESSARY)	SP*45656-119

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the

WATER WELL REPORT CEIVEDE WEIL No. 30 28 E 34

(Please type or print)

28E

W.M.

STATE ENGINEER, SALEM, OREGON SISTE (Please type	ove this line NOV 1 1976 State Permit N	o
(1) OWNER:	(10) LOCATION OF WELL:	
Name Glen Maddox	County Umatilla Driller's well no	umber
Address P. O. Drawer P, Moses Lake, Wa. 98837	34 % Section 34 T. 3N	R.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on co
New Well M Deepening □ Reconditioning □ Abandon □		_
If abandonment, describe material and procedure in Item 12.		
	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	4(
Rotary 🗓 Driven 🗍 Domestic 🗋 Industrial 🗎 Municipal 🗎	Static level 425 ft. below land s	surface
Cable	Artesian pressure lbs. per squar	re incl
CASING INSTALLED: Threaded Welded &	(12) WELL LOG: Diameter of well k	
16 "Diam from +1 ft. to 44 ft. Gage •250	Depth drilled 830 ft. Depth of compl	eted v
	Formation: Describe color, texture, grain size a	and st
PERFORATIONS: Perforated? Yes No.	and show thickness and nature of each stratur with at least one entry for each change of formal position of Static Water Level and indicate prin	m and tion. F
Type of perforator used	MATERIAL	Fro
		-
Size of perforations in. by in.	Top Soil Gravel cemented	
perforations fromft. toft.	Basalt broken brown	36
perforations fromft. toft.	Basalt med hard brown	30
perforations from ft. to ft.	Basalt med black	57
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Basalt hard black	7
Manufacturer's Name	Basalt soft blk(quartz & clay	
Type Model No Model No.	Basalt hard black	117
Diam. Slot size Set from ft. to ft.	Basalt soft brown	144
Diam. Slot size Set from ft. to ft.	Basalt soft black	160
(8) WELL TESTS: Drawdown is amount water level is	Basalt med black	177
(8) WELL TESTS: Drawdown is amount water level is lowered below static level Valley	Basalt soft black & blue clay	186
Was a pump test made? T Yes No If yes, by whom? Pump	Basalt soft black	200
Vield: 3260 gal./min. with 17 ft. drawdown after 8 hrs.	Basalt med black	22
" " "	Basalt soft black	262
n " "	Basalt hard black	270
Bailer test gal./min. with ft. drawdown after hrs.	Basalt soft black	272
	Basalt med black	287
Artesian flow g.p.m.	Basalt hard black	29
perature of water Depth artesian flow encounteredft.	Work started 8/20 19 76 Complete	ed
(9) CONSTRUCTION:	Date well drilling machine moved off of well	
Compant	Drilling Machine Operator's Certification:	
Web sear Material useu	This well was constructed under my	dire
Well sealed from land surface to	Materials used and information reported best knowledge and belief.	abov
Diameter of well bore below seal	1	Doto
Number of sacks of cement used in well seal	(Drilling Machine Operator)	Date
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No.	TC
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisd	
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.	true to the best of my knowledge and bel	TGT.
Did any strata contain unusable water? Yes X You Save Save Save Save Save Save Save Save	(Person, firm or corporation)	
Type of water? depth of strata RECEVED	Address P. O. Box P, Moses Lake	e, W
Method of sealing strata off Wes well ground neglected TI Was ST No. Size of well IN 0 8 2012	[Signed] Steve Moon (Water Well Control	ruetor'
Was well gravel packed? Yes 2 No Size of gravel 08 2012	(water well Contr	actor)

n corner ell. 404 9/20/76 urface. Date e inch. Date clow casing 830 eted well ft. nd structure of materials; n and aquifer penetrated, tion. Report each change in cipal water-bearing strata. 0 2 36 36 39 39 57 57 77 77 100)100 117 117 144 144 160 160 177 177 186 186 200 200 227 262 227 262 270 270 272 287 287 295 330 9/10 19 76 9/10 19 76 direct supervision. above are true to my, 19.76 10/1 Date 1007. ction and this report is (Type or print) Wa. 98837 (Water Well Contractor) 10/1 ., 19...76 628 Contractor's License No. Date SP*45656-119 SHEETS IF NECESSARY)

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT UMAT


(Please type or print)

(Do not write above this line)

Page	2
------	---

State Well No. G-5812
State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		
Name Glen Maddox	County Umatilla Driller's well nu	mber #1	
Address P. O. Box P, Moses Lake, Wa. 98837	14 14 Section 34 T. 3N	R. 28E	W.M.
	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	·		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found		ft.
Rotary Driven Domestic Industrial Municipal	Static level ft. below land s	urface. Date	
Cable	Artesian pressure lbs. per square		
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well b	elow casing	
	Depth drilled ft. Depth of comple		ft.
	Formation: Describe color, texture, grain size a	nd structure of mat	terials:
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum	n and aquifer pene	trated,
PERFORATIONS: Perforated?	with at least one entry for each change of format position of Static Water Level and indicate princ		
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Basalt soft black	330 339	
	Basalt hard black	339 362	
perforations fromft. toftft.	Basalt soft black	362 404	
perforations fromft. toft.	Basalt hard black	404 486	
perforations from	Basalt soft blk & clay seams	486 498	
(7) SCREENS: Well screen installed? Yes No	Basalt soft black	498 535	
Manufacturer's Name	Basalt med black	535 559	
Type Model No	Basalt brown & black water	559 561	
Diam	Basalt soft black	561 569	
Diam, ft. to ft.	Basalt med black	569 584	
(8) WELL TESTS: Drawdown is amount water level is	Basalt soft black 621/water	584 660	
lowered below static level	Basalt hard black 646 water	660 666	
Was a pump test made? 🗌 Yes 📋 No If yes, by whom?	Basalt soft black 700 water.	666 707	
Yield: gal./min. with ft. drawdown after hrs.	Basalt hard black	707 732 732 740	
" " " " " " " " " " " " " " " " " " "	Basalt soft black broken Basalt red soft 740 water	732 740 740 750	
и и и	Basalt red soft 740 water Basalt hard black	750 804	
Bailer test gal./min. with ft, drawdown after hrs.	Basalt soft black 812 water	804 830	
Artesian flow g.p.m.	825 water		
perature of water Depth artesian flow encountered ft.	Work started 19 Complete	d	19
(9) CONSTRUCTION:	Date well drilling machine moved off of well		19
Well seal—Material used	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported		
Diameter of well bore to bottom of sealWATER RESOURCES DEPT	best knowledge and belief.	above are true t	,o my
Diameter of well bore below seal SALEM OREGON	[Signed](Drilling Machine Operator)	Date,	19
Number of sacks of cement used in well sealsacks			
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gailons	This well was drilled under my jurisdi	ction and this rer	ort is
of waterlbs./100 gals.	true to the best of my knowledge and bel	ief.	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name (Person, firm or corporation)	/Plant	
Did any strata contain unusable water? Yes No			
Type of water? depth of strata	Address		
Method of sealing strata off	[Signed](Water Well Contr		
Was well gravel packed? Yes No Size of gravel:	1		
	Contractoria License No. Date	_	10



Water Resources Department 1178 Chemeketa Street N. E. Salem, Oregon 97310

Re: File #G-5820 - Permit #G-5812

Gentlemen:

As you can see from the enclosed well log, this well yields 3,260 gallons per minute. This is sufficient water to irrigate the ground that this permit applies to, so it will not be necessary to drill another well. I hope this meets with your approval.

Sincerely yours,

Glen Modde

GLEN MADDOX

P. O. Drawer P

Moses Lake, Wa. 98837

RECEIVED

JUN 0 8 2012

WATER RESOURCES DEPT SALEM OREGON

Ü11429

WMAT RECEIVED WELL I.D.# 408754

STATE OF OREGON WATER SUPPLY WELL REPORT

MAR 1 4 1997

CTART CARDY # 496888

(as required by ORS 537.765) Instructions for completing this report are on the last page of this ATER		
	M) 2BEANN OF WELL by legal description:	
Name SIMPLOT	County Limitale Longitude Longitude	
Address Po Box 850	Township S N or S Range 28 E or W.	WM.
City State OR Zip 97838	Section 34 Los Plack Subdivision	
(2) TYPE OF WORK	Tax Lot Lot Block Subdivision Street Address of Well (or nearest address)	
New Well Deepening Alteration (repair/recondition) Abandonment 3) DRILL METHOD:	Street Address of Well (of ficulest address)	
Cable Auger	(10) STATIC WATER LEVEL:	
Other	482 ft. below land surface. Date 2-27	-97
(4) PROPOSED USE:	Artesian pressurelb. per square inch. Date	
Domestic Community Industrial Irrigation	(11) WATER BEARING ZONES:	_
Thermal Injection Livestock Other		
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found	_
Special Construction approval Yes No Depth of Completed Well ft.		CW
Explosives used Yes No Type Amount	From To Estimated Flow Rate	SWL
Diameter From To Material From To Sacks or pounds		
	(12) WELL LOG:	
How was seal placed: Method A B C D E	Ground Elevation	
Other		
Backfill placed from ft. to ft. Material	Material From To S	SWL
Gravel placed from ft. to ft. Size of gravel	clear out obstruction in well	
(6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Threaded	and seem 12" STEBELIZEE	
	TU BOTTOM	
Casing:		
Liner:		
Final location of shoe(s)		
(7) PERFORATIONS/SCREENS:		
Perforations Method Screens Type Material		
Slot Tcle/pipe	TO THE STATE OF TH	
From To size Number Diffracter size Casing Liner	RECEIVED	
	JUN 0 8 2012	
	WITTE DECOURAGE AND ADDRESS OF THE PROPERTY OF	
	WATER RESOURCES DEPT	
	SALEM OREGON	
(8) WELLTESTS: Minimum testing time is 1 hour	Date started 2-20-97 Completed 3-5-97	
Flowing Pailer Air Air	(unbonded) Water Well Constructor Certification: I certify that the work 1 performed on the construction, alteration, or abando	Onment
Pump Bailer Air Artesian Yield gal/min Drawdown Debt stem at Time	of this well is in compliance with Oregon water supply well construction stand	lards.
Yield gal/min Drawdown Dolff stem at Time	Materials used and information reported above are true to the best of my know and belief.	riedge
	WWC Number _ 1683	3
	Signed TONY BOWMEN Date 2-5-9	
Temperature of water Depth Artesian Flow Found	(bonded) Water Well Constructor Certification:	
Was a water analysis done? Yes By whom	I accept responsibility for the construction, alteration, or abandonment work	
Did any strata contain water not suitable for intended use? Too little	performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well	
Salty Muddy Odor Colored Other	construction standards. This report is true to the best of my knowledge and bel	lief.
Depth of strata:	WWC Number 544	-
/	COND COPY-CONSTRUCTOR THIRD COPY-CUSTOMER	77
ORIGINAL & FIRST COPY-WATER RESOURCES DEPARTMENT SE	COND COPY-CONSTRUCTOR THIRD COPY-CUSTOMER	