NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

BONWATER WELL REPORT CEIVED

STATE OF OREGON JUL 13 1976 state Well No.

(Please type or print)

(Please type or print)

(Please type or print)

(Do not write above this line)

(Do not write above this line)

SALEM. OF ECCN

(1) OWNER:	(10) LOCATION OF WELL:		
Name Tom Evans	County Benton Driller's well number		
Address Rt. 3 Box 414C			
Corvallis, Ore. 97330	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):	7.0		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
if abandonment, describe material and procedure in Itam 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 23		
Rotary Driven Domestic Industrial Municipal Domestic	Static level 15 ft. below land s	urface. Date 4/29/76	
☐ Bored ☐ Irrigation XX est Well ☐ Other ☐	Artesian pressure Ibs. per squar	e inch. Date	
(5) CASING INSTALLED: Threaded Welded The Control of the Control o	(12) WELL LOG: Diameter of well b		
"Diam fromft. toft. Gage	Depth drilled 30 ft. Depth of completed well 30 ft.		
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
(d) PERFORMANTONIA	with at least one entry for each change of format	ion. Report each change in	
(6) PERFORATIONS: Perforated? IX Yes No.	position of Static Water Level and indicate princ		
Type of perforator used <u>acetylene</u>	MATERIAL	From To SWL	
Size of perforations 2 in. by 6 in.	topsoil	0 2 -	
perforations from	sand & gravel	2 6	
perforations fromft. toft.	cemented_sand & gravel	6 20 -	
perforations fromft. toft.	loose sand & gravel	20 28	
(7) SCREENS: Well screen installed? Yes Kno	baring 100 gpm	28 30	
Manufacturer's Name	gray clay	- 	
Type Model No			
Diam. Slot size Set from ft. to ft.			
Diam Slot size Set from ft. to ft.	RECEIVED		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes No If yes, by whom?	JUN 2 2 2012		
d: gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT		
Hart death of the second of th	SALEM, OREGON	-	
<u>" </u>			
Bailer test 100 gal./min. with 2 ft. drawdown after 2 hrs.			
testan flow g.p.m.			
supperature of water 51 Depth artesian flow encountered	Work started 11/26/ 19 76 Complete	d 11/29/ 1976	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4/29/19 76	
Well seal-Material used	Drilling Machine Operator's Certification: This well was constructed under my	· · · · · · · · · · · · · · · · · · ·	
Well sealed from land surface toft.	Materials used and information reported	above are true to my	
Diameter of well bore to bottom of seal 12 in.	best knowledge and belder.	r/20/ 74	
Diameter of well bore below seal in.	[Signed] (Drilling Machine Operator)	Date 5/28/, 1976	
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No	503	
Brand name of bentonite	*		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	.: .:	
of water lbs./100 gals.	This well was drilled under my jurisdi- true to the best of my knowledge and beli		
Was a drive aboe used? Yes No Plugs Size: location ft. Did any strata contain unusable water? Yes No	NameRaymond C. Gellatly &Ronald S. Witham (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address P.O. Box 1, Philoma	th. Ore. 97370	
Method of sealing strata off	aumush	Holloch.	
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contri	ictor)	
Gravel placed fromft. toft.	Contractor's License No7.7 Date	5/28/ 19.76	
/TION AND WINDLY AT AN	PDMC TE NTOCOGGANU	CONTRACT TO	

125/5W-24

MEGEIVEU

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

Bentwater Well REPORTUL 171974

Abandon |

STATE OF OREGONTATE ENGINEER State Well No. ..

(Please type or print) SALEM. OREGON State Permit No. (Do not write above this line)

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. (1) OWNER:

(2) TYPE OF WORK (check):

Driven 📙

CASING INSTALLED:

Jetted

PERFORATIONS:

..... perforations from

Diam. Slot size Set from _

Type of perforator used Size of perforations

(7) SCREENS:

Type

Yield:

Bailer test Artesian flow

Manufacturer's Name

Diam. Slot size ...

(8) WELL TESTS:

(9) CONSTRUCTION:

Brand name of bentonite

Method of sealing strata off

Gravel placed from

Type of water?

Well seal-Material used coment.

Number of pounds of bentonite per 100 gallons

Did any strata contain unusable water? 🔲 Yes 🔏 No

Was well gravel packed? [] Yes [ANo Size of gravel: .

(3) TYPE OF WELL:

Tom Evans

Deepening [

." Diam. from ft. to

nerforations from

perforations from

Was a pump test made?
Yes No If yes, by whom?

gal./min. with

gal./min. with

Number of sacks of bentonite used in well seal _____

g.p.m. perature of water 52 Depth artesian flow encountered ...

Was a drive shoe used? ☐ Yes ☐No Plugs _____ Size: locationft.

depth of strata

If abandonment, describe material and procedure in Item 12.

2805 N.W. Ashwood Dr.

Corvallis, Oregon 97330

6 "Diam. from 0 ft. to 29 ft. Gage 250 " Diam, from ft. to ft. Gage

in. by

..... Set from

Reconditioning [

(4) PROPOSED USE (check):

Irrigation [] Test Well [] Other

Perforated? 🗌 Yes 🔣 No.

Well screen installed? 🗌 Yes 🛣 No

... Model No.

Drawdown is amount water level is lowered below static level

ft. drawdown after

21 ft. drawdown after 2

... ft. to ..

ft. to -

Domestic 📑 Industrial 🗆 Municipal 🗆

Threaded [] Welded []

..... ft. Gage

Name

Address

Rotary

Dug

New Well

(10) LOCATION OF WELL:			
County Benton Driller's well nu			
	R. 5W		W.M.
Bearing and distance from section or subdivisi	on corne	r	
(11) WATER LEVEL: Completed w	ell.		
Depth at which water was first found	່ ວວ		ft.
Static level 11 ft. below land s	urface.	Date に	10/7
Artesian pressure lbs. per squar			10/14
(12) WELL LOG: Diameter of well h	oelow car	sing 6'	!
Depth drilled 29 ft. Depth of compl			
Formation: Describe color, texture, grain size and show thickness and nature of each stratu			
with at least one entry for each change of format	tion. Rep	ort each	change in
position of Static Water Level and indicate prin	cipal wa	ter-beari	ng strata.
MATERIAL	From	To	SWL
sand and gravel	0	12	
cemented gravel	12	20	
sand & gravel (50)gpm	20	25	
large gravel	25	27	
cemented gravel	27	29	
	-,	_,	
RECEIVED			
JUN 2 2 2012	<u> </u>		
VATER RESOURCES DEPT			
SALEM, OREGON			
			
- U			
	-3	1 1	<u> </u>
Vork started 5/8/ 19 7) Complete	<u>~ 5</u> ,	/10/	-174
ate well drilling machine moved off of well	5/10	0/	1974
orilling Machine Operator's Certification:		. •	
This well was constructed under my Materials used and information reported	direct	super are tru	vision.
est knowledge and byllief.			_1
[Signed] (Drilling Machine Operator)	Date 6	/28/	., 1974.
Orilling Machine Operator's License No.			
Water Well Contractor's Certification:	-	<u> </u>	
This well was drilled under my jurisdi rue to the best of my knowledge and bel		nd this 1	report is
Name Raymond CGellatly & B	onal	d.s.k	li th em.
(Person, firm or corporation) Address P.O. Box 1, hil		ope or pri	
Signed] MAMMIN 9	éll	wie	
Contractor's Micense No. 77 Date		/28/.] ı
Contractor & another 1107			
ETS IF NECESSARY)		83	P*45656-119

hrs.