

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED BY CORRECTION REPORT MAR 13 1971 STATE OF OREGON STATE ENGINEER SALEM, OR.

Authorized POA

State Well No. 5N/36-26

State Permit No. MORR 1237

STATE ENGINEER, SALEM, OREGON 97310 (Please type or print) within 30 days from the date of well completion (Do not write above this line)

(1) OWNER:

Name E.L. Bettencourt Address Irigon, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

Threaded [] Welded [x] 1" Diam. from 78 ft. to ... ft. Gage 250

(6) PERFORATIONS:

Perforated? [] Yes [x] No. Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs.

CONSTRUCTION:

Well seal—Material used Bentonite Well sealed from land surface to 20 ft. Diameter of well bore to bottom of seal 11 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 1 sacks Number of sacks of bentonite used in well seal 1 sacks Brand name of bentonite National Number of pounds of bentonite per 100 gallons of water ... lbs./100 gals. Was a drive shoe used? [x] Yes [] No Plugs ... Size: location ... ft. Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [x] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Morrow Driller's well number 1/4 Section 26 T. 54 N. R. 26 E. W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 63 ft. Static level 55 ft. below land surface. Date 3-4-71 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing Depth drilled 78 ft. Depth of completed well 78 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows: Sand, Gravel, med., Gravel, coarse.

RECEIVED BY OWRD

JUL 27 2012

SALEM, OR

Work started 3-2 1971 Completed 3-4 1971 Date well drilling machine moved off of well 3-4 1971

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Troy Griffin Date 3/5, 1971 Drilling Machine Operator's License No. 15

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name TROY GRIFFIN (Person, firm or corporation) Address 925 HERMISTON AVE. HERMISTON ORE. [Signed] Troy Griffin (Water Well Contractor) Contractor's License No. 65 Date 3/5, 1971

1011450

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT

STATE OF OREGON

State Well No. 53/26E-266d

State Permit No. G-8158EG-8356

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date of well completion.

SEP 19 1977

(Please type or print)

(Do not write above this line)

WATER RESOURCES DEPT.

MORR 1234

(1) OWNER: SALEM, OREGON

Name MAX HELLBERG
Address Rt 2 Box 452 FRIGAN, OR

(2) TYPE OF WORK (check):

New Well [] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):

Rotary [] Driven [] Domestic [] Industrial [] Municipal []
Cable [] Jetted [] Irrigation [] Test Well [] Other []
Dug [] Bored []

(6) CASING INSTALLED: Threaded [] Welded []

18" Diam. from 1 ft. to 85 ft. Gage 250
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

(5) PERFORATIONS: Perforated? [X] Yes [] No.

Type of perforator used TORCH
Size of perforations 1/4" in. by 5" in.
perforations from 85 ft. to 67 ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.

(7) SCREENS: Well screen installed? [] Yes [] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from " ft. to " ft.
Diam. Slot size Set from " ft. to " ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?
Yield: gal./min. with " ft. drawdown after " hrs.
" " " " " "
" " " " " "
Bailer test gal./min. with " ft. drawdown after " hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered " ft.

(9) CONSTRUCTION:

Well seal-Material used BENTONITE
Well sealed from land surface to 18' ft.
Diameter of well bore to bottom of seal 1 9/16" in.
Diameter of well bore below seal 18" in.
Number of sacks of cement used in well seal " sacks
Number of sacks of bentonite used in well seal 5 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water " lbs./100 gals.
Was a drive shoe used? [X] Yes [] No Flugs " Size: location " ft.
Did any strata contain unusable water? [] Yes [X] No
Type of water? " depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [] No Size of gravel:
Gravel placed from " ft. to " ft.

(10) LOCATION OF WELL:

County MORROW Driller's well number
SE 1/4 NW 1/4 Section 26 T. 5 R. 26 E W.M.
Bearing and distance from section or subdivision corner WELL IS 30' WEST AND 284' SOUTH OF THE NE CORNER OF SE 1/4 NW 1/4 SEC 5

(11) WATER LEVEL: Completed well.

Depth at which water was first found 58 ft.
Static level 56 ft. below land surface. Date 6/8
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 18"

Depth drilled 87 ft. Depth of completed well 87 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Contains entries for SANDY SOIL (1-9) and SAND & GRAVEL (9-87).

RECEIVED BY OWRD

JUL 27 2012

SALEM, OR

Work started NOV 2 1976 Completed AUG 26 1977
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Max Hellberg Date 29 1977
(Drilling Machine Operator)

Drilling Machine Operator's License No.
Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name (Person, firm or corporation) (Type or print)
Address
[Signed] (Water Well Contractor)
Contractor's License No. Date 19

1011452