

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WASC WATER WELL REPORT

RECEIVED

STATE OF OREGON APR 3 1973 State Well No. 45/11E-14

45/11E-14

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE ENGINEER SALEM, OREGON
(Please type or print name)
Do not write above this line.

RECEIVED BY OWRD

003548

(1) OWNER:
Name Dean Voght/ Sportsmans Park
Address 5016 St. Johns Rd.
Vancouver, Washington 98661

(10) LOCATION OF WELL: JUN 17 2013
County Wasco Driller's well number
N 1/2 - S 1/2 SW 1/4 Section 14 T. 4S R. 11E W.M.
SALEM, OR
Bearing and distance from section or subdivision corner
320 Ft. N & 275 Ft. E of SW corner of
N 1/2 - S 1/2 - SW 1/4

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(11) WATER LEVEL: Completed well.
Depth at which water was first found 670-770 ft.
Static level 599'9" ft. below land surface. Date 3-12-73
Artesian pressure lbs. per square inch. Date

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
Dug Bored

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 806 ft. Depth of completed well 785 ft.
Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

(5) CASING INSTALLED: Threaded Welded
8" Diam. from 0 ft. to 217 ft. Gage 277
6" Diam. from 0 ft. to 785 ft. Gage 277

MATERIAL	From	To	SWL
brown top soil	0	2	
brown clay	2	5	
brown clay & small gravel	5	15	
red-brown-gray broken decomposed rock	15	39	6'
gray rock med. hard (M)	39	46	
brown & gray broken rock	46	74	
red & brown shale soft w/gray rock layers	74	86	
brown gray rock med.	86	94	
brown & gray porous lava rock soft	94	110	
gray & brown broken rock	110	144	(M)
red & brown shale w/ red brown/gray lava rock lay	144	171	
brown & gray red black broken gritty rock (soft)	171	580	
broken gray basalt	580	620	
gr-br-red-broken gritty rock w/gr broken basalt	620	806	
Work started 2-13 1973 Completed 3-12 1973			
Date well drilling machine moved off of well 3-14 1973			

(6) PERFORATIONS: Perforated? Yes No.
Type of perforator used torch
Size of perforations 1/4 in. by 10 in.
34 perforations from 765 ft. to 785 ft.
34 perforations from 665 ft. to 685 ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom? Driller
Yield: 80 gal./min. with 0 ft. drawdown after 12 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 78 Depth artesian flow encountered ft.

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] *Jan Hansen* Date 3-21, 1973
(Drilling Machine Operator)
Drilling Machine Operator's License No. 841

(9) CONSTRUCTION:
Well seal—Material used Portland, Cement
Well sealed from land surface to 218 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 4 yds-1 1/2 grout sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Hansen Drilling Co., Inc.
(Person, firm or corporation) (Type or print)
Address 6711 N.E. 58th Ave.
[Signed] *Joe Hansen* (Water Well Contractor)
Contractor's License No. 400 Date 3-30, 1973

(USE ADDITIONAL SHEETS IF NECESSARY)

SP-45858-119

1011619

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED
JAN 3 1966
STATE ENGINEER

WATER WELL REPORT
003546
(Please type or print)

State, Well No. 4/11-14
State Permit No.

(1) OWNER: SALEM, OREGON
Name ED SMART
Address Route 1 WAMIC, ORE

(2) LOCATION OF WELL:
County WASC Driller's well number
S 1/2 SW 3/4 N 1/2 S 1/2 W 1/2 Section 14 T. 4 S R. 11 E W.M.
Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):
 Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic Industrial Municipal
Irrigation Test Well Other

(5) TYPE OF WELL:
Rotary Driven
Cable Jetted
Dug Bored

(6) CASING INSTALLED: Threaded Welded
6" Diam. from 0 ft. to 25 ft. Gage 4 wall
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS: Perforated? Yes No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Cement
Depth of seal 24 ft. Was a packer used? NO
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off

(10) WATER LEVELS:
static level 434 ft. below land surface Date Dec 1/65
Artesian pressure lbs. per square inch Date

(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
" " " " "
Baller test 3 gal./min. with 65 ft. drawdown after 2 hrs.
Artesian flow g.p.m. Date
Temperature of water 62 Was a chemical analysis made? Yes No

(12) WELL LOG: Diameter of well below casing 6 in
Depth drilled 623 ft. Depth of completed well 623 ft.
Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.

MATERIAL	FROM	TO
Boulders Bedded in clay	0	19
Lava grey	19	26
Very hard Red Rock	26	59
clay yellow	59	74
Lava grey soft	74	131
Sandstone brown	131	158
Lava grey medium hard	158	210
volcanic ash fine	210	242
Lava, blue grey	242	265
Sandstone brown	265	620
Blue basalt hard	620	623

RECEIVED BY OWRD

JUN 17 2013

SALEM, OR

Work started Sept 20 1965 Completed Dec 1 1965
Date well drilling machine moved off of well Dec 2 1965

(13) PUMP: Manufacturer's Name Aeromotor
Type Submersible H.P. 2

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME LAWRENCE KOWALESKI
(Person, firm or corporation) (Type or print)
Address 741-4th MADRAS ORE

Drilling Machine Operator's License No. 1
[Signed] Lawrence Kowaleski
(Water Well Contractor)

Contractor's License No. 209 Date Dec 17, 1965

(USE ADDITIONAL SHEETS IF NECESSARY)