The original and first copy of this report are to be filed with the	ERECEIVED WEI	30 1 1	
	OREGON APR 24 1978 State Well No. or print)	J	
of well completion. (Do not write all	OVANATED RESOURCES DEPT Permit I	G-10229	
(1) OWNER:	(10) LOCATION OF WELL:		
Name WALLACE L. COLEMAN	County HARNEY Driller's well n	umber	
Address	SE 14 SW 14 Section 23 T. 395		
fields Oregon 97710	Bearing and distance from section or subdivis		
(2) TYPE OF WORK (check):	330" North + 1980   East		
New Well Deepening   Reconditioning   Abandon	Sec 22		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	vell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 18 ft.		
Rotary Driven Domestic Dindustrial Municipal	Static level 23 ft. below land surface. Date   23-78		
Cable   Jetted   Johnson   Industrial   Municipal   Dug   Bored   Irrigation   Test Well   Other		re inch. Date	
CASING INSTALLED: Threaded Welded Welded to Diam from 1 ft. to 108 ft. Gage 1025	(12) WELL LOG: Diameter of well below casing		
"Diam. fromft. toft. Gage	Depth drilled 408 ft. Depth of comp Formation: Describe color, texture, grain size	<del></del>	
" Diam. fromft. toft. Gage	and show thickness and nature of each stratu	m and aquifer penetrated.	
PERFORATIONS: Perforated? V Yes   No.	with at least one entry for each change of forms position of Static Water Level and indicate pri	ation. Report each change in acipal water-bearing strata.	
PERFORATIONS: Perforated? Yes   No.	MATERIAL	From To SWL	
Size of perforations 732 in. by 2 in.	Top Soul	0 18	
64/FT perforations from 112 ft to 408 ft	Clays day	18 28	
perforations fromft. toft.	Grand Charmy		
perforations fromft. toft.	Small Charles and mixed	98 138	
	Brown Strain & Charles War Samulation		
(7) SCREENS: Well screen installed?   Yes   No	Statut Sand	198	
Manufacturer's Name	Especial in small and of clay	18 208	
Type Model No Slot size Set from ft. to ft.	Bus Clay and sand	3/4 3/5	
Diam. Slot size Set from ft. to ft.	Sand & orangel	348 348 348	
	sand & son, and of Brown day	218 278	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sand & Grayel & Small strips of clay	278 388	
Was a pump test made? Yes No If yes, by whom?	Sandy Clay	788 788	
Yield: 2950 gal/min. with 15 ft. drawdown after 15 hrs.	Sand & Gravel	298 318	
2950 " 115 " 175 "	Hard Brown Clay	318 338	
<i>II</i>	Hard Sandy Clay	338 342	
Bailer test gal./min, with ft. drawdown after hrs.	Hard Brown Clay	358 398	
Artesian flow g.p.m.	Sand Pea Gravel	398 408	
perature of water Depth artesian flow encountered	Work started  -    1978 Complete	ied 9-28 1978	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1-22 1878	
Well seal-Material used Concrete	Drilling Machine Operator's Certification		
Well sealed from land surface toft_	This well was constructed under my	direct supervision.	
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief	above are true to my	
Diameter of well bore below seal	[Signed] Wolffel   Golfa-	Date 9 19 19	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)		
How was cement grout placed? Concrete mix	Drilling Machine Operator's License No.		
Truck	Water Well Contractor's Certification:	· · · · · · · · · · · · · · · · · · ·	
	This well was drilled under my jurisd true to the best of my knowledge and be		
Was a drive shoe used?    Yes    No Plugs    Size: location    in ft.	Name	<del></del> -	
Did any strata contain unusable water?   Yes No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address		
Method of sealing strata off	[Signed] / xlace F, Cotten	ion .	
Was well gravel packed? MYes   No   Size of gravel; 74 - 14	(Water Well Conf	ractor)	
Gravel placed from 22 ft. to 408 ft.	Contractor's License No Date	19/3	
(USE ADDITIONAL SE	KETS IF NECESSARY RD	SF1+45656-119	

NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report  are to be filed with the  WATER WEI	L REPORT CITED We	ell 9	-
WATER RESOURCES DEPARTMENT STATE OF SALEM, OREGON 97310 within 30 days from the date of well completion.  (Do not write all	or print) MATER RESOURCES Description in	To	-
Novelac		<u>APPL, 1022</u>	8 (4)
(1) OWNER:	(10) LOCATION OF WELL:		
Name WALLY COLEMAN	County HARNEY Driller's well n	umber	
Address FIELDS, ORE	3520 - 100 % Section 22 T. 395	R. 35E	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	lon corner	
New Well Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.	(11) WATER I EVEL Commission		
TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed w		-
	Depth at which water was first found	30	<u>ft.</u>
Cable Jetted 🗆 Domestic 🗀 industrial 🗀 Municipal 📋		surface. Date 7	-10
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure NONE lbs. per squar	re inch. Date	
(5) CASING INSTALLED: Threaded Welded Welded Decrease Threaded Thr	(12) WELL LOG: Diameter of well	_	
" Diam. fromft. toft. Gage	Depth drilled 20/ ft. Depth of compl		0/ ft.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu	and structure of	materials;
(6) PERFORATIONS: Perforated? M Yes   No.	with at least one entry for each change of forma position of Static Water Level and indicate prin	tion. Report each	change in
Type of perforator used MILLS KNIFE	MATERIAL	From To	SWL
Size of perforations /4 in, by 4 in.	TOPSOIL	0 2	
1333/2 perforations from 108 ft. to 134 ft.	BROWN CLAY / FINE SAND	2 19	
180 perforations from 148 ft. to 163 ft.	BLUE CLAY	19 28	
264 perforations from 172 ft. to 194 ft.	FINE BLACK SAND /MED GRIVE	28 61	28
(7) SCREENS: Well screen installed?  Yes W No	BROWN CLAY/COAPSE SAND	61 68	711
Manufacturer's Name	BROWN CLAY/COARSE BROWN SAND	76 88	24
Type Model No.	COARSE BROWN SAND /MED GRAVEL		"
Diam,	BROWN CLAY/COARSE BLACK SAND		"
Diam. Slot size Set from ft. to ft.	COARSE BROWN GRAVEL	104 116	1/
WELL TESTS: Drawdown is amount water level is	MED PROWN BRAVEL	116 134	"
lowered below static level	GREEN CLAY	134 141	- 1/
Was a pump test made? Yes   No If yes, by whom? WELL DRILLER	BROWN CLAY MED PLACK SAN	141 148	71
Yield: 1029 gal./min. with 66 ft. drawdown after 3 hrs.	MED BROWN SAND	153 157	11
* /5/4 " 8/.5 "	MED BLACK GRAVEL TOOKSE SAND		11
" " " " " " " " " " " " " " " " " " "	BLUE - GREEN CLAY	163 172	11
Bailer test gal./min. with ft. drawdown after hrs.	COARSE BLACK SAND	172 201	6'
Artesian flow NONE g.p.m.		<u> </u>	<u> </u>
Temperature of water 54 Depth artesian flow encountered ft.	Work started 7-9 19 79 Complete	ed 8-17	19 79
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8-28	19 7 <b>9</b>
Well seal-Material usedCONCRETE_ GROUT	Drilling Machine Operator's Certification:		
Well sealed from land surface to 22 ft.	This well was constructed under my Materials used and information reported		
Diameter of well bore to bottom of sealin.	best knowledge and belief.	1	
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date HUG. 29.	., 19.ZX
How was cement grout placed? SLURRY	Drilling Machine Operator's License No.	/33/	
now was centert grout praceur		-	
	Water Well Contractor's Certification:		
TO THE TOTAL OF THE OWNER OF THE PROPERTY OF THE OWNER	This well was drilled under my jurisd true to the best of my knowledge and bel		report is
Was a drive shoe used? MYes 🖸 No Plugs Size: location ft.		RIGATION	
Did any strata contain unusable water? 🔲 Yes 🛣 No	(Person, firm or corporation)	- (Type or pri	int)
Type of water? . depth of strata	Address GRANE ORE	I	***************************************
Method of sealing strata off	[Signed] John N Too	lierd	
Was well gravel packed?  Yes No Size of gravel BY OW	(Water Well Conti		
Gravel placed fromft. toft.	Contractor's License No. 272 Date	100 70 -	
(THE ADD MICHALL ED			

		SE
NOTICE TO WATER WELL CONTRACTOR STATES THE ATTERNATION AND THE ATT	OREGON Well 3 (located 47 OREGON AND A 1000)	0 of McLean Well No.1)
are to be filed with the	TRRECFIVED.	$\sim$ al $\sim$ and
WATER RESOURCES DEPARTMENT.	OREGON State Well Noc	375 35E-22C
Cipiease Up	FOR PINC PAPER 24 1070	To
of well completion.	boys # Pero RESOURCES DEPT	Victoria de la Constitución de l
	(10) ESCATION FOONWELL:	
(1) OWNER: Name Wallace L Coleman	5 fb (m. 1 mm)	
Address Fields		
Address 1.8.1.3.	NW % SW % Section 23 T. 395  Bearing and distance from section or subdivisi	r. 35 E w.m.
(2) TYPE OF WORK (check):		Cor Sec. 22
New Well  Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	rell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 48 ft.	
Rotary Driven Domestic Industrial Municipal	Static level 40 ft. below land	
Cable   Jetted   Dug   Bored   Irrigation   Test Well   Other		re inch. Date
A GRAG PAGE AT A TOP		
CASING INSTALLED: Threaded Welded Welded Down Diam from O ft. to 448 ft. Gage 025		pelow casing 20
"Diam from ft. to ft. Gage L. C.	Depth drilled 448 ft. Depth of completed well 448 ft.	
"Diam from the to fage	Formation: Describe color, texture, grain size	and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in	
PERFORATIONS: Perforated? Yes   No.	position of Static Water Level and indicate prin	
Type of perforator used	MATERIAL TOV SOIL	From To SWL
Size of perforations 3/32 in. by 2 in.	Brown Class Sond & Green Brown Class Sand & Brasen	12 48
(eH/F4, perforations from 1/05 ft. to 148 ft.	Sand & States	\$5 125 -
perforations fromft. toft.	Sand Ghedel Sand Ghedel	148 153 -
	Sunt Can	196 195
(7) SCREENS: Well screen installed?   Yes No	Blue Sand & Small Gravel	225 235
Manufacturer's Name Model No,	- Bom Olan	235 245
Diam. Slot size Set from ft. to ft.	Sand & Gravel	245 265
Diam. Slot size Set from it to ft.	Brenon Clay	285 295
(8) WELL TESTS: Drawdown is amount water level is	Sand i Coronel	295 315
lowered below static level	Brown Clay	315 345
Was a pump test made? ☐ Yes ☐ No If yes, by whom? OWNER	Light Br. Clay & Ships of grand	345 355
Yield: 1750 gal./min. with ft. drawdown after 6 hrs.	Gray Con & Strips of graves	355 365 365 385
1525 " 56 " 225"	Sand Grand 6 Stripe of Clay	385 395
	Sand & Gravel	395 435
Bailer test gal./min. with ft. drawdown after hrs.	-Burn Clay	H35 445
Artesian flow g.p.m.	<u> </u>	
perature of water Depth artesian flow encountered ft.	Work started )-28 1978 Complete	ed 220 1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	<u> </u>
Well seal-Material used Concrete	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision.	
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief	
The Number of sacks of cement used in well seal	[Signed (Drilling Machine Operator)	Date
Number of sacks of cement used in well seal sacks How was cament spout placed? Concrete mix Truck	Drilling Machine Operator's License No.	puput 1787 d d o dan a a da a da da da da a a a a a a a
DEC 16 2013		
	Water Well Contractor's Certification:	
SALEM, OR	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
Was a drive shoe used?  Yes No Plugs Size: location ft.		•
Did any strata contain unusable water?   Yes M No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed Hallace V. Letema	-
Was well gravel packed? A Yes No Size of gravel: 34 - 14	(Water Well Contr	actor)
Gravel placed from 20 ft. to 448 ft.	Contractor's License No Date	7-17 19/2