NATICE TO WATER WELL CONTRACTOR AC WATER WELL REPORT CEIVED The original and first copy of this report are to be JUL 1 7 1975 State Well No. 45/1E-35 filed with the STATE OF OBEGON STATE ENGINEER, SALEM, OREGON within 30 days from the date of well completion. (10) LOCATION OF WELL: (1) OWNER: Richard L. & Shirley V. Gingerich County Clackamas Driller's well number Name 10765 S. Barnards Road Address 34 Section 35 T. 4S R. 1E W.M. Canby, Oregon 97013 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Abandon [7] New Well X Deepening [Reconditioning | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. Depth at which water was firs Anna 1 2014 (3) TYPE OF WELL: (4) PROPOSED USE (check): Driven 🛘 tt. below land surface. Date 7-12-75
WATER RESOURCES DEPT
SALEM, OREGON Domestic X Industrial | Municipal | Static level Cable Jetted Dug Bored | Irrigation

Test Well
Other Artesian pressure CASING INSTALLED: Threaded [Welded [] (12) WELL LOG: Diameter of well below casing .. 10 " Diam. from ____ 0 ___ ft. to ____ 217 __ ft. Gage ___ 250. Depth drilled ft. Depth of completed well ft. to . Formation: Describe color, texture, grain size and structure of materials;" Diam. from ft. to and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? [] Yes 🛣 No. Type of perforator used MATERIAL From Size of perforations in. by in. Topsoil-brown 0 2 Clay-sticky-brown 2 perforations from Clay-sandy-brown 5 17 ___ perforations from Sand-blue-water 17 20 ___ perforations from 20 Clav-blue 23 (7) SCREENS: Well screen installed? 🗌 Yes 🕱 No Gravel-cemented-brown 23 50 Manufacturer's Name Clay-brown 50 Model No. Gravel-sand-water 57 63 Diam, Slot size Set from ft. to 99 Cemented gravel Diam. Slot size Set from ft. to ft. Cemented-gravel-water 99 120 139 Cemented_gravel 120 Drawdown is amount water level is lowered below static level (8) WELL TESTS: Cemented_gravel_water 139 143 Was a pump test made? W Yes | No If yes, by whomaqua Pump Co Clay-gray8 149 143 Gravel_small_water Yield: 100 149 35 ft. drawdown after 156 gal./min. with hrş. 156 Clay-blue 169 250 Claystone-blue-water 169 176 350 " 102 Clay-sandy-blue 176 218 Bailer test gal./min. with ft. drawdown after hrş. Sandstone-black-coarse-water 218 256 33 Artesian flow g.p.m. mperature of water Depth artesian flow encountered ... Work started 7-10 19 75 Completed 7-12 1975 Date well drilling machine moved off of well 7-12 1975 (9) CONSTRUCTION: **Bentonite** Drilling Machine Operator's Certification: Well seal-Material used This well was constructed under my direct supervision. 19 Materials used and information reported above are true to my Well sealed from land surface to . Diameter of well bore to bottom of seal best knowledge and beller [Signed] Haved Wound Date 7-15, 19.75 Diameter of well bore below seal ... 10. (Drilling Machine Operator) Number of sacks of cement used in well seal Number of sacks of bentonite used in well seal Brand name of bentonite Wilbur Ellis Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is ... 1bs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? X Yes I No Plugs Size: location Name S&M Drilling & Supply, Inc.
(Person, firm or corporation) (Type or print) Did any strata contain unusable water? 🖸 Yes 🔀 No 399 SE Walnut Street Type of water? depth of strata Canby, Oregon

Contractor's License No. 497 Date 7-15

Method of sealing strata off

Was well gravel packed? ☐ Yes 🛛 No Size of gravel:

Gravel placed from ft. to

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

_ filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL*REPORT STATE OF OREGON JUL 1 7 1975 State Well No. 45/12-35 (Please type of Whiter RESOURCES DEST. Permit No. (Do not write above this line); EM. OPECON.

(Do not write above this lineRLEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL;	
Name Richard L. & Shirley V. Gingerich	County Driller's well number	
Address		W.M.
((CONTINUED)	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well □ Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Rotary Driven Domestic Dindustrial Municipal Domestic Dindustrial Municipal	Static level ft. below land surface. Date	
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date	
CASING INSTALLED: Threaded Welded Diff. to the thing of the total the transform	(12) WELL LOG: Diameter of well below casing	ft.
PERFORATIONS: Perforated? Yes No.	Formation: Describe color, texture, grain size and structure of mate and show thickness and nature of each stratum and aquifer penets with at least one entry for each change of formation. Report each chan position of Static Water Level and indicate principal water-bearing s	rated, nge in
Type of perforator used	MATERIAL From To S	WL.
Size of perforations in. by in.	Clay-blue 256 261	
perforations from ft. to ft.	Sand-black-fine-water 261 265 33	3
perforations from		
(7) SCREENS: Well screen installed? Yes No	Each filled with 1 to 2 pee gravel to 255.	
Manufacturer's Name		
Type Model No ft. to ft.		-
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	AN 2 1 2014	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.	WATER RESQUECES DI	EPT
" " "	SALEM, DREGON	
" " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
mperature of water Depth artesian flow encountered ft.	Work started 19 Completed	19
(9) CONSTRUCTION:	The same of the sa	19
Well seal—Material used	Drilling Machine Operator's Certification:	
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	This well was constructed under my direct supervise Materials used and information reported above are true to best knowledge and belief.	o my
Diameter of well bore below seal in. Number of sacks of cement used in well seal	[Signed] Date 7-15 1	
Number of sacks of cement used in well sealsacks Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No883	
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report true to the best of my knowledge and belief.	ort is
Was a drive shoe used? 🗆 Yes 🔝 No Plugs Size: location ft.		
Did any strata contain unusable water? Yes No	Name S&M Drilling & Supply, Type or print)	
Type of water? depth of strata	Address 399 SE Welnut Street Canby, Orego	2 n
Method of sealing strata off	[Signed] Natur Huac	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)	
Current placed from # to #	Contractor's License No. 497 Date 7-15 1	ゅクち