NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

Rotary

STATE ENGINEER, SALEM, OREGON 97310 1 224 within 30 days from th of well completion

WATER WELL REI

STATE OF OREGON

(Please type or print)

of well completion. (Do not write a	bove this line NOV 1 1976 State Permit N	lo	
(1) OWNED.	WATER RESCURCES DEPT.		
(1) OWNER:	(10) DONETHOUSE GONETE:		//-
Name Glen Maddox	County Umatilla Driller's well n		#1
Address P. O. Drawer P, Moses Lake, Wa. 98837	34 14 Section 34 T. 3N	R. 28	E W.M.
	Bearing and distance from section or subdivis-	ion corner	::
(2) TYPE OF WORK (check):			
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1		
Rotery IV Driven	Depth at which water was first found	404	ft.
Cable	Static level 425 ft. below land	surface. Dat	e 9/20/76
Dug 🛘 Bored 🗍 Irrigation 🖪 Test Well 🖂 Other 🔻	Artesian pressure lbs. per squa	re inch. Dat	e
CASING INSTALLED: Threaded [] Welded El 44 ft. Gage •250	(12) WELL LOG: Diameter of well Depth drilled 830 ft. Depth of comp		•
ft. Gageft.			830 ft.
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu		
	with at least one entry for each change of forms		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prir		
Type of perforator used	MATERIAL	From	To SWL
Size of perforations in. by in.	Top Soil	0	2
perforations from ft. to ft.	Gravel cemented	 	36
perforations from ft. to ft.	Basalt broken brown		39
	Basalt med hard brown		57
perforations from	Basalt med black		77
(7) SCREENS: Well screen installed? ☐ Yes ☒ No	Basalt hard black	77 10	
Manufacturer's Name	Basalt soft blk(quartz & clay	1	
Type Model No	Basalt hard black	117 1	
Diam. Slot size Set from ft. to ft.	Basalt soft brown	144 16	
Diam, Slot size Set from ft. to ft.	Basalt soft black	160 17	
	Basalt med black	177 18	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Basalt soft black & blue clay		
Was a pump test made? ★ Yes No If yes, by whom? Pump	Basalt soft black	200 22	
	Basalt med black	227 26	
Yield: 3260 gal./min. with 17 ft. drawdown after 8 hrs.	Basalt soft black	262 27	
" "	Basalt hard black	270 27	L
и и п	Basalt soft black	272 28	
Bailer test gal./min. with ft. drawdown after hrs.	Basalt med black	287 29	,
Artesian flow g.p.m.	Basalt hard black	295 37	<u> </u>
	0.400	 	
perature of water Depth artesian flow encountered ft.		9/1 9/1	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	9/1	.0 19 76
Well seal—Material used Cement Well sealed from land surface to 44 ft. Diameter of well bore to bottom of seal 26 in. Diameter of well bore below seal 15 in.	Drilling Machine Operator's Certification: This well was constructed under my Materials used and information reported best knowledge and belief. [Signed] Adda A. F. Justin.	direct su above are	true to my
Number of sacks of cement used in well seal105sacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal	Drilling Machine Operator's License No.	TOO'.	
Brand name of bentonite			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisd		his report is
Was a drive shoe used? ☐ Yes ⊠ No Plugs Size: location ft.	true to the best of my knowledge and be	HeI.	
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Туре	or print)
	P. O. Box P. Moses Lak	e, Wa. 9	8837
Type of water? depth of strata	Address		*******************
Method of sealing strata off	[Signed] Stave Moon		
Was well gravel packed? Yes No Size of gravel:	628	10/1	76
Gravel placed from ft. to ft.	Contractor's License No Date		

RECEIVED BY OWRD

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be filed with the

APR 18 20MATER WELL REPORT UMAT

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310

SALEM, OREGON 97310

SALEM, OR

(Please type or print)

Page 2 State Well No. G-5812

of well completion. (Do not write ab	ove this line)	V4
(1) OWNER:	(10) LOCATION OF WELL:	
Name Glen Maddox	County Umatilla Driller's well no	
Address P. O. Box P, Moses Lake, Wa. 98837	34 34 Section 34 T. 3N	R. 28E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on_corner
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.
Rotary Driven Domestic Industrial Municipal	Static level ft. below land s	urface. Date
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: 'Diameter of well h	elow casing
"Diam. from	Depth drilled ft. Depth of compl	eted well ft.
ft. Gage	Formation: Describe color, texture, grain size a	nd structure of materials:
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratur	n and aquifer penetrated,
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of format position of Static Water Level and indicate prin	
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Basalt soft black	330 339
perforations fromft. toft.	Basalt hard black	339 362
perforations from ft. to ft.	Basalt soft black	362 404
perforations from ft. to ft.	Besalt hard black	404 486
real to the second of the seco	Basalt soft blk & clay seams	486 498
(7) SCREENS: Well screen installed? Yes No	Basalt soft black	498 535
Manufacturer's Name	Basalt med black	535 559
Type Model No.	Basalt brown & black water	559 561
Diam. Slot size Set from ft. to ft.	Basalt soft black	561 569
Diam Slot size Set from ft. to ft.	Basalt med black	569 584
(8) WELL TESTS: Drawdown is amount water level is	Basalt soft black 621/water	584 660
towered perow statte tever	Basalt hard black 646 water	660 666
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	Basalt soft black 700 water. Basalt hard black	707 732
Yield: gal./min. with ft. drawdown after hrs.	Basalt soft black broken	732 740
" " " "	Basalt red soft 740 water	740 750
H " H	Basalt hard black	750 804
Bailer test gal./min. with ft. drawdown after hrs.	Basalt soft black 812 water	804 830
Artesian flow g.p.m.	825 water	
perature of water Depth artesian flow encountered ft.	Work started 19 Complete	ed 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	19
	Drilling Machine Operator's Certification:	
Well seal—Material used	This well was constructed under my	direct supervision.
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore below sealin.		Dete 10
Number of sacks of cement used in well sealsacks	[Signed](Drilling Machine Operator)	Date 10
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	.,
Brand name of bentonite		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of water lbs./100 gals.	This well was drilled under my jurisditure to the best of my knowledge and bel	
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.		
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address	
Method of sealing strata off	[Signed]	
Was well gravel packed? Yes No Size of gravel:	[Signed](Water Well Conta	actor)
	Contractor's License No. Date	19

RECEIVED

NOV I 1976

VIATER RESOURCES DEPT.

SALEM, CREGON

Water Resources Department 1178 Chemeketa Street N. E. Salem, Oregon 97310

Re: File #G-5820 - Permit #G-5812

Gentlemen:

As you can see from the enclosed well log, this well yields 3,260 gallons per minute. This is sufficient water to irrigate the ground that this permit applies to, so it will not be necessary to drill another well. I hope this meets with your approval.

Sincerely yours,

GLEN MADDOX

P. O. Drawer P

Moses Lake, Wa. 98837

WARD'

RECEIVED BY OWRD

APR 18 2014

SALEM, OR

UMAT 50474

RECEIVED WELL I.D.# 40 8754

STATE OF OREGON
WATER SUPPLY WELL REPORT
(as required by ORS 537.765)

MAR 1 4 1997

(START CARD) # ... 9 96 8 88

Instructions for completing this report are on the last page of the	
(1) OWNER: Well Number SAL	EM, OBEGANN OF WELL by legal description:
Name SIMPLOT	County Limitale Longitude Longitude
Address PO BOX 850	Township 5 N or S Range 28 E E or W. WM.
City Marita State OR Zip 97838	Section 34 NE 1/4 88 1/4
(2) TYPE OF WORK	Tax LotLotBlockSubdivision
New Well Deepening Alteration (repair/recondition) Abandonment	Street Address of Well (or nearest address)
(3) DRILL METHOD:	
Rotary Air Rotary Mud Cable Auger	(10) STATIC WATER LEVEL:
Other	482 ft. below land surface. Date 2-27-97
(4) PROPOSED USE:	Artesian pressurelb. per square inch. Date
Domestic Community Industrial Irrigation	(11) WATER BEARING ZONES:
Thermal Injection Livestock Other	
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found
Special Construction approval Yes No Depth of Completed Well ft.	
Explosives used Yes No Type Amount	From To Estimated Flow Rate SWL
HOLE SEAL	
Diameter From To Material From To Sacks or pounds	
	(12) WELL LOG:
How was seal placed: Method A B C D E	Ground Elevation
Other	
Backfill placed from ft. to ft. Material	Material From To SWL
Gravel placed from ft. to ft. Size of gravel	
(6) CASING/LINER:	clear out obstruction in well
Diameter From To Gauge Steel Plastic Welded Threaded	and seem 12" STEBELIZEE
Casing:	TO BOTTOM
	I App
Liner:	CE/I
	1500
Final location of shoe(s)	APR 18 201
(7) PERFORATIONS/SCREENS:	
Perforations Method	2014
Screens Type Material Tele/pipe	S4/ × 1/4
From To size Number Diameter size Casing Liner	SM D
	SALEM, OR
(O) NUMBER OFFICE AND INCOME.	Date started 2-20-97 Completed 3-5-97
(8) WELLTESTS: Minimum testing time is 1 hour	Date started 2-20-77 Completed 3-5-77 (unbonded) Water Well Constructor Certification:
Flowing ☐ Pump ☐ Bailer ☐ Air ☐ Antesian	I certify that the work I performed on the construction, alteration, or abandonment
☐ Pump ☐ Bailer ☐ Air ☐ Artesian Yield gal/min Drawdown Dpinf stem at Time	of this well is in compliance with Oregon water supply well construction standards.
Yield gal/min Drawdown Dimistem at 1 hr.	Materials used and information reported above are true to the best of my knowledge and belief.
11111	WWC Number 1683
	Signed TONY BOWMEN Date 2-5-97
Temperature of water Depth Artesian Flow Found	(bonded) Water Well Constructor Certification:
Was a water analysis done? Yes By whom	I accept responsibility for the construction, alteration, or abandonment work
Did any strata contain water not suitable for intended use? Too little	performed on this well during the construction dates reported above. All work
Salty Muddy Odor Colored Other	performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.
Depth of strata:	WWC Number 544
The state of the s	Signed Jany Burel Date 35-97
ONIONAL & FIRST CORVIVATOR RECOURCES DEPARTMENT SE	COND CODY CONSTRUCTOR THIRD CODY CUSTOMER

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 91310 (Please type within 30 days from the date of well completion. (Do not write all	or print) WAT 20 1510 Over the HATER RESOURCES THE Permit No. LELE 2 SALEM, OREGON		
(1) OWNER:	(10) LOCATION OF WELL:		
Name LAL FARMS INC.	County UMATILIA Driller's well number 7-76		
Address P.G. Box 611	NE 1/4 NW1/4 Section 26 T. 3N R. 28 E, W.M.		
ECHO, URE,	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	The second secon		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 327 ft.		
Rotary Driven Domestic Industrial Municipal			
Cable Jetted			
Dug Bored Irrigation Test Well Other	Artesian pressure NONE lbs. per square inch. Date		
CASING INSTALLED: Threaded welded to give the Gage 1250	(12) WELL LOG: Diameter of well below casing and to 45° of the Depth drilled 9// ft. Depth of completed well 9// ft.		
ft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
numeron a myorid	with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated?	position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	SAND SILT 0 4		
perforations fromft. toft.	CLAY 4 /2		
perforations fromft. toft.	GRAVEL 12 38		
perforations from ft. to ft.	BROWN BASALT 38 67		
(7) SCREENS: Well screen installed? Yes No	HARD GREY BASALT 67 145		
(7) SCREENS: Well screen installed? Yes No	BRICKEN KEO PASALT 145 165		
	HARD GREY BASALT 165 274		
Type	BRIKEN GREY BASALT 274 295		
Diam. Slot size Set from ft. to ft.	HAPP GPEY BASILT 295 327		
Dev and	HARD GREY BASALT 341 427		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	BRINEN GREV SOADSTONE 1/25 1/35 WATE		
Was a pump test made? Yes No If yes, by whom?	HARD GREY BASALT 435 601		
Yield: 1000 Tgal./min. with ft. drawdown after hrs.	BROKEN GREV BASAUT 601 608		
AIR LIFT "	HARE GREY BASALT 608 615		
HIR GIP!	BROKEN GREY BASALT 615 650		
" " " " " " " " " " " " " " " " " " "	MED. HARD GREY 650 870		
Bailer test gal./min. with ft. drawdown after hrs.	BROKEN GREY BASALT 810 901 WATE		
Artesian flow NONE g.p.m.	HARD GREY BASALT 901 911		
erature of water 6 7 Depth artesian flow encountered MANE it.	Work started 4-26 1976 Completed 5- 7 19.7		
(9) CONSTRUCTION:	Date well drilling machine moved off of well 5-7 197		
Well seal-Material used NEAT CEMENT	Drilling Machine Operator's Certification:		
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of seal	best knowledge and belief		
Diameter of well bore below seal in. To 450FT.	[Signed] Everell A. Willer Bate 5-23, 1976		
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No		
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons TER BAC COMENT	This well was drilled under my jurisdiction and this report is		
of water lbs./100 gais.	true to the best of my knowledge and belief		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name WALLACE WELL LELY CO.		
Did any strata contain unusable water? Yes Wo	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address DOX///		
Method of sealing strata off	[Signed] Werelt H. William		
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)		
Cravel placed from	Contractor's License No. 593 Date 5-25 1976		

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPARE CEIVED 6. Blate Well No.

(Please type or print)

 •	
 b	6

(Do not write above this AMPR RESOURCES DEPT.

	SALEM ARECAN
(1) OWNER:	(10) LOCATION OF WELL:
(1) OWNER: Name I. F. FRENS (UMAT)	County WHATILLA Driller's well number
Address F. C. Box	NW 14 NW4 Section 23 T. 3N. R. 28 E.W.M.
KCHO, ORE.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well	
If abandonment, describe material and procedure in Item 12.	(11) WATER I EVEL. Completed well
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Botary & Driven	Depth at which water was first found 40 f
Cable Jetted	Static level 5/ ft. below land surface. Date /2-/8-7
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure NONE lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(18) HIST LOC
16 " Diam. from +/ tt to -60 ft. Gage . 250	(12) WELL LOG: Diameter of well below casing 8 " 120
" Diam, from ft. to ft. Gage	Depth drilled 936 ft. Depth of completed well 936 f
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials
Diani. Irolli	and show thickness and nature of each stratum and aquifer penetrated with at least one entry for each change of formation. Report each change is
(6) PERFORATIONS: Perforated? [] Yes [7] No.	position of Static Water Level and indicate principal water-bearing strate
Type of perforator used	MATERIAL From To SWL
	31804 Soil 0 12
Size of perforations in. by in.	SOFT BROWN BASHUT 12 40 mate
perforations fromft. toft.	HARD GREY BASALT 40 127
perforations from	BPIKEN RED WISON PSTONE 127 146 Wall
perforations fromft. toft.	GREV BASAST 140 172
(7) SCREENS: Well screen installed? Yes Wo	BRIKEN RED WISOMOSTONE 172 190 WATE
Manufacturer's Name	VERY HARU GERY BASALT 190 272
Type Model No	(LPEV 11) 90 A POTE NE 272 277
Diam. Slot size Set from ft. to ft.	MED HADS (PRY PASHED 277 415
Diam, Slot size Set from ft. to ft.	VEDJ NADO GREY " 415 448
	SOFT GREU BASALT 478 489
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	HARD GREV 11 489 1.38
Was a pump test made? ☐ Yes P No If yes, by whom?	SCET GREY " 438 645
gal./min. with ft. drawdown after hrs.	MED. HARD GREY " 145 670
	BROKEN RED " 1.90 702-WAT
EST - STOC GIM AIN DIVI	HARD GREY " 762 814
n n n	BRONER GREY " 814 842 WAL
Bailer test gal./min. with ft. drawdown after hrs.	HARO GREY " 842 912
sian flow g.p.m.	BRENEN GIZEV 11 912 936 WATE
Temperature of water Depth artesian flow encountered ft.	Work started 12-3 19 76 Completed 12-18 197
	Date well drilling machine moved off of well 12-18 19
(9) CONSTRUCTION:	
Well seal-Material used NEAT CEMENT	Drilling Machine Operator's Certification: This well was constructed under my direct supervision
Well sealed from land surface toft.	Materials used and information reported above are true to m
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Date Date 197
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's Dicense 140.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report
of waterlbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? 🗆 Yes 💆 No Plugs Size: location ft.	Name COALLACE COELL URLY. C.
Did any strata contain unusable water? Yes No	(Type or print)
Type of water? depth of strata	Address EADLE ON, C'RC,
Method of sealing strata off	1Signed & Shaller
Was well gravel packed? ☐ Yes M No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from the to the fit.	Contractor's License No. 583 Date19/



RECEIVED UMAT, 3N/28E/234

STATE OF OREGON	MAY 171993	58/6			-00
WATER WELL REPORT (as required by ORS 537.765)	· · · · · · · · · · · · · · · · · · ·	(START CARD) # 46	860)	
WA.	TER RESOURCES DEPT.	(SIARI CARD) #	000		
(1) OWNER:	SALEM, OREGON	(9) LOCATION OF WELL by legal descr	intion,		
Name L&L Farn		County Lmatille Latitude	I ongitude		
Address P.O. Box 63		Township_3/V N or S. Range_28			WM
City Echo	State OR Zip 97826	Section 23 NW 4	VU)	4	
(2) TYPE OF WORK:		Tax Lot 7/00 Lot Block			-
New Well Deepen Deepen	ondition	Street Address of Well (or nearest address)	· ho.	79	7826
(3) DRILL METHOD:		(0. 1101000 01 1101000 1101000 1101000)			
<u> </u>	Cable	(10) STATIC WATER LEVEL:			
Other		349 ft. below land surface.	Date	1-26	-93
(4) PROPOSED USE:		Artesian pressure			
Domestic Community Indu	Istrial Irrigation	(11) WATER BEARING ZONES:			
☐ Thermal ☐ Injection ☐ Other	er	000	,		
(5) BORE HOLE CONSTRUCTION	ON:	Depth at which water was first found			
Special Construction approval Yes No	Depth of Completed Well 1055 ft.				
Explosives used Yes No Type	Amount		nated Flow	Rate	SWL
HOLE SE	EAL Amount	978 986.	300		
Diameter From To Material	From To sacks or pounds				
14" 0 600 N/H					
8" 600 1055					
		(12) WELL LOG:			
		Ground elevation			
How was seal placed: Method \(\subseteq A \)	3 C C D CE				
Other		Material	From	То	SWL
Backfill placed from ft. to ft	. Material	Keconditioning &			
Gravel placed from ft. to ft	. Size of gravel	Deepening Procedure	15		
(6) CASING/LINER:					
	Steel Plastic Welded Threaded	Existing hole was:			
Casing: N/A		14" from 0 to 500			
		8" from 500 to 936			
		Well was reamed to	+		
			-		
Liner:	1	Well was deepened from 936 to 1055.	 		
Pinel Institute of sheets)	, t	Tronc 136 10 10336	 		
Final location of shoe(s)		Grav basalt	93/	978	
Perforations Method		Black basalt with	978	986	WR
Screens Type	Material	green soapstone	17.0	700	w
,,		Gray baselt	986	1055	
Slot From To size Number Dian	Tele/pipe neter size Casing Liner				
(8) WELL TESTS: Minimum test	ing time is 1 hour			L	
(b) While Tables William 9650	_ Flowing	Date started 12-22-93 Completed		26-	13
☐ Pump ☐ Bailer 🎉	Air Artesian	(unbonded) Water Well Constructor Certification:			
Yield gal/min Drawdown D	Orill stem at Time	I certify that the work I performed on the constru- ment of this well is in compliance with Oregon well con-			
		used and information reported above are true to my be			
1500+	/0.5.5 1 hr.	does and information reported above the day to my		_	
				lumber _	
		Signed	Date		
	th Associate Plant P	(bonded) Water Well Constructor Certification:		J	
	th Artesian Flow Found	I accept responsibility for the construction, alteration formed on this well during the construction dates report			
	whom	during this time is in compliance with Oregon well const	ruction sta	ndards. T	his repor
Did any strata contain water not suitable for Salty Muddy Odor Colon		is true to the best of my knowledge and belief.		Number 2	
•	eu L Otter	Signed Letreck Wallace	Date _	_	-92
Depth of strata:	SOURCES DEPARTMENT SECO	ND COPY - CONSTRUCTOR THIRD COPY - C			809C 10/9
UNIGHAL & FIRST COPT - WATER KEN	JOURCES DEFARINGENT SECO	THRO COFT - CONSTRUCTOR THRO COFT - C	COLONIE	,	555C (0/7

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be

UMAT

/	20
3N/28	1236
7 .	

STATE ENGINEER, SALEM, OREGON 97310 1715
within 30 days from the date
of well completion.

(Please type or print) (Do not write above this lighater RESOURCES DEPT. No.

3N/28	EN
7 .	. */
	7

(1) OWNER:	(10) LOCATION OF WELL:		
Name L+ L FARMS INC.	County HINATILLA Driller's well number 04-76		
Address 807 W, TAMARACK	SW 14 SE 14 Section 26 T. 3N R. 28 E. W.M.		
HERMISTON DREGON	Bearing and distance from section or subdivision		
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon	*		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		06 m	
Rotary Driven D Domestic Industrial Municipal		urface. Date 4-20.76	
Cable			
	Artesian pressure NonE lbs. per squar		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well h	16" 5 457 Delow casing 16" to 1,012	
/6 "Diam. from +/ ft. to -49 ft. Gage 1250		eted well / 0/2 ft.	
ft. to ft. Gage	Formation: Describe color, texture, grain size a	· · · · · · · · · · · · · · · · · · ·	
ft. toft. Gage	and show thickness and nature of each stratum	n and aquifer penetrated,	
PERFORATIONS: Perforated? Yes W No.	with at least one entry for each change of format position of Static Water Level and indicate prince		
	MATERIAL	From To SWL	
Size of perforations in. by in.	SILT, SAND	0 14	
perforations fromft. toft.	GRAVEL CLAY	14 30	
perforations fromft. toft.	MED HARD BROWN BASALT	65 85	
perforations from ft. to ft.	MED HARD GREY "	85 127	
(7) SCREENS: Well screen installed? Yes No	SOFT GREY "	127 135	
Manufacturer's Name	HARD GREY "	135 256	
Type Model No,	MED. HARD GREY "	256 28/	
Diam Slot size Set from ft. to ft.	HAPE GREY "	281 306	
Diam. Slot size Set from ft. to ft.	SOFT BROKEN SEPNS!	306 33/ WATER	
(8) WELL TESTS: Drawdown is amount water level is		331 452	
lowered below static level	BROKEN GREY W/SCAPSTONE	432 456 WINTER	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	HARD GREY BASALT	156 538	
: 2000 + gal./min. with ft. drawdown after hrs.	PREN WISEAMY	588 638 41 47 EX	
AIR LIFT "	BROKEN WSOAPSTONE	538 888	
" " " " " " " " " " " " " " " " " " "	17	888 913 WATER 913 913	
Bailer test gal./min. with ft. drawdown after hrs.	BROKEN BASALT	973 988 WAIER	
Artesian flow MONE g.p.m.		788 1012-	
perature of water 66 Depth artesian flow encounteredft.	Work started 2-26 1976 Complete		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-24 1976	
Well soal-Material used MEAT CEMENT	Drilling Machine Operator's Certification:		
Well sealed from land surface to 49 ft.	This well was constructed under my	direct supervision.	
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and helief	above are true to my	
Diameter of well bore below sealin.	[Signed] Level H. Wallace	hoto 5-23 1076	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	## ## ## ## ## ## ## ## ## ## ## ## ##	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	<i>386</i>	
Brand name of bentonite	Water Well Contractor's Cartification		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	otion and this was set is	
of water lbs./190 gals.	title to the pest of biy knowledge and bener.		
Was a drive shoe used? ☐ Yes XNo Plugs Size: location ft.	Name WALLACE WELL	Elelg, Co.	
Did any strata contain unusable water? Yes, No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address 500	100	
Method of sealing strata off	[Signed] wered A.U.	allace	
Was well gravel packed? [] Yes No Size of gravel:	(Water Well Contra		
Gravel placed fromft, toft.	Contractor's License No. 333 Date	5-33 1976	