

51473

STOREY DRILLING SERVICES



P.O. Box 98 • MIDLAND, OREGON 97634
(541) 884-3990 • (800) 245-8122
Fax #: (530) 528-2562
22560 ADOBE ROAD • RED BLUFF, CALIFORNIA 96080
CONTRACTOR'S LICENSES:
OR #601 • CA #583153 • NV #38199

RECEIVED

DEC 14 1998

WATER RESOURCES DEPT.
SALEM, OREGON

START May 19, 1998
FINISH: July 29, 1998

Mrs. Hilda Francis
Francis Loving Trust
P. O. Box 213
Chiloquin, Oregon 97624

WELL LOCATION: ½ mile north of Weyerhaeuser train shops off Sycan Road in Beatty, Oregon
NE¼ NW¼ S12 T36S R12E in Klamath County, Oregon

LOG

0 - 6	Sandy brown clay
6 - 29	Decomposed ash rock with white sticky ash
29 - 64	Hard ash rock
64 - 93	Grey ash with sticky ash
93 - 95	Hard ash rock
95 - 136	Decomposed bubbly brown lava
136 - 171	Hard brown ash
171 - 226	Hard black basalt with streaks brown ash
226 - 242	Brown lava
242 - 250	Hard brown ash rock
250 - 290	Hard black basalt with brown ash
290 - 296	Hard black basalt
296 - 356	Hard brown ash with sticky ash
356 - 360	Grey basalt
360 - 396	Hard brown ash with sticky ash
396 - 398	Brown & Red lava
398 - 460	Hard brown ash with sticky ash
460 - 470	Brown ash with sticky ash & pumice
470 - 488	Brown ash with sticky ash
488 - 498	Very hard brown ash
498 - 507	Broken brown ash
507 - 522	Hard broken brown ash
522 - 558	Hard brown ash
558 - 591	Hard black ash
591 - 683	Black ash with sticky ash
683 - 738	Black basalt
738 - 844	Black ash with sticky ash
844 - 868	Black ash with sticky ash
868 - 875	Hard black ash with sticky ash
875 - 1088	Black ash with sticky ash
1088 - 1124	Brownish black ash
1124 - 1149	Black as with sticky ash

RECEIVED

SEP 01 1998

WATER RESOURCES DEPT.
SALEM, OREGON

RECEIVED

AUG 14 2018

OWRD

139½ feet of 16 inch O.D. x .250 wall steel casing set & cemented at 138 feet with 16 inch rolled drive shoe
16 inch weld-on flange installed at top of casing
15 inch diameter hole drilled from 138 to 248 feet; 12¼ inch diameter hole drilled from 248 - 1149 feet
Static Water Level - 9 feet; Temperature 53° Fahrenheit
Test Pumped 1200 GPM @ 200 feet.

6.28 GPM SPECIFIC
CAPACITY

T 13004