

Groundwater Transfer Review Summary Form

Transfer/PA # T- 14738

GW Reviewer Grayson Fish Date Review Completed: 10/24/2025

Summary of Same Source Review:

☐ The proposed change in point of appropriation is not within the same aquifer as per OAR 690-380-2110(2).

Summary of Water Level Decline Condition Review:

☐ Water levels at the original point(s) of appropriation have exceeded the allowed decline threshold defined by conditions in the originating water right.

Summary of Injury Review:

☐ The proposed transfer will result in another, existing water right not receiving previously available water to which it is legally entitled or result in significant interference with a surface water source as per 690-380-0100(3).

Summary of GW-SW Transfer Similarity Review:

☐ The proposed SW-GW transfer doesn't meet the definition of "similarly" as per OAR 690-380-2130.

This is only a summary. Documentation is attached and should be read thoroughly to understand the basis for determinations.



Oregon Water Resources Department
725 Summer Street NE, Suite A
Salem, Oregon 97301-1271
(503) 986-0900
www.wrd.state.or.us

Ground Water Review Form:

- ☒ **Water Right Transfer**
☐ **Permit Amendment**
☐ **GR Modification**
☐ **Other**

Application: T-14738

Applicant Name: J.R.S. Properties III LP

Proposed Changes: ☒ POA ☒ APOA ☐ SW→GW ☐ RA
 ☐ USE ☒ POU ☐ OTHER

Reviewer(s): Grayson Fish

Date of Review: 10/24/2025

Date Reviewed by GW Mgr. and Returned to WRSD: _____

The information provided in the application is insufficient to evaluate whether the proposed transfer may be approved because:

- ☐ The water well reports provided with the application do not correspond to the water rights affected by the transfer.
- ☐ The application does not include water well reports or a description of the well construction details sufficient to establish the ground water body developed or proposed to be developed.
- ☐ Other _____
-

1. Basic description of the changes proposed in this transfer: Applicant is requesting a temporary transfer of POAs and POUs for certificates 93777 and 93778.

a. Cert 93777

- b) Authorized FROM Wells: Well 1 (LAKE 4564), Well 2 (LAKE 51182), Well 3 (LAKE 50941), Well 4 (LAKE 51031).
- c) Proposed TO Wells: Well 8 (LAKE 52491), Well 9 (LAKE 52492), Well 10 (LAKE 52770), Well 11 (LAKE 53479) and Well 7R (not yet constructed)
- d) Combined max rate: 1.02 CFS, duty 3 AF/acre for 81.3 acres, period of use is 3/1- 10/31

b. Cert 93778

- b) Authorized FROM Wells: Well 3: LAKE 50941, Well 4: LAKE 51031
- c) Proposed TO Wells: Well 8 (LAKE 52491), Well 9 (LAKE 52492), Well 10 (LAKE 52770), Well 11 (LAKE 53479) and Well 7R (not yet constructed)

- d) Combined max rate: 2.42 CFS, duty 3 AF/acre for 193.6 acres, period of use is 3/1 – 10/31

Note: This temporary transfer proposes the same changes listed under permanent transfer T-14011. The only difference is that Well 11 (LAKE 53479) has been constructed as of 7/9/2025.

The authorized POAs and POUs and the proposed APOAs and POUs have variously been subject to the following transfers: T-11341 (temporary, 2012 to 2016), T- 11602 (temporary, 2013 to 2017), T-11654 (temporary, 2014 to 2018), T-12386 (regular, approved 2018), T-12794 (regular, withdrawn), T-13524 (temporary, 2021 to 2025) and T-14011 (permanent, in review).

2. Will the proposed POA develop the same aquifer (source) as the existing authorized POA?
☒ Yes ☐ No Comments: Available data indicates a predominantly volcanic rock and sediment unit (some identify the unit as predominantly basalt) occurs beneath a predominantly basin fill sediment unit. Reports for the Goose and Summer Lakes Basin indicate groundwater occurs in both the predominantly basin fill sediment unit and predominantly volcanic rock and sediment unit. The groundwater is likely hydraulically connected, making a single groundwater system occurring in different geologic units with different permeability for each unit. A higher permeability and transmissivity generally occur in the predominantly volcanic rock and sediment unit and a lower permeability and transmissivity generally occur in the predominantly basin fill sediment unit.

Given the predominantly basin fill sediment unit and predominantly volcanic rock and sediment unit often have notably different hydraulic properties despite being hydraulically connected, they should be considered different in regard to this portion of the review. Wells completed solely in the predominantly volcanic rock and sediment unit tend to be more seasonally protective of shallower wells and surface water.

The currently authorized POA wells:

LAKE 4564 is 388-feet total depth and constructed to obtain groundwater solely from the shallower and lower permeability predominantly basin fill sediment unit;

LAKE 51031 is 551-feet total depth and constructed with casing to 466-feet blsd and a split seal to obtain groundwater primarily from the deeper and higher permeability predominantly volcanic rock and sediment unit below the casing and minimally from the shallower and lower permeability predominantly basin fill sediment unit;

LAKE 50941 is 490-feet total depth and constructed with casing to 448-feet blsd and a split seal to obtain groundwater solely from the deeper and higher permeability predominantly volcanic rock and sediment unit below the casing;

LAKE 51182 is 619-feet total depth and constructed with casing to 560-feet blsd and a split seal to obtain groundwater solely from the deeper and higher permeability predominantly volcanic rock and sediment unit below the casing.

The proposed POA wells:

LAKE 52491 and LAKE 52492 are 450-feet and 330-feet total depth respectively and constructed to obtain groundwater solely from the shallower and lower permeability predominantly basin fill sediment unit.

LAKE 52770 is 1,100-feet total depth with a 600-foot seal to obtain groundwater from the deeper and higher permeability predominantly volcanic rock and sediment unit.

LAKE 53479 is 800-feet total depth with a 50-foot seal and likely obtains groundwater from both the basin fill sediment unit and the predominantly volcanic rock and sediment unit.

The applicant proposes that Wells 7R source water from “basalt” with a total depth of 500 feet. However, based on nearby well logs it is likely that wells with the proposed construction would source water the from the shallower and lower permeability predominantly basin fill sediments. To source water from the predominantly volcanic rock and sediment unit (“basalt”), the well would need to be cased and sealed to ~625 feet (closer to the construction of LAKE 52770).

3. a) Is the existing authorized POA subject to a water level decline condition?
☒ Yes ☐ No Comments: Certificate 93777 has reference levels for wells 1 -4. The water user shall discontinue use of, or reduce the rate or volume of withdrawal from, the well if annual water level measurements reveal any of the following events:
- a. An average water level decline of three or more feet per year for five consecutive years; or
 - b. A water level decline of 15 or more feet in fewer than five consecutive years; or
 - c. A water level decline of 25 or more feet; or
 - d. Hydraulic interference leading to a decline of 25 or more feet in any neighboring well with senior priority.
- b) If yes, for each POA identify the reference level, most recent spring-high water level, and whether an applicable permit decline condition has been exceeded:

Well	Reference Level (ft bls / date)	Recent Spring-High (ft bls / date)	Exceeded?
LAKE 4564	20.61 on 3/25/2003	33.82 on 3/14/2013	No (no recent data)
LAKE 51182	68.63 on 3/25/2003	53.90 on 3/25/2025	No
LAKE 50941	60.67 on 3/25/2003	68.65 on 3/25/2025	No
LAKE 51031	71.17 on 3/25/2003	79.22 on 3/25/2025	No

Recommend reference levels for the “To” wells proposed under this transfer are listed in Section 8 of this review form.

4. a) Is there more than one source developed under the right (e.g., basalt and alluvium)?
☒ Yes ☐ No Comments: Wells authorized under Certificates 93777 and 93778 source water from basin fill sediments, volcanic rock and sediments or both.

b) If yes, estimate the portion of the right supplied by each of the sources and describe any limitations that will need to be placed on the proposed change (rate, duty, etc.): Changing the pumping from the current "From" authorized POA wells to the proposed "To" APOA wells will shift tapping groundwater from about 73% from the deeper predominantly volcanic rock and sediment unit via three wells and 27% from the shallower predominantly basin fill sediment unit via one well (percentages based upon 2002 to 2022 reported water use for certificates 93777 and 93778) to possibly about 40% from the deeper predominantly volcanic rock and sediment unit and 60% from the shallower predominantly basin fill sediment unit.

Newly installed Well 11 (KLAM 53479) is 800 feet deep with a 50-foot seal and a 1200 gpm yield. The well report lists a single water bearing zone between 50 to 800 feet bls and appears to document basin fill sediments to a depth of 410 feet. The materials described below 410 feet appear part of the deeper volcanic rock and sediment unit despite no "basalt" being described. Given the information available, it is likely that most of the water would be sourced from the deeper volcanic units encountered below 410 feet due to the porous nature of the material described ("pumice stone" and "perlite").

5. a) Will this proposed change, at its maximum allowed rate of use, likely result in an increase in interference with **another ground water right**?

☒ Yes ☐ No Comments: The proposed change will move groundwater pumping about 6.8 to 8.8 mile south from the north side of Upper Chewaucan Marsh to the south side of Upper Chewaucan Marsh (see attached maps). The proposed change will move groundwater pumping closer to a different set of groundwater right wells (see attached maps).

b) If yes, would this proposed change, at its maximum allowed rate of use, likely result in another groundwater right not receiving the water to which it is legally entitled?

☐ Yes ☒ No If yes, explain: The calculated increase in seasonal drawdown at the nearest neighboring groundwater right well (south side of Upper Chewaucan Marsh) ranges from more than 8.75 feet (pro-rated pumping rate) to more than 17.75 feet (full pumping rate) at the end of 30 days to more than 15.25 feet (pro-rated pumping rate) to nearly 31.25 feet (full pumping rate) at the irrigation season end (245 days) (see attached calculations). Interference at wells further away will be less. A decline condition within certificate 93777 addresses the potential situation of the authorized groundwater use adding 25 or more feet of seasonal interference (decline) at a neighboring senior groundwater right well. While an increase in seasonal interference (drawdown) of 25 feet or more is possible (see attached hydrograph showing seasonal drawdown exceeding 30 feet total at well LAKE 52770), the maximum increase in seasonal interference at the nearest neighboring groundwater right well due solely to the proposed transfer is likely to be closer to the pro-rated pumping rate calculated nearly 15.50 feet at the end of 245 days. The neighboring well should be able to accommodate 15 feet of additional seasonal drawdown.

Additionally, the proposed change moves groundwater pumping into a vicinity that appears to be experiencing a groundwater level decline since 2005 (see attached hydrographs). The groundwater level at well LAKE 1719 is relatively stable, near 4302 feet elevation amsl from 1960 to the mid-1970s, a decline of about 5.5 feet from the mid-1970s to early 1980s to a new equilibrium of about 4297 feet elevation amsl that is close to the Chewaucan River stage near the Narrows (relatively steady from about 1980 to 2005), and an ongoing decline since 2005, possibly taking the groundwater level below the river bottom. The groundwater level decline in the 1970s and after 2010 may correspond to increased groundwater development in the area.

The applicant has submitted 2017 to 2023 data (see hydrographs) for wells LAKE 52769 [60 feet total depth], and LAKE 52770 [1,100 feet total depth], and LAKE 52463 [410 feet total depth]. The data can be interpreted as showing an annual decline like LAKE 1719 which has experienced a total groundwater level decline of 20.2 feet over the period of record.

Based on a preponderance of the evidence standard, it is unlikely that another groundwater right will not receive the water to which it is legally entitled.

6. a) Will this proposed change, at its maximum allowed rate of use, likely result in an increase in interference with **another surface water source**?

☒ Yes ☐ No Comments: Yes. Despite the proposed POA change moving the net groundwater pumping further away from Chewaucan River, which typically decreases the net seasonal groundwater level drawdown at the river and the net groundwater interference with the river, the proposed POA change will likely increase the net seasonal groundwater level drawdown at the river and the net groundwater interference with the river due to a higher percentage of "To" wells sourcing water from the shallow basin fill sediments (see the attached seasonal drawdown calculation and seasonal interference calculation summary).

The proposed POA change will likely increase the net seasonal groundwater level drawdown at the river and the net groundwater interference with the river given the current "From" POA wells tap groundwater from mostly from the deeper predominantly volcanic rock and sediment unit (73%) and less from the shallower predominantly basin fill sediment unit (27%) (percentages based upon 2002 to 2022 reported water use for certificates 93777 and 93778); whereas the proposed "To" POA wells tap groundwater less from the deeper predominantly volcanic rock and sediment unit (possibly 40%, two wells, driller report indicates well yield from 500 to 1,200 gpm) and more from the shallower predominantly basin fill sediment unit (about 60%, three wells, driller reports indicate well yields from 2,700 to 3,000 gpm each). This is less protective of shallower wells and surface water. Consequently, the seasonal groundwater interference with the river at the end of the irrigation season (240 days) is calculated to increase from about 11.5% of the pumping rate when pumping the "From" wells to about 23.7% of the pumping rate when pumping the "To" wells. This results in an estimated additional 0.21 cfs of surface water depletion after 240 days of pumping at the pro-rated rate.

- b) If yes, at its maximum allowed rate of use, what is the expected change in degree of interference with any **surface water sources** resulting from the proposed change?

Stream: Chewaucan River☒ Minimal ☐ Significant

Stream: _____

☐ Minimal ☐ Significant

Provide context for minimal/significant impact: See discussion in part 6a above. There is a potential that the seasonal groundwater interference with the Chewaucan River could increase from about 11.5% to 23.7% of the pumping rate after 240 days of pumping. However, given the relatively minor estimated increase in interference (0.21 cfs after 240 days of pumping at the pro-rated rate) and the fact that use has already been occurring at the "From" wells under temporary transfer T-13524, it is likely that the expected change in degree of interference with the Chewaucan River would be minimal.

7. For SW-GW transfers, will the proposed change in point of diversion affect the surface water source similarly (as per OAR 690-380-2130) to the authorized point of diversion specified in the water use subject to transfer?
☐ Yes ☐ No Comments: N/A
8. What conditions or other changes in the application are necessary to address any potential issues identified above:

Reference Levels:

The "From" certificate 93777 contains water level decline permit language and establishes reference levels for the 4 authorized wells based on static water level measurements collected on 3/25/2003 (see section 3b). Given that the proposed "To" wells were not yet constructed in 2003, reference levels will need to be extrapolated back to 2003 to prevent a situation where enlargement is able to occur.

Groundwater level measurements have been collected from observation well LAKE 1719 starting in 1959 and continuing through 2025. LAKE 1719 is located 0.5 to 1.6 miles to the east of the proposed "To" wells associated with this transfer and is constructed to obtain water from shallow basin fill sediments and deeper volcanic rock and sediments. LAKE 52770 is proposed "To" POA 10 associated with this transfer and has water level measurement data available starting in May 2017 through March 2023. LAKE 52770 is sealed to 600 feet and sources water from the deeper volcanic rock and sediments. Where LAKE 1719 and LAKE 52770's periods of record overlap, the measured water levels trend similarly and are at similar elevations with annual highs being within several feet. Well 7R has not been installed at the time of this review, however, recent groundwater level data from LAKE 52463 (the well that 7R is to replace) is available. Spring water level data available for LAKE 52463 show similar trends and water levels as LAKE 1719 and LAKE 52770. The similar trend and spring water levels in recent years suggest that LAKE 1719, LAKE 52770 and LAKE 52463 are accessing the same groundwater reservoir.

LAKE 52491 and LAKE 52492 were installed in 2013, however, March groundwater levels have not been collected despite these wells being listed under temporary transfer T-13524. No groundwater levels are available from LAKE 53479 other than at time of well completion in July of 2025. Given the lack of water level data for these wells, it is not possible to make well specific evaluations regarding extrapolating reference levels. However, given that data available from LAKE 1719, LAKE 52770 and LAKE 52463 suggest similar groundwater levels and trends despite differing construction, it is likely that the other "From" POAs listed on this transfer would also show similar groundwater levels and trends (See attached "Reference Level Discussion Hydrographs").

The water level in LAKE 1719 was 19.84 bls (4298.22 ft amsl) on 2/14/2003 which is the same year that the reference levels were established for the “From” POA under Certificate 93777. Groundwater elevations measured in LAKE 52770 are several feet lower than water levels measured at roughly the same time in LAKE 1719 during March. Taking this elevation difference into consideration, a water level elevation of 4295 ft amsl is likely a reasonable estimation of water level in LAKE 52770 in March of 2003. The ground surface elevation at the location (as shown on the transfer application map and in GWIS) of LAKE 52770 as determined by LiDAR is 4329 ft amsl. Using a reference level elevation of 4295 ft amsl results in a reference level of 34 feet bls for LAKE 52770. This same reasoning was used to establish reference levels for the other wells listed on this transfer. See the below table for a summary of these reference levels:

POA #	Well Log ID	2003 Water Level Reference Elevation (amsl)	Land Surface Elevation at Well Location (amsl)	Permit Condition Reference Level (bls)
7R	Not constructed	4295	4315	20
8	LAKE 52491	4295	4320	25
9	LAKE 52592	4295	4329	34
10	LAKE 52770	4295	4329	34
11	LAKE 53479	4295	4319	24

Additional recommendations:


“Large” flow meter condition for all the “From” POA and the proposed “To” POA wells to prevent enlargement. Require the flow meter for each well be properly installed and maintained. Each meter shall be either within 50 feet of the well head with a clearly visible monument adjacent to the meter or a surveyed location shall be provided and a clearly visible monument adjacent to the meter shall be installed for each meter more than 50 feet from the well head.

Condition 7P (well tag condition) for all the “To” and “From” POA wells.


Condition 7T (modified) for both the proposed “To” wells: “Prior to use, the proposed “To” wells shall be configured to allow a strictly clean water (no oil) static water level measurements with an electric-tape. That can include measurement access via an unobstructed vertical discharge pipe that allows the groundwater level to fluctuate freely within the discharge pipe (no valves, etc.). Otherwise, a dedicated measuring tube must be installed prior to use. The tube must be unobstructed, have a diameter of ¾ inch (0.75 inch) or greater, and pursuant to figure 200-5 in OAR 690-200.”



9. Any additional comments:_____

T-14738 - From Wells



T-14738 - To Wells



Area Hydrographs**Reference Level Discussion Hydrographs**

Aquifer Parameters

Theis Equation specific capacity to transmissivity					
From Driller Water Well Report Recorded Pump Test Data					
Basin Fill					
Well County	Well Num	Transmissivity gpd/ft	Transmissivity ft2/day	Open Interval feet	Conductivity ft/day
From Wells					
LAKE	4564	51,036.85	6,822.63	360.00	18.95
		51,036.85	6,822.63	From Wells Average	18.95
To Wells					
LAKE	1712	5,187.30	693.44	435.00	1.59
LAKE	1714	4,869.60	650.97	365.00	1.78
LAKE	1717	3,657.33	488.91	464.00	1.05
LAKE	1715	17,137.04	2,290.89	252.00	9.09
LAKE	1719	71,089.20	9,503.24	284.00	33.46
LAKE	1724	6,934.26	926.98	297.00	3.12
		18,145.79	2,425.74	To Wells Average	8.35
		22,844.51	3,053.87	Overall Average	9.87
Basalt, Volcanic Rocks & Sediments					
Well County	Well Num		Transmissivity ft2/day	Open Interval feet	Conductivity ft/day
From Wells					
LAKE	51882	76,985.84	10,291.51	59.00	174.43
LAKE	50941	56,521.18	7,555.78	42.00	179.90
LAKE	51031	66,988.37	8,955.04	85.00	105.35
		66,831.80	8,934.11	From Wells Average	153.23
To Wells					
None	(all air tests, no pump test)				
		----	----	To Wells Average	----
		66,831.80	8,934.11	Overall Average	153.23

Well-to-Well Interference Calculations

Drawdown Calculations Using Theis Equation													
Theis Equation: $s = \frac{Q}{4\pi T} W(u)$ $u = \frac{r^2 S}{4 T t}$ $W(u) = -\ln u - 0.5772157 + (u^{1/4}) - (u^{3/4}) + (u^{5/4}) - (u^{7/4}) + \dots$ s = drawdown (L) T = transmissivity (L ² /T) S = storage coefficient (dimensionless) π = 3.141592654 r = radial distance (L) t = time (T) u = dimensionless $W(u)$ = well function													
Transmissivity T (gpd/ft)	Transmissivity T (ft ² /day)	Storage Coefficient S	Pumping Rate Q (gal/min)	Pumping Rate Q (ft ³ /sec)	Time t (days)	Distance r (feet)	pl	u	W(u)	Drawdown s (feet)	Drawdown Change s (feet)	Well	Comments
Note : W(u) calculation valid when $u < 7.1$													
Note: yellow grid areas are where values are calculated													
W(u) calculation test													
From POA wells to closest Water Right Well LAKE 51588 (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	385.57	0.86	30.00	7,910.00	3.14	0.1707	1.3545	2.6187		LAKE 4564	Continuous Pumping at Full Rate (Basin Fill Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	30.00	7,525.00	3.14	0.0528	2.4159	1.5970		LAKE 51182	Continuous Pumping at Full Rate (Volcanics Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	30.00	2,600.00	3.14	0.0063	4.4955	2.9718		LAKE 50941	Continuous Pumping at Full Rate (Volcanics Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	30.00	7,015.00	3.14	0.0459	2.5495	1.6854		LAKE 51031	Continuous Pumping at Full Rate (Volcanics Portion)
			1,542.30	3.44						8.87			
To POA wells to closest Water Right Well Solheim Well POD #1 (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	385.57	0.86	30.00	4,425.00	3.14	0.0534	2.4052	4.6502		LAKE 52463	Continuous Pumping at Full Rate (Basin Fill Portion)
22,852.99	3,055.00	0.00100	385.57	0.86	30.00	3,555.00	3.14	0.0345	2.8245	5.4609		LAKE 52491	Continuous Pumping at Full Rate (Basin Fill Portion)
22,852.99	3,055.00	0.00100	385.57	0.86	30.00	4,515.00	3.14	0.0556	2.3671	4.5765		LAKE 52492	Continuous Pumping at Full Rate (Basin Fill Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	30.00	2,170.00	3.14	0.0044	4.8552	3.2095		LAKE 52770	Continuous Pumping at Full Rate (Volcanics Portion)
			1,542.30	3.44						17.99	9.0242		
From POA wells to closest Water Right Well LAKE 51588 (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	190.43	0.42	30.00	7,910.00	3.14	0.1707	1.3545	1.2933		LAKE 4564	Continuous Pro-Rated Pumping (Basin Fill Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	30.00	7,525.00	3.14	0.0528	2.4159	0.7887		LAKE 51182	Continuous Pro-Rated Pumping (Volcanics Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	30.00	2,600.00	3.14	0.0063	4.4955	1.4677		LAKE 50941	Continuous Pro-Rated Pumping (Volcanics Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	30.00	7,015.00	3.14	0.0459	2.5495	0.8324		LAKE 51031	Continuous Pro-Rated Pumping (Volcanics Portion)
			761.71	1.70						4.38			
To POA wells to closest Water Right Well Solheim Well POD #1 (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	190.43	0.42	30.00	4,425.00	3.14	0.0534	2.4052	2.2966		LAKE 52463	Continuous Pro-Rated Pumping (Basin Fill Portion)
22,852.99	3,055.00	0.00100	190.43	0.42	30.00	3,555.00	3.14	0.0345	2.8245	2.6970		LAKE 52491	Continuous Pro-Rated Pumping (Basin Fill Portion)
22,852.99	3,055.00	0.00100	190.43	0.42	30.00	4,515.00	3.14	0.0556	2.3671	2.2602		LAKE 52492	Continuous Pro-Rated Pumping (Basin Fill Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	30.00	2,170.00	3.14	0.0044	4.8552	1.5851		LAKE 52770	Continuous Pro-Rated Pumping (Volcanics Portion)
			761.71	1.70						8.84	4.4569		

Drawdown Calculations Using Theis Equation													
Theis Equation: $s = \frac{Q}{4\pi T} W(u)$ $u = \frac{r^2 S}{4 T t}$ $W(u) = -\ln u - 0.5772157 + (u^{1/4}) - (u^{3/4}) + (u^{5/4}) - (u^{7/4}) + \dots$ s = drawdown (L) T = transmissivity (L ² /T) S = storage coefficient (dimensionless) π = 3.141592654 r = radial distance (L) t = time (T) u = dimensionless $W(u)$ = well function													
Transmissivity T (gpd/ft)	Transmissivity T (ft ² /day)	Storage Coefficient S	Pumping Rate Q (gal/min)	Pumping Rate Q (ft ³ /sec)	Time t (days)	Distance r (feet)	pl	u	W(u)	Drawdown s (feet)	Drawdown Change s (feet)	Well	Comments
Note : W(u) calculation valid when $u < 7.1$													
Note: yellow grid areas are where values are calculated													
W(u) calculation test													
From POA wells to closest Water Right Well LAKE 51588 (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	385.57	0.86	245.00	7,910.00	3.14	0.0209	3.3117	6.4027		LAKE 4564	Continuous Pumping at Full Rate (Basin Fill Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	245.00	7,525.00	3.14	0.0065	4.4703	2.9551		LAKE 51182	Continuous Pumping at Full Rate (Volcanics Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	245.00	2,600.00	3.14	0.0008	6.5901	4.3564		LAKE 50941	Continuous Pumping at Full Rate (Volcanics Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	245.00	7,015.00	3.14	0.0056	4.6098	3.0473		LAKE 51031	Continuous Pumping at Full Rate (Volcanics Portion)
			1,542.30	3.44						16.76			
To POA wells to closest Water Right Well Solheim Well POD #1 (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	385.57	0.86	245.00	4,425.00	3.14	0.0065	4.4591	8.6211		LAKE 52463	Continuous Pumping at Full Rate (Basin Fill Portion)
22,852.99	3,055.00	0.00100	385.57	0.86	245.00	3,555.00	3.14	0.0042	4.8946	9.4632		LAKE 52491	Continuous Pumping at Full Rate (Basin Fill Portion)
22,852.99	3,055.00	0.00100	385.57	0.86	245.00	4,515.00	3.14	0.0068	4.4191	8.5438		LAKE 52492	Continuous Pumping at Full Rate (Basin Fill Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	245.00	2,170.00	3.14	0.0005	6.9514	4.5952		LAKE 52770	Continuous Pumping at Full Rate (Volcanics Portion)
			1,542.30	3.44						31.22	14.4619		
From POA wells to closest Water Right Well LAKE 51588 (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	190.43	0.42	245.00	7,910.00	3.14	0.0209	3.3117	3.1621		LAKE 4564	Continuous Pro-Rated Pumping (Basin Fill Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	245.00	7,525.00	3.14	0.0065	4.4703	1.4595		LAKE 51182	Continuous Pro-Rated Pumping (Volcanics Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	245.00	2,600.00	3.14	0.0008	6.5901	2.1515		LAKE 50941	Continuous Pro-Rated Pumping (Volcanics Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	245.00	7,015.00	3.14	0.0056	4.6098	1.5050		LAKE 51031	Continuous Pro-Rated Pumping (Volcanics Portion)
			761.71	1.70						8.28			
To POA wells to closest Water Right Well Solheim Well POD #1 (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	190.43	0.42	245.00	4,425.00	3.14	0.0065	4.4591	4.2578		LAKE 52463	Continuous Pro-Rated Pumping (Basin Fill Portion)
22,852.99	3,055.00	0.00100	190.43	0.42	245.00	3,555.00	3.14	0.0042	4.8946	4.6736		LAKE 52491	Continuous Pro-Rated Pumping (Basin Fill Portion)
22,852.99	3,055.00	0.00100	190.43	0.42	245.00	4,515.00	3.14	0.0068	4.4191	4.2196		LAKE 52492	Continuous Pro-Rated Pumping (Basin Fill Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	245.00	2,170.00	3.14	0.0005	6.9514	2.2695		LAKE 52770	Continuous Pro-Rated Pumping (Volcanics Portion)
			761.71	1.70						15.42	7.1424		

Drawdown Calculations Using Theis Equation													
Theis Equation: $s = \frac{Q}{4\pi T} W(u)$ $u = \frac{r^2 S}{4 T t}$ $W(u) = (-\ln u) - (0.5772157) + (u^{1/4}) - (u^{1/2}) + (u^{3/4}) - (u^{5/4}) + (u^{3/2}) - (u^{5/2}) + (u^{7/4}) - (u^{9/4}) + \dots$ s = drawdown (L) T = transmissivity (L²/T) S = storage coefficient (dimensionless) π = 3.141592654 r = radial distance (L) t = time (T) u = dimensionless $W(u)$ = well function													
Transmissivity T (gpd/ft)	Transmissivity T (ft ² /day)	Storage Coefficient S	Pumping Rate Q (gal/min)	Pumping Rate Q (ft ³ /sec)	Time t (days)	Distance r (feet)	pi	u	W(u)	Drawdown s (feet)	Drawdown Change s (feet)	Well	Comments
								Note : W(u) calculation valid when u < 7.1					
Note: yellow grid areas are where values are calculated								7.0000	1.1545E-04	W(u) calculation test			
"From" POA wells to closest reach of Chewaucan River (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	385.57	0.86	30.00	3,700.00	3.14	0.0373	2.7474	5.3117		LAKE 4564	Continuous Pumping at Full Rate (Basin Fill Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	30.00	8,020.00	3.14	0.0600	2.2955	1.5174		LAKE 51182	Continuous Pumping at Full Rate (Volcanics Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	30.00	10,680.00	3.14	0.1064	1.7671	1.1682		LAKE 50941	Continuous Pumping at Full Rate (Volcanics Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	30.00	11,315.00	3.14	0.1194	1.6639	1.0999		LAKE 51031	Continuous Pumping at Full Rate (Volcanics Portion)
			1,542.30	3.44						9.10			
"To" POA wells to closest reach of Chewaucan River (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	385.57	0.86	30.00	5,635.00	3.14	0.0866	1.9538	3.7775		LAKE 52463	Continuous Pumping at Full Rate (Basin Fill Portion)
22,852.99	3,055.00	0.00100	385.57	0.86	30.00	7,810.00	3.14	0.1664	1.3760	2.6602		LAKE 52491	Continuous Pumping at Full Rate (Basin Fill Portion)
22,852.99	3,055.00	0.00100	385.57	0.86	30.00	11,325.00	3.14	0.3499	0.7945	1.5361		LAKE 52492	Continuous Pumping at Full Rate (Basin Fill Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	30.00	9,350.00	3.14	0.0815	2.0094	1.3283		LAKE 52770	Continuous Pumping at Full Rate (Volcanics Portion)
			1,542.30	3.44						9.30	0.2049		
"From" POA wells to closest reach of Chewaucan River (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	190.43	0.42	30.00	3,700.00	3.14	0.0373	2.7474	2.6234		LAKE 4564	Continuous Pro-Rated Pumping (Basin Fill Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	30.00	8,020.00	3.14	0.0600	2.2955	0.7494		LAKE 51182	Continuous Pro-Rated Pumping (Volcanics Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	30.00	10,680.00	3.14	0.1064	1.7671	0.5769		LAKE 50941	Continuous Pro-Rated Pumping (Volcanics Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	30.00	11,315.00	3.14	0.1194	1.6639	0.5432		LAKE 51031	Continuous Pro-Rated Pumping (Volcanics Portion)
			761.71	1.70						4.49			
"To" POA wells to closest reach of Chewaucan River (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	190.43	0.42	30.00	5,635.00	3.14	0.0866	1.9538	1.8656		LAKE 52463	Continuous Pro-Rated Pumping (Basin Fill Portion)
22,852.99	3,055.00	0.00100	190.43	0.42	30.00	7,810.00	3.14	0.1664	1.3760	1.3138		LAKE 52491	Continuous Pro-Rated Pumping (Basin Fill Portion)
22,852.99	3,055.00	0.00100	190.43	0.42	30.00	11,325.00	3.14	0.3499	0.7945	0.7586		LAKE 52492	Continuous Pro-Rated Pumping (Basin Fill Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	30.00	9,350.00	3.14	0.0815	2.0094	0.6560		LAKE 52770	Continuous Pro-Rated Pumping (Volcanics Portion)
			761.71	1.70						4.59	0.1012		

Drawdown Calculations Using Theis Equation													
Theis Equation: $s = \frac{Q}{4\pi T} W(u)$ $u = \frac{r^2 S}{4 T t}$ $W(u) = (-\ln u) - (0.5772157) + (u^{1/4}) - (u^{1/2}) + (u^{3/4}) - (u^{5/4}) + (u^{3/2}) - (u^{5/2}) + (u^{7/4}) - (u^{9/4}) + \dots$ s = drawdown (L) r = radial distance (L) T = transmissivity (L ² /T) t = time (T) S = storage coefficient (dimensionless) u = dimensionless π = 3.141592654 $W(u)$ = well function													
Transmissivity T (gpd/ft)	Transmissivity T (ft ² /day)	Storage Coefficient S	Pumping Rate Q (gal/min)	Pumping Rate Q (ft ³ /sec)	Time t (days)	Distance r (feet)	pl	u	W(u)	Drawdown s (feet)	Drawdown Change s (feet)	Well	Comments
								Note : W(u) calculation valid when u < 7.1					
								7.0000	1.1545E-04				W(u) calculation test
Note: yellow grid areas are where values are calculated													
"From" POA wells to closest reach of Chewaucan River (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	385.57	0.86	245.00	3,700.00	3.14	0.0046	4.8150	9.3093		LAKE 4564	Continuous Pumping at Full Rate (Basin Fill Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	245.00	8,020.00	3.14	0.0073	4.3438	2.8714		LAKE 51182	Continuous Pumping at Full Rate (Volcanics Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	245.00	10,680.00	3.14	0.0130	3.7766	2.4965		LAKE 50941	Continuous Pumping at Full Rate (Volcanics Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	245.00	11,315.00	3.14	0.0146	3.6626	2.4212		LAKE 51031	Continuous Pumping at Full Rate (Volcanics Portion)
			1,542.30	3.44						17.10			
"To" POA wells to closest reach of Chewaucan River (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	385.57	0.86	245.00	5,635.00	3.14	0.0106	3.9797	7.6943		LAKE 52463	Continuous Pumping at Full Rate (Basin Fill Portion)
22,852.99	3,055.00	0.00100	385.57	0.86	245.00	7,810.00	3.14	0.0204	3.3366	6.4509		LAKE 52491	Continuous Pumping at Full Rate (Basin Fill Portion)
22,852.99	3,055.00	0.00100	385.57	0.86	245.00	11,325.00	3.14	0.0428	2.6155	5.0567		LAKE 52492	Continuous Pumping at Full Rate (Basin Fill Portion)
66,838.45	8,935.00	0.00100	385.57	0.86	245.00	9,350.00	3.14	0.0100	4.0395	2.6703		LAKE 52770	Continuous Pumping at Full Rate (Volcanics Portion)
			1,542.30	3.44						21.87	4.7738		
"From" POA wells to closest reach of Chewaucan River (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	190.43	0.42	245.00	3,700.00	3.14	0.0046	4.8150	4.5976		LAKE 4564	Continuous Pro-Rated Pumping (Basin Fill Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	245.00	8,020.00	3.14	0.0073	4.3438	1.4181		LAKE 51182	Continuous Pro-Rated Pumping (Volcanics Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	245.00	10,680.00	3.14	0.0130	3.7766	1.2330		LAKE 50941	Continuous Pro-Rated Pumping (Volcanics Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	245.00	11,315.00	3.14	0.0146	3.6626	1.1958		LAKE 51031	Continuous Pro-Rated Pumping (Volcanics Portion)
			761.71	1.70						8.44			
"To" POA wells to closest reach of Chewaucan River (Transmissivity from specific capacity data: Used S = 0.001)													
22,852.99	3,055.00	0.00100	190.43	0.42	245.00	5,635.00	3.14	0.0106	3.9797	3.8000		LAKE 52463	Continuous Pro-Rated Pumping (Basin Fill Portion)
22,852.99	3,055.00	0.00100	190.43	0.42	245.00	7,810.00	3.14	0.0204	3.3366	3.1859		LAKE 52491	Continuous Pro-Rated Pumping (Basin Fill Portion)
22,852.99	3,055.00	0.00100	190.43	0.42	245.00	11,325.00	3.14	0.0428	2.6155	2.4974		LAKE 52492	Continuous Pro-Rated Pumping (Basin Fill Portion)
66,838.45	8,935.00	0.00100	190.43	0.42	245.00	9,350.00	3.14	0.0100	4.0395	1.3188		LAKE 52770	Continuous Pro-Rated Pumping (Volcanics Portion)
			761.71	1.70						10.80	2.3577		

Surface water Interference Calculations

T-14738 JRS Properties III LP River Interence Compared Updated 2025													
From Wells				Distance to	Pumping rate		River Interference (cfs)		River Interference (cfs)		River Interference (cfs)		
Well	GW Source	Steam Depletion	Transmissivity (ft ² /day)	Chewaucan River	Full Rate	Pro-Rated	Full Rate	Pro-Rated	Full Rate	Pro-Rated	Full Rate	Pro-Rated	
		Evaluated with		(Feet)	(cfs)	(cfs)	30 days	30 days	120 days	120 days	240 days	240 days	
LAKE 4564	Basin Fill Seds	Hunt (1999)	3055	3700	0.8591	0.4243	0.1480	0.0730	0.2950	0.1460	0.3820	0.1890	
LAKE 51182	Basalt	Hunt (2003)	8935	8020	0.8591	0.4243	0.0000	0.0000	0.0020	0.0010	0.0080	0.0040	
LAKE 51031	Volcanic Seds & Rocks	Hunt (2003)	8935	11315	0.8591	0.4243	0.0000	0.0000	0.0000	0.0000	0.0020	0.0010	
LAKE 50941	Basin Fill and Basalt	Hunt (2003)	8935	10680	0.8591	0.4243	0.0000	0.0000	0.0000	0.0000	0.0020	0.0010	
Average				8428.75	0.8591	0.4243	0.0370	0.0183	0.0743	0.0368	0.0985	0.0488	
Net Total				33715	3.4364	1.6972	0.1480	0.0730	0.2970	0.1470	0.3940	0.1950	
Total River Interference as Percent of Total Pumping Rate							4.31%	4.30%	8.64%	8.66%	11.47%	11.49%	
To Wells				Distance to	Pumping rate		River Interference (cfs)		River Interference (cfs)		River Interference (cfs)		
Well	GW Source	Steam Depletion	Transmissivity	Chewaucan River	Full Rate	Pro-Rated	Full Rate	Pro-Rated	Full Rate	Pro-Rated	Full Rate	Pro-Rated	
		Evaluated with		(Feet)	(cfs)	(cfs)	30 days	30 days	120 days	120 days	240 days	240 days	
7R (prop)	Basin Fill Seds	Hunt (1999)	3055	5635	0.6880	0.3400	0.0970	0.0480	0.2160	0.1070	0.2890	0.1430	
LAKE 52491	Basin Fill Seds	Hunt (1999)	3055	7810	0.6880	0.3400	0.0760	0.0380	0.1950	0.0960	0.2700	0.1330	
LAKE 52492	Basin Fill Seds	Hunt (1999)	3055	11325	0.6880	0.3400	0.0500	0.0250	0.1630	0.0810	0.2400	0.1190	
LAKE 52770	Volcanic Seds & Rocks	Hunt (2003)	8935	9350	0.6880	0.3400	0.0000	0.0000	0.0010	0.0000	0.0040	0.0020	
LAKE 53479	Basin Fill & Volcanics	Hunt (2003)	8935	6900	0.6880	0.3400	0.0000	0.0000	0.0030	0.0010	0.0100	0.0050	
Average				8204	0.6880	0.3400	0.0446	0.0222	0.1156	0.0570	0.1626	0.0804	
Net Total				41020	3.4400	1.7000	0.2230	0.1110	0.5780	0.2850	0.8130	0.4020	
Total River Interference as Percent of Total Pumping Rate							6.48%	6.53%	16.80%	16.76%	23.63%	23.65%	