STATE ENGINEER Salem, Oregon	MARI 9.5	Well Record	COUNT	WELL NO7/2 YMARION ATTON NO	
OWNER: W. Edgar 1	Nafziger	MAILING ADDRESS:	Rt. 2, Bo	x 536	
LOCATION OF WELL		CITY AND	Salem, Or	egon	
SE 1/4 NW 1/4 Sec	2. T7. S., R	2	· ;		
Bearing and distance for	rom section or subdi	•		_	
corner E. 1/403' 8	& N. 1501	***************************************			
4					

Altitude at well	•	***************************************		+	
TYPE OF WELL: Dr.			ĺ		
Depth drilled 139			Section		
CASING RECORD:					
10-inch				RECEIVE	D
			1	MAR 12 2008 NATER RESOURCES OF	}
FINISH:				SALEM, OREGON	EPT -
WATER LEVEL;		gravel and Hard par	1		
30½-fee	t 		·		
Capacity225	NT: Type	Berkelsy Turbina		Н.Р	15
WELL TESTS: Drawdown 55½	ft. after	hours Pt	umping 300		G.P.M.
		hours Pt			
DRILLER or DIGGE ADDITIONAL DATA:	MATIONGR-25 R	Temp			
	Level Measuremen	ts Chemical A	nalysis	Aquifer Test	
REMARKS:	d quick sand	20	0 20		
Blue cl	ay _	5	0 70		
Yellow Cement	gravel	10 8	88		
Water g	ravel d gravel	? 12	95 2 107		
Loose g	gravel 1 1	0557	110		
Water g Cement Hard pa	gravel	State Printing 80918	0 130	Clay	

WATER RESOURCES DEPARTMENT. STATE OF SALEM, OREGON 97310 (Please type	1/10 1 0 0000	eslaw-	34		
	SALEM, OREGON		-		
(1) OWNER:	(10) LOCATION OF WELL:				
Name Donald L. Stuart	County Marion Driller's well nu	mber 2258			
Address 6545 Hazel Green Rd. NE	% Section 34 T. 6S	R. 2W	W.M.		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n_corner			
```					
New Well Deepening Reconditioning Abandon C					
if abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 74		ft.		
tary Driven Domestic Industrial Municipal	Static level 39 ft. below land surface. Date 9/8/79				
Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square				
(5) CASING INSTALLED: Threaded   Welded					
8 Diam. from top ft to 164 ft. Gage . 250	(12) WELL LOG: Diameter of well b	elow casing			
Diam. from ft. to ft. Gage	Depth drilled 164 ft. Depth of completed well 164 ft				
Diam. from tt. to tt. Gage	Formation: Describe color, texture, grain size a				
	and show thickness and nature of each stratur with at least one entry for each change of format	ion. Report each	change iz		
(6) PERFORATIONS: Perforated? N Yes No.	position of Static Water Level and indicate prin	cipal water-beari	ng strata		
Type of perforator used Mills Knife	MATERIAL	From To	SWL		
Size of perforations 3/8 in. by 2½ in.	Topsoil	Q 2			
552 perforations from 114 ft. to 162 ft.	Brown Clay	2 53			
perforations from ft. to ft.	Cemented Brown Sand and Grave	. 53 74			
perforations fromft, toft.	Brown Sand and Gravel, with				
7) SCDPPNS.	cementation	74 110			
(7) SCREENS: Well screen installed?  Yes  No	Brown Sand and Gravel	110 135			
Manufacturer's Name	Brown Clay	135 136			
Type	Brown Sand and Gravel	136 164			
Diam, Slot size Set from ft. to ft.					
Diam. Slot size Set from ft. to ft.		<u> </u>			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		<del></del>			
	- WEST ACT				
a pump test made? K) Yes   No If yes, by whom? driller	DEC-61979	<del></del>			
Yield: 650 gal./min. with 22 ft. drawdown after 1½ hrs.	WATER RESOURCES DEPT				
<u>"                                    </u>	CALES DEPT				
, , , , , , , , , , , , , , , , , , ,	SALEM OREGON				
er test gal./min. with ft. drawdown after hrs.					
Artesian flow g.p.m.					
Temperature of water Depth artesian flow encountered ft.	Work started 9/6/79 19 Complete	ed 9/8/79	19		
	Date well drilling machine moved off of well	9/8/79	19		
(9) CONSTRUCTION:		······································			
Well seal-Material used Portland Cement	Drilling Machine Operator's Certification:				
Well sealed from land surface to 19	This well was constructed under my Materials used and information reported	above are tru	e to m		
Diameter of well bore to bottom of seat	best knowledge and belief.				
Diameter of well bore below seal in.	[Signed] Coroling Machine Operator)	Date9/8/79	, 19		
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No.				
How was cement grout placed? pumped in	The second of th				
	Water Well Contractor's Certification:				
	This well was drilled under my jurisd true to the best of my knowledge and bel		report i		
Was a drive shoe used? 🕱 Yes 🗌 No Plugs Size: location ft.	Name Willamette Drilling Co.				
Did any strata contain unusable water? 🔲 Yes 🔀 No	(Person, firm or corporation)	(Type or pr	-		
Type of water?depth of strata	Address 7365 O'Neil Rd. NE Sale	m, Oregon	97303		
Method of sealing strata off	On J Di				
••	[Signed] Water Well Control	ractor)			
Was well gravel packed? ☐ Yes 👸 No Size of gravel:		2 /7.9	10		
Gravel placed from ft. to ft.	Contractor's License No.	1	, 19		
(USE ADDITIONAL S	HERTS IF NECESSARY)		15.6		