NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the


WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)



(1) OWNER:	(10) LOCATION OF WELL:
Name KOKKA MONTEE	County UMan A Driller's well number
Address (III NW 3C	. NW4 SW4 Section 35 T. 2N R. 32E W.M.
VENDLETON ORGON 97801	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 385 ft.
Rotary & Oriven	Static level 141 ft, below land surface, Date 4-18-80
De Jetted Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 8
0 Diam from +2 ft to 18 ft Gage 1250	Depth drilled ft. Depth of completed well ft.
Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
"Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
(6) PERFORATIONS: Perforated Yes TNO.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	SOIL 0 6
perforations fromft. toft.	olayel 68
perforations from ft. to ft.	Black Bayat 8 96
perforations from ft. to ft.	Black+Brown Bank 45 85
(7) SCREENS.	Black Bosalt PS 965
(7) SCREENS: Well screen installed? Yes And	Brock + Brown Broad 385
Manufacturer's Name Model No.	Black + Red Bosell 385 395 KO
Diam. Slot size Set from ft. to ft.	Black Bosalt Large Tale 400 450
Diam. Slot size Set from ft. to ft.	8/sel Barall 450 480
	Week that Bosalt Vell as Tak 480 490 H.O
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	- 490 495
a pump test made? Yes No If yes, by whom? R.	HECEINED BELLEINED
Yield: 300 gal/min. with 25/ ft. drawdown after / hrs.	
The same was to be a supply of the same to be a	MAR 1 9 2008 - UN : 9 1980
The second secon	TO PEODUPOE DE WATER RESOURCES DEPT
er test gal/min. withft. drawdown after hrs.	SAI FU OPECON
Artesian flow g.p.m.	-SALEM, OREGON
Temperature of water Depth artesian flow encounteredft.	Work started 4- 18 19 80 Completed 5-18 19 80
(9) CONSTRUCTION:	Date well drilling machine moved off of well 4-/8 1980
Weil seal-Material used ORTLAND CENCY	Drilling Machine Operator's Certification:
Well sealed from land surface to	This wall was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used soil information/reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] 7 ASSI HO Date 5-/8 1980
Number of sacks of cemant used in well seal	(Drilling Machine Operator)
How was cement grout placed?	
	Water Well Contractor's Certification:
The second secon	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? Yes Mo Files Size: location	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes 176	(Person, firm or corporation) (Type or print)
Type of water? depth of strate	Address Rt 16064 (LOT like Oly 99%)
Method of sealing strata off	Stoll Him
Was well gravel packed? Yes Bing Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 739 Date 5-18-1980
(USE ADDITIONAL SI	·